

THIS REPORT HAS BEEN DELIMITED
AND CLEARED FOR PUBLIC RELEASE
UNDER DOD DIRECTIVE 5200.20 AND
NO RESTRICTIONS ARE IMPOSED UPON
ITS USE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

NAWEPs REPORT 8837

1 MARCH 1966

NAWEPs REPORT 8837

481279

**SPX-A BOOSTER EXPLOSIVE WHICH
CAN BE INITIATED BY SOURCES
OF SMALL DIMENSIONS**

R. H. STRESAU

R. L. DEGNER

D D C
RECEIVED
MAY 6 1966
RECEIVED
B

Distribution of this document
is unlimited.



NAVAL ORDNANCE LABORATORY CORONA
CORONA, CALIFORNIA

NAVAL ORDNANCE LABORATORY CORONA

E. B. JARMAN, CAPT., USN
Commanding Officer

F. S. ATCHISON, Ph. D.
Technical Director

ABSTRACT

The objective of the work described was the development of an RDX-base explosive that can be initiated by explosive charges of very small dimensions, such as Mild Detonating Fuse (MDF), but will meet Navy requirements for a booster explosive. By these requirements, an explosive may be no more sensitive than tetryl. Such characteristics may be expected of finely divided RDX desensitized with a waxy substance. RDX of a mean particle size close to 10 microns was prepared by pouring a solution of RDX in hot acetone into chilled water. The finely divided RDX was desensitized with various percentages of calcium stearate by precipitating the latter from a sodium stearate solution (the vehicle of an RDX slurry) with calcium chloride. The Spooner small-scale gap test, which is a poor man's version of the Naval Ordnance Laboratory, White Oak (NOL/WO) small-scale gap test, shows SPX (finely divided RDX coated with 1.5% calcium stearate) to have almost exactly the sensitivity of CH-6, which is, in turn, significantly less sensitive than tetryl. SPX can usually be initiated by means of MDF loaded with one grain per ft PETN and it is reliably initiated by five grains per ft MDF. In contrast, CH-6 cannot be initiated by means of 10 grains per ft MDF. A Varicomp (SVC) series of finely divided RDX/calcium stearate mixtures closely paralleled the NOL/WO Varicomp series of mill-run RDX/calcium stearate in small-scale gap test sensitivity. A microscale gap test was devised in which 5-grain MDF was used as the donor to simulate an intended condition of use. The microscale gap test sensitivities of the SVC series, when plotted against stearate content, showed more scatter than did the small-scale gap test sensitivities.

FOREWORD

The development work covered in this report was done by the authors in the summer of 1963 as part of Contract N123 (62738)31089A between the Naval Ordnance Laboratory, Corona, California, and the R. Stresau Laboratory, Inc., Spooner, Wisconsin.

The body of the report and the illustrations are substantially as submitted by the authors in fulfillment of contract requirements.

The work under the contract was authorized by WEPTASK RMMO-21-030/211-1/F009-08-01 (PA No. 5).

B. F. HUSTEN
Head, Fuze Department

CONTENTS

	<u>Page</u>
Abstract	Inside Front Cover
Foreword	i
Introduction	1
Qualitative Theoretical Considerations	2
Explosives	6
General	6
Standard Military Explosives	6
Preparation of Fine Particle RDX by Precipitation	7
Coating With Calcium Stearate To Produce SPX	8
SVC Series for Varicomp Evaluations of Explosive Systems	8
Experimental Arrangements and Procedure	9
General	9
The Bruceton Procedure	9
Loading Conditions	10
Firing Test Arrangements	12
SSSGT	12
MDF Initiation Susceptibility	12
MSGT	12
Results and Discussion	12
General	12
Comparison Between SSSGT and SSGT	17
Effect of Particle Size on Gap Sensitivity	17
Effect of Particle Size on MDF Initiation Susceptibility	17
Effect of Calcium Stearate on SSSGT of Finely Divided RDX	17
Effect of Calcium Stearate on MDF Initiation Susceptibility	19
MSGT Calibration of SVC Explosives	19
Loading of SPX	19
Output of SPX	23
Conclusion and Recommendation	23
References	24

INTRODUCTION

Recent developments, including that of Mild Detonating Fuse (Ref. 1),¹ suggest that fuze explosive trains and other high-explosive systems can be made by using explosive components of much smaller dimensions than those currently used in ordnance (Ref. 2). Since the total bulk and weight of many such systems is nearly proportional to that of the explosive components used, such smaller components would remove a barrier to miniaturizing fuzes and other systems. The miniaturized fuzes, in turn, could result in improved performance in smaller ordnance by making more space available for main charge explosives, improved reliability in larger ordnance by virtue of increased opportunities for redundancy, and substantial performance gains in ordnance of various types as the result of the more sophisticated systems which would be possible.

In most cases where smaller components offer advantages, it is necessary to transfer detonation from the small components to the main charge of a high-explosive weapon. Most of the advantages of the smaller components would be lost if safety policy prevented their use in direct communication with the main charge. The safety policy of the Bureau of Naval Weapons, as now interpreted, precludes the use of explosives more sensitive than tetryl in such direct communication. Explosives that are usable in such positions, but can be initiated by means of standard fuze explosive components, are referred to as "booster explosives." The booster explosives most commonly used in naval ordnance, tetryl and CH-6, will detonate quite reliably in rather small size columns, if well confined, as in MDF. However, the transfer from such small columns to larger charges is not particularly reliable unless it is accomplished quite gradually in a tapered lead or by relatively small stepwise increases.

To attain the full advantage of small explosive components, it should be possible to initiate a booster or relatively large lead directly. On first consideration, it would seem that a booster explosive that can be initiated by a smaller source than can tetryl is a contradiction of terms, since such an explosive would have to be more sensitive than tetryl. If the criterion of sensitivity were the size of source for threshold initiation, this would be unarguable. The criteria which have been used to characterize sensitivity in the application of Navy policy have been impact sensitivity tests,

¹Mild Detonating Fuse and MDF are trademarks of E. I. du Pont de Nemours & Company for metal-jacketed detonating cord with linear explosive densities of one to 20 grains per foot.

such as those with ERL Type 12 tools (Ref. 3), and gap tests, such as the Naval Ordnance Laboratory, White Oak (NOL/WO) small-scale gap test (SSGT) (Ref. 4). In such tests, the quantity of explosive exposed to the experimental stimulus remains nearly constant, while the intensity of the stimulus is varied. In contrast, initiation by a small source, such as MDF, involves stimuli of nearly the same intensity as that delivered by a fuze component of currently used dimensions, but the quantity of explosive exposed to the stimulus is much reduced. Even without consideration of the mechanisms involved, it is reasonable to expect that the susceptibilities of various explosives to initiation by such differing types of impulse should be something other than direct. There is no reason to expect that an explosive that can be reliably initiated by means of smaller MDF than can tetryl would be automatically more sensitive than tetryl in a gap or impact test.

The experiments described herein were directed toward the development of an RDX-base explosive that, when loaded into explosive components of standard dimensions (Ref. 2), can be reliably initiated by means of MDF (five grains of RDX per ft or less), but which is less sensitive than tetryl according to impact or gap tests. Because of the high cost of an ERL impact machine and the difficulties of establishing the validity of impact data obtained with a machine of original design, a gap test was used to characterize the sensitivities of explosives prepared in this program. The general agreement between gap and impact sensitivities (Ref. 5) leads to the expectation that impact sensitivities of the new explosives developed in this program and the standard explosives tested would assume the same general order as their gap-test sensitivities.

QUALITATIVE THEORETICAL CONSIDERATIONS

Detonation has been described as a reactive shock. A more detailed description includes a nonreactive shock followed by a reaction zone of finite thickness. In a stable detonation, the inherent losses associated with shock waves are exactly compensated by the chemical energy liberated by the reaction.

Stable detonation, where the advancing shock front is a plane surface, so that only movement perpendicular to the shock front need be considered, is referred to as "ideal detonation." Conditions at the end of the reaction zone (usually referred to as the "Chapman-Jouguet point"), as well as the rate of propagation of an ideal detonation, are determined by the density and available chemical energy of the unreacted explosive and the equation of state of the reaction products.

In a "nonideal" detonation, movement in directions other than that of propagation have significant effects. The two common "naturally occurring"

situations that result in nonideal detonation are found (1) in a charge so small that the effects of expansion at boundaries are transmitted to the Chapman-Jouguet point at the charge axis, and (2) in the expanding detonation in a larger charge which results when it is initiated by a smaller charge.

Eyring and his associates (Ref. 6) showed that the radial movement in cylindrical charges results in curvature of the detonation front and they related the conditions and stability of such detonation to the ratio of the reaction zone length of the explosive to the radius of this curvature. This relationship of detonation conditions and stability to front curvature, quite obviously also applies (though transiently) to the expanding wave that results when a large charge is initiated by means of a smaller charge.

In a detonation, as in any shock, the pressure, density, temperature, particle velocity, and propagation velocity are so interdependent that, in any given medium, the values of each can be determined if one is given. In applying their curved front theory to predict nonideal detonation conditions in cylindrical columns of explosive, Eyring and his associates characterized the strength of detonation in terms of propagation velocity, facilitating direct comparison of theoretical predictions with the largest bulk of experimental data. In Ref. 7, it was suggested that the growth of detonation waves from sources of small dimensions can be traced more easily in a system of coordinates in which vigor of shock or detonation waves from sources of small dimensions is characterized in terms of pressure. The general approach that had been used by Eyring and his associates was to construct a "failure diagram" for expanding spherical waves in coordinates of pressure and the ratio of reaction zone length to radius of front curvature.

In Figure 1, which is a copy of the failure diagram with a few additions, the curves P_1N_10 and P_1N_20 represent equilibrium detonation conditions for expanding spherical detonation waves in two explosives with the same hydrodynamic-thermodynamic conditions (defined by the pressure, P_1) and the reaction zone length, a_1 , for ideal detonation but differing as to the pressure dependence of the reaction rate. P_1N_1 and P_1N_2 are stable equilibrium conditions, which are approached by all spherical detonations that are not failing. N_10 and N_20 are critical conditions above and to the left of which detonation may be expected to grow to the stable conditions and below which it may be expected to fail. To the right of N_1 and N_2 , the term "detonation" loses its meaning, but the curves N_1M and N_2M define conditions for which the energy lost by the spherically expanding shock wave is exactly compensated by that liberated by the reaction of the explosive. If, when a spherically expanding shock wave is induced in an explosive, conditions are given by a point above and to the left of ON_2M or ON_1M (whichever is applicable to the particular explosive), the reaction will grow to a high-order detonation. If conditions are represented by a point below and to the right of this curve, the reaction will fail.




FIGURE 1. Failure Diagram for Expanding Spherical Detonation Waves, Including Typical Experimental Threshold Initiation Conditions

In addition to the failure diagram, Figure 1 includes a curve representing the estimated detonation pressure dependence of a lead-encased charge (such as MDF), loaded with a material of constant P_i and a_i (such as RDX at a constant state of aggregation), and a representation of typical small-scale gap test conditions.

It may be noted that, since the abscissae of Figure 1 are ratios of reaction zone length to radius of front curvature, and since the radius of front curvature must be nearly proportional to that of a small column such as MDF, which is used to induce a shock wave in the explosive, the critical size (C_1 or C_2) of the small column for threshold initiation should be directly proportional to the reaction zone length, a , of the explosive that is being initiated. On the other hand, the effect of the pressure dependence of reaction rate (C_1 versus C_2) is quite small. In contrast, it may be noted that in a typical gap test, the effect of changes in the pressure dependence of reaction rate (G_1 versus G_3 or G_2 versus G_4) is greater than that of the ideal reaction zone length (G_1 versus G_2 or G_3 versus G_4). It may be implied from Figure 1 that the critical dimension of a small source for threshold initiation is directly proportional to the reaction zone length and only slightly affected by the pressure dependence of the reaction rate, while gap test sensitivity is more affected by the pressure dependence of reaction rate than by the reaction zone length in ideal detonation.

Eyring and his associates proposed that the reaction that occurs between the shock front and the Chapman-Jouguet point in a granular explosive is a deflagration at the surfaces of the grains. This "surface-burning theory," which is supported by a wide variety of experimental data (Refs. 8, 9, 10, and 11), implies that reaction zone lengths should be nearly proportional to particle size. It follows that the critical source size for initiation of an explosive should be nearly proportional to its particle size.

The fact that the most effective desensitizers for RDX are waxy materials may, in terms of the experimentally verified "hot spot" theory of initiation published by Bowden and Yoffe (Ref. 12), which is mutually supporting with the Eyring surface-burning model of detonation, be interpreted as an indication that the lubricating properties of these materials inhibit the localized heating at grain boundaries. In the terms of Figure 1, this lubrication might be expected to have more effect upon the pressure dependence of the reaction zone rate than upon the ideal reaction zone length. It might, then, be expected that waxy desensitizers should have more effect upon gap or impact sensitivity than upon susceptibility to initiation by small high-intensity sources.

The foregoing suggests that RDX of fine particle size should be more susceptible to initiation by sources of small dimensions, and that this property should not be greatly affected by desensitization with waxy substances, such as stearates. As the experiments described later in this report have shown, this appears to be correct.

EXPLOSIVES

General

All explosives used in the experiments described herein were standard military explosives, presumed to have been made in accordance with applicable military specifications, or were modifications of such materials prepared at the Stresau Laboratory.

Standard Military Explosives

All the standard military explosives used were supplied by the Naval Ordnance Laboratory, White Oak, Maryland. The numbers given are NOL/WO designations for storage lots.

RDX X334. This is also labeled "Holston" RDX, which would indicate that it is made by the Bachman process at the Holston River Ordnance Works and in accordance with Ref. 13. It is Type B RDX, containing about 10% HMX. An approximate sieve analysis is given in Table 1.

TABLE 1. Approximate Sieve Analysis
of RDX X334

U. S. Standard Sieve		Percentages
Through	On	
	40	0
40	60	2
60	80	18
80	100	26
100	150	27
150	270	10
270		17

Ch-6, X-391, Z-417. The specification for CH-6 is given in Ref. 14. It is understood, however, that most CH-6 has been made with waivers of some parts of this specification.

Tetryl. Presumed to be in accordance with Ref. 15. Identified on bottle as "yellow tetryl." Although no sieve analysis was made, an appreciable fraction was coarse enough to be held on a No. 30 U. S. Standard sieve.

Preparation of Fine Particle RDX by Precipitation

To prepare RDX of fine particle size, the RDX was dissolved in boiling acetone and the solution poured into chilled distilled water while stirring the water vigorously. The usual proportion was 8.5 grams of RDX to 100 cm³ of acetone (about 55% saturation). The quantity of water used was twice (in later preparations, three times) that of acetone. Several such preparations were made, using various types of RDX and variations in detailed procedure. Of these, only one was used in experiments discussed herein:

RDX XF-2. Made by the process described above from RDX X334. The particles in this precipitation (Figure 2) range from 2 to 20 microns in maximum dimension, with the average close to 10 microns.

The particle size distribution of RDX XF-2 is quite typical of that obtained by this process.



FIGURE 2. Photomicrograph of RDX XF-2 Particles (X 750)

Coating With Calcium Stearate To Produce SPX

The process used to coat the finely precipitated RDX was adapted from that used in the manufacture of CH-6 (Ref. 14) and the NOL/WO Varicomp (Ref. 16) mixtures. After washing to remove the acetone and after removing excess moisture by either decanting or filtering but without drying, a 100-gram batch of the precipitated RDX was added to a solution of sodium stearate in distilled water and stirred to form a slurry (a small amount of oil-soluble red dye had been added to the stearate solution). While continuing to stir, a distilled water solution of calcium chloride was added gradually, precipitating the calcium stearate and leaving a sodium chloride solution, which was removed by washing on a filter. (The oil-soluble dye, of course, followed the stearate and colored the resulting product pink. The uniformity of the color is visible evidence of the uniformity of the coating.) After filtering, the material was dried in an aluminum pan at about 80°C. Three SPXs (SPooner eXplosives) have been made:

SPX-1. 100 grams of RDX dissolved in 40 fluid oz of hot acetone was poured into 80 fluid oz of distilled water. Acetone concentration was reduced by repeatedly adding distilled water, allowing to settle, and decanting supernatant liquid. Three grams of sodium stearate in 32 fluid oz of water was added and the mixture stirred while adding 2 grams of calcium chloride. Settling, decanting, and adding of water was repeated for several cycles, after which material was dried. Since only 70 grams was recovered, and time distribution of losses is not known, stearate content may be anything from slightly less than 3% to a bit over 4%.

SPX-2. Process is similar to that for SPX-1, but 1.5 grams of sodium stearate and 1 gram of calcium chloride were used with an original 100 grams of RDX. Recovery was 80-85 grams.

SPX-2a. Proportions are the same as for SPX-2, but a double-size batch was made. Precipitate and final product washed on filter rather than by decanting. Yields obtained using filter washing were about 90%.

SVC Series for Varicomp Evaluations of Explosive Systems

In the determination of the reliability of detonation transfer between small charges and SPX, the same difficulties are encountered that led to the development of the Varicomp method for such determinations with "standard" size explosive components. To apply the Varicomp technique to small-charge SPX transfers, a series of explosives similar to SPX, except that larger proportions of stearate were used, was prepared.

These mixtures are designated SVC, which is followed by a number indicating the number of parts of sodium stearate used per 100 parts of RDX. The other materials prepared at the Stresau laboratory have been included in Table 2. SPX-12a was made because SPX-12 was

TABLE 2. The SVC Series for Varicomp Methods

SVC No.	Other Designation	Percentage Calcium Stearate ^a
SVC-0	XF-2	0
SVC-1.5	SPX-2 & SPX-2a	1.47
SVC-3	SPX-1	2.88
SVC-6		5.62
SVC-12 & SVC-12a		10.6
SVC-24		19.1

^a Assuming 100% yields.

somewhat lighter in color and somewhat more sensitive than had been anticipated, indicating that it may have contained somewhat less stearate than intended. SVC-12 was retained as a useful member of the SVC series.

EXPERIMENTAL ARRANGEMENTS AND PROCEDURE

General

The explosives prepared in the course of the work described herein were compared with standard military explosives by means of the Spooner small-scale gap test (SSSGT)—a poor man's version of the small-scale gap test (SSGT) standardized by Ayres (Ref. 4) at NOL/WO—as to their susceptibility to initiation by means of Mild Detonating Fuse. In addition, to simulate an application more closely than does the SSSGT, the "micro-scale gap test" (MSGT) was devised for calibration of the SVC series.

The Bruceton Procedure

The so-called Bruceton test procedure was used in all tests reported herein. In this procedure, the first trial of a test is performed at one of a series of preestablished sets of conditions or steps. If a detonation results, the next trial is performed at the adjacent condition or step in the direction less conducive to detonation. If it misfires, the next trial

is performed at the adjacent step in the direction of increasing detonation transfer probability. The test is continued in this manner, the conditions of each trial being determined by the results of the previous trial. Figure 3 is a typical test data sheet.

Information obtained in a Bruceton test may be analyzed to obtain estimates of the mean (the condition at which 50% will detonate) and standard deviation of the test variable and of the errors of these estimates. The validity of these estimates rests on the assumption that the probability of detonation is normally distributed with respect to the test variable or the function thereof used in establishing the series of steps. Experience indicates that for gap tests, as for many other sensitivity tests, steps so chosen that the logarithms of the gap lengths form an arithmetic progression lend as much validity to this assumption as is practically possible. The "gap decibang" (DBg) series proposed by Ayres (Ref. 4) and used in the SSGT is such a series, for which the transformation function is

$$X = -10 \log G$$

where X is the initiation intensity in DBg and G is the gap in inches. For the SSSGT, the same series of gap lengths was adopted, but to avoid ambiguities resulting from its differences in detailed test conditions from the SSGT, the sensitivity gap decibang unit is abbreviated DBgs rather than DBg.

For the MDF Initiation Susceptibility Test, the steps used were available sizes of MDF—1, 2, 5, 10, and 20 grains per ft. These steps, of course, are not uniform with respect to any function. Even if they were, they are too large to give any reasonable estimate of the standard deviation. In these experiments, the Bruceton procedure was used merely as a convenient test plan, and the "means" should be considered merely as indices of this susceptibility rather than estimates of the size of MDF that would result in 50% detonation of the acceptor.

Uniform step sizes were used for convenience in the MSGT. Although logarithmic steps would be more realistic, the linearly distributed steps result in more conservative estimates of reliability.

Loading Conditions

With one or two exceptions, all the explosives used in these experiments were loaded at 10,000 lb per sq in. Increments were measured volumetrically, following the general rule that the length-to-diameter ratio of an increment should not exceed 1. Because of the low bulk density of the fine particle explosives prepared at the Stresau laboratory, increment lengths of these materials were usually much shorter than this.

FIRING TEST ARRANGEMENTS

SSSGT

The setup shown in Figure 4 was used for the SSSGT. A 1 in. long steel cylinder, with 1 in. O. D. and 13/64 in. I. D., was loaded with the acceptor explosive. The donor explosive used in all the SSSGT tests was a 1-1/2 in. length of B100 LJDF (lead-jacketed detonating fuse containing 100 grains of RDX per ft). The length of donor was fitted flush in a wooden block and paraffin wax spacers (in 1/4 DBg step sizes) were used as the variable. The parts of the firing test arrangement were aligned by fitting them in a paper tube as shown in the diagram. Initiation of the donor was accomplished with a blasting cap, which was butted head-on to the MDF with spaghetti tubing.

MDF Initiation Susceptibility

For this test, the explosive being tested was loaded in a steel cylinder (Figure 5), as in the SSSGT tests. The donor explosive was various sizes of Mild Detonating Fuse. Holes of the proper size were drilled in steel blocks and the donor length of MDF was fitted flush with the surface of the block. A blasting cap, butted head-on to the length of MDF donor, served to initiate it.

MSGT

A diagram of the firing test arrangement for these tests is shown in Figure 6. The explosive being tested was loaded in 3/8 in. steel cases, 1/2 in. long, with a 0.132 in. I. D. The correct number of Mylar spacers (0.002 in. steps) and the loaded case were then fitted into the wooden location block. A 1 in. length of A5 MDF (5 grains of PETN per ft) was then inserted in the wooden block and cut off flush with the surface of the wooden block when it was seated on the Mylar spacers. Initiation of the donor MDF was accomplished with a blasting cap, which was taped to the wooden block in a horizontal position with its side butted against the MDF.

RESULTS AND DISCUSSION

General

Experimental results are given in Table 3, which also includes some SSGT data, supplied by Ayres (Ref. 17), for comparison of SSSGT and SSGT data.




FIGURE 4. Diagram of SSSGT Setup




FIGURE 5. Diagram of MDF Initiation Susceptibility Test Setup




FIGURE 6. Diagram of MSGT Firing Test Arrangement

TABLE 3. Experimental Results

Explosive	Density (gm/cm ³)	Loading Pressure (lb/in. ²)	NOL/WO SSGT Mean (DBg)	SSSGT ^a Mean (DBgs)	SSSGT ^a Std. Dev. (DBgs)	MDF Mean ^b Sensitivity (Grains PETN per ft)	MSGT Mean ^b (in. of Mylar Barrier)
RDX X334	1.62	10,000		5.13	0.19	4.1	0.001
RDX X189		10,000	3.28				
RDX XF-2	1.51	10,000		5.93	0.25	1.2	0.020
Tetryl	1.58	10,000		6.30	0.18	5.5	
Tetryl X102		10,000	3.63				
SPX-2	1.51	10,000		6.75	0.30	0.7	0.019 ^a
SPX-2		5,000					0.020 ^c
CH-6	1.60	10,000		6.80	0.15	15.0	
CH-6 X255		10,000	3.58				
CH-6 X267		10,000	4.54				
SPX-2 (a)	1.47	5,000		6.90	0.13	0.5	0.019
SPX-2 (a)	1.52	10,000		7.13	0.28	0.7	0.021
SPX-1	1.58	10,000		7.55	0.15	2.0	0.012
SVC-6	1.52	10,000		7.80	0.10	1.7	0.010
SVC-12	1.51	10,000		7.88	0.25	3.5	0.014
SVC-12 (a)	1.42	10,000		8.29	0.13	2.9	0.011
SVC-24	1.53	10,000		9.63	0.25	15.0	<000

^aBased on 20-shot Bruceteton tests.

^bBased on 10-shot Bruceteton tests.

^cBased on 40-shot Bruceteton tests.

Comparison Between SSSGT and SSGT

Unfortunately, none of the explosives at hand were of lots for which SSGT data are available. From data for RDX, tetryl, and CH-6 given in Table 3, it may be seen that SSSGT values in DBgs units are two or three units higher than SSGT values in DBg. The tests agree regarding the ordering of RDX, tetryl, and CH-6. The scatter of the differences between values for the same explosives is of the same order as the scatter of SSGT values for various lots of the same explosive. The fact that the lowest standard deviation in the group of explosives tested is 0.10 DBgs, although in almost any similar group of SSGT data one or a few deviations as small as 0.05 DBg is observed, may be taken as evidence that the inherent variability of the SSSGT may be somewhat greater than that of the SSGT. This larger variability is to be expected in view of the many refinements of the SSGT, which have been left out of the SSSGT.

Effect of Particle Size on Gap Sensitivity

Previous experience with explosives in the size range from 20 to 100 mesh indicated that gap sensitivity increases with decreasing particle size (Ref. 18 and 19). In the present experiments, however, the RDX XF-2, with a mean particle size on the order of 10 microns, turned out to be significantly less sensitive than RDX X334, with a mean particle size well over 100 microns. Ayres (Ref. 17) mentions similar observations with the SSGT. Note that this trend is sufficient to counteract the effects of the density differential. It may be suggested that gap sensitivity is maximized at some "optimum" particle size. An interesting practical application of this trend lies in the possibility that RDX with a still finer particle size may, without additive, comply with the Navy definition of a booster explosive as an explosive less sensitive than standard tetryl.

Effect of Particle Size on MDF Initiation Susceptibility

Note the substantially greater susceptibility of RDX XF-2, as compared with RDX X334, and the still greater contrast in this respect between SPX-2 and CH-6. The effect is essentially as predicted in the discussion of qualitative theoretical considerations above.

Effect of Calcium Stearate on SSSGT of Finely Divided RDX

As may be seen in Figure 7, SSSGT sensitivity of SVC explosives closely parallels SSGT sensitivity of NOL Varicomp explosives. Unfortunately, these data are not particularly pertinent to explosive systems for which SPX was devised.




FIGURE 7. Sensitivity of Mixtures of RDX and Calcium Stearate

Effect of Calcium Stearate on MDF Initiation Susceptibility

In Figure 8, note that for the finely divided SVC explosives the effect of calcium stearate, in concentrations up to 10%, is appreciably less than that of particle size. This is as would be predicted from the construction of Figure 1.

MSGT Calibration of SVC Explosives

In Figures 9 and 10, it is seen that although the general trend of MSGT sensitivity as related to stearate concentration is in the right direction and in reasonable agreement with SSSGT sensitivity, the scatter is much too great for Varicomp techniques (Ref. 16) using series of explosives of graded sensitivity. For a particular application (Ref. 20), it was found possible to use one of the single Varicomp explosive techniques (Ref. 16). The scatter of the MSGT data (as well as that of the MDF initiation susceptibility data, Figure 8) is possibly attributable to variations in particle size, particle size distribution, and uniformity of stearate coating. The relatively crude preparation techniques that have been used up to now are apparently insufficient for the preparation of an adequate series of Vari-comp explosives for use in the evaluation of explosive systems with micro-miniaturized explosive components. However, the control of properties, which has been attained with such rudimentary techniques, gives promise that, with a little refinement to improve control, a satisfactory series can be prepared. An interesting possibility would be a series in which particle size rather than composition is the variable used to control initiation susceptibility. Such a series would, of course, have to be calibrated for various sizes of source, and might reverse its slope for greatly different sizes.

Loading of SPX

The very low bulk densities and poor flow properties of finely divided explosives such as SPX are not conducive to efficient production loading by present techniques. A possibility, the investigation of which has been assigned to the Stresau laboratory as a future task, is that of "graining" the material into larger grains, each consisting of many particles of SPX. Of course graining may affect the small charge initiation susceptibility for which this material was developed. This would probably depend upon the graining technique used. It is believed that a material with much improved loading properties can be developed, one that will retain the desirable properties of SPX. Meanwhile, in many applications the advantages of miniaturization of fuzes and other explosive systems should outweigh a certain inconvenience in loading.




FIGURE 8. MDF Initiation Susceptibility




FIGURE 9. MSGT Sensitivities Plotted as a Function of SSSGT Sensitivities




FIGURE 10. MSGT Sensitivity of SVC Explosives (Includes SPX Explosives)

Output of SPX

The relatively low loading densities obtained when SPX is loaded at 10,000 lb per sq in. (see Table 3) might lead to the impression that the output would be correspondingly decreased. Quite to the contrary, measurements of the dents produced in the witness plates of the SSSGT indicate that SPX-2, at a density of 1.47 gm/cm^3 has at least as great an output as RDX X334 at 1.62 gm/cm^3 and appreciably greater output than CH-6 at 1.60 gm/cm^3 . In addition, "low orders," which were the usual type of misfire in the tests of CH-6 and were occasionally observed with tetryl, were completely absent with SPX and SVC explosives, which either detonated "high order" or failed completely.

CONCLUSION AND RECOMMENDATION

It may be concluded that SPX-2 can be reliably initiated by means of MDF and other explosive components with charge diameters on the order of $1/32$ in. Although further development is needed in the areas of improved loadability and refinement of explosive system evaluation techniques, it is possible to recommend that serious consideration be given the advantages inherent in systems with explosive components of such small dimensions.

REFERENCES

1. "DuPont Mild Detonating Fuse (MDF)," E. I. du Pont de Nemours & Company, Chemical Sales, Explosive Specialties, Wilmington 98, Delaware. Bulletin ES-58-3B.
2. MIL-STD-320, "Terminology, Dimensions, and Materials of Explosive Components for Use in Fuzes."
3. Wenograd, J. "The Correlation of the Impact Sensitivity of Organic High Explosives With Their Thermal Decomposition Rates," Naval Ordnance Laboratory, White Oak, Maryland, 30 September 1957. NAVORD Report 5730.
4. Ayres, J. N. "Standardization of the Small-Scale Gap Test Used to Measure the Sensitivity of Explosives," Naval Ordnance Laboratory, White Oak, Maryland, 16 January 1961. NAVWEPS Report 7342.
5. Stresau, R. H., Jr. and L. E. Starr, Jr. "Some Studies of Propagation of Detonation Between Small Confined Explosive Charges," Naval Ordnance Laboratory, White Oak, Maryland, 15 July 1950. NOLM 10577.
6. Eyring, H., R. E. Powell, G. H. Duffy, and R. B. Parlin, "The Stability of Detonation," Chem. Rev., Vol. 45, No. 69 (1949).
7. Stresau, R. H., "A Theory of the Growth of Detonation from Sources of Subcritical Dimensions," Proceedings of Electric Initiator Symposium, 1960, sponsored by Naval Ordnance Laboratory, White Oak, Maryland, at the Franklin Institute, Philadelphia, Pennsylvania, November 29 and 30, 1960. Paper 17a.
8. Duff, R. E., and E. E. Houston, "Measurement of the Chapman-Jouguet Pressure and Reaction Zone Length in a Detonating High Explosive," Second ONR Symposium on Detonation, Washington, D. C., February 9-11, 1955. Paper No. 16.
9. Cook, M. A., "The Science of High Explosives," Reinhold Publishing Corporation, New York, 1958.
10. Urizar, M. J., E. James, Jr., and L. C. Smith, "The Detonation Velocity of Pressed TNT," Third Symposium on Detonation, September 26-28, 1960. ONR Symposium Report ACR-52, Vol. 2, p. 327.
11. Sadwin, L. D., R. H. Stresau, and J. Savitt, "Nonideal Detonation of Ammonium Nitrate Fuel Mixtures," Third Symposium on Detonation, September 26-28, 1960. ONR Symposium Report ACR-52, Vol. 1, p. 309.

12. Bowden, F. P., and A. D. Yoffe, "Initiation and Growth of Explosion in Liquids and Solids," Monographs on Physics, Cambridge University Press, Cambridge, England (American Branch, New York).
13. Military Specification MIL-R-00398B (ORD), "RDX," dated 29 November 1957.
14. Military Specification MIL-R-21723 (NOrd), "CH-6."
15. Joint Army-Navy Specification, JAN-T-339, "Tetryl," 13 May 1946.
16. Ayres, J. N., L. D. Hampton, I. Kabik, and A. D. Solem, "Varicomp, a Method for Determining Detonation Transfer Probabilities," Naval Ordnance Laboratory, White Oak, Maryland, 30 June 1961. NAVWEPS Report 7411.
17. Ayres, J. N., Naval Ordnance Laboratory, White Oak, Maryland, private communication.
18. Dimmock, W. E., Jr., L. D. Hampton, and L. E. Starr, Jr., "Investigation of the Propagation of Detonation Between Small Confined Explosive Charges, Progress Report," Naval Ordnance Laboratory, White Oak, Maryland, 1 April 1952. NAVORD Report 2385. (Confidential)
19. Hampton, L. D., "Sensitivity and Pelleting Characteristics of Certain Desensitized RDX Mixtures," Naval Ordnance Laboratory, White Oak, Maryland, 25 June 1956. NAVORD Report 4320. (Confidential)
20. Degner, R. L., and R. H. Stresau, "Mild Detonating Fuse Distribution System for Simultaneous Multiple Point Initiation of a Warhead," R. Stresau Laboratory, Inc., Spooner, Wisconsin, for the Naval Ordnance Laboratory, Corona, California, 26 July 1963. RSLR 63-6-2. (Confidential)

DOCUMENT CONTROL DATA - R&D		
<i>(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)</i>		
1 ORIGINATING ACTIVITY (Corporate author)	2a REPORT SECURITY CLASSIFICATION	
Naval Ordnance Laboratory Corona, California	UNCLASSIFIED	
	2b GROUP	
3 REPORT TITLE		
SPX—A BOOSTER EXPLOSIVE WHICH CAN BE INITIATED BY SOURCES OF SMALL DIMENSIONS		
4 DESCRIPTIVE NOTES (Type of report and inclusive dates)		
Development work done in FY 64		
5 AUTHOR(S) (Last name, first name, initial)		
Stresau, R. H., and Degner, R. L.		
6 REPORT DATE	7a TOTAL NO OF PAGES	7b NO OF REFS
1 March 1966	30	20
8a CONTRACT OR GRANT NO	9a ORIGINATOR'S REPORT NUMBER(S)	
N123(62738)31089A	NAWWEPS Report 8837	
b PROJECT NO WEPTASK		
RMMO-21-030/211-1/F009-08-01		
c (PA No. 5)	9b OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
d	Stresau Laboratory Report 63-7-1	
10 AVAILABILITY/LIMITATION NOTICES		
Distribution of this document is unlimited.		
11 SUPPLEMENTARY NOTES	12 SPONSORING MILITARY ACTIVITY	
Prepared under contract, by R. Stresau Laboratory for NOLC Fuze Department	Chief, Bureau of Naval Weapons Navy Department	
13 ABSTRACT		
<p>An RDX-base explosive (SPX) was developed that satisfies Navy requirements for a booster (no more sensitive than tetryl) and can be initiated by explosive charges of very small dimensions. SPX is finely divided RDX (mean particle size, 10 μ) coated with 1.5% calcium stearate. The Spooner small-scale gap test (SSSGT) showed SPX to have nearly the sensitivity of CH-6 and significantly less sensitivity than tetryl. SPX can usually be initiated by MDF loaded with 1 grain/ft PETN and is reliably initiated by 5 grains/ft MDF. In contrast, CH-6 cannot be initiated by 10 grains/ft MDF.</p>		

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Guided Missile Fuzes Booster Explosive Gap Test Explosives Fuze Explosive Trains Fuze Initiation Susceptibility						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C) or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.

<p>Naval Ordnance Laboratory Corona. (NAVWEPS Report 8837) SPX—A BOOSTER EXPLOSIVE WHICH CAN BE INITIATED BY SOURCES OF SMALL DIMENSIONS, by R. H. Stresau and R. L. Degner, R. Stresau Laboratory, Inc., for Fuze Department, NOLC. 1 March 1966. 30p. 10 figs. UNCLASSIFIED</p> <p>An RDX-base explosive (SPX) was developed that satisfies Navy requirements for a booster (no more sensitive than tetryl) and can be initiated by explosive charges of very small dimensions. SPX is finely divided RDX (mean particle size, 10 μ) coated with 1.5% calcium stearate. The Spooner small-scale gap test (SSSGT) showed SPX to have nearly the sensitivity of CH-6 and significantly less sensitivity than tetryl. SPX can usually be initiated by MDF loaded with 1 grain/ft PETN and is reliably initiated by 5 grains/ft MDF. In contrast, CH-6 cannot be initiated by 10 grains/ft MDF.</p>	<p>1. Explosive trains 2. Boosters I. Stresau, R. H. II. Degner, R. L. III. Title</p> <p>WEPTASK: RMMO-21-030/ 211-1/F009-08-01 (PA No. 5)</p>	<p>Naval Ordnance Laboratory Corona. (NAVWEPS Report 8837) SPX—A BOOSTER EXPLOSIVE WHICH CAN BE INITIATED BY SOURCES OF SMALL DIMENSIONS, by R. H. Stresau and R. L. Degner, R. Stresau Laboratory, Inc., for Fuze Department, NOLC. 1 March 1966. 30p. 10 figs. UNCLASSIFIED</p> <p>An RDX-base explosive (SPX) was developed that satisfies Navy requirements for a booster (no more sensitive than tetryl) and can be initiated by explosive charges of very small dimensions. SPX is finely divided RDX (mean particle size, 10 μ) coated with 1.5% calcium stearate. The Spooner small-scale gap test (SSSGT) showed SPX to have nearly the sensitivity of CH-6 and significantly less sensitivity than tetryl. SPX can usually be initiated by MDF loaded with 1 grain/ft PETN and is reliably initiated by 5 grains/ft MDF. In contrast, CH-6 cannot be initiated by 10 grains/ft MDF.</p>	<p>1. Explosive trains 2. Boosters I. Stresau, R. H. II. Degner, R. L. III. Title</p> <p>WEPTASK: RMMO-21-030/ 211-1/F009-08-01 (PA No. 5)</p>
<p>----- This card is UNCLASSIFIED -----</p>		<p>----- This card is UNCLASSIFIED -----</p>	
<p>Naval Ordnance Laboratory Corona. (NAVWEPS Report 8837) SPX—A BOOSTER EXPLOSIVE WHICH CAN BE INITIATED BY SOURCES OF SMALL DIMENSIONS, by R. H. Stresau and R. L. Degner, R. Stresau Laboratory, Inc., for Fuze Department, NOLC. 1 March 1966. 30p. 10 figs. UNCLASSIFIED</p> <p>An RDX-base explosive (SPX) was developed that satisfies Navy requirements for a booster (no more sensitive than tetryl) and can be initiated by explosive charges of very small dimensions. SPX is finely divided RDX (mean particle size, 10 μ) coated with 1.5% calcium stearate. The Spooner small-scale gap test (SSSGT) showed SPX to have nearly the sensitivity of CH-6 and significantly less sensitivity than tetryl. SPX can usually be initiated by MDF loaded with 1 grain/ft PETN and is reliably initiated by 5 grains/ft MDF. In contrast, CH-6 cannot be initiated by 10 grains/ft MDF.</p>	<p>1. Explosive trains 2. Boosters I. Stresau, R. H. II. Degner, R. L. III. Title</p> <p>WEPTASK: RMMO-21-030/ 211-1/F009-08-01 (PA No. 5)</p>	<p>Naval Ordnance Laboratory Corona. (NAVWEPS Report 8837) SPX—A BOOSTER EXPLOSIVE WHICH CAN BE INITIATED BY SOURCES OF SMALL DIMENSIONS, by R. H. Stresau and R. L. Degner, R. Stresau Laboratory, Inc., for Fuze Department, NOLC. 1 March 1966. 30p. 10 figs. UNCLASSIFIED</p> <p>An RDX-base explosive (SPX) was developed that satisfies Navy requirements for a booster (no more sensitive than tetryl) and can be initiated by explosive charges of very small dimensions. SPX is finely divided RDX (mean particle size, 10 μ) coated with 1.5% calcium stearate. The Spooner small-scale gap test (SSSGT) showed SPX to have nearly the sensitivity of CH-6 and significantly less sensitivity than tetryl. SPX can usually be initiated by MDF loaded with 1 grain/ft PETN and is reliably initiated by 5 grains/ft MDF. In contrast, CH-6 cannot be initiated by 10 grains/ft MDF.</p>	<p>1. Explosive trains 2. Boosters I. Stresau, R. H. II. Degner, R. L. III. Title</p> <p>WEPTASK: RMMO-21-030/ 211-1/F009-08-01 (PA No. 5)</p>
<p>----- This card is UNCLASSIFIED -----</p>		<p>----- This card is UNCLASSIFIED -----</p>	