FTD-HT-23-230-72

AD 748907

FOREIGN TECHNOLOGY DIVISION

THE QUESTION OF THE INFLUENCE OF A PERMANENT MAGNETIC FIELD ON WATER

by

V. B. Yevdokimov and V. A. Zubarev

D D C
RECEIVED
OCT 3 1972
D

Approved for public release;
Distribution unlimited.

Reproduced by
NATIONAL TECHNICAL
INFORMATION SERVICE
U S Department of Commerce
Springfield VA 22151

Best
Available
Copy

UNCLASSIFIED
Security Classification

DOCUMENT CONTROL DATA - R & D
(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author)
Foreign Technology Division
Air Force Systems Command
U. S. Air Force

2a. REPORT SECURITY CLASSIFICATION
UNCLASSIFIED

2b. GROUP

3. REPORT TITLE
THE QUESTION OF THE INFLUENCE OF A PERMANENT MAGNETIC FIELD ON WATER

4. DESCRIPTIVE NOTES (Type of report and inclusive dates)
Translation

5. AUTHOR(S) (First name, middle initial, last name)
V. B. Yevdokimov and V. A. Zubarev

6. REPORT DATE
1969

7a. TOTAL NO. OF PAGES
4

7b. NO. OF REFS
7

8a. CONTRACT OR GRANT NO.
F-3615-71-C-1182 (71 Jan 01)

b. PROJECT NO.

c.

d.

9a. ORIGINATOR'S REPORT NUMBER(S)
FTD-HT-23-0230-72

9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)

10. DISTRIBUTION STATEMENT
Approved for public release; distribution unlimited.

11. SUPPLEMENTARY NOTES

12. SPONSORING MILITARY ACTIVITY
Foreign Technology Division
Wright-Patterson AFB, Ohio

13. ABSTRACT

In technical journals over the past ten years a great many works have appeared which have been devoted to the influence of the so-called "magnetization" of feed water against the formation of scale on boiler walls. This article explains the possibility of the effect of a uniform, permanent magnetic field on the structural properties of rest water and its solutions under strictly monitored conditions. As the control measurements we carried out a series of experiments with freshly-produced bidistilled and distilled water with pH's of 6.8 and 6.3, respectively, at temperatures T = 283 and 293°K and magnetic field strengths of 1000 and 2000 Oe. The experiment results were processed statistically. Data show that with an accuracy of ±2% with a confidence level of 95% a permanent uniform magnetic field with strengths of 1000 and 2000 Oe does not change the properties of pure water at temperatures T = 283 and T = 293°K.

DD FORM 1 NOV 65 1473

UNCLASSIFIED
Security Classification

UNCLASSIFIED
Security Classification

14. KEY WORDS	LINK A ROLE	LINK A WT.	LINK B ROLE	LINK B WT.	LINK C ROLE	LINK C WT.
Viscosity Index						
Permanent Magnetic Field						
Water						
Temperature						
Parameters						

II

UNCLASSIFIED
Security Classification

EDITED TRANSLATION

FTD-HT-23-230-72

THE QUESTION OF THE INFLUENCE OF A PERMANE MAGNETIC FIELD ON WATER

By: V. B. Yevdokimov and V. A. Zubarev

English pages: 4

Source: Moscow. Universitet. Vestnik. Seriya II. Khimiya (Moscow. Univers'ty. Herald. Series II. Chemistry Vol. 24, No. 2, 1969, pp. 110-111.

Requester: ASD

Translated by: John Miller

Approved for public release;
Distribution unlimited.

THIS TRANSLATION IS A RENDITION OF THE ORIGINAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DIVISION.

PREPARED BY:

TRANSLATION DIVISION
FOREIGN TECHNOLOGY DIVISION
WP-AFB, OHIO.

THE QUESTION OF THE INFLUENCE OF A PERMANENT MAGNETIC FIELD ON WATER

V. B. Yevdokimov and V. A. Zubarev

In technical journals over the past ten years a great many works have appeared which have been devoted to the influence of the so-called "magnetization" of feed water against the formation of scale on boiler walls [1]. In a brief report it is impossible to give a complete analysis of the works; however, we should point out their insufficiently high level of methodology. In this regard, at the present time many researchers are attempting to detect, in water and its solutions subjected to magnetic processing, changes in the physical and physicochemical indices [2-5].

The purpose of our work was to explain the possibility of the effect of a *uniform, permanent* magnetic field on the structural properties of *real* water and its solutions under strictly monitored conditions, for which we determined the viscosity of the water by the method of the average bilateral time of first passage (the Tekarek method) [6]. The essence of this method, developed by Mynshteyn and Stolukhovskiy [7], is to estimate the behavior of Brownian particles in a liquid. As the Brownian particles [illegible] used diamagnetic carbon particles with radius of the order [illegible], in a concentration such that they are, on the average, 10-[illegible] apart. The thickness of the liquid in the measured propa-

[illegible]

ration was about 100μ. We estimated the change in number n which shows how often, in time t, a particle of radius r covers a given distance l in a magnetic field (n) or without it (n_0). From forms $\eta = \frac{RT}{N} \frac{t}{3\pi r l^2 n}$, where R is the gas constant, N is the Avogadro number, T is absolute temperature and η is the coefficient of viscosity, we see that $\frac{\eta_0}{\eta} = \frac{n_0}{n_H}$, i.e., from the change in n with the other parameters remaining constant we can judge as to structural changes in the liquid. The measured preparation was thermostatted with an accuracy of ±0.05°, which could lead to variations of ±0.2% in the viscosity index. The uniform permanent magnetic field was established and maintained with an accuracy of ±2%. In time t = 15 ± 0.1 min we simultaneously measured values of n for two mutually perpendicular directions n along and across the field force lines ($n_\parallel$ and $n_\perp$).

$n_\parallel$	f	$\overset{s}{M}=23$	fs	fs^2
20	1	−3	−3	9
21	2	−2	−4	8
22	4	−1	−4	4
23	6	0	0	0
24	5	+1	5	5
25	2	+2	4	8
26	0	+3	0	0
Σ	20		−2	34

$n_\perp$	f	$\overset{s}{M}=23$	fs	fs^2
20	1	−3	−3	9
21	1	−2	−2	4
22	5	−1	−5	5
23	6	0	0	0
24	4	+1	4	4
25	2	+2	4	8
26	1	+3	3	9
Σ	20		+1	39

As the control measurements we carried out a series of experiments with freshly-produced bidistilled and distilled water with pH's of 6.8 and 6.3, respectively, at temperatures T = 283 and 293°K and magnetic field strengths of 1000 and 2000 Oe. The experiment results were processed statistically. As an example, let us present the analysis of data obtained for bidistilled water with pH = 6.8 at T = 293°K in a magnetic field with H = = 2000 Oe. The total observation time was 5 hours with 5 preparations:

$$\sigma_{\parallel} = \pm\sqrt{\frac{\Sigma f\varepsilon^2}{K-1}} = \pm 1{,}4, \quad \sigma_{\perp} = \pm 1{,}43; \quad \sigma_{A\perp} = \pm 0{,}3,$$

$$\sigma_{A\parallel} = \frac{\sigma_{\parallel}}{\sqrt{K}} = \pm 0{,}3, \quad A_{\perp} = 23{,}05 \pm 0{,}3 (\pm 1{,}3\%),$$

$$A_{\parallel} = M + \frac{\Sigma f\varepsilon}{\Sigma f} = 22{,}9 \pm 0{,}3 (\pm 1{,}3\%), \quad A_{cp} = 23{,}0 \pm 0{,}2 (\pm 1{,}0\%).$$

Here we have used the following arbitrary designations: f - frequency of appearance of a given value of n; ε - central deviation, the difference between the date and the condition of the arithmetic mean M; A - arithmetic mean, with subscript (cp.) (mean) = ($A_{\parallel}+A_{\perp}$):2; $\sigma_{\parallel}$ and $\sigma_{\perp}$ are, respectively, the quadratic deviations of $n_{\parallel}$ and $n_{\perp}$ individually; σ_A is the standard error in the arithmetic mean A; K is the sum of f.

In experiments with bidistilled and distilled water, carried out under the same conditions but without a field (H = 0), with 8 preparations with a total observation time of 8 hours we obtained the following values: $\sigma_{\parallel} = \pm 1.5$ $\sigma_{A\parallel} = \pm 0.3$, $A_{\parallel} = 23{,}0 \pm 0{,}3 (\pm 1{,}3\%)$, $\sigma_{\perp} = \pm 1.4$ $\sigma_{A\perp} = \pm 0.3$. $A_{\perp} = 23{,}1 \pm 0.3 (\pm 1.3\%)$, $A_{cp} = 23{,}1 \pm 0{,}2 (\pm 1{,}0\%)$

With H = 2000 Oe and T = 293°K, using three preparations with the bidistillate for a total of 5 hours we obtained the values: $A_{\parallel} = 17{,}0 \pm 0{,}2 (\pm 1{,}2\%)$; $A_{\perp} = 17{,}2 \pm 0{,}2$; $A_{cp} = 17{,}1 \pm 0{,}14 (\pm 1{,}0\%)$. With H = 1000 Oe and T = 283°K and 293°K the values of $A_{\parallel}$, $A_{\perp}$ and A_{cp}, obtained during a total observation time of 10 hours, do not differ from the corresponding values obtained for H = 2000 Oe for the same temperatures times the value of the standard error. Thus, these data show that with an accuracy of ±2% with a confidence level of 95% a permanent uniform magnetic field with strengths of 1000 and 2000 Oe does not change the properties of pure water at temperatures T = 283 and T = 293°K.

BIBLIOGRAPHY

1. Магнитная и электромагнитная обработка воды. Библиографические карточки, № 662, № 5300. ГПНТБ, 1965.
2. Миненко В. И. и др. Магнитная обработка воды. Харьковское книжное изд-во, 1962.
3. Классен В. И., Зиновьев Ю. З. Коллоидный журнал, 29, № 5, 758, 1967.
4. Левич В. Г. Успехи физ. наук, 88, вып. 4, 787, 1966.
5. Киргинцев А. Н., Соколов В. М. Ж. физ. химии, 40, 2053, 1966.
6. Бурлакова Е. В., Кольс О. Р., Кригер Ю. А. Физико-химические методы в биологии. Практикум по общей биофизике, вып. I. М., «Советская наука», 1958.
7 Эйнштейн А., Смолуховский М. Броуновское движение. Л., Главная редакция общетехнической литературы, 1936.

Department of Physical Chemistry

Recieved
8 May 1968