

AD-752 050

CHEMICAL MILLING

Defense Documentation Center  
Alexandria, Virginia

November 1972

DISTRIBUTED BY:

**NTIS**

National Technical Information Service  
U. S. DEPARTMENT OF COMMERCE  
5285 Port Royal Road, Springfield Va. 22151

**UNCLASSIFIED**


**AD-752 050**

**CHEMICAL MILLING**  
**A DDC BIBLIOGRAPHY**

**DDC-TAS-72-60**

**NOVEMBER 1972**

**BEST  
AVAILABLE COPY**



Approved for public release;  
distribution unlimited.

Reproduced by  
**NATIONAL TECHNICAL  
INFORMATION SERVICE**  
U S Department of Commerce  
Springfield VA 22151

**UNCLASSIFIED**



**DEFENSE DOCUMENTATION CENTER**  
**DEFENSE SUPPLY AGENCY**

157

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author)

DEFENSE DOCUMENTATION CENTER  
Cameron Station  
Alexandria, Virginia 22314

2a. REPORT SECURITY CLASSIFICATION

UNCLASSIFIED

2b. GROUP

3. REPORT TITLE

CHEMICAL MILLING

4. DESCRIPTIVE NOTES (Type of report and inclusive dates)

Bibliography (August 1957 - January 1972)

5. AUTHOR(S) (First name, middle initial, last name)

6. REPORT DATE

November 1972

7a. TOTAL NO. OF PAGES

160

7b. NO. OF REFS

104

8a. CONTRACT OR GRANT NO.

b. PROJECT NO.

c.

d.

9a. ORIGINATOR'S REPORT NUMBER(S)

DDC-TAS-72-60

9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)

AD-752 050

10. DISTRIBUTION STATEMENT

Approved for public release; distribution unlimited

11. SUPPLEMENTARY NOTES

Superseded AD-702 750

12. SPONSORING MILITARY ACTIVITY

13. ABSTRACT

This report includes references on the capabilities and limitations of Chemical Milling Techniques, materials for which it is suitable, and the quality of the finished surfaces.

Corporate Author-Monitoring Agency, Subject, Title, Personal Author, Contract Number and Report Number Indexes are provided.

DD FORM 1473  
1 NOV 65

UNCLASSIFIED

Security Classification

ia

UNCLASSIFIED

Security Classification

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
*Bibliographies *Chemical Milling Etching Titanium Alloys Aluminum Alloys Stainless Steel Electrolytes Beryllium Alloys Metallography Machining Material Removal Transistors Manufacturing Methods Nickel Alloys Reagents Cobalt Alloys Precision Finishing Crystals Copper Alloys Tin Alloys Zinc Alloys Refractory Metals Printed Circuits						

ib

UNCLASSIFIED

Security Classification

**UNCLASSIFIED**

AD- 752 050

**CHEMICAL MILLING**

**A DDC BIBLIOGRAPHY**

August 1957 - January 1972

**DDC-TAS-72-60**

**NOVEMBER 1972**

Approved for public release;  
distribution unlimited.

**DEFENSE DOCUMENTATION CENTER  
DEFENSE SUPPLY AGENCY  
CAMERON STATION  
ALEXANDRIA, VIRGINIA 22314**

**UNCLASSIFIED**

11

**F O R E W O R D**

This bibliography is a compilation of references on *Chemical Milling*. Entries were selected, using the authorized term chemical milling, from references processed into the AD data banks from January 1953 to July 1972 and supersedes AD-702 750.

Corporate Author-Monitoring Agency, Subject, Title, Personal Author, Contract Number and Report Number Indexes are provided.

**BY ORDER OF THE DIRECTOR, DEFENSE SUPPLY AGENCY**

**OFFICIAL**

  
ROBERT B. STEGMAIER, JR.  
Administrator

**Defense Documentation Center**

C O N T E N T S

	<u>Page</u>
FOREWORD.....	iii
AD BIBLIOGRAPHIC REFERENCES.....	1
INDEXES	
CORPORATE AUTHOR-MONITORING AGENCY.....	0-1
SUBJECT.....	D-1
TITLE.....	T-1
PERSONAL AUTHOR.....	P-1
CONTRACT.....	C-1
REPORT NUMBER.....	R-1

Preceding page blank

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL No. /ZOML6

AD-252 129  
WATERVLIET ARSENAL N Y

CHEMICAL MILLING

(U)

DEC 60 23P ROSE, C.H.;  
REPT. NO. WVT RI-60001 IRI 60001 I

UNCLASSIFIED REPORT

DESCRIPTORS: \*CHEMICAL MILLING, ALLOYS, ALUMINUM ALLOYS, CASTING, CHEMICAL REACTIONS, CORROSION, GUNS, MACHINE TOOLS, MACHINING, MAGNESIUM ALLOYS, MANUFACTURING METHODS, MECHANICAL PROPERTIES, METALS, PHYSICAL PROPERTIES, PRECISION FINISHING, PROCESSING, PRODUCTION, SHEETS, STEEL, SURFACE PROPERTIES, TEMPLATES, TITANIUM ALLOYS (U)

A PROCESS STUDY, OUTLINING THE CAPABILITIES AND LIMITATIONS OF CHEMICAL MILLING, THE MATERIALS FOR WHICH IT IS SUITABLE, THE ACCURACIES AND SURFACE FINISHES EXPECTED; DERIVED FROM A STUDY OF THE AVAILABLE LITERATURE AND VISITS TO USERS OF THE PROCESS, ARE MADE TO DETERMINE THE APPLICABILITY OF THE METHOD TO THE PILOT PRODUCTION REQUIREMENTS OF WATERVLIET ARSENAL. FORTY-TWO POUNDS OF 4340 STEEL WERE REMOVED FROM A 90MM M41 BREECH RING IN 61 HOURS BY CHEMICAL MILLING. SURFACE FINISH WAS 62 MICROINCHES. METAL REMOVAL RATE WAS .0007 IN. PER MINUTE. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL No. /ZOML6

AD-256 351

PENNSYLVANIA STATE UNIV UNIVERSITY PARK

INFLUENCE OF DISPLACIVE-SHEARING STRESSES ON THE  
KINETICS OF RECONSTRUCTIVE TRANSFORMATIONS EFFECTED  
BY PRESSURE IN THE RANGE 0-100,000 BARS (U)

IV DACHILLE, FRANKROY, RUSTUMI

UNCLASSIFIED REPORT

DESCRIPTORS: \*CHEMICAL MILLING, \*PHASE STUDIES,  
\*TRANSFORMATIONS, CHEMICAL BONDS, CHEMICAL ENGINEERING,  
PRESSURE, REACTION KINETICS, SHEAR STRESSES,  
TEMPERATURE (U)

EARLIER RESULTS SHOWED THAT ORDINARY LABORATORY GRINDERS AND MIXERS WERE ABLE TO CONVERT SEVERAL PHASES (E.G.  $PbO_2$ ,  $MnF_2$ ,  $CaCO_3$ ,  $BeF_2$ , ETC.) INTO THEIR RESPECTIVE HIGH-PRESSURE FORMS WHICH, AT EQUILIBRIUM REQUIRE 10-15,000 ATMOSPHERES AT ROOM TEMPERATURE. HENCE, EXPERIMENTS WERE DEVISED TO ATTEMPT TO SEPARATE THE EFFECT OF HYDROSTATIC PRESSURE FROM THOSE OF SHEARING STRESSES AND BOND-BREAKAGE. A STUDY OF THE INFLUENCE OF SHEARING STRESSES SUPERIMPOSED UPON QUASIHYDROSTATIC PRESSURES OF UP TO 100,000 BARS AT TEMPERATURES BELOW 550 C WAS MADE POSSIBLE BY THE DEVELOPMENT OF SIMPLE APPARATUS. THIS CONSISTS OF THE BRIDGMAN UNIAXIAL-TYPE APPARATUS, WITH A PROVISION FOR CONTINUOUS ROTATION OF THE BOTTOM PISTON VERY SLOWLY BACK AND FORTH THROUGH A 2 DEGREE ARC. THE SAMPLE IS HEATED EXTERNALLY; DISPLACIVE-SHEARING RUNS WITH PRESSURE AND TEMPERATURE AUTOMATICALLY CONTROLLED CAN BE MADE FOR PERIODS EXCEEDING SEVERAL DAYS IF DESIRED. THE RESULTS CLEARLY SEPARATE THE INFLUENCE OF HYDROSTATIC PRESSURE ITSELF UPON REACTION RATES FROM THE EFFECT OF THE ADDED DISPLACIVE-SHEARING STRESSES. FROM THE RESULTS IT BECOMES CLEAR THAT EQUILIBRIUM RELATIONS BETWEEN PHASES ARE NOT ALTERED BY THE SHEARING STRESSES. (AUTH:JR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-261 959

AEROJET-GENERAL CORP SACRAMENTO CALIF

STRUCTURAL TESTS OF A CHEMICALLY MILLED LADISH D-6AC  
STEEL SECOND-STAGE MINUTEMAN AFT CLOSURE (U)

JUL 61 1V THOMAS, R.W. ;  
CONTRACT: AF33 600 36610

UNCLASSIFIED REPORT

DESCRIPTORS: \*CHEMICAL MILLING, \*ROCKET CASES,  
DEFORMATION, DESIGN, GUIDED MISSILES, HYDROSTATIC  
PRESSURE, MEASUREMENT, MECHANICAL PROPERTIES,  
PROCESSING, ROCKET MOTORS, STAGING, STEEL, STRESSES,  
SURFACE-TO-SURFACE, TESTS (U)  
IDENTIFIERS: MINUTEMAN (U)

A STUDY WAS MADE TO DETERMINE IF THE STRUCTURAL  
STRENGTH REQUIREMENTS FOR THE AFT CLOSURE OF THE  
SECOND-STAGE MINUTEMAN ENGINE COULD BE MET WITH  
REDUCED-WEIGHT, CHEMICALLY MILLED CLOSURE OF LADISH  
D-6AC STEEL. THE STUDY INDICATED THAT THE  
CHEMICALLY MILLED AFT CLOSURE, WHICH WEIGHED 60 LB  
LESS THAN THE CONVENTIONAL STEEL CLOSURE, HAD  
SATISFACTORY STRUCTURAL STRENGTH. THE STRUCTURAL  
TESTS WERE MADE WITH AN AFT CLOSURE OF THE  
PRELIMINARY FLIGHT RATING TEST (PFRT)  
DESIGN. THE CLOSURE WAS CHEMICALLY-MILLED TWICE TO  
REDUCE THE THICKNESS OF PART OF THE SHELL, THE NOZZLE  
BOSSES, AND THE BOLTED JOINT. STRESSCOAT WAS  
APPLIED TO THE AFT CLOSURE AND THE UNIT WAS  
HYDROSTATICALLY TESTED AFTER EACH MILLING OPERATION.  
AN ANALYSIS OF STRESS AND STRAIN DATA INDICATED  
THAT THE REDUCED-WEIGHT CLOSURE SATISFACTORILY  
WITHSTOOD A PRESSURE OF 600 PSIG AND WILL MEET  
ULTIMATE STRENGTH DESIGN CRITERIA. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZDML6

AD-262 184

NORTHROP AIRCRAFT INC HAWTHORNE CALIF

DEVELOPMENT OF IMPROVED METHODS, PROCESSES, AND  
TECHNIQUES FOR PRODUCING STEEL EXTRUSIONS (U)

JUN 61 IV CHRISTENSEN, L.M. ROSE, W.I.  
REPT. NO. NOR 61 199  
CONTRACT: AF33 600 36713

UNCLASSIFIED REPORT

DESCRIPTORS: \*AIRFRAMES, \*EXTRUSION, \*STEEL, CHEMICAL  
MILLING, CORROSION-RESISTANT ALLOYS, DIES, DIFFUSION,  
DRAWING (MACHINE PROCESSING), GLASS, HARDNESS, HEAT  
TREATMENT, LUBRICANTS, MANUFACTURING METHODS, MECHANICAL  
PROPERTIES, MICROSTRUCTURE, NICKEL, PLATING, PROCESSING,  
SURFACE PROPERTIES, TENSILE PROPERTIES (U)  
IDENTIFIERS: B-70 AIRCRAFT (U)

DIMENSIONAL INTEGRITY AND SURFACE QUALITIES  
OBTAINED IN THE 0.06-IN. TEE SECTIONS OF PHASE  
I ARE CONSIDERED SUFFICIENT FOR PROCEEDING TO  
PHASE II. LOW AND ERRATIC MECHANICAL  
PROPERTIES WERE NOTED IN THE EVALUATION OF PHASE  
I EXTRUSIONS IN BOTH H-11 AND PH 15-7MO  
MATERIALS. METALLURGICAL STUDIES INDICATED THAT  
THESE LOW PROPERTIES RESULTED FROM DIFFUSION OF THE  
NICKEL LUBRICANT MATERIAL INTO THE SURFACE OF THE  
EXTRUSIONS. AFTER REMOVAL OF THE CONTAMINANT  
COATING BY CHEMICAL ETCHING, THE RESULTANT MECHANICAL  
PROPERTIES WERE WELL WITHIN SPECIFICATIONS FOR THE  
MATERIALS. THE CHEMICAL ETCHING ALSO YIELDS  
IMPROVED SURFACE QUALITY. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /Z0ML6

AD-264 685

GENERAL DYNAMICS/CONVAIR SAN DIEGO CALIF

TITANIUM DEVELOPMENT PROGRAM. VOLUME IV.

(U)

MAY 61 IV LANGLOIS, A.P. MURPHY, J.F. GREEN

E.D.:

CONTRACT: AF33 600 34876

MONITOR: ASD TR617 576

UNCLASSIFIED REPORT

DESCRIPTORS: \*ALLOYS, \*JOINTS, \*MANUFACTURING METHODS,  
\*TITANIUM ALLOYS, AIRPLANE ENGINE DUCTS, AIRPLANE  
PANELS, ALUMINUM ALLOYS, BOLTED JOINTS, BRAZING,  
CHEMICAL MILLING, CONFIGURATION, DESIGN, FUSELAGES, HEAT  
TREATMENT, MATERIALS, MOLYBDENUM ALLOYS, PROCESSING,  
RIVETED JOINTS, SMALL TOOLS, SPOT WELDS, STIFFENED  
CYLINDERS, TAILS (AIRCRAFT), TORPEDO COMPONENTS,  
VANADIUM ALLOYS, WELDING, WELDS, WINGS (U)

CONTENTS: MANUFACTURING METHOD DEVELOPMENT  
DEVELOPMENT OF OPTIMUM OPERATIONAL SEQUENCING  
PROCESS DEVELOPMENT CHEMICAL MILLING  
TOOLING CONCEPTS ROOM TEMPERATURE FORM -  
FURNACE HOT SIZE AND AGE ROOM TEMPERATURE  
FORM - HEATED PRESS HOT SIZE - FURNACE AGE  
SHORT CYCLE HOT FORM - AGE SEQUENCE TOOL  
MATERIALS PARTS MANUFACTURE TAIL CONE  
LEADING EDGE CANTED FUSELAGE BULKHEAD  
ASSEMBLIES ENGINE BLEED AIR DUCTS PANELS (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZDML6

AD-265 701

FOREIGN TECHNOLOGY DIV WRIGHT-PATTERSON AFB OHIO

ELECTRIC AND CHEMICO-MECHANICAL METHODS OF WORKING METALS (CHAPTER VII) (U)

IV POPILOV, L. YA.:

UNCLASSIFIED REPORT

DESCR PTORS: \*METALS, \*PROCESSING, BRAZING, CHEMICAL MILLING, ELECTRODEPOSITION, ELECTROEROSIVE MACHINING, ELECTROLYTIC POLISHING, ELECTROPLATING, HEAT TREATMENT, HEATING, PICKLING, SINTERING, SOLDERING, SPARK MACHINING, TECHNOLOGICAL INTELLIGENCE, TRANSLATIONS (U)  
IDENTIFIERS: USSR (U)

ELECTROCHEMICAL METHODS OF ELECTROPLATING AND ELECTROCHEMICAL POLISHING ARE DEMONSTRATED. CHEMICAL MILLING AND METAL HEATING PROCESSES ARE DISCUSSED. HEAT TREATING OF STEEL BY CONTACT ELECTROHEATING (N. V. GEVELING'S METHOD), HEATING IN ELECTROLYTES (I. Z. YASNOGODSKIY'S METHOD), AND SURFACE FLAME HARDENING ARE ALSO DISCUSSED. (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-267 806

METAL HYDRIDES INC BEVERLY MASS

DEC 61 IV

CONTRACT: DA91 591EUC1722

UNCLASSIFIED REPORT

DESCRIPTORS: \*COPPER, ACETIC ACIDS, CADMIUM, CHEMICAL MILLING, CHLORIDES, CRYSTALLIZATION, DISKS, FEASIBILITY STUDIES, HEATING, IRON COMPOUNDS, MELTING, NITRIC ACID, PHOSPHORIC ACIDS, PRODUCTION, SHEETS, SINGLE CRYSTALS, SPACE NAVIGATION, TEST METHODS (U)

A METHOD WAS DEVELOPED FOR PRODUCING A STACK OF CU SINGLE CRYSTAL DISKS 50-MICRONS THICK WHICH UTILIZED THE SPARK PLANNING TECHNIQUE FOLLOWED BY CHEMICAL POLISHING. THE METHOD FOR PROCESSING 35- TO 50-MICRON THICK DISKS IS AS FOLLOWS: (1) GROW 2.5-MM THICK SLABS AS BIG AS POSSIBLE, (2) SPARK-TEPAN 1-CM DIAM DISCS AND SPARK PLANE TO 75 TO 100 MICRONS THICK, AND (3) CHEMICALLY THIN TO 35 TO 50 MICRONS. ATTEMPTS TO GROW SINGLE CRYSTAL CU DISKS RESULTED IN THE FORMATION OF POLYCRYSTALLINE SHEETS. (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /Z0ML6

AD-268 U33

AIR FORCE CAMBRIDGE RESEARCH LABS L G HANSCOM FIELD  
MASS

A NOTE ON SEMICONDUCTOR DEVICE FABRICATION (U)

AUG 61 IV BERMAN, I. I  
REPT. NO. 729

UNCLASSIFIED REPORT

DESCRIPTORS: ALLOYS, BONDING, CHEMICAL MILLING,  
ELECTROEROSIVE MACHINING, GERMANIUM COMPOUNDS, HEATING,  
IMPURITIES, INTERMETALLIC COMPOUNDS, PICKLING  
COMPOSITIONS, PLATING, PRODUCTION, SEMICONDUCTORS,  
SILICON COMPOUNDS, TEST METHODS (U)

A DISCUSSION IS PRESENTED OF THE BASIC STEPS IN THE  
MAKING OF GE AND SI JUNCTION DEVICES. IT  
INCLUDES A LIST OF THE COMMON ETCHANTS WITH THEIR  
RELATION TO VARIOUS PHASES OF DEVICE FABRICATION.  
CONSIDERATION IS GIVEN TO ALLOYING FOR JUNCTIONS  
AND OHMIC CONTACTS, AS WELL AS INFORMATION ON  
APPLYING THE DOPANT ALLOY. ELECTROLESS NI OR  
AU GOLD, FURNACE FIRING, AND PLATING ARE EXAMINED  
IN VIEW OF REQUIRED MODIFICATIONS. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL No. /ZOML6

AD-269 209

BATTELLE MEMORIAL INST COLUMBUS OHIO DEFENSE METALS  
INFORMATION CENTER

A REVIEW OF RECENT DEVELOPMENTS IN TITANIUM AND  
TITANIUM ALLOY TECHNOLOGY

(U)

DEC 61 IV WOOD, R.A. :  
REPT. NO. M144

UNCLASSIFIED REPORT

DESCRIPTORS: \*METALLURGY, \*SHEETS, \*TITANIUM ALLOYS,  
AIR, ANTIOXIDANTS, CHEMICAL MILLING, COATINGS,  
CONTAMINATION, CORROSION INHIBITION, EXTRUSION, GASES,  
HIGH-TEMPERATURE RESEARCH, IGNITION, IMPURITIES,  
MANUFACTURING METHODS, MECHANICAL PROPERTIES, OXIDATION,  
PROCESSING

(U)

A STUDY OF THE AIR CONTAMINATION AND PROTECTION FOR  
4 DOD TI SHEET ALLOYS INDICATED THAT TI-  
4AL3MO-1V AND TI-6AL-4V HAD ABOUT EQUAL  
RESISTANCE TO PENETRATION BY INTERSTITIAL  
CONTAMINANTS. THE HARDNESS PENETRATION TESTS  
SHOWED TI-13V11CR-3AL AND TI-2.5AL-16V  
ALLOYS HAD LOWER RESISTANCE TO CONTAMINATION IN THAT  
ORDER. THE TI-5AL-2.5SN, TI-6AL-4V,  
AND TI-13V-11CR-3AL ALLOYS WERE EVALUATED  
FOR SUSCEPTIBILITY TO H EMBRITTLEMENT INDUCED BY  
CHEMICALLY MILLING IN A HYDROFLUORIC ACID BATH.  
THE ALL-ALPHA TI-5AL2.5SN ALLOY WAS NOT  
EMBRITTLED. THE TI-6AL-4V ALLOY WAS ONLY  
SLIGHTLY EMBRITTLED, WHILE THE TI-13V-11CR-  
3AL ALLOY WAS SEVERELY EMBRITTLED. AN  
INVESTIGATION CONCERNING THE TITANIUM-LOX REACTION  
WAS CONDUCTED BY USING HIGH-PRESSURE GASEOUS O.  
THE STUDY ESTABLISHED THAT A FRESH TI SURFACE  
WOULD REACT WITH GASEOUS O UNDER ABOUT 100-PSIG  
PRESSURE BETWEEN -250 F AND ROOM TEMPERATURE.  
SEVERAL METHODS OF PRODUCING FLAT SOLUTION-TREATED  
TITANIUM ALLOY SHEET ARE REVIEWED AND A NEW CONCEPT  
IS DESCRIBED. BASICALLY, THE NEW METHOD INVOLVES  
HEATING AND COOLING THE SHEET UNDER TENSION.  
(AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-271 167

BOEING CO WICHITA KANS WICHITA DIV

BOEING-WICHITA MATERIALS AND RESEARCH DEVELOPMENT  
PROGRAMS, 1957-1961

(U)

SEP 61 BY POE, A.H.; SHIGLEY, H.E.;  
CONTRACT: AF33 616 8141

UNCLASSIFIED REPORT

DESCRIPTORS: \*AIRFRAMES, \*MATERIALS, \*RADOMES,  
ADHESIVES, ALLOYS, ALUMINUM, BONDING, BRAZING, CADMIUM,  
CERAMIC COATINGS, CERAMIC MATERIALS, CHEMICAL MILLING,  
COMPOSITE MATERIALS, HEAT-RESISTANT PLASTICS, HIGH-  
TEMPERATURE RESEARCH, IGNITION, JET ENGINE FUELS,  
LAMINATES, LUBRICANTS, MACHINING, MANGANESE, METAL  
JOINTS, METALS, ORGANIC COATINGS, PLASTICS, PLATING,  
POLYMERS, STAINLESS STEEL, TEXTILES, TITANIUM,  
VARNISHES

(U)

CONTENTS: IRON AND STEEL: AM 350 STAINLESS  
STEEL, CHEMICAL ETCHING; LIGHT METALS AND ALLOYS:  
TI FASTENERS (6AL-4V); VACUUM PLATED AL,  
CORROSION RESISTANCE OF VARIOUS ALUMINUMS; HEAVY  
NON-FERROUS METALS AND ALLOYS: VACUUM PLATED CD,  
ELECTROPLATED MN; PLASTICS: METAL BONDING  
MATERIALS, ADHESIVES, PARAPLAST 33, EPOXY TUBING,  
3M-471 PLASTIC TAPE, EPOXY MAT MOLD DIE; LIQUID  
AND SEMI-SOLID HIGH POLYMERS; ADHESIVES, HIGH  
TEMPERATURE LUBRICANTS, ENAMELS AND LACQUERS, EPOXY  
ORGANIC COATINGS, NEOPRENE ORGANIC COATING; FIBROUS  
AND FILAMENTARY MATERIALS: INVESTIGATION OF  
FABRICS FOR LINT FREE CONDITION; COMPOSITE  
MATERIALS; CERAMIC BRAZE, EPON 828 AND 143 GLASS  
FABRIC LAMINATES, 181 VULAN AND 181-A-1100 SILANE  
FINISH FABRIC, REINFORCED LASTICS FOR RADOMES,  
DECALS,

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-271 536

DOUGLAS AIRCRAFT CO INC LONG BEACH CALIF

CHEMICAL COMPOUNDS FOR METAL SHAPING

(U)

JAN 62 IV JAMIESON, J.L.; LOCKHART, F.J.;  
CONTRACT: AF33 600 43027  
MONITOR: ASD TR7 648 VI

UNCLASSIFIED REPORT

DESCRIPTORS: \*ALLOYS; \*CHEMICAL MILLING; \*METALS,  
\*REFRACTORY MATERIALS, AIRCRAFT, ALUMINUM ALLOYS,  
CARBOXYMETHYLCELLULOSE, CHEMICALS, CHROMIUM ALLOYS,  
GELS, HEAT RESISTANT METALS + ALLOYS, MATERIALS,  
MOLYBDENUM ALLOYS; NICKEL ALLOYS, NIOBIUM, POROUS  
MATERIALS, PROCESSING, PRODUCTION, SOLIDS, SOLUTIONS,  
STAINLESS STEEL, STEEL, STRUCTURES, TANTALUM, TITANIUM  
ALLOYS, VANADIUM ALLOYS (U)

SEVERAL GEL SYSTEMS WERE PREPARED WITH ACID  
SOLUTIONS SUSPENDED IN A GEL MATRIX OF ORGANIC, WATER  
SOLUBLE RESINS. THESE GEL ETCHANTS CAN BE CAST  
INTO SEMIRIGID SHAPES AND ARE STABLE AT TEMPERATURES  
UP TO 140 TO 160 F. IN CONTACT WITH A STEEL  
SURFACE, THE GEL ETCHANTS CHEMICALLY REACT AND REMOVE  
METAL AT A CONTROLLED RATE. THE REACTION PRODUCTS  
AND REACTANTS MIGRATE COUNTERCURRENTLY THROUGH THE  
GEL MEDIA. FURTHER DEVELOPMENT AND TESTING WILL  
DETERMINE APPLICABILITY AS NON-LIQUID ETCHANTS.  
(AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL No. /ZOML6

AD-271 965

METAL HYDRIDES INC BEVERLY MASS

INVESTIGATION OF SINGLE-CRYSTAL AND POLYCRYSTALLINE  
TITANIUM DIBORIDE: METALLOGRAPHIC PROCEDURES AND  
FINDINGS

(U)

NOV 61 IV LYNCH,C.T.;VAHLDIK,F.W.;  
MONITOR: ASD TR61 350

UNCLASSIFIED REPORT

DESCRIPTORS: \*BORIDES, \*CRYSTALS, \*SINGLE CRYSTALS,  
\*TITANIUM COMPOUNDS, ABRASIVES, CHEMICAL MILLING,  
CRYSTAL STRUCTURE, ELECTROLYTIC POLISHING, GRINDERS,  
GRINDING WHEELS, HIGH-TEMPERATURE RESEARCH, PREPARATION,  
PROCESSING, REFRACTORY MATERIALS, SPECTROGRAPHIC  
ANALYSIS

(U)

SINGLE-CRYSTAL AND POLYCRYSTALLINE TIB<sub>2</sub> WAS  
EXAMINED TO DEVELOP APPLICABLE METALLOGRAPHIC  
TECHNIQUES FOR SECTIONING, MOUNTING, GRINDING,  
POLISHING, AND ETCHING OF TIB<sub>2</sub> SPECIMENS. THIS  
WORK DEMONSTRATES THE USABILITY AND PRACTICABILITY OF  
USING VARIOUS SIC PAPERS TOGETHER WITH DIFFERENT  
GRADES OF DIAMOND PASTE ON POLISHING WHEELS IN  
PREFERENCE TO USING CLOTHS. IT HAS BEEN FOUND THAT  
H<sub>2</sub>SO<sub>4</sub>, AS A CONSTITUENT OF ETCHANTS, PRODUCES  
MORE RELIABLE AND MORE CONSISTENT RESULTS THAN HF.  
THE SAME IS TRUE OF H<sub>2</sub>SO<sub>4</sub> WHEN USED AS A  
CONSTITUENT OF ELECTROLYTES. SINGLE-CRYSTAL  
TIB<sub>2</sub> WAS FOUND TO HAVE A TYPE OF WIDMANSTATTEN  
STRUCTURE WHILE POLYCRYSTALLINE TIB<sub>2</sub> HAD A  
NEEDLE-LIKE PATTERN. (AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-272 227

GENERAL DYNAMICS/FORT WORTH TEX

MATERIALS - HONEYCOMB CORE RIBBON RELATIONSHIP  
BETWEEN FLOW CHARACTERISTICS OF BRAZING ALLOY AND  
OXIDE FILM FORMATIONS OF - DETERMINATION OF (U)

JAN 62 1V PRATT, W.M.;  
REPT. NO. FGT 2510  
CONTRACT: AF33 600 36200

UNCLASSIFIED REPORT

DESCRIPTORS: \*BRAZING, \*HONEYCOMB CORES, \*SANDWICH  
PANELS, \*STAINLESS STEEL, ALLOYS, CHEMICAL MILLING,  
CLEANING, CONTROLLED ATMOSPHERES, COPPER ALLOYS,  
ELECTRON DIFFRACTION ANALYSIS, FILMS, HEAT TREATMENT,  
HYDROGEN, LITHIUM ALLOYS, OXIDES, PROCESSING, SILVER  
ALLOYS, SPECTROGRAPHIC ANALYSIS, SURFACE PROPERTIES,  
SURFACES, ULTRASONIC RADIATION (U)

BRAZING FLOW TESTS WERE RUN ON 17-7PH .0015  
IN. THICK STAINLESS STEEL SPECIMENS, USING THE 92.8-7-  
C.2 AG-CU-LI BRAZING ALLOY.  
SPECTROPHOTOMETRIC MEASUREMENTS, ELECTRON  
DIFFRACTION STUDIES, AND FERRIC CHLORIDE ETCH TESTS  
REVEALED DIFFERENCES IN COLOR AND REFLECTANCE,  
COMPOSITION, THICKNESS, PHYSICAL CHARACTERISTICS, AND  
ETCHING OF THE SURFACES OF SPECIMENS HAVING A  
DIFFERENT ANNEALING HISTORY. FLOW RESPONSE OF 17-  
7PH FOIL UNDER CONDITIONS OF CAPILLARITY CAN BE  
DETERMINED BY A SANDWICH FLOW TEST. WHEN THE  
MATERIAL WAS ANNEALED IN A HYDROGEN ATMOSPHERE OF  
VERY LOW DEW POINT (-85 F), VERY GOOD ALLOY FLOW  
WAS OBTAINED UPON BRAZING UNDER CAPILLARY CONDITIONS  
OF THE SANDWICH FLOW TEST. LIMITED SANDWICH FLOW  
TESTING OF THE ULTRASONICALLY CLEANED SPECIMENS GAVE  
EXCELLENT IMPROVEMENT IN BRAZING RESPONSE FOR DEW  
POINTS RANGING FROM -30 TO 41 F. AD- 72 2 9  
SPONSE OF 17-7PH FOIL UNDER CONDITIONS OF  
CAPILLARITY CAN BE DETERMINED BY A SANDWICH FLOW  
TEST. WHEN THE MATERIAL WAS ANNEALED IN A HYDROGEN  
ATMOSPHERE OF VERY LOW DEW POINT (-85 F), VERY  
GOOD ALLOY FLOW WAS OBTAINED UPON BRAZING UNDER  
CAPILLARY CONDITIONS OF THE SANDWICH FLOW TEST.  
LIMITED SANDWICH FLOW TESTING OF THE ULTRASONICALLY  
CLEANED SPECIMENS GAVE EXCELLENT IMPROVEMENT IN  
BRAZING RESPONSE FOR DEW POINTS RANGING FROM -30 TO  
41 F. (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-272 526

MCDONNELL AIRCRAFT CORP ST LOUIS MO

MOLYBDENUM STRUCTURAL COMPONENT PROGRAM

(U)

FEB 62 12P

CONTRACT: NON-61-0653

UNCLASSIFIED REPORT

DESCRIPTORS: •COATINGS, •MOLYBDENUM ALLOYS, •RIVETS, AIRFRAMES, ALUMINUM COATINGS, ANTIOXIDANTS, BOLTED JOINTS, BOLTS, CHEMICAL MILLING, CHROMIUM COMPOUNDS, COMPATIBILITY, COMPOSITE MATERIALS, DESIGN, FORGING, HIGH-TEMPERATURE RESEARCH, LOCKING FASTENER DEVICES, METAL COATINGS, METAL JOINTS, MOLYBDENUM, NIOBIUM, REFRACTORY COATINGS, RIVETED JOINTS, SILICON COATINGS, SPACECRAFT, STRUCTURES, TEMPLATES, TITANIUM ALLOYS, ZIRCONIUM ALLOYS (U)

PROGRESS IS REPORTED ON THE MO STRUCTURAL COMPONENTS. COATING VENDORS WERE INTERVIEWED TO DETERMINE THE MOST ECONOMICAL DESIGN AND ASSEMBLY PROCEDURE FOR THE RUDDER FROM A COATING STANDPOINT. COMPATIBILITY STUDIES OF MO-COATED AND NB-COATED PARTS WERE COMPLETED. PRE-PRODUCTION MO MATERIAL WHICH COULD BE USED FOR PRELIMINARY EVALUATION WAS SELECTED FOR ROLLING FOR THE DETAIL FABRICATION EVALUATION. THE RUDDER FITTINGS CANNOT BE MADE AS MO OR NB FORGINGS UNDER WESTINGHOUSE OR CRUCIBLE STEELS STUDY PROGRAM. THE BLANKING OF MO PARTS BY CHEM-MILLING WAS INVESTIGATED. (AUTHOR) (U)

UNCLASSIFIED

ODC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-276 887

ALLOY ENGINEERING AND CASTING CO CHAMPAIGN ILL

A FUNDAMENTAL STUDY OF ROLLING CONTACT FATIGUE (U)

MAY 62 10P KIRSHENBAUM, N.W.;  
CONTRACT: NOW-61-0656

UNCLASSIFIED REPORT

DESCRIPTORS: \*CRYSTALS, \*FATIGUE (MECHANICS),  
\*FLUORIDES, \*LITHIUM COMPOUNDS, CHEMICAL MILLING,  
ELECTRON BEAMS, HEAT TREATMENT, PHYSICAL PROPERTIES,  
PICKLING, PROCESSING, RADIATION EFFECTS, ROLLING MILL (U)

CHEMICAL POLISHING OF LIF CRYSTALS USING HBF<sub>4</sub>  
WAS UNSATISFACTORY. POLISHING UNANNEALED  
IRRADIATED CRYSTALS IN AGITATED SOLUTIONS OF 2 TO  
5% NH<sub>4</sub>OH WAS PROMISING. AN AQUEOUS SOLUTION  
OF 1.5 X 10 TO THE -4TH POWER M FEF<sub>3</sub> WAS  
SUPERIOR TO FECL<sub>3</sub> AS AN ETCHANT MEDIUM.  
CLEAVAGE OF LIF CRYSTALS AT LIQUID N  
TEMPERATURE APPARENTLY DECREASED BRITTLINESS.  
CLEAVED CRYSTALS ANNEALED BETWEEN 350 AND 500 C  
SHOWED EVIDENCE OF THERMAL ETCHING. HIGH VOLTAGE  
ELECTRON IRRADIATION OF LIF CRYSTALS PRODUCED  
ATOMISTIC EFFECTS SIMILAR TO GAMMA IRRADIATION.  
IRRADIATED CRYSTALS WERE CLEAVED WITH LESS EFFORT  
AND DEFORMATION THAN THE AS-RECEIVED CRYSTALS. A  
TECHNIQUE FOR OBSERVING DISLOCATIONS INTRODUCED BY  
ROLLING WAS DEVISED. (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL No. /ZOML6

AD-278 526

AERONCA MFG CORP MIDDLETOWN OHIO

BERYLLIUM COMPOSITE STRUCTURES. VOLUME II. MATERIALS  
AND PROCESSES (U)

MAY 62 IV KRUSOS, J.N.; KJELBY, A.S.;  
REPT. NO. TR61 706 V2  
CONTRACT: AF33 616 7050  
MONITOR: ASD TR61 706 V2

UNCLASSIFIED REPORT

DESCRIPTORS: AEROSPACE CRAFT, ALLOYS, ALUMINIUM  
COMPOUNDS, BRAZING, CERAMIC MATERIALS, CHEMICAL MILLING,  
DIOXIDES, FOAMS, FOILS, HEAT SHIELDS, HIGH-TEMPERATURE  
RESEARCH, HONEYCOMB CORES, MANUFACTURING METHODS, METAL  
PLATES, OSRD, OXIDES, REINFORCING MATERIALS, SHEETS,  
SHIELDING, SILICON COMPOUNDS, STAINLESS STEEL, TESTS,  
THERMAL INSULATION, ZIRCONIUM COMPOUNDS (U)

THE METHODS DEVELOPED FOR FABRICATION OF BE SHEET  
COMPOSITE STRUCTURES ARE DESCRIBED. DESCRIPTIONS  
AND PERFORMANCE EVALUATION ARE INCLUDED FOR A VARIETY  
OF PANELS FABRICATED UNDER THE CONTRACT CONSISTING OF  
BE LOAD BEARING PANELS AND POROUS CERAMIC HEAT  
SHIELDS DEVELOPED TO WITHSTAND TEMPERATURES IN EXCESS  
OF 3000 F. CONCEPTS ARE OUTLINED DEFINING  
APPLICATION OF BE-CERAMIC COMPOSITES TO AEROSPACE  
VEHICLE STRUCTURES. BE SHEET FABRICATION METHODS  
AND TOOLING ARE DESCRIBED AND INCLUDE SUCH PROCESSES  
AS CUTTING, FORMING, CHEM-MILLING, AND BRAZING. BE  
SHEET FACES WERE BRAZED TO A VARIETY OF SUPERALLOY  
AND STAINLESS STEEL HONEYCOMB CORES. THREE BASIC  
POROUS CERAMIC FOAMS WERE DEVELOPED IN THE HEAT  
SHIELD: AL2O3, ZRO2, AND SiO2.  
(AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-281 843

HARRY DIAMOND LABS WASHINGTON D C

MICROCIRCUITRY BY CHEMICAL DEPOSITION,

(U)

JUN 62

47P

HEBB, EMMA LEE :

REPT. NO. TR-1052

PROJ: 96392

UNCLASSIFIED REPORT

DESCRIPTORS: \*CIRCUITS, \*METAL FILMS,  
\*MICROMINIATURIZATION (ELECTRONICS), \*RESISTORS,  
\*SUBMINIATURE ELECTRONIC EQUIPMENT, CHEMICAL MILLING,  
COPPER, FILMS, MANUFACTURING METHODS, NICKEL, NICKEL  
ALLOYS, PHOSPHORUS ALLOYS, PLATING (U)  
IDENTIFIERS: THIN FILMS, THIN FILMS  
ELECTRONICS (M)

TECHNIQUES FOR CHEMICALLY DEPOSITING NI ALLOY  
FILMS ON INSULATING SUBSTRATES AND FOR ETCHING  
PATTERNS IN THIN CU CONDUCTORS, WERE COMBINED AND  
MODIFIED TO PERMIT THE FABRICATION OF NI ALLOY THIN  
FILMS IN VARIED AND CONTROLLED GEOMETRIES. THE  
RESISTIVITIES OF THE FILMS PRODUCED WERE VARIED FROM  
A FEW OHMS PER SQUARE TO SEVERAL THOUSAND OHMS PER  
SQUARE, BUT, AT PRESENT, TOLERANCES ON  
REPRODUCIBILITY LIMIT THE WORKING RANGE TO A MAXIMUM  
OF ABOUT 500 OHMS PER SQUARE. RESISTIVE AND  
CONDUCTIVE PARTS MADE OF NICKEL ALLOY FILMS OF  
APPROXIMATELY 500 OHMS PER SQUARE HAVE BEEN EMPLOYED  
IN MICROCIRCUITS IN WHICH THE TOLERANCES ON  
RESISTANCE VALUES ARE ABOUT + OR - 30%.  
ALTHOUGH VARIATIONS IN FILMS RESISTIVITY BETWEEN  
BATCHES SOMETIMES EXCEEDS THESE TOLERANCES, THE CLOSE  
AGREEMENT AMONG FILMS FROM THE SAME BATCH AND THE  
ABILITY TO MEASURE RESISTIVITIES PRIOR TO COMMITTING  
FILMS TO CIRCUIT PRODUCTION ALLOWED SUCH CIRCUITS TO  
BE FABRICATED. MODIFICATIONS OF PROCEDURES TO  
INCREASE THE REPRODUCIBILITY OF RESISTANCE VALUES ARE  
BEING INVESTIGATED. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /Z0ML6

AD-282 U17  
MARTIN CO BALTIMORE MD

THE EFFECT OF SURFACE-ACTIVE AGENTS ON THE MECHANICAL PROPERTIES OF METALS. PART II. THE EFFECT OF SURFACE-ACTIVE AGENTS ON THE MECHANICAL BEHAVIOR OF ALUMINUM SINGLE CRYSTALS. (U)

DESCRIPTIVE NOTE: REPT. FOR JAN 60-JAN 61, ON RESEARCH ON NEW CHEMICAL SYSTEMS AND METHODS OF SYNTHESIS.

APR 61 20P

CONTRACT: AF33 616 6220  
PROJ: 7023  
MONITOR: WADD TR-61-58-PT-2

UNCLASSIFIED REPORT

DESCRIPTORS: (\*METALLIC CRYSTALS), (\*SINGLE CRYSTALS), SURFACE PROPERTIES, SHEAR STRESSES, WETTING AGENTS, STEARIC ACIDS, METALLIC SOAPS, ADSORPTION, MECHANICAL PROPERTIES, CHEMICAL MILLING, ALUMINUM (U)

SINGLE CRYSTALS OF AL WERE PULLED IN TENSION IN A SOLUTION OF PARAFFIN OIL AND STEARIC ACID. THE CRITICAL RESOLVED SHEAR STRESS DID NOT CHANGE WITH THE CONCENTRATION OF THE STEARIC ACID SOLUTION; HOWEVER, THE EXTENT AND SLOPES OF STAGES I AND II WERE AFFECTED GREATLY. THE OBSERVATIONS LEND EVIDENCE THAT THE WEAKENING EFFECT OF SURFACE-ACTIVE AGENTS IS CONTROLLED BY THE RATE OF DESORPTION OF THE METAL SOAP FORMED BY THE REACTION OF THE SURFACE-ACTIVE AGENT AND THE METAL SURFACE. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-282 920

DOUGLAS AIRCRAFT CO. INC LONG BEACH CALIF

CHEMICAL COMPOUNDS FOR METAL SHAPING

(U)

NOV 61 IV CADY, J.R. JAMIESON, J.L.  
REPT. NO. 1111  
CONTRACT: AF19 604 4556  
MONITOR: AFCL 1111

UNCLASSIFIED REPORT

DESCRIPTORS: \*CHEMICAL MILLING, \*GELS, \*METALS,  
\*STAINLESS STEEL, ACETATES, ACIDS, AIRCRAFT, ALLOYS,  
CARBOXYLIC ACIDS, CELLULOSE ACETATES, CHEMICAL  
PROPERTIES, CHEMICALS, CHLORIDES, COLLOIDS, HONEYCOMB  
CORES, IRON COMPOUNDS, MATERIALS, MECHANICAL PROPERTIES,  
METAL PLATES, METHANES (I C), METHYL RADICALS, MOLDING,  
PLASTICS, POROUS MATERIALS, PROCESSING, REAGENTS,  
SOLIDS, SOLUTIONS, SURFACES, TESTS, VINYL RADICAL (U)

FURTHER DEVELOPMENT OF GEL SYSTEMS HAS IMPROVED  
PHYSICAL, CHEMICAL AND MECHANICAL PROPERTIES.  
MILLING METAL PLATE STOCK IS LIMITED BY THE AMOUNT  
OF CHEMICAL ENERGY PRESENTLY AVAILABLE IN THE GEL.  
STAINLESS STEEL HONEYCOMB WAS CHEMICALLY CONTOURED  
WITH GOOD DIMENSIONAL CONTROL. POROUS SOLIDS  
CARRYING LIQUID ETCHANTS FORMED PROFILE CUTS, BUT  
TOLERANCE AND SURFACE FINISH NEED IMPROVEMENT.  
COMPARATIVE TESTS WITH LIQUID AND NON-LIQUID  
ETCHANTS DETERMINED PROBABLE LIMITS OF PERFORMANCE.  
(AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-285 085

ALLOY ENGINEERING AND CASTING CO CHAMPAIGN ILL

A FUNDAMENTAL STUDY OF ROLLING CONTACT FATIGUE (U)

AUG 62 17P HORDON, M. J.  
CONTRACT: NOW-61-0656

UNCLASSIFIED REPORT

DESCRIPTORS: \*DEFORMATION, \*FATIGUE (MECHANICS),  
\*LITHIUM COMPOUNDS, CHEMICAL MILLING, CRYSTAL LATTICE  
DEFECTS, CRYSTALS; ETHYLENES, FLUORIDES, FRICTION,  
LOADING, NYLON, POLYMERS, PREPARATION, ROLLING MILLS,  
SINGLE CRYSTALS, SPHERES, STRESSES, SURFACES (U)

SPHERES OF NYLON AND TEFLON MATERIAL WERE  
ROLLED AT CONSTANT SPEED OVER A (001) SURFACE OF  
CAREFULLY PREPARED CRYSTALS OF LIF UNDER APPLIED  
LOADS RANGING FROM 1 TO 400 GMS. IN THE ROLLING  
CONTACT APPARATUS. UNDER THE IMPACT OF THE  
APPLIED LOAD, A NARROW DEFORMATION TRACK, REVEALED BY  
A HIGH DISLOCATION ETCH PIT DENSITY, WAS LEFT IN THE  
WAKE OF THE ROLLING SPHERE. WITHIN THE TRACK,  
ETCH PITS WERE CLUSTERED IN LOCALIZED AREAS PROBABLY  
CAUSED BY SUBMICROSCOPIC ASPERITIES IN THE SURFACES  
OF CONTACT. ORTHOGONAL (110) SLIP BANDS WERE  
GENERALLY OBSERVED TO BE ALIGNED PARALLEL AND NORMAL  
TO THE ROLLING DIRECTION AT MODERATE STRESS LEVELS;  
HOWEVER, AT HIGHER STRESSES, THE TWO OTHER AVAILABLE  
SLIP SYSTEMS WERE ALSO OBSERVED. THE EXPERIMENTAL  
LOAD DATA ARE GENERALLY IN GOOD AGREEMENT WITH  
THEORETICAL CONSIDERATIONS. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL No. /ZOML6

AD-286 U74

GENERAL DYNAMICS/FORT WORTH TEX.

WING - ALUMINUM SHEET AND PLATE - DYNAMIC ETCHED OR  
CHEM-MILLED - MECHANICAL PROPERTIES - DETERMINATION  
OF (U)

SEP 62 IV FARNER, H.B.:  
REPT. NO. FGT 2100  
CONTRACT: AF33 600 32841

UNCLASSIFIED REPORT

DESCRIPTORS: \*ALUMINUM ALLOYS, \*CHEMICAL MILLING,  
FATIGUE (MECHANICS), MECHANICAL PROPERTIES, METAL  
PLATES, PROCESSING, SHEETS, SURFACES, TENSILE  
PROPERTIES, TEST METHODS, THICKNESS (U)  
IDENTIFIERS: 7075 T ALUMINUM ALLOYS (U)

THE EFFECT OF CHEMICAL MILLING ON MECHANICAL  
PROPERTIES OF 2024, 7075, 7079 AL ALLOYS WAS  
DETERMINED. THE TENSILE STRENGTHS WERE AFFECTED AS  
FOLLOWS: ALL THE 0.064 IN. GAGE 2024-T86 ALCLAD  
ALUMINUM SHOWED STRENGTH LOSSES, BARE 1.50 IN.  
GAGE 7075-T6 AND 7079-T6 ALUMINUM PLATE, SHOWED  
STRENGTHS APPROXIMATELY 10% BELOW THE STRENGTH OF  
THE CONTROL SPECIMENS. THERE WAS NO SIGNIFICANT  
CHANGE IN THE MECHANICAL PROPERTIES WHEN THE .125  
IN. THICK ALCLAD 2024-T86 WAS REDUCED TO 0.098 IN.  
THICKNESS, THE 0.312 IN. THICK 2024-T86 AND 7075-  
T6 WERE REDUCED TO 0.098 IN. THICKNESS, THE 1-1/2  
IN. THICK 7075-T6 WAS REDUCED TO 0.030 IN.  
THICKNESS, OR THE 1-1/2 IN. THICK 7079-T6 IN THE  
LONGITUDINAL DIRECTION WAS REDUCED TO 0.030 IN.  
THICKNESS. THE 7079-T6 IN THE TRANSVERSE DIRECTION  
SHOWED A LOSS IN YIELD STRENGTH OF ABOUT 10%.  
THE 0.312 IN. THICK 2024-T86 PLATE REDUCED TO  
0.015 IN. THICKNESS, SHOWED A LOSS OF APPROXIMATELY  
68% IN YIELD AND ULTIMATE STRENGTHS IN THE  
TRANSVERSE DIRECTION. GENERALLY, ALL THE MATERIALS  
SHOWED SOME LOSS OF DUCTILITY. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL No. /ZOML6

AD-286 872

GENERAL MOTORS CORP KOKOMO IND DELCO RADIO DIV

PRODUCTION ENGINEERING MEASURE TO IMPROVE PRODUCTION  
TECHNIQUES AND INCREASE THE RELIABILITY OF THE  
2N1358A TRANSISTOR (U)

JUL 62 JV KUHNS, J.C.:  
CONTRACT: DA36 D19SC86725

UNCLASSIFIED REPORT

DESCRIPTORS: \*MANUFACTURING METHODS, \*TRANSISTORS,  
CHEMICAL MILLING, CRYSTALS, ELECTRIC CURRENTS,  
GERMANIUM, GROWTH, INDIUM ALLOYS, LIFE EXPECTANCY,  
MATERIALS, PROCESSING, RELIABILITY, SEMICONDUCTORS,  
TEMPERATURE, TEST EQUIPMENT, TEST METHODS, THERMAL  
STRESSES (U)

EFFORTS WERE MADE TO IMPROVE THE RELIABILITY OF  
2N1358A TRANSISTORS BY IMPROVEMENT OF  
MANUFACTURING TECHNIQUES INCLUDING EQUIPMENT AND  
PROCESS MODIFICATIONS, RELIABILITY TESTS, FAILURE  
ANALYSIS AND ANALYTICAL-EMPIRICAL SURFACE STUDIES.  
THE WAFER FLASH-ETCH WAS INCORPORATED IN THE ALLOY  
AREA TO MINIMIZE THE TIME BETWEEN ETCH AND ALLOY.  
ALL OF THE GERMANIUM WAFERS FOR 2N1358 TYPE  
TRANSISTORS ARE CURRENTLY BEING SLICED BY THE  
INTERNAL SAWING METHOD. THE MAJOR RELIABILITY  
PROBLEMS ARE DEGRADATION OF THE COLLECTOR DIODE DUE  
TO SURFACE CONTAMINATION; EMITTER DIODE DEGRADATION  
DUE TO SURFACE DEFECTS; AND HIGH FLOATING POTENTIAL  
DUE TO FRACTURING OF SPUR REGROWTH AT THE COLLECTOR  
PERIPHERY. THE RESIDUAL GAS ANALYSIS HAS  
INDICATED ON ALL UNITS TESTED THE PRESENCE OF WATER  
VAPOR (POSSIBLY ADSORBED) BEYOND WHAT WAS EXPECTED  
IN VIEW OF THE BAKING AND DRY AIR CAPPING PROCEDURE  
IN PRODUCTION. THIS, IN CONJUNCTION WITH  
INDICATIONS OF ADSORBED GAS IN NICKEL PLATED PARTS,  
AND THE RESULTS OF BAKE-OUT RECOVERY TECHNIQUES ON  
DEGRADED COLLECTOR DIODES, PROVIDES CLUES AND  
SUGGESTS EXPERIMENTS TO DETERMINE CORRECTIVE ACTION  
FOR THE COLLECTOR DIODE DEGRADATION PROBLEM. (U)  
AUTHOR) AD-286 8729N2 +++THE RELIABILITY OF  
THE 2N1358A TRANSISTOR BY IMPROVEMENT OF  
MANUFACTURING TECHNIQUES INCLUDING EQUIPMENT AND  
PROCESS MODIFICATIONS, RELIABILITY TEST, FAILURE  
ANALYSIS AND ANALYTICAL-EMPIRICAL SURFACE STUDY. (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL No. /ZOML6

AD-286 886

GENERAL ELECTRIC CO SCHENECTADY N Y

SILICON PLANAR EPITAXIAL TRANSISTOR TYPE 2N2193 (U)

JUL 62 IV JOHNSON, S.O. J

CONTRACT: DA36 039SC86727

UNCLASSIFIED REPORT

DESCRIPTORS: •TRANSISTORS, ALLOYS, ALUMINUM ALLOYS, BORON COMPOUNDS, CHEMICAL MILLING, DIFFUSION, ELECTRIC POTENTIAL, ELECTRODES, EVAPORATION, FAILURE (MECHANICS), GASES, HEATING, HUMIDITY, HYDROGEN, INFRARED LAMPS, LIFE EXPECTANCY, MANUFACTURING METHODS, MATERIALS, NITROGEN, PHOSPHORUS, PROCESSING, RELIABILITY, SEMICONDUCTORS, SILICON, TEMPERATURE, TESTS, THERMAL STRESSES, TRANSONIC CHARACTERISTICS, VIBRATION (U)

CONTENTS: IMPROVED KPR RESOLUTION CONTACT EVAPORATION AND ALLOYING COLLECTOR ETCHING BORON DIFFUSION PHOSPHORUS DIFFUSION COLLECTOR CONTACT TO THE HEAD R INTERSECTIONS RELIABILITY MEASUREMENT FAILURE ANALYSIS (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL No. /ZQML6

AD-286 907  
PHILCO CORP LANSDALE PA

PEM FOR TRANSISTOR MANUFACTURING PROCESS  
IMPROVEMENT

(U)

JUL 62 IV. SANDERS, J.;  
REPT. NO. R 232 1  
CONTRACT: DA36 0395C06720

UNCLASSIFIED REPORT

DESCRIPTORS: (\*TRANSISTORS), (\*MANUFACTURING  
METHODS), RELIABILITY, STRESSES, STORAGE,  
OPERATION, ENCAPSULATION, ELECTRODES,  
TEMPERATURE, SEALS (STOPPERS), DEGASIFICATION,  
CHEMICAL MILLING, HIGH-TEMPERATURE RESEARCH,  
PRODUCTION

(M)

A PRODUCTION ENGINEERING MEASURE WAS STUDIED FOR  
IMPROVEMENT OF PRODUCTION TECHNIQUES TO INCREASE THE  
RELIABILITY FOR THE JET ETCH TRANSISTOR TYPE  
2N501A, WITH A MAXIMUM OPERATING FAILURE RATE OF  
0.01% PER 1000 HOURS AT A 90% CONFIDENCE LEVEL AT  
25 C AS AN OBJECTIVE. EFFORTS WERE MADE TO  
IMPROVE THE FOLLOWING SEVEN MANUFACTURING PROCESSES:  
(1) PLATING EDGE DEFINITION, (2) HIGHER  
TEMPERATURE ALLOYS, (3) LEAD ATTACHMENTS  
(INCLUDES COLLECTOR ATTACHMENTS), (4)  
CONTROLLED FORMATION OF SURFACE OXIDES FOR SURFACE  
STABILIZATION, (5) GETTERING TECHNIQUES FOR  
ENCAPSULATING AND SEALING, (6) THERMAL  
DISSIPATION OF PACKAGE, AND (7) LEAK  
DETERMINATION. ESTABLISHMENT OF A PILOT LINE TO  
INCORPORATE THESE PROCESS IMPROVEMENTS IS REPORTED.  
PRELIMINARY OPERATING STRESS DATA ON TRANSISTORS  
FABRICATED ON THE PILOT LINE INDICATES AN  
IMPROVEMENT IN POWER HANDLING CAPABILITY AS A RESULT  
OF THE PROCESS IMPROVEMENTS COMPLETED. PROBLEMS  
ASSOCIATED WITH OPERATING STRESS TESTING AND WITH  
OBTAINING CORRELATION BETWEEN OPERATING STRESS  
TESTING AND STORAGE STRESS TESTING ARE DISCUSSED.  
(AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-287 594

IIT RESEARCH INST CHICAGO ILL

FIBER-REINFORCED METALS AND ALLOYS

(U)

OCT 62 6P PARIKH, N.M. I  
REPT. NO. B241 3  
CONTRACT: NOW-62-0650

UNCLASSIFIED REPORT

DESCRIPTORS: \*COMPOSITE MATERIALS, \*METALS, \*REINFORCING MATERIALS, ALLOYS, ALUMINUM ALLOYS, BERYLLIUM, CHEMICAL MILLING, FIBERS, FLUORIDES, GERMANIUM, GERMANIUM ALLOYS, HYDROGEN COMPOUNDS, MELTING, METALLIC TEXTILES, MICROSTRUCTURE, NITRIC ACID, POWDER METALS, SOLIDS, WIRE

(U)

BE FIBER-AG ALLOY MATRIX COMPOSITES WERE PREPARED FROM 0.0047 IN DIAM WIRES. ALTHOUGH THERE IS AN ETCHING EFFECT ON THE WIRE SURFACES DUE TO THE HIGH PROCESSING TEMPERATURES, THE BOND BETWEEN BE FIBER SURFACE AND AG MATRIX IS A COHERENT ONE. POWDERS WERE PREPARED BY METING AND ATOMIZATION. HE AL ALLOY MATRIX WS USED FOR PREPARING SOME EXTRUDED BARS FOR DETERMINING THE OPTIMUM HEAT TREATMENT CONDITIONS. ALL THESE COMPOSITES ARE BEING EVALUATED. (AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL No. /ZOML6

AD-291 600

TEXAS INSTRUMENTS INC DALLAS

SILICON SEMICONDUCTOR NETWORKS MANUFACTURING  
METHODS

(U)

NOV 62 IV LATHROP, J.W.; BROWER, W.C.;  
REPT. NO. IR7 865 V6  
CONTRACT: AF33 600 42210  
MONITOR: ASD IR7 865 V6

UNCLASSIFIED REPORT

DESCRIPTORS; \*SEMICONDUCTORS, \*SILICON, \*SUBMINIATURE  
ELECTRONIC EQUIPMENT, BONDING, BRAZING, CHEMICAL  
MILLING, CIRCUITS, CONTAINERS, DESIGN, DIFFUSION,  
ELECTRON BEAMS, EVAPORATION, FILMS, GLASS, GROWTH, LEAD,  
MATERIALS, MATHEMATICAL ANALYSIS, PROCESSING,  
PRODUCTION, SWITCHING CIRCUITS, TEST EQUIPMENT, TEST  
METHODS, VAPOR PLATING, WELDING

(U)

PROCESS STUDIES WERE CONCLUDED. TECHNIQUES HAVE  
BEEN DEVELOPED FOR EVALUATION OF ALL DIFFUSION  
PARAMETERS. ALL MACHINES FOR THE PILOT LINE ARE  
EITHER COMPLETED, BEING CONSTRUCTED OR MODIFIED, OR  
IN ADVANCED DESIGN STAGE. THE PHILOSOPHY GUIDING  
CREATION OF THESE MACHINES IS THAT ALL POSSIBLE  
OPERATIONS WILL BE PERFORMED ON THE FUNCTIONAL  
ELECTRONIC BLOCKS WHILE THEY ARE STILL IN SLICE FORM.  
THESE OPERATIONS INCLUDE CLEANING, POLISHING,  
PHOTORESIST APPLICATIONS, ETCHING, DIFFUSION, AND  
APPLICATION OF EVAPORATED LEADS AND CONTACTS.  
CONSIDERABLE PROGRESS HAS BEEN MADE TOWARD  
PERFECTING A WELDED PACKAGE. (AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-291 876

PHOTOCIRCUITS CORP GLEN COVE N Y

MICROMINIATURE LAYERED PRINTED WIRING

(U)

SEP 62 IV MESSNER, G.; MCCAUGHY, R.; PALUSZEK, M.;  
CONTRACT: DA-36-009-SC-90763

UNCLASSIFIED REPORT

DESCRIPTORS: \*MANUFACTURING METHODS,  
\*MICROMINIATURIZATION (ELECTRONICS), \*PRINTED CIRCUITS,  
CHEMICAL MILLING, COPPER, GELS, LAMINATES, METAL FILMS,  
PHOTOENGRAVING, PICTURES, PLATING, SANDWICH PANELS (U)

SPRAY ETCHING FOR PRODUCING THIN LINES, AND LAMINATING  
TECHNIQUES FOR MULTILAYER PRINTED CIRCUITS IN A  
MICROMINIATURIZATION PROGRAM.

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-293 259

IIT RESEARCH INST CHICAGO ILL

FIBER-REINFORCED METALS AND ALLOYS

(U)

JAN 63 IUP PARIKH, N.M.:  
REPT. NO. B241 4  
CONTRACT: N04-62-0650

UNCLASSIFIED REPORT

DESCRIPTORS: \*COMPOSITE MATERIALS, \*FIBERS, \*METALS,  
\*REINFORCING MATERIALS, ALLOYS, ALUMINUM ALLOYS,  
ATMOSPHERIC PRECIPITATION, BERYLLIUM ALLOYS, CARBIDES,  
CHEMICAL MILLING, CHEMICAL PRECIPITATION, EXTRUSION,  
GRAIN STRUCTURES (METALLURGY), HEAT TREATMENT, IRON  
ALLOYS, MICROSTRUCTURE, POWDER METALLURGY, POWDER  
METALS, PROCESSING, PRODUCTION, SILVER, SINTERING,  
TUNGSTEN ALLOYS, WIRE

(U)

WORK WAS CONTINUED ON THE CHEMICAL ETCHING OF RAWN  
BE WIRES TO REDUCE THEIR DIAMETERS FROM 0.0047 TO  
ABOUT 0.001 INCH. SEVERAL MATRIX ALLOYS WERE  
PREPARED BY ATOMIZING. THESE WERE PREPARED BY  
FIRST MELTING 25 AL IN A CRUCIBLE, ADDING THE  
ALLOYING ELEMENTS TO THE MELT, AND DISINTEGRATING THE  
MOLTEN STREAM OF METAL OF ABOUT 100 PSI PRESSURE OF  
DRY COMPRESSED AIR. THE POWDERS THUS COLLECTED  
WERE SIEVED THROUGH A 60 MESH SCREEN AND COMPACTED IN  
A 1-INCH DIE. IN THE WORK ON BE FIBER COMPOSITES,  
THE SPREAD IN THE SIZE OF THE FIBERS WAS SO GREAT  
THAT IT WAS DIFFICULT TO DESIGNATE AN AVERAGE SIZE.  
THE FIBERS WERE MIXED WITH PLAIN 25 AL POWDER  
(-60 MESH), COMPACTED IN A 1-INCH DIE AT 15 TSI  
AND EXTRUDED AT TEMPERATURES BELOW 870F AT AN  
EXTRUSION RATIO OF ABOUT 40:1. THE TENSILE  
PROPERTIES AND ELASTIC MODULUS WERE MEASURED ON A  
HOUNSFIELD TENSOMETER. IT WAS A CHIEF OBJECTIVE  
OF THIS SERIES OF EXPERIMENTS TO SEE IF THESE  
COMPOSITES COULD BE DENSIFIED BY EXTRUSION TECHNIQUE  
, AND IT APPEARS THAT THIS TECHNIQUE IS SATISFACTORY.  
(AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-293 445  
INNSBRUCK UNIV (AUSTRIA)

DISLOCATION MOBILITY IN ZINC SINGLE CRYSTALS (U)

DEC 62 1V ADAMS, K.H.; VREELAND, T. JR.;  
CONTRACT: NONR22037

UNCLASSIFIED REPORT

DESCRIPTORS: \*DEFORMATION, \*SINGLE CRYSTALS, \*ZINC,  
CHEMICAL MILLING, CONFIGURATION, CRYSTAL LATTICE  
DEFECTS, DENSITY, LOADING, METALLIC CRYSTALS, SHEAR  
STRESSES, STRESSES, TEST METHODS (U)

RESULTS OF A STUDY OF DISLOCATION MOBILITY IN HIGH  
PURITY ZINC SINGLE CRYSTALS ARE PRESENTED.  
DISLOCATION POSITIONS WERE DETERMINED USING A  
SPECIAL ETCHING TECHNIQUE, AND THE DISLOCATION DEN-  
SITY AND CONFIGURATION WERE DETERMINED BEFORE AND AFTER  
STATIC LOADING AND SHORT PULSE LOADING. LOADING  
AT STRESS LEVELS SLIGHTLY BELOW THE FLOW STRESS  
PRODUCE LOCAL DISLOCATION ARRANGEMENT, WITH THE  
MAXIMUM DISLOCATION DISPLACEMENT SOMEWHAT LESS THAN  
THE SUB-BOUNDARY SPACING. AT THE FLOW STRESS  
DISLOCATIONS PENETRATE THE SUB-BOUNDARIES AND  
RELATIVELY LARGE DISLOCATION DISPLACEMENTS ARE IN-  
DICATED (COMPARABLE TO THE SPECIMEN DIMENSIONS)  
IN STRESS PULSE TESTS OF APPROXIMATELY 30 SEC  
DURATION. SHORT DURATION STRESS PULSE LOADING AT A  
STRESS LEVEL APPROXIMATELY 70 TIMES THE FLOW STRESS  
PRODUCED A MAXIMUM DISLOCATION VELOCITY OF APPROXIMATELY  
6 PER CENT OF THE SHEAR WAVE VELOCITY.  
(AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL No. /ZDML6

AD-294 786

ARMY ELECTRONICS LABS FORT MONMOUTH N J

DESIGN CONSIDERATIONS FOR MICROWAVE GERMANIUM TUNNEL  
DIODES (U)

SEP 62 W WANDINGER, L. IKLOHN, K. I  
REPT. NO. TR2318

UNCLASSIFIED REPORT

DESCRIPTORS: •DIODES, •MANUFACTURING METHODS,  
•SEMICONDUCTORS, CHEMICAL MILLING, ELECTROFORMING,  
ENCAPSULATION, GERMANIUM, MEASUREMENT, MICROWAVE  
EQUIPMENT, NEGATIVE RESISTANCE CIRCUITS, PRODUCTION,  
RESISTANCE (ELECTRICAL), SURFACE PROPERTIES (U)

A DISCUSSION IS PRESENTED ON THE TECHNOLOGY AND  
PROBLEMS INVOLVED IN THE DESIGN CONSIDERATIONS,  
FABRICATION, AND MEASUREMENT OF GERMANIUM TUNNEL  
DIODES. FABRICATION INCLUDES MATERIAL PREPARATION,  
METHODS OF CREATING ABRUPT P-N JUNCTIONS SUCH AS DOT  
ALLOYING, ELECTRICAL FORMING OR PULSE DISCHARGE  
FORMING AND SOLUTION GROWTH, ETCHING PROCEDURES  
NECESSARY TO OBTAIN LOW PEAK CURRENTS AND HIGH PEAK  
TO VALLEY CURRENT RATIOS, AND PACKAGING  
CONSIDERATIONS FOR LOW SERIES INDUCTANCE.  
MEASUREMENT TECHNIQUES TO DETERMINE THE IMPORTANT  
HIGH-FREQUENCY PARAMETERS,  $R_S$ ,  $L_S$ ,  $C$ , AND  $R_N$ , OF  
THE DIODE ARE DISCUSSED. THE RESULTS OF  
EXPERIMENTAL UNITS EXHIBITING CUTOFF FREQUENCIES UP  
TO 5 GC ARE TABULATED. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-295 057

SPRAGUE ELECTRIC CO NORTH ADAMS MASS

PRODUCTION ENGINEERING MEASURE RELIABILITY  
IMPROVEMENT JET ETCH TRANSISTOR

(U)

OCT 62 IV GAGNE, R.M.; KRANTZ, J.E.; FOLSTER,  
J.H.D.;

UNCLASSIFIED REPORT

DESCRIPTORS: \*MANUFACTURING METHODS, CHEMICAL MILLING,  
ELECTRICAL PROPERTIES, LIFE EXPECTANCY, PRODUCTION;  
RELIABILITY; TRANSISTORS (U)

THE OPTIMUM COLLECTOR RESISTIVITY, THE OPTIMUM  
COLLECTOR THICKNESS, THE OPTIMUM ELECTRICAL  
BASEWIDTH, AND THE PROPER EMITTER PLACEMENT WERE  
DETERMINED. INVESTIGATIONS LEADING TO THESE  
DETERMINATIONS ARE DESCRIBED. WORK HAS CONTINUED  
TOWARD DEVISING A METHOD TO STOP AUTOMATICALLY THE  
DELINEATION ETCHING PROCESS AFTER THE COLLECTOR  
JUNCTION WAS DELINEATED. SOME PROGRESS WAS MADE IN  
THIS AREA, AND WORK IS CONTINUING. TWO NEW PROCESS  
STEPS WERE INTRODUCED AND DESCRIPTIONS OF THESE ARE  
ALSO GIVEN. THE STATUS OF THE PROGRAM, LIFE TEST  
RESULTS TO DATE, AND CURRENT FAILURE RATES ARE ALSO  
PRESENTED. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-295 752

DOUGLAS AIRCRAFT CO INC LONG BEACH CALIF

CHEMICAL COMPOUNDS FOR METAL SHAPING (U)

JAN 63 IV JAMIESON, J.L.; PARTRIDGE, E.G.  
REPT. NO. TR7 648 V3  
CONTRACT: AF33 600 43027  
MONITOR: ASD TR7 648 V3

UNCLASSIFIED REPORT

DESCRIPTORS: \*HONEYCOMB CORES, \*STAINLESS STEEL, ACIDS,  
CARBOXYMETHYLCELLULOSE, CELLULOSE ACETATES, CHEMICAL  
MILLING, CHEMICALS, ELECTRIC CURRENTS, ELECTROCHEMISTRY,  
ELECTRODES, ELECTROLYTES, ELECTROLYTIC CELLS, GELS,  
METALS, POLARIZATION, POROUS MATERIALS, PROCESSING,  
REDUCTION, RESISTANCE (ELECTRICAL), SOLIDS, SOLUTIONS,  
THICKNESS (U)

ELECTROLYTIC ETCHING OF STAINLESS STEEL PLATES AND HONEYCOMB  
CORES; VARIOUS CHEMICAL COMPOUNDS USED FOR METAL  
SHAPING; PROCESSING OF AIRCRAFT MATERIALS.

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-295 707  
TEXAS INSTRUMENTS, INC DALLAS

RESEARCH AND DEVELOPMENT OF HIGH TEMPERATURE  
SEMICONDUCTOR DEVICES

(U)

DEC 61 17 WURST, E.C.; PETRITZ, R.L. ;  
CONTRACT: NOBSR85424

UNCLASSIFIED REPORT

DESCRIPTORS: ARSENIDES, CHEMICAL MILLING, DIFFUSION,  
ENCAPSULATION, GALLIUM COMPOUNDS, GOLD ALLOYS,  
MAGNESIUM, MANUFACTURING METHODS, OXIDES, SILICON  
COMPOUNDS, TEMPERATURE, TESTS, TIN ALLOYS

(U)

GALLIUM ARSENIDE TRANSISTORS ARE FABRICATED AND  
TESTED AT 150 C! SEVERAL TECHNIQUES ARE INVESTIGATED,  
INCLUDING MAGNESIUM DIFFUSION IN GAAS AND THE  
FEASIBILITY OF SiO<sub>2</sub> COATINGS ON GAAS AS A MASK AGAINST  
IMPURITY DIFFUSION; POSTALLOY DIFFUSION AND CHEMICAL  
POLISHING.

UNCLASSIFIED

UDC REPORT BIBLIOGRAPHY SEARCH CONTROL No. /ZDML6

AJ-400 732

PHOTOCIRCUITS CORP GLEN COVE N Y

MICROMINIATURE LAYERED PRINTED WIRING (U)

DEC 62 IV MESSNER, G. | MCCA W, R. | PALUSZEK, M. |  
CONTRACT: DA-36-039-SC-90783

UNCLASSIFIED REPORT

DESCRIPTORS: CHEMICAL MILLING, CONFIGURATION, COPPER,  
DRILLING MACHINES, ELECTRIC CONNECTORS, ELECTRIC  
TERMINALS, EPOXY PLASTICS, GOLD, LAMINATED PLASTICS,  
LAMINATES, MANUFACTURING METHODS, METAL COATINGS,  
MICROMINIATURIZATION (ELECTRONICS), NICKEL, PANEL BOARDS  
(ELECTRICITY), PLATING, PRINTED CIRCUITS, PRODUCTION,  
SOLDERING (U)

PROCESS PARAMETERS FOR THE MANUFACTURE OF MICROMINIATURE  
LAYERED PRINTED WIRING WITH PLATED-THROUGH HOLES AS  
THE INTERCONNECTING LINK BETWEEN LAYERS.

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-402 164

GENERAL DYNAMICS/POHONA CALIF

EFFECT OF SURFACE FINISHES ON FATIGUE LIFE (U)

MAR 59 IV

WINSLOW, E.K.; LINDENEAU, G.D.; WISE,

W.E.;

REPT. NO. 8926 142

CONTRACT: AF33 657 8926

UNCLASSIFIED REPORT

DESCRIPTORS: ALLOYS, ALUMINUM ALLOYS, CHEMICAL MILLING,  
COLD WORKING, DATA, EFFECTIVENESS, FATIGUE (MECHANICS),  
HEAT TREATMENT, LIFE EXPECTANCY, MACHINING, STEEL,  
STRESSES (U)

IDENTIFIERS: 4340 STEEL (U)

THE EFFECT OF SURFACE FINISHES PRODUCED BY CHEMICAL MILLING  
AND MICRO-GLASS-PEENING ON THE FATIGUE LIFE  
OF STEEL AND ALUMINUM ALLOYS.

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-404 185

GENERAL ELECTRIC CO SCHENECTADY N Y

SILICON PLANAR EPITAXIAL TRANSISTPE 2N2193.

(U)

DESCRIPTIVE NOTE: QUARTERLY REPT. NO. 3, 31 OCT 62-31  
JAN 63.

JAN 63 .1V

CONTRACT: DA36 039SC86727

UNCLASSIFIED REPORT

DESCRIPTORS: \*TRANSISTORS, VAPOR PLATING, VACUUM  
APPARATUS, SILICON, CHEMICAL MILLING, BONDING,  
CLEANING, ALLOYS, BORON, PHOSPHORUS,  
DIFFUSION, RELIABILITY (ELECTRONICS), MEASURE  
MENT, MANUFACTURING METHODS.

(U)

IDENTIFIERS: PASSIVATION (SEMICONDUCTOR).

(U)

CONTENTS: IMPROVED KPR RESOLUTION CONTACT  
EVAPORATION AND ALLOYING COLLECTOR ETCHING BORON  
DIFFUSION PHOSPHORUS DIFFUSION COLLECTOR  
CONTACT TO THE HEADER INTERCONNECTIONS  
RELIABILITY MEASUREMENT INSPECTION AND QUALITY  
CONTROL PLAN

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-404 537

RADIO CORP OF AMERICA SOMERVILLE N J

PRODUCTION ENGINEERING MEASURE ON 2N1708 SILICON  
PLANAR EPITAXIAL TRANSISTOR. (U)

DESCRIPTIVE NOTE: QUARTERLY REPT. NO. 3, 1 NOV 62-31  
JAN 63,

JAN 63 36P POSSEMATO, L.R.;

CONTRACT: DA36 039SC86729

UNCLASSIFIED REPORT

DESCRIPTORS: \*MANUFACTURING METHODS, \*TRAN  
SISTORS, SILICON, CLEANING, EPITAXIAL GROWTH,  
DIFFUSION, CHEMICAL MILLING, CONTAMINATION,  
IMPURITIES, PHOSPHORUS, FIXED CONTACTS, GOLD,  
MALFUNCTIONS; PROCESSING. (U)

A TECHNIQUE OF ETCHING THE WAFERS WITH ANHYDROUS  
HCL IN THE EPITAXIAL TUBE PRIOR TO EPITAXIAL  
DEPOSITION WAS INCORPORATED INTO THE PROCESS. THE  
OXIDE ON THE SURFACE OF THE WAFER SERVES AS A MASK  
DURING THE DIFFUSION OPERATION AND GENERALLY SERVES  
TO PROTECT THE SILICON SURFACES DURING WAFER  
PROCESSING. IN PERFORMING THESE FUNCTIONS,  
HOWEVER, IMPURITIES MAY BE DIFFUSED INTO THE OXIDE AT  
THE HIGH DIFFUSION TEMPERATURES. A METHOD WAS  
DEVELOPED PROVIDING THE CLEANEST POSSIBLE OXIDE TO  
IMPROVE THE SURFACE PROTECTION ON THE FINISHED  
PELLETS. EXPERIMENTS ARE ALSO BEING MADE ON BAKING  
OF OXIDE TO DIFFUSE ENTRAPPED WATER MOLECULES TO THE  
SURFACE FOR SUBSEQUENT EVAPORATION.

(AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-405 861

WESTINGHOUSE ELECTRIC CORP YOUNGWOOD PA

MICROMINIATURE INTEGRATED CIRCUIT PACKAGE. (U)

DESCRIPTIVE NOTE: QUARTERLY PROGRESS REPT. NO. 2, 1 OCT  
62-1 JAN 63,

JAN 63 IIP BARBARO, E.P.;

CONTRACT: DA36 039SC90850

PROJ: DA PROJ. 3A99 21 002 01

UNCLASSIFIED REPORT

DESCRIPTORS: \*MICROMINIATURIZATION (ELEC  
TRONICS), \*INTEGRATED CIRCUITS, \*PACKAGED  
CIRCUITS, \*MODULES (ELECTRONICS), PROCESSING,  
SEALS (STOPPERS), GRAPHITE, GLASS, CHEMICAL  
MILLING, CLEANING, MECHANICAL PROPERTIES. (U)

TWO SUCCESSIVE DESIGN MODIFICATIONS WERE MADE TO  
THE GRAPHITE GLASSING BOATS IN ORDER TO ACHIEVE MORE  
UNIFORM PACKAGE APPEARANCE. FIFTY PACKAGE SAMPLES  
WERE SUBMITTED FOR MECHANICAL EVALUATION.  
TECHNIQUES FOR SEALING THE INTEGRATED CIRCUIT  
PACKAGE WERE ESTABLISHED. IMPROVED CLEANING  
TECHNIQUES WERE ESTABLISHED FOR DEOXIDIZING KOVAR  
PARTS PRIOR TO GOLD PLATING RESULTING IN LESS PITTING  
OF THE METAL. STAMPED LEAD PRE FORMS RECEIVED  
DURING THIS PERIOD. THE FIRST ONE HUNDRED  
MICROMINIATURE CIRCUIT PACKAGES SUBMITTED WERE  
FABRICATED WITH ETCHED LEADS. THE STAMPED LEADS ARE  
MORE UNIFORM IN CROSS SECTION. CERAMIC MICROMODULES  
WITH PADS WERE DESIGNED AND ORDERED. THIS  
MICROMODULE WILL BE UTILIZED TO DEVELOP AN INTEGRAL  
PACKAGE USING THE CERAMIC MICROMODULE AS A BASE.  
(AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-408 19U

ARMY ELECTRONICS LABS FORT MONMOUTH N J

TECHNOLOGY FOR PNP PLANAR SILICON TRANSISTORS:  
SWITCHING AND AMPLIFYING.

(U)

MAR 63 21P LAROCQUE, ARMOND P.; YATSKO,  
ROBERT S.; ROGEL, ALEX.; JACKSON, RAYMOND I.; RIBLE,  
VINCENT E.;

REPT. NO. TR-2339

PROJ: DA-3-A-992100302

UNCLASSIFIED REPORT

DESCRIPTORS: (TRANSISTORS, MANUFACTURING  
METHODS), DIFFUSION, IMPURITIES, ANTIMONY,  
BONDING, GAIN, CRYSTAL GROWTH, SILICON,  
CHEMICAL MILLING, POLISHES, PHOTOENGRAVING,  
BORON, METAL FILMS, TESTS, CAPACITORS,  
RESISTORS, ULTRAHIGH FREQUENCY, GOLD, MICRO  
MINIATURIZATION (ELECTRONICS).

(U)

IDENTIFIERS: 1963, PLANAR TRANSISTORS.

(U)

PROCESSES AND TECHNIQUES REQUIRED FOR FABRICATION  
OF EXPERIMENTAL PLANAR PNP SILICON TRANSISTORS WERE  
DEVELOPED AND DEMONSTRATED AS FEASIBLE. PROCESSES  
INVOLVED INCLUDE MATERIAL PREPARATION, ANTIMONY BASE  
DIFFUSION, BORON EMITTER DIFFUSION, OXIDE MASKING,  
PHOTORESIST TECHNIQUES, SIMULTANEOUS GOLD METALIZING  
OF EMITTER AND BASE REGIONS, COLLECTOR ALLOY CONTACT  
AND BIASING, AND THERMAL COMPRESSION BONDING. INITIAL  
TRANSISTORS HAVE TYPICAL DC BETA VALUES OF 35 TO 40  
AND FT VALUES AS HIGH AS 350 MCS. PROCESSES  
DESCRIBED WERE ALSO USED IN PRELIMINARY FABRICATION  
OF SOLID STATE MICROCIRCUIT PASSIVE COMPONENTS.  
(AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-412 841

LEAR SIEGLER INC SANTA MONICA CALIF

SEMICONDUCTOR THIN FILMS.

(U)

DESCRIPTIVE NOTE: QUARTERLY REPT. NO. 6, 1 APR-30 JUNE 63.

63 18P

CONTRACT: AF33 657 7623

UNCLASSIFIED REPORT

DESCRIPTORS: (\*SEMICONDUCTING FILMS), MANUFACTURING METHODS, VAPOR PLATING, VACUUM, GALLIUM COMPOUNDS, ARSENIDES, HALL EFFECT, MEASUREMENT, ELECTRON MICROSCOPY, CHEMICAL MILLING, X-RAY DIFFRACTION ANALYSIS.

(U)

IDENTIFIERS: THIN FILMS

(U)

(1) TO DEPOSIT FILMS IN A DYNAMIC 10 TO THE -8TH POWER VACUUM SYSTEM; (2) TO INVESTIGATE ANNEALING OF GAAS FILMS; (3) TO MAKE HALL MEASUREMENTS AT A SERIES OF TEMPERATURES; (4) TO INVESTIGATE DEPOSITION AT MICRONS PER SECOND; (5) TO IMPROVE THE RESOLUTION IN ELECTRON MICROSCOPE SURFACE STUDIES AND TO INVESTIGATE A SETUP FOR ETCHING THICKER FILMS DOWN TO THICKNESSES SUITABLE FOR ELECTRON MICROSCOPY; AND (6) TO CONTINUE DEVICE STUDIES WITH FILMS OF AVAILABLE QUALITY. (AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL No. /ZOML6

AD-414 913

RADIO CORP OF AMERICA SOMERVILLE N J

PRODUCTION ENGINEERING MEASURE ON 2N170B  
SILICON PLANAR EPITOXIAL TRANSISTOR.

(U)

DESCRIPTIVE NOTE: QUARTERLY REPT. NO. 4, 1 FEB-30 APR  
63,

APR 63 87P WARREN, A. I POSSEMATO, L. R. I

CONTRACT: DA36 039SC86729

UNCLASSIFIED REPORT

DESCRIPTORS: (\*TRANSISTORS, MANUFACTURING  
METHODS), (\*MANUFACTURING METHODS, TRANSIS  
TORS), CLEANING, EPITOXIAL GROWTH, SEMICONDC  
TOR DEVICES, CHEMICAL MILLING, FIXED CONTACTS,  
GOLD, ALUMINUM, CONTAMINATION, BONDING,  
QUALITY CONTROL, RELIABILITY, PROCESSING,  
SURFACES.

(U)

IDENTIFIERS: 1963.

(U)

PROCESS IMPROVEMENTS WERE COMPLETED IN ALL AREAS  
INVESTIGATED. AN IMPROVED METHOD OF REMOVING  
PHOTORESIST WAS DEVELOPED. A STUDY OF INORGANIC  
REAGENT MATERIALS AS SOURCES OF SEMI-CONDUCTOR  
SURFACE CONTAMINATION WAS COMPLETED. CONCLUSIONS  
CONCERNING THE CONCENTRATIONS OF IMPURITIES AND THE  
EFFECTIVENESS OF VARIOUS DESORPTION TECHNIQUES ARE  
INCLUDED. THE USE OF THIN ALUMINUM CONTACTS HAS  
INHIBITED FORMATION OF "PURPLE PLAGUE".  
EXPERIMENTS WITH GOLD CONTACTS WERE UNSUCCESSFUL.  
THE USE OF GOLD ALLOY WIRE DID NOT MATERIALLY  
IMPROVE THE BOND STRENGTH. NAILHEAD BONDING WITH  
A SMALLER DIAMETER GOLD WIRE TO REDUCE THE SIZE OF  
THE BALL MET WITH ONLY LIMITED SUCCESS. A PROGRAM  
OF RELIABILITY TESTING AND ANALYSIS AND STUDIES OF  
THERMAL RESISTANCE MEASUREMENTS FROM JUNCTION TO  
AMBIENT (T SUB J-A) WERE COMPLETED.

(AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-418 220

KELSEY-HAYES CO ROMULUS MICH

THE DESIGN AND EVALUATION OF PERFORATED ION  
EMITTERS.

(U)

DESCRIPTIVE NOTE: FINAL REPT. MAY 62-AUG 63,  
SEP 63 IV PETRICK, E. N.; KRAUSS, J. J.;  
CONTRACT: AF33 657 8638  
PROJ: AF-3141  
TASK: 3141U2  
MONITOR: ASD TOR63 750

UNCLASSIFIED REPORT

DESCRIPTORS: (\*ION ENGINES, ION SOURCES), (\*ION  
SOURCES, CESIUM), (\*CESIUM, IONIZATION),  
ELECTRIC PROPULSION, MANUFACTURING METHODS,  
ELECTRON BEAMS, CHEMICAL MILLING, SHEETS,  
RELIABILITY, FEASIBILITY STUDIES, POROUS  
METALS, GAS FLOW, NITROGEN, TUNGSTEN, MOLY  
BDENUM.

(U)

IDENTIFIERS: 1963.

(U)

THE FEASIBILITY OF UTILIZING EMITTERS OF PERFORATED SOLID SHEET RATHER THAN A SINTERED POWDER STRUCTURE WAS INVESTIGATED WITH THE OBJECTIVE OF INCREASING THE RELIABILITY AND DURABILITY OF ION ENGINES. VARIOUS TECHNIQUES FOR DRILLING MICRON-SIZE HOLES IN REFRACTORY METALS WERE EXPLORED. TWO OF THESE PROCESSES, ELECTRON BEAM DRILLING AND CHEMICAL PHOTO-ETCHING, WERE USED TO PROVIDE TEST EMITTERS WITH HOLE SIZES IN THE 10-MICRON RANGE. AN ELECTRON BEAM DRILLED EMITTER WAS CS FLOW TESTED FOR 83 HOURS AND EXHIBITED, WITHIN EXPERIMENTAL LIMITS, NO DISCERNIBLE CHANGE IN HOLE SIZE OR FLOW CONDUCTANCE. IN SEPARATE TESTS CORRELATION WAS MADE OF THEORETICAL AND MEASURED FLOW RATES OF N AND CS THROUGH THE EMITTERS. IT WAS DETERMINED THAT THE MEASURED CS FLOW RATE EXCEEDED THE THEORETICALLY CALCULABLE VALUE BASED ON AVAILABLE SURFACE DIFFUSION FORMULAE.  
(AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-418 684

GENERAL ELECTRIC CO SYRACUSE N Y

MATRIX CONTROLLED DISPLAY DEVICE.

(U)

DESCRIPTIVE NOTE: INTERIM DEVELOPMENT REPT. NO. 1, 1  
JULY 16 SEP 63.

AUG 63 30P

CONTRACT: NOBSR89334

PROJ: SR080301

TASK: 9475

UNCLASSIFIED REPORT

DESCRIPTORS: (\*DISPLAY SYSTEMS, ELECTRONIC  
RECORDING SYSTEMS), (\*ELECTRONIC RECORDING SYSTEMS,  
(\*OMETRIC FORMS), FEASIBILITY STUDIES, VIEWING  
SCREENS, BRIGHTNESS, THERMOPLASTICS,  
DEFORMATION, CIRCUITS, PHOTOENGRAVING, OPTICS,  
CHEMICAL MILLING, ELECTRODES, TEST  
EQUIPMENT.

(U)

IDENTIFIERS: 1963. MATRIX CONTROLLED DISPLAY.

(U)

A DESCRIPTION IS PRESENTED OF THE WORK ACCOM-  
PLISHED TO DEVELOP A FEASIBILITY MODEL OF A MATRIX  
CONTROLLED DISPLAY DEVICE USING TECHNIQUES CALLED IN-  
AIR SURFACE DEFORMATION RECORDING AND TIRP (TOTAL  
INTERNAL REFLECTION PRISROJECTION. TO  
INTRODUCE THE READER TO THESE TECHNIQUES, A BRIEF  
DESCRIPTION OF THEIR BASIC PRINCIPLES IS GIVEN.  
THE TEST SETUP TO PROVIDE AN ELEMENTAL PORTION OF  
THE LARGE SCREEN DISPLAY AT 20 TO 30 FOOT-LAMBERTS  
BRIGHTNESS BY OPTICAL READOUT OF DEFORMATIONS ON A  
THERMOPLASTIC OR OIL MEDIUM IS DISCUSSED.  
CIRCUITRY TO IMPLEMENT THE DEFORMATION RECORDING  
TECHNIQUE USING X-Y MATRIX CONTROL IS GIVEN. A  
BASIC MECHANICAL CONFIGURATION IS CONSIDERED.  
INFORMATION IS PROVIDED ON THE PREPARATION OF  
ARTWORK AND A PHOTOGRAPHIC MASK NECESSARY TO  
FABRICATE MATRIX ELECTRODES AT 5, 10, AND 20 LINE  
PAIRS PER MILLIMETER WITH THREE ELECTRODE WIDTHS.  
THE RESULTS OF INITIAL EXPERIMENTS IN ETCHING OF  
TRANSPARENT, CONDUCTIVE COATINGS TO FORM THE  
ELECTRODES ARE GIVEN. (AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-419 585

SYLVANIA ELECTRIC PRODUCTS INC WOBURN MASS

PRODUCTION ENGINEERING MEASURE FOR GALLIUM  
ARSENIDE VARACTOR DIODE.

(U)

DESCRIPTIVE NOTE: QUARTERLY PROGRESS REPT. NO. 4, 1 MAR-  
31 MAY 63,

MAY 63 IV DAVIS, C.F.; FELDMAN, E.J.;

CONTRACT: DA36 D39SC86736

UNCLASSIFIED REPORT

DESCRIPTORS: (VARACTOR DIODES, PRODUCTION),  
(MANUFACTURING METHODS, VARACTOR DIODES),  
GALLIUM ALLOYS, ARSENIC ALLOYS, EPITAXIAL  
GROWTH, FIXED CONTACTS, CONTAINERS, CAPACI  
TANCE, ELECTRIC POTENTIAL, CHEMICAL MILLING,  
DIFFUSING, IMPURITIES, ZINC, TELLURIUM,  
ARSENIC, PHOTOENGRAVING.

(U)

IDENTIFIERS: 1963, MESA (SEMICONDUCTOR).

(U)

STUDIES TO OBTAIN THE PROCESSES NECESSARY FOR THE  
HIGH VOLUME PRODUCTION OF GALLIUM ARSENIDE VARACTOR  
DIODES ARE DESCRIBED IN THIS REPORT. THESE  
INVESTIGATIONS INCLUDE STUDIES OF MESA CONTACTS,  
EPITAXIAL MATERIAL, PACKAGING, OHMIC CONTACTS AND  
ETCHING PROCEDURES. THE RESULTS OF THE FABRICATION  
OF COMPLETELY EPITAXIAL DIODES AND DIFFUSED  
EPITAXIAL DIODES ARE DISCUSSED AS WELL AS  
CONTROLABLE ETCHING PROCEDURES FOR VOLUME PRODUCTION.  
(AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL No. /ZOML6

AD-420 375

WESTINGHOUSE ELECTRIC CORP DAYTON OHIO

500 C SILICON CARBIDE RECTIFIER PROGRAM. (U)

DESCRIPTIVE NOTE: INTERIM TECHNICAL PROGRESS REPT. NO. 8.

1 JULY30 SEP 63.

OCT 63

20P

CHANG, H. C. ; JENNINGS, V. J.

; THORNBURG, D. R. ; KROKO, L. J. ; OSTROSKI, J. ;

CONTRACT: AF33 657 7027

PROJ: 7 727

MONITOR: ASD IR7 727, VOL. 8

UNCLASSIFIED REPORT

DESCRIPTORS: (\*CRYSTAL RECTIFIERS, SILICON ALLOYS),  
(\*SILICON ALLOYS, CRYSTAL RECTIFIERS), (\*DIODES  
(SEMICONDUCTORS), SILICON ALLOYS), POWER EQUIPMENT  
PARTS, CARBON ALLOYS, HIGHTEMPERATURE RESEARCH,  
EPITAXIAL GROWTH, IMPURITIES, CHEMICAL MILLING, BORATES,  
SODIUM COMPOUNDS, LIFE EXPECTANCY, STORAGE, SURFACE  
PROPERTIES, MANUFACTURING METHODS, TESTS (U)

IDENTIFIERS: 1963 (U)

EFFORTS WERE CONTINUED ON THE DEVELOPMENT OF 500  
DEGREE C SILICON CARBIDE RECTIFIERS. THE GROWTH  
RATE OF SILICON CARBIDE CRYSTALS PREPARED BY THE  
SUBLIMATION METHOD WAS DETERMINED BY MEASURING THE  
AMOUNT OF GROWTH BETWEEN SUCCESSIVE, TIMED DOPANT  
ADDITIONS. THIS WAS COMPARED WITH THE GROWTH RATE  
AS OBTAINED FROM A SIMPLE MODEL. ALL VALUES AGREE  
WITHIN A FACTOR OF FIVE. THE USE OF MOLTEN BORAX  
AS AN ETCHANT FOR SILICON CARBIDE WAS STUDIED. DUE  
TO ITS RELATIVELY SLOW ETCH RATE (ABOUT 30 TIMES  
SLOWER THAN A MOLTEN SODIUM PEROXIDE-SODIUM HYDROXIDE  
MIXTURE) A MUCH FINER CONTROL OF THE ETCHING IS  
POSSIBLE. DETAILS ARE GIVEN ON THE LIFE AND  
STORAGE TESTS WHICH WERE SUCCESSFULLY PASSED BY TWO  
SILICON CARBIDE RECTIFIERS. AN OPEN TUBE-FLOWING  
GAS SYSTEM WAS SHOWN SUITABLE FOR THE SURFACE  
PASSIVATION OF GROUPS OF SILICON CARBIDE RECTIFIERS.  
(AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL No. /ZOML6

AD-422 492

BELL TELEPHONE LABS INC WHIPPANY N J

ENGINEERING SERVICES ON TRANSISTORS.

(U)

DESCRIPTIVE NOTE: QUARTERLY PROGRESS REPT. NO. 1, 1 APR-

30 JUNE 63,

SEP 63

IV

ARNOLD, S. R. ; DAVIS, R. E. ;

GIBBONS, G. ; KOCIS, J. ; MARTERSTECK, K. E. ;

REPT. NO. 12

CONTRACT: DA36 039AMC0227

PROJ: 3A99 21 001

UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: CONTINUATION OF CONTRACT DA36  
0395C9U759.

DESCRIPTORS: (\*TRANSISTORS, MANUFACTURING METHODS),  
(\*INTEGRATED CIRCUITS, TRANSISTORS), GERMANIUM, SILICON,  
ELECTRIC POTENTIAL, SUPERHIGH FREQUENCY, CHEMICAL  
MILLING, ELECTRIC CURRENTS, EPITAXIAL GROWTH, ELECTRICAL  
CONDUCTANCE, RESISTORS, AGING (MATERIALS), DIODES  
(SEMICONDUCTOR), CIRCUITS, ELECTRONIC SWITCHES,  
ULTRAHIGH FREQUENCY, TEMPERATURE, BONDING, OXIDES (U)  
IDENTIFIERS: THIN FILMS, THIN FILMS  
ELECTRONICS (U)

RESEARCH CONCERNS STUDIES AND INVESTIGATIONS  
RELATED TO TRANSISTORS AND TRANSISTOR-LIKE DEVICES,  
WITH A VIEW TOWARD DEMONSTRATING AND INCREASING THE  
PRACTICABILITY OF THEIR USE IN OPERATING EQUIPMENT.  
WORK IS DISCUSSED ON A 6-GC GERMANIUM TRANSISTOR  
AND INTEGRATED CIRCUIT DEVICES. A COMPARISON IS  
MADE OF ELECTRICAL BREAKDOWN CHARACTERISTICS OF  
GERMANIUM DIODES MADE BY PLANAR TECHNIQUES AND BY  
MESA ETCHING. IT IS SHOWN THAT FOR THE PLANAR TYPE  
THE REVERSE CURRENT VOLTAGE CHARACTERISTIC WILL BE  
SOFTER THAN THAT OF A MESA DIODE FROM THE SAME  
MATERIAL AND THE BREAKDOWN VOLTAGE WILL BE LOWER.  
BREAKDOWN VOLTAGE IS CALCULATED FOR EPITAXIAL  
GERMANIUM AND SILICON STRUCTURES. IT IS SHOWN THAT  
WHEN THE CONDUCTIVITY OF THE SUBSTRATE AND THE  
DIFFUSED LAYER ARE BOTH MUCH GREATER THAN THAT OF THE  
EPITAXIAL LAYER, THEN FOR THIN LAYERS THE BREAKDOWN  
VOLTAGE DEPENDS ONLY ON THE THICKNESS BETWEEN THE  
DIFFUSED JUNCTION AND THE SUBSTRATE. FABRICATION  
TECHNIQUES AND PROBLEMS RELATED TO THE 6-GC  
TRANSISTOR ARE DISCUSSED. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-422 940

RAYTHEON CO LEWISTON MAINE

PRODUCTION ENGINEERING MEASURE ON SILICON ALLOY  
TRANSISTORS. (U)

DESCRIPTIVE NOTE: QUARTERLY REPT. NO. 3, 1 JAN-31 MAR  
63,

MAR 63 28P JONES, R. W. 1

CONTRACT: DA36 039SC86744

UNCLASSIFIED REPORT

DESCRIPTORS: (\*TRANSISTORS, PRODUCTION), (\*MANUFACTURING  
METHODS, TRANSISTORS), RESISTANCE (ELECTRICAL), SILICON,  
RELIABILITY (ELECTRONICS), TIN, ALLOYS, FIXED CONTACTS,  
SOLDERING, CHEMICAL MILLING, FAILURE (MECHANICS),  
QUALITY CONTROL, CRYSTAL LATTICE DEFECTS, SOLDERING  
FLUXES (U)

IDENTIFIERS: 1963; JET ETCHING, VIBRATORY ETCHING,  
PASSIVATION (SEMICONDUCTOR) (U)

EFFORTS CONTINUED ON THE IMPROVEMENT OF PRODUCTION  
TECHNIQUES TO INCREASE THE RELIABILITY OF SILICON  
TRANSISTORS. FURTHER CONTROL OF CHIP DIMENSIONS WAS  
ACHIEVED. THE BULK MATERIAL PARAMETERS OF  
RESISTIVITY AND DISLOCATION DENSITY WERE STUDIED.  
METALLOGRAPHIC ANALYSIS OF ALLOYING LED TO FIRING  
JIG REDESIGN. THE EFFECTS OF TIN, DISLOCATION  
DENSITY, AND CHIP THICKNESS ON ALLOYING WERE  
DETERMINED. AN IMPROVED EMITTER WHISKER WAS  
INTRODUCED. HIGH TEMPERATURE SOLDER WAS INTRODUCED  
WITH PARTIAL FLUX ELIMINATION. A NEW APPROACH TO  
MORE EFFICIENT ETCHING WAS EXPLORED. STEP-STRESS  
EQUIPMENT IS UNDER CONSTRUCTION. FORMAL FAILURE  
MODE ANALYSIS IS INITIATED. OPERATION STANDARDS,  
DRAWINGS, AND QUALITY INSPECTION PROCEDURES WERE  
ISSUED AND WORK ON THE INSPECTION AND QUALITY CONTROL  
PLAN WAS INITIATED. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO: /ZDHL6

AD-423 325

GENERAL ELECTRIC CO IRMO S C

SOLID ELECTROLYTE TANTALUM FOIL CAPACITOR. (U)

DESCRIPTIVE NOTE: QUARTERLY RESEARCH AND DEVELOPMENT REPT,

1 JULY 27 SEP 63,

SEP 63 27P JENNY, A. L. ;

CONTRACT: N06SR09386

PROJ: SR0080303

TASK: 9636

UNCLASSIFIED REPORT

DESCRIPTORS: (TANTALUM CAPACITORS, FOILS),  
ELECTROLYTES, SOLIDS, PHOSPHORIC ACIDS, CLEANING,  
MANGANESE COMPOUNDS, OXIDES, SEMICONDUCTORS,  
ELECTRODEPOSITION, AGING (MATERIALS), CATHODES, CHEMICAL  
MILLING (U)  
IDENTIFIERS: 1963, ETCHING (U)

EXPERIMENTAL WORK HAS SHOWN THAT UNDER CERTAIN  
CONDITIONS PERMANENT DAMAGE TO THE ANODIC OXIDE CAN  
BE MADE DURING THE PROCESS OF DEPOSITING THE  
MANGANESE OXIDE. FROM THE VIEWPOINT OF THE SOLID  
FOIL TANTALUM CAPACITOR, THE RESULTS SUGGEST THAT A  
MINIMUM NUMBER OF DEPOSITION CYCLES MUST BE USED WITH  
CAREFUL CONTROL OF THE SOLUTION CONCENTRATION. THE  
BREAKDOWN VOLTAGE TESTS CONFIRM THAT THE TYPE OF  
TANTALUM FOIL, IN PARTICULAR, THE SURFACE CONDITION,  
HAS A CONTROLLING EFFECT ON SUBSEQUENT HIGH VOLTAGE  
PERFORMANCE. THE FORMATION CONDITIONS, FORMATION  
VOLTAGE, NUMBER OF COATS OF MANGANESE DIOXIDE, AREA  
OF DEPOSIT AND TIME AT DECOMPOSITION TEMPERATURE ARE  
ALSO VERY IMPORTANT IN CONTROLLING THE BREAKDOWN  
VOLTAGE. FOR THE 250 VOLT SOLID FOIL CAPACITOR  
APPLICATION, IT IS SOMEWHAT DISTURBING TO NOTE THAT  
THE BEHAVIOR OF THE TA2O5/MNOX INTERFACE  
APPEARS TO CHANGE FOR THICKNESS GREATER THAN THE  
EQUIVALENT OF 200 VOLTS FORMATION. MORE WORK IS  
NECESSARY TO DETERMINE WHETHER THE POORER PERFORMANCE  
AT THE HIGHER VOLTAGES IS DUE TO SOME BASIC PHYSICAL  
PHENOMENA OR DUE TO UNSUITABLE TANTALUM FOIL AND  
PROCESSING CONDITIONS WHICH ARE NOT THE OPTIMUM.  
(AUTHOR) (U)

48

UNCLASSIFIED

/ZDHL6

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL No. /ZOML6

AD-423 367

NAVAL ORDNANCE LAB WHITE OAK MD

POLISHES AND ETCHES FOR TIN TELLURIDE, LEAD SULFIDE,  
LEAD SELENIDE, AND LEAD TELLURIDE, (U)

MAY 63 27P NORR, MARRINER K. I  
REPT. NO. NOLTR-63-156

UNCLASSIFIED REPORT

DESCRIPTORS: (\*CHEMICAL MILLING, CRYSTALS),  
(\*ELECTROLYTIC POLISHING, CRYSTALS), (\*CRYSTALS,  
PRECISION FINISHING), SELENIDES, SULFIDES, TELLURIDES,  
LEAD COMPOUNDS, TIN COMPOUNDS, ETCHED CRYSTALS,  
CASTINGS, CRYSTAL LATTICE DEFECTS, SOLUTIONS, REVIEWS,  
SELENIUM ALLOYS, TELLURIUM ALLOYS, LEAD ALLOYS, TIN  
ALLOYS (U)  
IDENTIFIERS: 1963, ETCHES, POLISHES (U)

A REVIEW IS GIVEN OF CHEMICAL AND ELECTROLYTIC  
POLISHES AND DISLOCATION ETCHES FOR SNTe,  
PBS, PBSE, AND PBTE, COVERING THE PERIOD  
FROM 1907 TO 1962. RECIPES, CONDITIONS, AND RESULTS  
ARE DESCRIBED. SATISFACTORY POLISHES FOR ALL  
COMPOUNDS EXCEPT PBS AND ETCHES FOR ALL EXCEPT  
SNTe ARE INCLUDED. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL No. /ZOML6

AD-423 388

GENERAL DYNAMICS/FORT WORTH TEX

DEVELOPMENT OF CHEMICAL MILLED WAFFLE GRID BERYLLIUM  
STRUCTURAL PANEL, (U)

NOV 63 31P ROGERS, C. W. ; FEHRLE, A. C. ;  
LOVE, T. S. ;  
REPT. NO. ERR FW135  
CONTRACT: AF33 657 11214

UNCLASSIFIED REPORT

DESCRIPTORS: (\*BERYLLIUM, METAL PLATES), (\*METAL PLATES,  
CHEMICAL MILLING), MATERIAL REMOVAL, TENSILE PROPERTIES,  
STRESSES, STRAIN (MECHANICS), COMPRESSIVE PROPERTIES,  
STRUCTURAL PROPERTIES, ELASTICITY, SHEAR STRESSES,  
STRUCTURAL PARTS, AEROSPACE CRAFT (U)  
IDENTIFIERS: 1963 (U)

THIS REPORT CONCERNS THE RESEARCH AND DEVELOPMENT  
OF AN AEROSPACE STRUCTURAL PANEL MADE FROM QMV  
BERYLLIUM HOT-ROLLED PLATE. THE PROGRAM WAS A  
JOINT EFFORT OF THREE COMPANIES. THE BRUSH  
BERYLLIUM COMPANY MANUFACTURED THE BERYLLIUM  
PLATE. THE UNITED STATES CHEMICAL MILLING  
CORPORATION MILLED THE INTEGRALLY STIFFENED  
STRUCTURAL PANEL TO THE DESIGN SPECIFICATION  
ESTABLISHED BY THE GENERAL DYNAMICS  
CORPORATION/FORT WORTH. GENERAL DYNAMICS  
CORPORATION/FORT WORTH CONDUCTED THE FINAL  
STRUCTURAL TESTS ON THE FINISHED PANEL. RESULTS OF  
THIS PROGRAM CONFIRM THE ABILITY OF TODAY'S TECHNOLOGY  
TO PRODUCE A SATISFACTORY STRUCTURAL PANEL MADE FROM  
BERYLLIUM. THE MOST CRITICAL PROBLEM ENCOUNTERED  
WAS THE VARIATION OF APPARENT MODULUS OF ELASTICITY.  
STATIC STRENGTH WAS FOUND TO VARY EXCESSIVELY WITH  
SURFACE FINISH. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL No. /ZOML6

AD-425 102

MCDONNELL AIRCRAFT CORP ST LOUIS MO

CHEMICAL MILLING OF NARROW CLOSE TOLERANCE SLOTS IN ALUMINUM AND STAINLESS STEEL. (U)

DESCRIPTIVE NOTE: FINAL REPT.,  
DEC 63 22P WEEKS, ROBERT F.; MALAKELIS,  
ELIAS ;  
REPT. NO. A239  
CONTRACT: AF33 657 11215

UNCLASSIFIED REPORT

DESCRIPTORS: (\*STAINLESS STEEL, CHEMICAL MILLING);  
(\*ALUMINUM, CHEMICAL MILLING), (\*CHEMICAL MILLING,  
FLUIDS), PANELS (STRUCTURAL), MATERIAL REMOVAL,  
VARNISHES, PHOTSENSITIVITY, METALLOGRAPHY, SOLUTIONS,  
PHOTOMICROGRAPHY (U)  
IDENTIFIERS: 7176-T6 ALUMINUM, 321 STAINLESS STEEL.  
ETCHANTS, MASKANTS, 1963 (U)

FIVE TYPES OF MASKANTS AND THREE ETCHANT SOLUTIONS WERE EVALUATED FOR THE PURPOSE OF PRODUCING PRECISION SLOTS IN STAINLESS STEEL AND ALUMINUM. THE SCREEN PRINTING MASKANTS TESTED WERE NELCO SILK SCREEN STOP-OFF LACQUER R-5018 AND MEAKER STOP-OFF LACQUER. THE PHOTSENSITIVE MASKANTS TESTED WERE KODAK PHOTO RESIST, KODAK METAL ETCH RESIST, AND KODAK PHOTO LACQUER. COMBINATIONS OF THE DIFFERENT PHOTSENSITIVE MASKANTS WERE ALSO TESTED. THE 321 STAINLESS STEEL PANELS WERE MILLED WITH STEEL CHEM-MILL ETCHANTS PER PS 20022.2 AND THE 7178-T6 ALUMINUM PANELS WERE MILLED WITH EITHER HCL SOLUTION OR AN ALKALINE ETCHANT SOLUTION PER PS 20023. THE HYDROGEN ION NORMALITY WAS KEPT WITHIN A SPECIFIED NORMALITY RANGE DURING THE STEEL CHEM-MILLING. THE CUTTING RATE OF THE ETCHANT SOLUTION VARIED DEPENDING ON THE HYDROGEN ION CONCENTRATION, THE SPRAYING CONDITIONS, AND THE MASKANT CONFIGURATION. THE ONLY SUITABLE MASKANT TESTED ON STEEL WAS KODAK PHOTO RESIST OVER KODAK METAL ETCH RESIST. THE MEAKER AND NELCO MASKANTS WERE TESTED FOR CHEM-MILLING ALUMINUM. BOTH MASKANTS WERE SUITABLE FOR MILLING THE LARGER SLOT WIDTHS. THE CUTTING RATE VARIED DEPENDING ON ETCHANT SOLUTION AND MASKANT CONFIGURATION. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-426 356

CRYSTALONICS INC CAMBRIDGE MASS

PRODUCTION ENGINEERING MEASURE TO IMPROVE PRODUCTION  
TECHNIQUES AND TO INSURE THE RELIABILITY OF THE C600  
SERIES FIELD EFFECT TRANSISTORS. (U)

DESCRIPTIVE NOTE: QUARTERLY REPT. NO. 1, 1 JULY-30 SEP  
63,

SEP 63 41P WILLIAMS, JOHN R. I  
CONTRACT: DA36 039AMC01483E

UNCLASSIFIED REPORT

DESCRIPTORS: (•TRANSISTORS, PRODUCTION), SILICON,  
DIFFUSION, POSITIONING DEVICES (MACHINERY), BONDING,  
ULTRASONIC RADIATION, CHEMICAL MILLING, OXIDATION,  
BORON, RELIABILITY (ELECTRONICS) (U)  
IDENTIFIERS: 163, FIELD EFFECT TRANSISTORS (U)

IMPROVEMENTS WERE MADE IN THE DIFFUSION EQUIPMENT  
AND TECHNIQUE. HULK-DIFFUSION WAS STUDIED AND  
GRAPHS PRESENTED OF DIFFUSION DISTANCE VERSUS TIME.  
STUDIES WERE ALSO MADE OF THE DIODE  
CHARACTERISTICS AS A FUNCTION OF DIFFUSION CONDITION.  
ULTRASONIC BONDING - AN ULTRASONIC BONDER WAS  
PURCHASED AND INSTALLED. PRELIMINARY EVALUATION OF  
USB DEVICES WERE MADE. MASKS AND ALIGNMENT  
SYSTEMS - A NEW MASK ALIGNMENT SYSTEM WAS  
PURCHASED AND INSTALLED. MASKS WERE ORDERED FOR  
INTERNAL SHORTING OF THE DEVICE. ETCHING FIXTURE  
- SEVERAL PROTOTYPE DESIGNS WERE FABRICATED AND  
EVALUATED. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD#426 932

ARMY MISSILE COMMAND REDSTONE ARSENAL ALA ARMY INERTIAL  
GUIDANCE AND CONTROL LAB AND CENTER

MISSILE-BORNE TRACKING ANTENNA.

(U)

DESCRIPTIVE NOTE: FINAL PROGRESS REPT. FOR 1963,  
JUL 63 52P HOWELL, JAMES E.;  
REPT. NO. RG-TR-63-2U

UNCLASSIFIED REPORT

DESCRIPTORS: (•GUIDED MISSILE ANTENNAS, ELEC  
TRONIC SCANNERS), PHASE MEASUREMENT, POLARIZA  
TION, AUTOMATIC, TRACKING, ANTENNA FEEDS,  
IMPEDANCE MATCHING, COAXIAL CABLES, ANTENNA  
CONFIGURATIONS, ANTENNA LOBES, SUPERHIGH FRE  
QUENCY, HELICAL ANTENNAS, SPIRAL ANTENNAS,  
PRINTED CIRCUITS, CHEMICAL MILLING, CAVITY  
RESONATORS, GRAIN, PHASE SHIFTERS, ANTENNA  
RADIATION PATTERNS.

(U)

IDENTIFIERS: 1963, LOGARITHMIC SPIRAL ANTENNA,  
BALUN.

(U)

THE DEVELOPMENT OF ELECTRONICALLY STEERABLE,  
AUTOMATICALLY SELF-DIRECTING, MISSILE-BORNE ANTENNAS  
IS DESCRIBED. THE LITERATURE WAS SEARCHED AND A  
PRELIMINARY STUDY WAS MADE ON THE USE OF CIRCULARLY  
POLARIZED ANTENNAS FOR PRODUCING THE NECESSARY PHASE  
SHIFTS REQUIRED IN THE LOBING OF ANTENNA ARRAYS.  
HELICAL ANTENNAS WERE USED FIRST IN TESTS AROUND 5,  
000 MC IN AN EFFORT TO DETERMINE THE PHASING  
CHARACTERISTICS AND FEASIBILITY OF CIRCULARLY  
POLARIZED ANTENNAS. NEXT, A CAVITY-BACKED  
ARCHIMEDEAN SPIRAL ANTENNA AND BALUN WERE DESIGNED  
AND FABRICATED FOR 5,000 MC OPERATION. A  
LOGARITHMIC SPIRAL ANTENNA WAS ALSO DESIGNED AND  
FABRICATED FOR USE IN THE DEVELOPMENTAL ANTENNA  
TESTS. THE SPIRAL ANTENNAS WERE FABRICATED FROM  
COPPER CLAD BOARD BY PRINTED CIRCUIT ETCHING  
TECHNIQUES. SOME OF THE PROBLEMS ENCOUNTERED  
DURING LABORATORY TESTS WERE BALUN UNBALANCE,  
RADIATION FROM THE BALUN AND THE DETRIMENTAL EFFECTS  
OF THE REFLECTED WAVE WHEN USING CAVITIES.  
(AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD431 602

MCDONNELL AIRCRAFT CORP ST LOUIS MO

ELECTROCHEMICAL DEBURRING OF MOLYBDENUM, ALUMINUM AND  
STAINLESS STEEL. (U)

DESCRIPTIVE NOTE: FINAL REPT.,

MAR 64 54P WOLF, JAMES E. I

REPT. NO. A478

CONTRACT: AF33 657 11215

UNCLASSIFIED REPORT

DESCRIPTORS: (METALS, MATERIAL REMOVAL), (MATERIAL  
REMOVAL, ELECTROCHEMISTRY), CHEMICAL MILLING,  
ELECTROLYTIC POLISHING, MOLYBDENUM, ALUMINUM ALLOYS,  
STAINLESS STEEL, SOLUTIONS, ALCOHOLS, CHROMIC ACIDS,  
NITRIC ACID, SULFURIC ACID, FLUORINE COMPOUNDS, ACIDS(U)

SHARP EDGES LEFT AFTER CHEMICAL MILLING AND  
BLANKING ARE PRESENTLY BEING MECHANICALLY REMOVED AT  
HIGH COST. THE SHARP EDGES WOULD BE AREAS OF HIGH  
CURRENT DENSITY IN ELECTROCHEMICAL OPERATIONS AND  
COULD BE EASILY REMOVED IN ELECTROCHEMICAL  
SOLUTIONS. THE CRITERIA OF A GOOD ELECTROCHEMICAL  
DEBURRING SOLUTION WERE LEVELING CHARACTERISTICS AND  
REMOVAL RATE. VARIOUS SOLUTIONS WERE EVALUATED FOR  
BREAKING SHARP EDGES ON MOLYBDENUM, AMONG THEM BEING  
25% BY WEIGHT NITRIC ACID, NITRIC-HYDROFLUORIC ACID  
SOLUTION FOR MILLING MOLYBDENUM AND VARIATIONS OF  
TURCO 105 STEEL ETCHANT. THESE SOLUTIONS WERE  
SUCCESSFUL IN A LEVELING ACTION ON SHARP BURRS, BUT  
WOULD NOT ROUND THE SIDE EDGES. A COMBINATION OF  
NITRIC ACID LEVELING AND SIDE EDGE BURNISHING  
PRODUCED THE MOST PROMISING RESULTS. ALUMINUM AND  
STAINLESS STEEL DEBURRING WAS EVALUATED IN  
PROPRIETARY SOLUTIONS, WITH GOOD RESULTS OBTAINED IN  
POLISHING AND BREAKING OF SHARP EDGES. (AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-431 617

MCDONNELL AIRCRAFT CORP ST LOUIS MO

DETERMINATION OF MECHANICAL PROPERTIES AND SURFACE  
CONDITION OF CHEM-MILLED CB-5ZR COLUMBIUM ALLOY  
SAMPLES.

(U)

MAR 64 7P JACOBUS, H. ;  
REPT. NO. A473  
CONTRACT: AF33 657 11215

UNCLASSIFIED REPORT

DESCRIPTORS: (•NIOBIUM ALLOYS, MECHANICAL PROPERTIES),  
(•MECHANICAL PROPERTIES, NIOBIUM ALLOYS), SURFACE  
PROPERTIES, CHEMICAL MILLING, TENSILE PROPERTIES,  
ZIRCONIUM ALLOYS, EXPERIMENTAL DATA, METALLOGRAPHY (U)  
IDENTIFIERS: 1964, CB-5ZR NIOBIUM ALLOY (U)

MECHANICAL PROPERTIES AND SURFACE CONDITION OF CHEMICALLY  
MILLED SPECIMENS OF CB-5ZR NIOBIUM ALLOY.

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-433 118

LOCKHEED MISSILES AND SPACE CO SUNNYVALE CALIF

PACKAGING MINIATURIZATION, CHARGE NUMBERS 31-8027-  
D201-01, 31-8027-0901 AND RES 2 AND 4, (U)

SEP 61 137P ABE, SHIRO ; CHURCHON, STUART ;  
NEWMAN, H. L. ;  
REPT. NO. R5832 3 80 61 41

UNCLASSIFIED REPORT

DESCRIPTORS: (\*MODULES (ELECTRONIC), MANUFACTURING  
METHODS), (\*MANUFACTURING METHODS, MODULES  
(ELECTRONIC)), (\*SWITCHING CIRCUITS, MODULES  
(ELECTRONIC)), AMPLIFIERS, POWER, ENCAPSULATION,  
TRANSISTORS, PRODUCTION, RESISTORS, CAPACITORS, WELDING,  
CHEMICAL MILLING, MINIATURE ELECTRONIC EQUIPMENT,  
PACKAGED CIRCUITS, TABLES, ELECTRICAL PROPERTIES,  
PERFORMANCE (ENGINEERING), DIODES (SEMICONDUCTOR),  
ELECTRIC TERMINALS, SOLDERING, WIRING DIAGRAMS, PRINTED  
CIRCUITS, TEMPERATURE, CONFIGURATION, RELIABILITY  
(ELECTRONICS) (U)

IDENTIFIERS: 1961 (U)

HIGH POWER AMPLIFIER PARA-PLATE MODULES  
WERE BUILT AND FUNCTIONALLY TESTED. A FEW  
PROTOTYPE MODULES USING WELD PACK AND CHEM-  
MILL TECHNIQUES WERE CONSTRUCTED. SOME PROTOTYPE  
PARA-PLATE LOW POWER FLIP FLOPS WERE ASSEMBLED  
BUT NOT EVALUATED. SEVERAL OTHER VERSIONS OF THE  
LOW POWER FLIP FLOP WERE INVESTIGATED. THIS REPORT  
DESCRIBES THE DESIGN WORK AND INCLUDES ILLUSTRATIONS  
AND TABLES PLUS PRELIMINARY TEST RESULTS, LAYOUT  
ARTWORK, DRAWINGS, ENCAPSULATION TECHNIQUES,  
CONCLUSIONS AND RECOMMENDATIONS. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZCML6

AD-433 891

XEROX CORP ROCHESTER N Y

LOW-COST MICROCIRCUITS FOR MICROASSEMBLIES.

(U)

DESCRIPTIVE NOTE: QUARTERLY REPT. NO. 2, 1 OCT 63-1  
JAN 64,

JAN 64 55P MYTYCH,C. ;

CONTRACT: DA36 039AMC03257E

UNCLASSIFIED REPORT

DESCRIPTORS: (\*MICROMINIATURIZATION (ELECTRONICS),  
MANUFACTURING METHODS), (\*FIXED RESISTORS,  
MICROMINIATURIZATION (ELECTRONICS)), (\*FIXED CAPACITORS,  
MICROMINIATURIZATION (ELECTRONICS)), PHOTO ENGRAVING,  
VAPOR PLATING, VACUUM APPARATUS, ENVIRONMENTAL TESTS,  
PRINTED CIRCUITS, MODULES (ELECTRONIC), METAL COATINGS,  
COPPER, CHROMIUM, CHEMICAL MILLING, METAL FILMS (U)  
IDENTIFIERS: 1964, DOUBLE-ETCH PROCESS, MULTILAYERED  
FILMS (U)

AN APPROACH TO LOW-COST RESISTOR AND CAPACITOR  
ELEMENTS UTILIZING THE MICROELEMENT WAFER CONCEPT AND  
THE DOUBLE-ETCH PROCESS IS UNDER INVESTIGATION.  
MULTI-LAYERED FILMS WERE PLACED ON CERAMIC  
SUBSTRATES BY VACUUM AND ELECTROLESS DEPOSITION  
TECHNIQUES TO FORM MICROELEMENT WAFERS. THE MULTI-  
LAYERED FILMS ARE CONVERTED TO RESISTOR AND CAPACITOR  
ELEMENTS BY SUBSTRUCTIVE METHODS, UTILIZING  
XEROGRAPHIC STENCILING AND SELECTIVE ETCHING. DATA  
COVERING T.C.R., TEMPERATURE CYCLING, LOAD LIFE  
STABILITY AND YIELD FOR RESISTOR ELEMENTS IS  
PRESENTED. THE CAPACITOR AND MICROMODULE ASSEMBLY  
PROGRAMS ARE OUTLINED. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-438 138

GENERAL DYNAMICS/FORT WORTH TEX

MATERIAL BERYLLIUM WAFFLE PANEL. CHEMICAL MILLED,  
SHEAR TEST OF.

(U)

APR 64 13P MAY, J. ;  
REPT. NO. FTOM 3068

UNCLASSIFIED REPORT

DESCRIPTORS: (\*BERYLLIUM, PANELS (STRUCTURAL)), (\*PANELS  
(STRUCTURAL), BERYLLIUM), CHEMICAL MILLING, SHEAR  
STRESSES, LOADING (MECHANICS), STRAIN (MECHANICS) (U)

SHEAR TEST OF CHEMICAL MILLED BERYLLIUM WAFFLE PANEL.

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-438 478

NAVAL AIR ENGINEERING CENTER PHILADELPHIA PA AERONAUTICAL  
MATERIALS LAB

STUDY OF SIZE EFFECT IN FINE BERYLLIUM WIRE PHASE II,  
(U)

MAR 64 2P SOLTIS, PAUL ;  
REPT. NO. NAEC-AML-1909

UNCLASSIFIED REPORT

DESCRIPTORS: (\*BERYLLIUM, WIRE), (\*METALLIC TEXTILES,  
BERYLLIUM), FIBERS, TENSILE PROPERTIES, CHEMICAL  
MILLING, TEST EQUIPMENT, HARDNESS, GRAIN STRUCTURES  
(METALLURGY), PHOTOMICROGRAPHY, FRACTURE (MECHANICS),  
DUCTILITY, SCALE (U)

THE 0.0046-IN. DIAMETER, AS-DRAWN, BERYLLIUM WIRE  
CAN BE CHEMICAL-MILLED TO SIZES NEAR 0.0010 IN.  
DIAMETER WHICH SHOW DIMENSIONAL UNIFORMITY AND GOOD  
SURFACE QUALITY. A CONTINUOUS TREND TOWARD HIGHER  
STRENGTH WITH DECREASING DIAMETER OF THE WIRE WAS  
NOTED, AND IT APPEARS POSSIBLE THAT ULTRAFINE WIRE  
WITH STRENGTH APPROACHING THE 200,000 PSI LEVEL CAN  
BE PRODUCED WITH CONSISTENCY. A GOOD DEGREE OF  
DUCTILITY WAS NOTED IN WIRE CHEMICAL-MILLED BELOW  
0.0025-IN. DIAMETER AS EVIDENT IN NECKING OF  
SPECIMENS; ALTHOUGH, THIS DUCTILITY DID NOT APPEAR IN  
TENSILE ELONGATION VALUES. FRACTURE STRENGTHS IN  
WIRE SHOWING DUCTILE FRACTURES REACHED VALUES NEAR  
220,000 PSI. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD#450,549

BIGNETICS CORP SUNNYVALE CALIF

AN ECONOMICAL FLAT PACKAGE FOR INTEGRATED  
CIRCUITS.

(U)

DESCRIPTIVE NOTE: INTERIM DEVELOPMENT REPT. NO. 1, 15  
JUNE 15 SEP 64.

SEP 64 22P

CONTRACT: NOBSR91298

UNCLASSIFIED REPORT

DESCRIPTORS: (\*PACKAGING, INTEGRATED CIRCUITS),  
(\*INTEGRATED CIRCUITS, PACKAGING), CIRCUIT  
INTERCONNECTIONS, METAL FILMS, CHEMICAL MILLING,  
ELECTROPLATING, PRODUCTION, MANUFACTURING METHODS,  
SILICON, ALUMINUM

(U)

THE SCHEDULE FOR MAKING THE FIRST SEAL OF THE METAL  
LEADS TO THE PACKAGE SUBSTRATE IS COMPLETE. BY A  
PROCESS OF ELECTROPLATING AND ETCHING METAL FILM  
INTERCONNECTIONS HAVE BEEN LAID DOWN, BUT MANY  
PROBLEMS REMAIN IN THIS AREA. A FEW CIRCUITS WERE  
ASSEMBLED ON THIS SUBSTRATE AND WHERE ALL PREVIOUS  
STEPS WERE SATISFACTORY, ELECTRICAL CONTINUITY HAS  
BEEN ESTABLISHED. (AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-453 855  
HONEYWELL RESEARCH CENTER HOPKINS MINN

THIN FILM IMAGE CONVERTER. (U)

DESCRIPTIVE NOTE: INTERIM TECHNICAL PROGRESS REPT. NO. 6,  
24 JUL-23 OCT 64,  
NOV 64 IV KRUSE, PAUL W. ; PRIBBLE,  
FRED C. ; SCHULZE, RICHARD G. ;  
CONTRACT: DA44 009AMC168T  
PROJ: 2F23 11 001 07

UNCLASSIFIED REPORT

DESCRIPTORS: (SEMICONDUCTING FILMS, INFRARED IMAGES),  
(INFRARED IMAGES, SEMICONDUCTING FILMS), EPITAXIAL  
GROWTH, THICKNESS, GALLIUM ALLOYS, ARSENIC ALLOYS,  
GERMANIUM, ELECTRICAL PROPERTIES, CHEMICAL MILLING,  
DIFFUSION, PROCESSING, FIXED CONTACTS, RESISTANCE  
(ELECTRICAL), PHOSPHORUS ALLOYS, METAL COATINGS, GOLD,  
SILVER, NICKEL, DIODES (SEMICONDUCTOR) (U)  
IDENTIFIERS: IMAGE CONVERTERS, ETCHING, THICK  
FILMS (U)

EFFORTS WERE CONTINUED ON A PROGRAM TO CONDUCT  
FUNDAMENTAL STUDIES OF NEW APPROACHES TO IMAGE  
CONVERSION. THE EMPHASIS HAS BEEN UPON EVALUATION  
OF A CONCEPT OF A SOLID STATE THIN FILM IMAGE  
CONVERTER (TFIC). INVESTIGATIONS OF THE  
EPITAXIAL GROWTH OF N-GAAS ON P-GE HAVE MADE IT  
POSSIBLE TO PREPARE 200 MICRON THICK LAYERS OF  
SINGLE CRYSTAL GAAS ON GE. AN EVALUATION OF  
THE ELECTRICAL PROPERTIES OF SAMPLES ETCHED TO A MESA  
CONFIGURATION, TOGETHER WITH CHEMICAL STAINING  
STUDIES OF ANGLE LAPPED SAMPLES, REVEAL THAT AN N-  
GE LAYER IS FORMED BETWEEN THE N-GAAS AND P-  
GE REGIONS DURING THE INITIAL STAGES OF GROWTH.  
THE MOST PROBABLE DONOR IS AS, DIFFUSED FROM THE  
VAPOR INTO THE GE. METHODS FOR PREPARING  
STRONG, OHMIC, LOW RESISTANCE CONTACTS TO N-GAAS,  
P-GAAS, N-GAP, AND P-GAP HAVE BEEN  
DEvised UTILIZING ULTRASONIC SOLDERING. THE BEST  
TECHNIQUES ARE SUMMARIZED. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOMI 6

AD-468 378

JOHNS HOPKINS UNIV SILVER SPRING MD APPLIED PHYSICS  
LAB

THE MINISTICK PROCESS FOR PACKAGING INTEGRATED  
CIRCUIT FLAT PACKS.

(U)

DESCRIPTIVE NOTE: TECHNICAL MEMO.,  
APR 65 39P NOYES, CARLTON F. ;  
REPT. NO. TG-675  
CONTRACT: NOW62 0604C

UNCLASSIFIED REPORT

DESCRIPTORS: (•INTEGRATED CIRCUITS, PACKAGING),  
(•PRINTED CIRCUITS, PACKAGING), PROCESSING,  
MANUFACTURING METHODS, TEMPLATES, CHEMICAL  
MILLING, GLASS TEXTILES, EPOXY PLASTICS, LAMINATED  
PLASTICS, BONDING, DIELECTRICS,  
MODULES (ELECTRONIC), WELDING  
IDENTIFIERS: MINISTICK PROCESS, SUBSTRATES

(U)  
(U)

THE MINISTICK PROCESS FOR FABRICATING FLAT-PACK  
TYPE MULTILAYER CIRCUITRY BOARDS HAS BEEN DEVELOPED  
BECAUSE OF THE NEED FOR SPACE CIRCUITRY THAT MEETS  
EASE OF DESIGN AND MANUFACTURE REQUIREMENTS.  
STARTING WITH A CIRCUIT DESIGN IN THE FORM OF A  
LOGIC DIAGRAM, THE DESIGN PHASE PROGRESSES TO THE  
FINAL ARTWORK TEMPLATE. THIS TEMPLATE, PHOTO  
REDUCED, IS THE BASIC TOOL IN THE FABRICATION OF THE  
ASSEMBLY FRAMES. THE CIRCUIT OF EACH LAYER OF AN  
ASSEMBLY FRAME IS PRODUCED BY CHEMICALLY MILLING  
SUBSTRATES WHICH HAVE BEEN SENSITIZED WITH THE  
DESIRED CIRCUIT BY USE OF THE FINAL ARTWORK TEMPLATE.  
THESE SUBSTRATES ARE MADE BY LAMINATING AN EPOXY  
GLASS CLOTH DIELECTRIC MATERIAL TO A KOVAR SHEET.  
INDIVIDUAL CIRCUIT LAYERS ARE THEN COMBINED TO FORM  
AN ASSEMBLY FRAME, AND INTEGRATED CIRCUIT MODULES  
ARE WELDED TO THE FRAME TO COMPLETE THE CIRCUITRY.  
WHEN MORE THAN ONE ASSEMBLY FRAME IS REQUIRED TO  
COMPLETE THE CIRCUITRY, THE FRAMES ARE ELECTRICALLY  
CONNECTED BY MEANS OF A MOTHER BOARD. ALTHOUGH  
MULTILAYER CIRCUIT BOARDS ARE USED IN THIS PROCEDURE,  
NO INTERLAYER CONNECTIONS ARE REQUIRED. (AUTHOR)

(U)

UNCLASSIFIED

UDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-485 297 13/8 11/6  
AIR FORCE MACHINABILITY DATA CENTER CINCINNATI OHIO

MACHINING DATA FOR BERYLLIUM METAL, (U)

JUN 66 22P SNIDER, ROBERT E. KAHLES,  
JOHN F. ;  
REPT. NO. AFMDC-66-3  
CONTRACT: AF 33(615)-5262  
PROJ: AF-9-700

UNCLASSIFIED REPORT

DESCRIPTORS: (•BERYLLIUM ALLOYS, •MACHINING),  
(•BERYLLIUM, MACHINING), TOXICITY, CRYSTAL  
LATTICE DEFECTS, TWINNING (CRYSTALLOGRAPHY),  
FRACTURE (MECHANICS), CHEMICAL MILLING,  
MATERIAL REMOVAL, TENSILE PROPERTIES, HARDNESS,  
CARBIDES, MECHANICAL PROPERTIES,  
MICROSTRUCTURE (U)

THIS REPORT CONTAINS EVALUATED MACHINING  
INFORMATION FOR BERYLLIUM WHICH HAS BEEN EXTRACTED  
FROM MANY SOURCES. MACHINING DATA ARE TABULATED  
AND PRESENTED IN CHART FORM FOR THE FOLLOWING  
PROCESSES: TURNING, MILLING, DRILLING, BAND SAWING,  
GRINDING, BORING, TREPANNING, REAMING, ROUTING,  
TAPPING, ELECTRICAL DISCHARGE MACHINING,  
ELECTROCHEMICAL MACHINING, AND CHEMICAL MACHINING.  
ALSO INCLUDED IS A GENERAL COMMENT SECTION DEALING  
WITH THE PROBLEMS ASSOCIATED WITH BERYLLIUM  
MACHINING, SUCH AS TWINNING, MICROCRACKING, TOXICITY,  
CHIPOUT AND SPALLING, AND CUTTING FLUIDS.  
(AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-603 460

MOTOROLA INC PHOENIX ARIZ

PRODUCTION ENGINEERING MEASURE. HIGH SPEED  
SEMICONDUCTOR SWITCH (TWO TERMINAL) HIGH SPEED  
SEMICONDUCTOR SWITCH (GATE).

(U)

DESCRIPTIVE NOTE: QUARTERLY REPT. NO. 4, 29 FEB-28 MAY  
64.

MAY 64 32P BURLINGAME, B. G. I

CONTRACT: DA36 039AMC01475E

UNCLASSIFIED REPORT

DESCRIPTORS: (•ELECTRONIC SWITCHES, SEMICONDUCTOR  
DEVICES), (•SEMICONDUCTOR DEVICES, MANUFACTURING  
METHODS), BONDING, ULTRASONIC RADIATION, ELECTRIC  
TERMINALS, DESIGN, PACKAGING, DIODES (SEMICONDUCTORS),  
DISKS, CHEMICAL MILLING, EPITAXIAL GROWTH, DIFFUSION,  
METAL COATINGS, ALLOYS, ELECTRICAL PROPERTIES, VAPOR  
PLATING, GOLD, BORON, ALUMINUM, PHOSPHORUS, TEST  
EQUIPMENT (ELECTRONICS)

(U)

A PILOT PRODUCTION FACILITY CAPABLE OF PRODUCING  
HIGH SPEED SEMICONDUCTOR SWITCHES IN ACCORDANCE WITH  
SIGNAL CORPS TECHNICAL SPECIFICATIONS IS  
CONSIDERED. THE MAJOR PROBLEM AREAS TO BE OVERCOME  
IN ORDER TO ACHIEVE THE PURPOSE OF THIS PROGRAM ARE  
FORWARD BREAKOVER VOLTAGE AND CURRENT ON THE TWO-  
TERMINAL DEVICE, FORWARD BLOCKING CURRENT ON THE  
THREE-TERMINAL DEVICE, AND SWITCHING SPEEDS, CURRENT  
CARRYING CAPABILITIES, FORWARD ANODE VOLTAGE, AND  
RATE OF FORWARD VOLTAGE RISE ON BOTH DEVICES. WORK  
PERFORMED DURING THE PERIOD 29 FEBRUARY 1964  
THROUGH 28 MAY 1964 IS COVERED. PACKAGE DESIGNS  
FOR BOTH DEVICES ARE DISCUSSED, AND PROGRESS MADE ON  
ASSEMBLY METHODS, GOLD DIFFUSION, EPITAXIAL, ALLOY,  
AND MOAT-ETCHING PROCEDURES IS REPORTED.  
(AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-605 #25

HARSHAW CHEMICAL CO CLEVELAND OHIO

INVESTIGATION OF THIN FILM CADMIUM SULFIDE SOLAR  
CELLS.

(U)

DESCRIPTIVE NOTE: QUARTERLY TECHNICAL PROGRESS REPT. NO.  
3, 26 MAY-25 AUG 64.

AUG 64

8P

SCHAEFER, J. C. HUMRICK, R. J. ;

BELT, R. F. ;

CONTRACT: AF33 615 1249

PROJ: 8173

TASK: 817301, 817332

UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: SEE ALSO AD-601 459.

DESCRIPTORS: (\*SOLAR CELLS, FILMS), (\*CADMIUM COMPOUNDS,  
SULFIDES), ENERGY CONVERSION, BATTERIES AND COMPONENTS,  
ELECTROPLATING, VAPOR PLATING, DEGRADATION, CHEMICAL  
MILLING, COPPER COMPOUNDS, CHLORIDES, SILICON COMPOUNDS,  
MONOXIDES, SURFACE PROPERTIES, EFFECTIVENESS (U)

IDENTIFIERS: THIN FILMS (M)

THE DEGRADATION OF ELECTROPLATED CELLS HAS BEEN  
CLOSELY OBSERVED AND IT HAS BEEN FOUND THAT RECOVERY  
CAN BE ACCOMPLISHED UNDER PROPER CONDITIONS.  
CHEMICAL MILLING OF THE SUBSTRATE IS AN EXCELLENT  
METHOD FOR PRODUCING HIGH POWER TO WEIGHT RATIO  
CELLS. FABRICATION OF THE ONE-HALF AND ONE SQUARE  
FOOT MECHANICAL SAMPLE ARRAYS INDICATE IMPROVED TOTAL  
AREA UTILIZATION FACTORS. PHOTOVOLTAIC CELLS AND  
DIODES HAVE BEEN PREPARED BY FIRST DEPOSITING A THIN  
FILM OF CUCL ON CDS. THE CUCL WAS  
SUBSEQUENTLY CONVERTED TO CU<sub>9</sub>SS<sub>5</sub> BY MEANS OF  
H<sub>2</sub>S. OPTICAL STUDIES ON ELECTROPLATED AND  
CHEMPLATED BARRIERS HAVE SERVED TO CONFIRM THE  
PRESENCE OF CU<sub>2</sub>S ALONE OR MIXED WITH CU<sub>2</sub>S.  
THIN LAYERS OF SiO<sub>2</sub> HAVE BEEN UTILIZED AS A  
WATER VAPOR BARRIER TO SIGNIFICANTLY DECREASE  
DEGRADATION OF CELLS. ADDITIONAL THEORETICAL WORK  
HAS BEEN PERFORMED ON A HETEROJUNCTION MODEL OF THE  
CELL OPERATION. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /Z0ML6

AD#606 191

SILICON TRANSISTOR CORP GARDEN CITY N Y

PRODUCTION ENGINEERING MEASURE TO INCREASE THE  
RELIABILITY OF THE TRANSISTOR TYPE 2N2034. (U)

DESCRIPTIVE NOTE: QUARTERLY PROGRESS REPT. NO. 4, 1 APR-  
30 JUN 64.

JUN 64 29P COCKING, J. ; COURIER, J. ;

DES ROCHES, F. ; HUGHES, D. ; MARTIN, E. ;

CONTRACT: DA36 039AMC01482E

UNCLASSIFIED REPORT

DESCRIPTORS: (\*TRANSISTORS, RELIABILITY (ELECTRONICS)),  
PROCESSING, DISKS, SILICON, CLEANING, ABRASIVE BLASTING,  
SOLDERING, CHEMICAL MILLING, ENCAPSULATION, WELDING,  
HERMETIC SEALS, TESTS, CONTROLLED ATMOSPHERES,  
PERFORMANCE (ENGINEERING), NICKEL, PELLETS (U)

THE REPORT DESCRIBES THE PROCESSING DEVELOPMENTS IN  
WAFER CLEANING, MESA DELINEATION, SCRIBING OF WATER,  
PELLET TO NICKEL-PLATED HEADER SOLDERING, NICKEL-  
PLATED CLIP TO PELLETS SOLDERING, FINAL ETCH OF  
SOLDERED UNIT, FINAL TEST AND ENCAPSULATION OF ETCHED  
UNITS, AND WELD AND HERMETIC SEAL TESTS FOR THE  
TRANSISTOR TYPE 2N2034. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-606 477

CRYSTALONICS INC CAMBRIDGE MASS

PRODUCTION ENGINEERING MEASURE TO IMPROVE PRODUCTION TECHNIQUES AND TO INSURE THE RELIABILITY OF THE C600 SERIES FIELD EFFECT TRANSISTORS. (U)

DESCRIPTIVE NOTE: QUARTERLY REPT. NO. 4, 1 APR-30 JUN 64.

JUN 64 40P WILLIAMS, JOHN R. ;  
CONTRACT: DA36 039AMC01483E

UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: LEGIBILITY OF THIS DOCUMENT IS IN PART UNSATISFACTORY. REPRODUCTION HAS BEEN MADE FROM BEST AVAILABLE COPY. SEE ALSO AD-601 433.

DESCRIPTORS: (\*TRANSISTORS, MANUFACTURING METHODS), (\*RELIABILITY (ELECTRONICS), TRANSISTORS), BONDING, DIES, CHEMICAL MILLING, VACUUM FURNACES, CONTROLLED ATMOSPHERES, ENCAPSULATION, INDUSTRIAL EQUIPMENT (U)

ULTRASONIC BONDING HAS BEEN DISCARDED IN PREFERENCE TO A NEW-METALLIZATION BALL-BONDING TECHNIQUE. ALL PRODUCTION FETS ARE BEING DIE-TO-HEADER BONDED USING A HEAVY GOLD PLATE ON DICE AND HEADERS. A SLIGHT MODIFICATION HAS BEEN MADE IN THE MASK DESIGN TO FACILITATE BONDING. MESA ETCHING FIXTURES AND SLICE PREPARATION FIXTURES ARE COMPLETE AND ARE IN USE IN THE PRODUCTION PROCESS. VARIOUS EXPERIMENTS HAVE BEEN RUN UTILIZING VARIOUS DEW POINT AMBIENTS, COATING AGENTS, AND BAKEOUTS. AS A RESULT, PRODUCTION UNITS ARE BEING VACUUM BAKED AT 200C. AND PACKAGED IN A DRY NITROGEN ATMOSPHERE OF -60C. DEW POINT OR BETTER. LIFE TEST RACKS ARE BEING CONSTRUCTED. A MANUAL OF Q.C. PROCEDURES HAS BEEN PREPARED. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-606 819  
MARTIN CO DENVER COLO

MANUAL AND REPAIR WELDING OF CHEMICALLY MILLED 2014-  
T6 ALUMINUM SHEETING. (U)

AUG 57 27P AGRICOLA, K. R. ;  
REPT. NO. WDD-M-MI-57-60

UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: LEGIBILITY OF THIS DOCUMENT IS IN PART  
UNSATISFACTORY. REPRODUCTION HAD BEEN MADE FROM BEST  
AVAILABLE COPY.

DESCRIPTORS: (ALUMINUM ALLOYS, WELDING), (WELDING,  
ALUMINUM ALLOYS), SHEETS, CHEMICAL MILLING, WELDS,  
TENSILE PROPERTIES, HARDNESS, PANELS (STRUCTURAL),  
MAINTENANCE (U)  
IDENTIFIERS: ALUMINUM ALLOY 2014-T6 (U)

A 2 INCH WIDE LAND 0.100 IN. THICK, WILL FULLY  
RETAIN THE WELD HEAT-AFFECTED ZONE OF REPAIRED WELDS  
(BASED ON HARDNESS DATA). PARENT METAL  
PROPERTIES ARE ONLY SLIGHTLY AFFECTED BY WELD HEAT ON  
REPAIRS OF 1.5 INCH LANDS. VALUES OF 59,000 PSI  
CAN BE EXPECTED WITH 90 PERCENT CONFIDENCE FOR  
REPAIRED 1.5 INCH LANDS. IF 95 AND 99 PERCENT  
CONFIDENCE IS REQUIRED, EXPECTED VALUES FOR REPAIRED  
1.5 INCH LANDS ARE 57,000 AND 55,400 PSI. IF LAND  
WIDTHS OF 1.625 INCHES AND ABOVE ARE USED, PARENT  
METAL STRENGTH CAN BE EXPECTED FOR MANUAL WELDS  
FOLLOWED BY REPAIR WELDS. (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-607 426

WESTINGHOUSE DEFENSE AND SPACE CENTER BALTIMORE MD

FAILURE MECHANISMS IN MICROELECTRONICS.

(U)

DESCRIPTIVE NOTE: FINAL REPT.

AUG 64 100P

REPT. NO. WDSC-385A4

CONTRACT: AF30 602 3017

PROJ: 5519

TASK: 551906

MONITOR: RADC . TDR64 252

UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: LEGIBILITY OF THIS DOCUMENT IS IN PART UNSATISFACTORY. REPRODUCTION HAS BEEN MADE FROM BEST AVAILABLE COPY.

DESCRIPTORS: (\*MICROMINIATURIZATION (ELECTRONICS), FAILURE (MECHANICS)), (\*FAILURE (MECHANICS), MICROMINIATURIZATION (ELECTRONICS)), DIODES (\*SEMICONDUCTOR), DISKS, TRANSISTOR AMPLIFIERS, SILICON COMPOUNDS, OXIDES, SURFACE PROPERTIES, ELECTRICAL PROPERTIES, CHEMICAL MILLING, STRESSES, ELECTRICAL CONDUCTANCE, ELECTRONIC EQUIPMENT, RELIABILITY (ELECTRONICS), SILICON (U)

INVESTIGATIONS WERE PERFORMED ON THREE TYPES OF MICROELECTRONIC DEVICES: MULTIPLE DIODE WAFERS, INVERSION LAYER DIODE AMPLIFIERS, AND VERSATILE LINEAR AMPLIFIERS. TWO FAILURE MECHANISMS WERE IDENTIFIED AND STUDIED IN DETAIL: UNSUSPECTED DIFFUSION BARRIERS FROM PHOTOETCH PROCEDURES, AND VARIATIONS IN PASSIVATION LAYER PROPERTIES. THE RELATIONSHIP TO THESE, OF CURRENT AMPLIFICATION (BETA), OR REVERSE VOLTAGE BREAKDOWN, OF LEAKAGE, AND OTHER QUANTITIES WAS EXAMINED. EACH STEP IN MICROELECTRONIC DEVICE FABRICATION WAS INVESTIGATED FOR ITS CONTRIBUTION TO FAILURE MECHANISMS. A PARTIALLY CONDUCTING REGION IN THE PASSIVATING OXIDE WAS IDENTIFIED AND STUDIED, 300-100 A FROM THE SILICON. THIS CONTRIBUTES TO THE LEAKAGE IN MICROELECTRONIC DEVICES USUALLY ATTRIBUTED ENTIRELY TO CHANNELS IN THE SILICON. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD4609 349

BATTELLE MEMORIAL INST COLUMBUS OHIO DEFENSE METALS  
INFORMATION CENTER

A SURVEY OF THE COMPARATIVE COSTS OF FABRICATING  
AIRFRAME FROM ALUMINUM AND FROM TITANIUM.

(U)

DESCRIPTIVE NOTE: TECHNICAL NOTE.

APR 64 20P

UNCLASSIFIED REPORT

DESCRIPTORS: (\*TITANIUM ALLOYS, AIRFRAMES), (\*AIRFRAMES,  
COSTS), (\*ALUMINUM ALLOYS, AIRFRAMES), MATERIAL FORMING,  
SHEETS, MACHINING, WELDING, CHEMICAL MILLING, FORGING,  
HEAT TREATMENT, SUPERSONIC PLANES, TRANSPORT PLANES (U)

BY PROCESS, THE COST RATIOS FOR FABRICATING  
TITANIUM AND ALUMINUM ARE ABOUT AS FOLLOWS: SHEET  
FORMING 1.5-2 TO 1, MACHINING 1.5-2 TO 1,  
WELDING .8-2 TO 1, CHEMICAL MILLING 3-4 TO 1,  
ASSEMBLING 1.1 TO 1, FORGING 1.5-2.3 TO 1, HEAT  
TREATING 1.5-5 TO 1. THE CURRENT COST ESTIMATES  
MADE BY THE EXPERIENCED TITANIUM FABRICATORS  
REPRESENT REALISTIC MINIMUM COST RATIOS FOR THE NEXT  
2 OR 3 YEARS. THEY ARE RATIOS WHICH THE LESS  
EXPERIENCED FABRICATORS SHOULD BE ABLE TO APPROACH IN  
ACTUAL PRODUCTION. THE EXPERIENCED FABRICATORS  
COULD PROBABLY NOT IMPROVE ON THEM GREATLY IN THE  
NEXT YEAR OR TWO. THE ABOVE COST RATIOS APPLY ONLY  
TO SPECIFIC FABRICATION OPERATIONS (SUCH AS  
FORMING, MACHINING, WELDING, ETC.). THESE  
OPERATIONS ACCOUNT FOR ONLY A FRACTION OF THE TOTAL  
COST OF MANUFACTURING AN AIRCRAFT. MOST OF THE  
MANUFACTURING COSTS NOT COVERED BY THESE OPERATIONS  
WOULD BE LARGELY UNAFFECTED BY THE CHOICE OF AIRFRAME  
MATERIAL. (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-610 434

FRANKLIN INST PHILADELPHIA PA LABS FOR RESEARCH AND  
DEVELOPMENT

RESEARCH IN THE GENERAL FIELD OF SUBSTRUCTURE AND  
DISLOCATION NETWORKS IN METALLIC CRYSTALS. (U)

DESCRIPTIVE NOTE: FINAL REPT. FOR 1 APR 60-30 APR 62,  
APR 62 48P DAMIANO, V. V. ; TINT, G. S. ;  
HERMAN, M. ;  
REPT. NO. F-A2400  
CONTRACT: AF49 638 821  
MONITOR: AFOSR , 2574

UNCLASSIFIED REPORT

DESCRIPTORS: (\*METALLIC CRYSTALS, CRYSTAL STRUCTURE),  
(\*CRYSTAL STRUCTURE, METALLIC CRYSTALS), CRYSTAL  
SUBSTRUCTURE, CRYSTAL LATTICE DEFECTS, CRYSTALS, ZINC,  
IMPURITIES, CADMIUM, CHEMICAL MILLING, PHOTOMICROGRAPHY,  
CRYSTALLOGRAPHY (U)

THE THREE DIMENSIONAL ASPECTS OF DISLOCATION  
SUBSTRUCTURES WERE STUDIED IN CADMIUM DOPED ZINC  
CRYSTALS GROWN FROM THE MELT. PRECIPITATES  
DELINEATING THE DISLOCATIONS WERE REVEALED BY  
ETCHING A SURFACE CLOSELY PARALLEL TO THE SLIP PLANE.  
USING A TECHNIQUE OF CONTINUOUS ETCHING AND  
CINEPHOTOMICROGRAPHY, THE COURSE OF THE DISLOCATIONS  
WAS FOLLOWED THROUGH THE CRYSTAL. TANGLES OF  
DISLOCATIONS WERE OBSERVED IN DEFORMED CRYSTALS.  
AFTER ANNEALING A REARRANGEMENT OF DISLOCATIONS  
INTO LOW-ANGLE AND HEXAGONAL NETWORKS WAS EVIDENCED.  
CLOSED LOOPS AND SPIRAL DISLOCATIONS WERE FOUND TO  
BE ASSOCIATED WITH LARGE INCLUSIONS. A MECHANISM  
FOR THE MULTIPLICATION OF DISLOCATIONS AT INCLUSIONS  
WAS PROPOSED. DISLOCATION REACTIONS ACCOUNTING FOR  
THE OBSERVED SUBSTRUCTURES HAVE BEEN PROPOSED.  
(AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZDML6

AD#612 617.

TEXAS INSTRUMENTS INC DALLAS

PRODUCTION ENGINEERING MEASURES (PEM) FOR A GERMANIUM  
MICROWAVE TRANSISTOR. (U)

DESCRIPTIVE NOTE: QUARTERLY PROGRESS REPT. NO. 1, 30

JUN-30 SEP 64.

SEP 64 79P

REPT. NO. 03-64-73

CONTRACT: DA36 039AMC03632E

PROJ: 74057

UNCLASSIFIED REPORT

DESCRIPTORS: (\*TRANSISTORS, MANUFACTURING METHODS),  
(\*MICROWAVE EQUIPMENT, TRANSISTORS), (\*GERMANIUM,  
TRANSISTORS), GAIN; NOISE (RADIO); VAPOR PLATING,  
SILICON COMPOUNDS, DIOXIDES, PACKAGING, ENCAPSULATION,  
INDUCTANCE, GALLIUM, IMPURITIES, VACUUM APPARATUS,  
CHEMICAL MILLING, DIFFUSION, ARSENIC, GOLD, RELIABILITY  
(ELECTRONICS) (U)

THE PROCESS FLOW USED IN FABRICATING THE L-78  
PLANAR EPITAXIAL GERMANIUM DIFFUSED-BASE TRANSISTOR  
IS DESCRIBED. THE INITIAL INTRINSIC  $f_{sub T}$  OF  
PLANAR DEVICES, APPROXIMATELY 1600 MC COMPARED TO  
2050 MC FOR A MESA DEVICE OF COMPARABLE DESIGN USING  
SIMILAR FABRICATION TECHNIQUES, WAS INCREASED TO  
EQUAL THAT OF THE MESA BY OPTIMIZING THE COMPOSITION  
OF THE EMITTER MATERIAL. THE L-78 PLANAR DEVICES  
FABRICATED EXHIBIT MINIMUM NOISE FIGURE AT 1.0  
GGGC OF 4.5 TO 5.5 DB AT APPROXIMATELY 1.5 MA OF  
EMITTER CURRENT WHILE PEAK  $f_{sub T}$  OCCURS AT  
APPROXIMATELY 5.0 MA. A MODIFICATION OF THE L-78  
PATTERN, DESIGNATED L-78A, VIA EMITTER AREA  
REDUCTION FROM 0.76 MIL SQUARED TO 0.27 MIL SQUARED  
MANIFESTED ITSELF BY A SHIFT IN PEAK  $f_{sub T}$  TOWARD  
LOWER VALUES OF EMITTER CURRENT. THE PURPOSE OF  
THIS MODIFICATION IS TO BRING INTO REGISTRY THE  $f_{sub T}$   
PEAK GAIN OF THE DEVICE AND MINIMUM NOISE FIGURE AT  
ONE PARTICULAR BIAS LEVEL. THE MATERIALS USED FOR  
THE BASE STRIPES OF THE PLANAR UNIT WERE OPTIMIZED TO  
PROVIDE GOOD OHMIC CONTACT TO GERMANIUM. ADHERENCE  
OF EXPANDED CONTACTS TO THE ACTIVE REGION OF THE  
DEVICE, THE EMITTER AND BASE STRIPES, WAS IMPROVED BY  
EMPLOYING A CHEMICAL ETCH COMPRISED OF INORGANIC  
CONSTITUENTS. AN EXCELLENT TECHNIQUE FOR UNIFORMLY  
DEPOSITING SILICON DIOXIDE ONTO GERMANIUM WAS  
OBTAINED.

72

UNCLASSIFIED

(U)

/ZDML6

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-613 068  
CRYSTALONICS INC CAMBRIDGE MASS

PRODUCTION ENGINEERING MEASURE TO IMPROVE PRODUCTION  
TECHNIQUES AND TO INSURE THE RELIABILITY OF THE C600  
SERIES FIELD EFFECT TRANSISTORS. (U)

DESCRIPTIVE NOTE: QUARTERLY REPT. NO. 6, 1 OCT-31 DEC  
64.

DEC 64 25P WILLIAMS, JOHN R. ;  
CONTRACT: DA36 039AMC01483E

UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: AVAILABLE COPY WILL NOT PERMIT FULLY  
LEGIBLE REPRODUCTION. REPRODUCTION WILL BE MADE IF  
REQUESTED BY USERS OF DDC. COPY IS AVAILABLE FOR PUBLIC  
SALE. SEE ALSO AD-609 596.

DESCRIPTORS: (\*TRANSISTORS, MANUFACTURING METHODS),  
(\*RELIABILITY (ELECTRONICS), TRANSISTORS), SILICON,  
PROCESSING, BORON, PHOSPHOROUS, DIFFUSION, CHEMICAL  
MILLING, ETCHED CRYSTALS, BONDING, TESTS, DATA  
PROCESSING SYSTEMS, PACKAGING, QUALITY CONTROL (U)  
IDENTIFIERS: C600 TRANSISTORS, PERT (U)

THE PURPOSE OF THIS PROGRAM IS TO IMPROVE THE  
RELIABILITY OF THE C600 SERIES FIELD EFFECT  
TRANSISTORS BY SPECIFIC IMPROVEMENTS OF MANUFACTURING  
TECHNIQUES. THE BASIC PROGRAM HAS BEEN OUTLINED IN  
A PERT PLAN WHICH IS BEING USED AS A REFERENCE.  
IN AN EFFORT TO ACHIEVE THE FAILURE RATE OBJECTIVE,  
THE FOLLOWING PROCESSES ARE TO BE IMPROVED: (1)  
OXIDATION OF SLICES; (2) BORON DIFFUSION OF  
SLICES; (3) MASK ALIGNMENT; (4) ETCHING  
OF SLICES; (5) DIE-TO-HEADER BONDING; (6)  
WIRE BONDING; (7) PACKAGING. (AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-613 261

BATTELLE MEMORIAL INST COLUMBUS OHIO DEFENSE METALS  
INFORMATION CENTER

METAL REMOVAL BY ELECTROCHEMICAL METHODS AND ITS  
EFFECTS ON MECHANICAL PROPERTIES OF METALS, (U)

JAN 65 45P GURKLIS, JOHN A. I  
REPT. NO. DMIC-213  
CONTRACT: AF33 615 1121  
PROJ: 8975

UNCLASSIFIED REPORT

DESCRIPTORS: (\*ELECTROEROSIVE MACHINING, METALS);  
(\*CHEMICAL MILLING, METALS); (\*ELECTROLYTIC POLISHING,  
METALS); MECHANICAL PROPERTIES, HYDROGEN EMBRITTLEMENT,  
STEEL, BERYLLIUM, NICKEL ALLOYS, COBALT ALLOYS,  
REFRACTORY METALS, REFRACTORY METAL ALLOYS, TITANIUM  
ALLOYS, SURFACE PROPERTIES, OXIDATION (U)

THIS REPORT ASSEMBLES AND CORRELATES INFORMATION ON  
THE EFFECTS OF ELECTROCHEMICAL METAL-REMOVAL (ECMR)  
PROCESSES ON MECHANICAL PROPERTIES. OF SPECIAL  
INTEREST AND CONCERN ARE THE EFFECTS OF ECMR ON  
FATIGUE STRENGTH. THE REPORT COVERS FOUR  
ELECTROCHEMICAL METAL-REMOVAL PROCESSES:  
ELECTROCHEMICAL MACHINING (ECM), ELECTROLYTIC  
GRINDING (EG), ELECTROCHEMICAL MILLING, AND  
ELECTROPOLISHING. GENERAL CHARACTERISTICS AND  
APPLICATIONS OF THE FOUR METHODS ARE PRESENTED AND  
DISCUSSED; SPECIAL EMPHASIS IS PLACED ON ECM. THE  
ECMR PROCESSES ARE ESPECIALLY USEFUL IN SHAPING  
HIGH-STRENGTH AND DIFFICULT-TO-MACHINE METALS AND  
ALLOYS, AS WELL AS IN SHAPING PARTS WITH UNUSUAL,  
COMPLEX, OR FRAGILE CHARACTERISTICS. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZQML6

AD-613 643

ARMY MATERIALS RESEARCH AGENCY WATERTOWN MASS

THE METALLOGRAPHY OF PYROLITIC GRAPHITE,

(U)

DEC 64 19P TARPINIAN, ARAM ;

REPT. NO. AMRA-TR-64-41

PROJ: 1A010501B010

TASK: 35183

UNCLASSIFIED REPORT

DESCRIPTORS: (•PYROLITIC GRAPHITE, MICROSTRUCTURE), ION BOMBARDMENT, ARGON, MERCURY, CHEMICAL MILLING, ELECTROLYTIC POLISHING

(U)

ETCHING OF PYROLITIC GRAPHITE BY BOTH ARGON ION BOMBARDMENT AND MERCURY ION BOMBARDMENT IS DESCRIBED. THE DIFFERENCE BETWEEN THE MICROSTRUCTURES REVEALED BY THE TWO METHODS IS DISCUSSED, AND AN INTERPRETATION IS SUGGESTED. ARGON ION BOMBARDMENT CREATES A LEAF-LIKE PATTERN REMINISCENT OF STACKED SHINGLES. MERCURY ION BOMBARDMENT REVEALS A LAMINAR STRUCTURE UNLIKE THAT PRODUCED BY ARGON ION BOMBARDMENT. ELECTROCHEMICAL POLISHING AND ETCHING REVEALS MICROSTRUCTURES SIMILAR TO THOSE CREATED BY ION BOMBARDMENT. USING AN ELECTROLYTE BASED ON PHOSPHORIC ACID, MICROSTRUCTURES SIMILAR TO THOSE RESULTING FROM MERCURY ION BOMBARDMENT ARE REVEALED. REPLACING THE PHOSPHORIC ACID WITH NITRIC ACID RESULTS IN MICROSTRUCTURES SIMILAR TO THOSE OBTAINED BY ARGON ION BOMBARDMENT. BASED ON THE CORRELATION BETWEEN MICROSTRUCTURES DEVELOPED BY ION BOMBARDMENT AND ELECTROCHEMICAL ETCHING, IT IS CONCLUDED THAT THE MICROSTRUCTURES REVEALED REPRESENT THE TRUE STRUCTURE. (AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-614 467

LINDEN LABS INC STATE COLLEGE PA

MACHINING HIGH PURITY ALUMINA.

(U)

DESCRIPTIVE NOTE: QUARTERLY REPT. NO. 2, 1 OCT-31 DEC  
64.

DEC 64 27P MARSHALL, P. A. , JR. INFIELD,  
J. M. :

CONTRACT: DA36 039AMC03634E

UNCLASSIFIED REPORT

DESCRIPTORS: (\*MACHINING, \*ALUMINA); SURFACE  
PROPERTIES, CHEMICAL MILLING, HYDROCHLORIC ACID,  
HYDROGEN COMPOUNDS, FLUORIDES, ACIDS,  
IMPREGNATION, SILICON COMPOUNDS, DIOXIDES,  
CUTTING TOOLS, DENSITY, HEAT TREATMENT  
IDENTIFIERS: HYDROFLUORIC ACID

(U)

(U)

MATERIAL A-96 SELECTED FOR THE MACHINING  
DEMONSTRATION CAN BE DRILLED, GROUND, THREADED,  
SLOTTED, TAPPED AND TURNED. THE MATERIAL CAN BE  
READILY REMOVED BY EITHER A GRINDING WHEEL OR A  
SINGLE POINT CUTTING TOOL. CARE MUST BE EXERCISED  
WHEN USING A SINGLE POINT CUTTING TOOL WITH REGARD TO  
FEEDS, SPEEDS, TOOL GEOMETRY, AND CUTTING ANGLES.  
THE CHEMISTRY BEHIND THE ACID TREATING AND THE  
RECONSTITUTION ARE NOT FULLY UNDERSTOOD. THE  
MATERIAL A-96 TREATED ALUMINA APPEARS TO BE ABLE TO  
BE RECONSTITUTED TO A DENSE BODY OF HIGHER PURITY  
THAN THE ORIGINAL BODY. HYDROFLUORIC ACID SEEMS TO  
ATTACK MOST BODIES MORE READILY THAN HYDROCHLORIC  
ACID AND 52% AQUEOUS HF SEEMS TO ATTACK MORE  
READILY THAN 70% AQUEOUS HF. THERE APPEARS TO BE  
SOME OPTIMUM PER CENT AQUEOUS ACID BETWEEN 70% AND  
40%. (AUTHOR)

(U)

UNCLASSIFIED

UDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-614 523

NATIONAL SEMICONDUCTOR CORP DANBURY CONN

PRODUCTION ENGINEERING MEASURE TO IMPROVE PRODUCTION  
TECHNIQUES AND INCREASE THE RELIABILITY OF THE  
2N328A TRANSISTOR. (U)

DESCRIPTIVE NOTE: FINAL REPT. FOR 30 JUN 63-30 DEC 64,

DEC 64 246P RAU, R. R. IDI PAOLA, R. I  
CONTRACT: DA36 039AMC01480E

UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: AVAILABLE COPY WILL NOT PERMIT FULLY  
LEGIBLE REPRODUCTION. REPRODUCTION WILL BE MADE IF  
REQUESTED BY USERS OF DDC. COPY IS AVAILABLE FOR PUBLIC  
SALE. SEE ALSO AD-608 583.

DESCRIPTORS: (TRANSISTORS, MANUFACTURING METHODS),  
RELIABILITY (ELECTRONICS), PRODUCTION, FAILURE  
(MECHANICS), TESTS, SILICON ALLOYS, PROCESSING,  
SPECIFICATIONS, QUALITY CONTROL, LIFE EXPECTANCY,  
CHEMICAL MILLING, ALUMINUM, VAPOR PLATING, GAS ANALYSIS,  
WELDING, HEATING, FURNACES, INDUSTRIAL EQUIPMENT (U)

A SUMMARY IS GIVEN OF THE WORK PERFORMED FOR  
IMPROVING THE RELIABILITY OF THE PNP SILICON  
ALLOY TRANSISTOR TYPE 2N328A. THE  
FOLLOWING PROCESSES WERE MODIFIED DURING THE COURSE  
OF THE CONTRACT: AN ETCH WHEEL WAS INTRODUCED TO  
MORE ACCURATELY CONTROL FINAL DEVICE ETCHING;  
ADDITIONAL BAKE-OUT FURNACES WERE INTRODUCED AND  
EVALUATED TO INCREASE THE AMOUNT OF TIME WHICH THE  
UNITS ARE HEATED AFTER ETCHING; A GAS RECIRCULATOR  
WAS INTRODUCED INTO THE FINAL DRY LINE TO REDUCE THE  
WATER VAPOR CONCENTRATION; WELDING SHIELDS WERE  
INTRODUCED AT TWO WELDING OPERATIONS WHILE ONE OTHER  
PROCESS WAS MODIFIED; ALL THESE CHANGES WERE MADE IN  
ORDER TO DECREASE THE AMOUNT OF WELD SPLASH STRIKING  
THE ACTIVE REGION OF THE TRANSISTOR. DEVICES  
PRODUCED FOR THE FIRST MONTH OF OPERATION OF THE  
IMPROVED MANUFACTURING LINE WERE USED FOR THE LONG  
TERM RELIABILITY TESTING. MEASUREMENTS ON DEVICES  
MADE DURING THIS PERIOD OF MANUFACTURE ARE INCLUDED.  
THIS RELIABILITY EVALUATION CONSISTED OF  
OPERATIONAL TESTS FOR A 1000 HOURS AT POWER LEVELS OF  
400, 450, AND 500 MILLIWATTS; A SPECIFICATION FOR  
AN IMPROVED 2N328A TYPE TRANSISTOR INCORPORATING  
SOME OF THE RESULTS OF EVALUATIONS MADE DURING THIS  
CONTRACT IS INCLUDED. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-616 786

RENSSELAER POLYTECHNIC INST TROY N Y

PRINCIPLES OF METALLOGRAPHIC ETCHING.

(U)

DESCRIPTIVE NOTE: TECHNICAL REPT.,

JUN 65 26P GREENE, NORBERT D. PRUDAW,

PETER S. LEE, LINDA ;

REPT. NO. TR-2

CONTRACT: NONR59117

UNCLASSIFIED REPORT

DESCRIPTORS: (\*CHEMICAL MILLING, ALLOYS),  
(\*METALLOGRAPHY, CHEMICAL MILLING), TIN ALLOYS,  
ZINC ALLOYS, SODIUM COMPOUNDS, HYDROXIDES,  
ELECTROLYTES, ANALYSIS

(U)

THE PRINCIPLES OF METALLOGRAPHIC ETCHING HAVE BEEN DETERMINED BY ELECTROCHEMICAL AND OPTICAL MEASUREMENTS ON TIN-ZINC ALLOYS IN SODIUM HYDROXIDE ELECTROLYTES. THE MINIMUM DISSOLUTION RATE RATIO AND THE MINIMUM AMOUNT OF SELECTIVE DISSOLUTION NECESSARY TO ACHIEVE METALLOGRAPHIC CONTRAST OF PHASES HAVE BEEN MEASURED. ETCHING RATE AND CONTRAST ARE UNIQUELY DEFINED BY ETCHING POTENTIAL BY POTENTIOSTATIC, ELECTROLYTIC AND CHEMICAL ETCHING METHODS. (AUTHOR

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD#615 628

FOREIGN TECHNOLOGY DIV WRIGHT-PATTERSON AFB OHIO

CHEMICAL MILLING,

(U)

JUL 65 7P RYBAK, P. T. ; SAVICH, V. V. ;  
REPT. NO. FTD-TT-65-865  
MONITOR: TT . 65-62694

UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: UNEDITED ROUGH DRAFT TRANS. OF  
MASHINOSTROITEL' (USSR) N3 P34-5 1964. AVAILABLE COPY  
WILL NOT PERMIT FULLY LEGIBLE REPRODUCTION. REPRODUCTION  
WILL BE MADE IF REQUESTED BY USERS OF DDC. COPY IS  
AVAILABLE FOR PUBLIC SALE.

DESCRIPTORS: (\*CHEMICAL MILLING, MANUFACTURING  
METHODS), USSR, PRINTED CIRCUITS, HEATING,  
INFRARED RADIATION, AUTOMATION

(U)

TRANSLATION OF RUSSIAN RESEARCH: CHEMICAL MILLING.

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD#619 295

MOTOROLA INC PHOENIX ARIZ SEMICONDUCTOR PRODUCTS DIV

PRODUCTION ENGINEERING MEASURE FOR SILICON OVERLAY  
TRANSISTORS.

(U)

DESCRIPTIVE NOTE: QUARTERLY PROGRESS REPT. NO. 1, 1 JAN-  
31 MAR 65,

MAR 65 52P KEARKUFF, THOMAS ;

CONTRACT: DA36 039AMC06156E

PROJ: 74001

UNCLASSIFIED REPORT

DESCRIPTORS: (\*TRANSISTORS, MANUFACTURING METHODS),  
(\*SILICON, TRANSISTORS), DIFFUSION, GOLD,  
CHEMICAL MILLING, PRECISION FINISHING, PROCESSING,  
ENCAPSULATION, BONDING, GLASS, WIRE, STORAGE,  
EPITIXIAL GROWTH, RELIABILITYELECTRONICS)

(U)

NEW BASE PREDEPOSITION AND BASE DIFFUSION SYSTEMS  
WERE PUT INTO PRODUCTION AND EVALUATED. WORK WAS  
STARTED ON A NEW EMITTER AND GOLD DIFFUSION PROCESS.  
WORK WAS STARTED ON THE EMITTER STRIPE WIDTH  
EVALUATION. CHEMICAL ETCHING WAS PLACED INTO  
PRODUCTION AND WORK ON SLURRY POLISHING IS ALMOST  
COMPLETE. A NEW PHOTORESIST WAS EVALUATED AND  
PRODUCTION CONTROLS ARE PRESENTLY BEING APPLIED.  
NEW ASSEMBLY PARTS AND PROCESSES WERE EVALUATED  
FROM THE ASSEMBLY VIEWPOINT. (AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-620 508

BATTELLE MEMORIAL INST COLUMBUS OHIO

MACHINING AND GRINDING OF TITANIUM AND ITS ALLOYS.

(U)

DESCRIPTIVE NOTE: NASA TECHNICAL MEMO.,

AUG 65 131P

OLOFSON, C. T. ;BOULGER, F. W.

;GURKLIS, J. A. I

CONTRACT: DA01 D2:AMC11651Z

MONITOR: NASA,RSIC

TM-X-53312,409

UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: SUBCONTRACTED TO REDSTONE SCIENTIFIC INFORMATION CENTER, REDSTONE ARSENAL, ALA.

DESCRIPTORS: (\*TITANIUM, MATERIAL REMOVAL); (\*TITANIUM ALLOYS, MATERIAL REMOVAL), (\*MATERIAL REMOVAL, TITANIUM); MACHINING, MACHINE TOOLS, GRINDERS, PRECISION FINISHING, CHEMICAL MILLING, CUTTING TOOLS, PERFORMANCE(ENGINEERING)

(U)

THE REPORT COVERS THE STATE OF THE ART OF METAL-REMOVAL OPERATIONS FOR TITANIUM AND ITS ALLOYS. IT DESCRIBES THE METHODS CURRENTLY EMPLOYED FOR CONVENTIONAL MACHINING, GRINDING, ELECTROLYTIC, AND CHEMICAL MACHINING PROCESSES. THE PRECAUTIONS WHICH SHOULD BE TAKEN TO AVOID TROUBLES RESULTING FROM THE CHARACTERISTICS TYPICAL OF TITANIUM ARE POINTED OUT. TEN MACHINING, TWO GRINDING, TWO CUTTING, AND TWO UNCONVENTIONAL METAL-REMOVAL OPERATIONS ARE DISCUSSED SEPARATELY. IN OTHER SECTIONS, THE MECHANICS OF CHIP-FORMING PROCESSES, THE RESPONSE TO MACHINING VARIABLES, COSTS, AND PRECAUTIONS DECTRABLE FROM THE STANDPOINT OF SAFETY ARE DISCUSSED. (AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-621 454

HARSHAW CHEMICAL CO CLEVELAND OHIO

RESEARCH ON PHOTOVOLTAIC CELLS:

(U)

DESCRIPTIVE NOTE: FINAL REPT. FOR 1 MAY 62-30 APR 65,  
JUN 65 125P HEYERDAHL, NORMAN E. HARVEY,

DONALD J. I

CONTRACT: AF33 657 7916

PROJ: 7885

TASK: 788502

MONITOR: ARL , 65-111

UNCLASSIFIED REPORT

DESCRIPTORS: (\*SOLAR CELLS, SEM CONDUCTING FILMS),  
(\*SEMICONDUCTING FILMS, SOLAR CELLS), CADMIUM  
COMPOUNDS, SULFIDES, SELENIUM, CADMIUM ALLOYS,  
SELENIUM ALLOYS, TELLURIUM ALLOYS, ZINC ALLOYS,  
GALLIUM ALLOYS, ARSENIC ALLOYS, CHEMICAL MILLING,  
VAPOR PLATING, MAGNETIC PROPERTIES, ELECTRICAL  
PROPERTIES, THERMOELECTRICITY, LIGHT  
TRANSMISSION

(U)

IDENTIFIERS: THIN FILMS

(M)

THE REPORT DESCRIBES RESEARCH AND DEVELOPMENT ON  
THIN FILM SOLAR BATTERIES. THE FABRICATION AND  
STUDY OF THIN FILMS OF CDS:SE, CDSE,  
CDTE, ZNSE, AND GAAS AND THIN FILM SOLAR  
BATTERIES OF CDS:SE, CDSE, AND CDTE IS  
DISCUSSED IN DETAIL. A STUDY OF THE ETCHING  
BEHAVIOUR OF II-VI COMPOUNDS, COMPLETED AS A PART  
OF THIS PROGRAM, HAS BEEN PUBLISHED ELSEWHERE. AN  
ABSTRACT OF THE WORK IS INCLUDED IN THIS REPORT.  
(AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-622 879

TRW SEMICONDUCTORS INC LAWDALE CALIF RESEARCH AND  
DEVELOPMENT DEPT

TRANSISTOR, VHF, SILICON, POWER (10W-500MC). (U)

DESCRIPTIVE NOTE: FINAL REPT. FOR 1 JUL 63-15 JAN 65,  
JAN 65 120P CLARKE, R. N. ICRISHAL, J. I  
REPT. NO. 59-RD-F  
CONTRACT: DA36 039AMC03189E  
PROJ: 1P6 22001A056  
TASK: 1P6 22001A056 01

UNCLASSIFIED REPORT

DESCRIPTORS: (TRANSISTORS, SILICON), VERY HIGH  
FREQUENCY, RADIOFREQUENCY POWER, CRYSTALS,  
PROCESSING, PACKAGING, CHEMICAL MILLING,  
DIFFUSION, SILICONE PLASTICS, VAPOR PLATING,  
METAL FILMS (U)

THE TRANSISTOR PRODUCES 10 WATTS AT 500 MC WITH 5-6  
DB OF POWER GAIN AND 30-40% COLLECTOR EFFICIENCY.  
THE CRYSTAL WAS ORIGINALLY DESIGNED ACCORDING TO  
PRESENT POWER GAIN THEORY, BUT IT ONLY HAD ONE TO TWO  
DB OF POWER GAIN AT 500 MC. THE SECOND CRYSTAL  
DESIGN WAS BASED UPON THE SMALLEST PRACTICAL PATTERN  
DIMENSIONS, OR A 0.1 MIL MINIMUM SPACING. THE  
REDESIGNED PATTERN ALSO HAD PROVISION FOR ANALYZING  
THE TRANSISTOR IN MULTIPLES OF SUB CELLS AS WELL AS  
IN ITS ENTIRETY. SUCH AN ANALYSIS SHOWED THE  
NECESSITY OF SYMMETRY OF BASE FEED IN COMMON EMITTER  
AMPLIFIERS TO GET ALL THE CELLS WORKING TOGETHER.  
PARALLELING OF CELLS ALSO INDICATED AN APPARENT  
LOSS IN F SUB T WITH INCREASED SIZE. PROCESSING  
AND ASSEMBLY WAS GENERALLY ALONG STANDARD INDUSTRY  
PRACTICE EXCEPT IN THE AREA OF PHOTORESIST. THERE,  
IMPROVED GLASS MASKS WERE USED, ALONG WITH THE NEW  
KTR PHOTORESIST. SUCCESSFUL ETCHING OF FINE  
METALLIZED PATTERNS WAS ACCOMPLISHED THROUGH THE  
DEVELOPMENT OF A JET ETCHING TECHNIQUE. TO RETAIN  
AS MUCH OF THE INNATE CRYSTAL PERFORMANCE CAPABILITY  
AS POSSIBLE, CONSIDERABLE WORK WAS DONE ON PACKAGING.  
IT WAS CONCLUDED THAT NO AVAILABLE PACKAGE WAS  
TRULY ADEQUATE. THE BEST AVAILABLE FOR THE R.F.  
PERFORMANCE IS THE SILICONE MOLDED PACKAGE DUE TO ITS  
SHORT, LOW-LOSS LEADS. (U)

83

UNCLASSIFIED

/ZOML6

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-625 317 9/1 13/8  
MOTOROLA INC PHOENIX ARIZ SEMICONDUCTOR PRODUCTS DIV

PRODUCTION ENGINEERING MEASURE FOR SILICON OVERLAY  
TRANSISTORS. (U)

DESCRIPTIVE NOTE: QUARTERLY PROGRESS REPT. NO. 2, 1 APR-  
30 JUN 65,  
JUN 65 31P CASSIDY, MICHAEL ; GREER, PAUL

CONTRACT: DA-36-U39-AMC-06156(E)  
PROJ: DA-74001

UNCLASSIFIED REPORT

DESCRIPTORS: (\*TRANSISTORS, MANUFACTURING METHODS),  
(\*SILICON, TRANSISTORS), DIFFUSION, GOLD,  
CHEMICAL MILLING, PRECISION FINISHING,  
PROCESSING, ENCAPSULATION, BONDING, GLASS,  
WIRE, EPITAXIAL GROWTH,  
RELIABILITY(ELECTRONICS), QUALITY CONTROL (U)

PROGRESS DURING THE REPORT PERIOD CONSISTED OF THE  
FOLLOWING: (1) FABRICATION OF DEVICES USING THE  
BORON TRIBROMIDE (BBR3) BASE DIFFUSION METHOD.  
WAFERS ARE ALSO IN PROCESS USING A COMBINATION OF  
THE BBR3 BASE DIFFUSION AND THE EMITTER-GOLD  
EMITTER DIFFUSION. (2) TRANSITION TO 2-INCH  
MASKS TO GIVE BETTER DEFINITION AND DETAIL. MASK  
MEASUREMENT BY PRECISE METHODS TO INSURE MASK  
ACCURACY AND REPEATABILITY. (3) EVALUATION OF  
EFFECTS OF VARIATIONS IN EMITTER STRIPE WIDTH.  
(4) FABRICATION OF WAFERS USING THE CHEMICAL ETCH  
PROCESS. (5) CONSTRUCTION OF WAFER STORAGE  
CABINET TO DETERMINE EFFECTS OF PROLONGED WAFER  
STORAGE BETWEEN VARIOUS PROCESS STEPS. (6)  
CONTINUED INVESTIGATION OF ULTRASONIC WIRE BONDING  
AND ANALYSIS OF THE RESULTS OBTAINED BY ULTRASONIC  
BONDING TO RAW KOVAR TOP POSTS. (7) DEVELOPMENT  
OF A PROCESS EVALUATION TEST PLAN AND AN  
ENVIRONMENTAL STEP STRESS TEST PLAN. COMPLETION OF  
INITIAL ELECTRICAL PARAMETER READOUTS. EVALUATION  
OF SAMPLES FABRICATED USING THE BBR3 BASE DIFFUSION  
METHOD. (AUTHOR) (U)

UNCLASSIFIED

UDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-628 230 9/1 13/8  
MOTOROLA INC PHOENIX ARIZ SEMICONDUCTOR PRODUCTS DIV

PRODUCTION ENGINEERING MEASURE FOR SILICON OVERLAY  
TRANSISTORS. (U)

DESCRIPTIVE NOTE: QUARTERLY PROGRESS REPT. NO. 3, 1 JUL-  
30 SEP 65,  
SEP 65 32P KEARKUFF, THOMAS ; GREER, PAUL

CONTRACT: DA-36-039-AMC-06156(E),  
PROJ: DA-74001.

UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: SEE ALSO AD-625 317.

DESCRIPTORS: (\*TRANSISTORS, MANUFACTURING METHODS),  
(\*SILICON, TRANSISTORS), DOPING, GOLD, CHEMICAL  
MILLING, PRECISION FINISHING, PROCESSING,  
ENCAPSULATION, ULTRASONIC RADIATION, BONDING,  
WIRE, ASSEMBLING, RELIABILITY(ELECTRONICS) (U)

PROGRESS DURING THE REPORTING PERIOD CONSISTED OF  
THE FOLLOWING: (1) DIFFUSION SYSTEMS. WORK WAS  
COMPLETED ON THE BBR3 BASE DIFFUSION SYSTEM, AND  
SYSTEM FEASIBILITY WAS DETERMINED. THE EMITTER-  
GOLD EMITTER DIFFUSION SYSTEM WAS ALSO EVALUATED FOR  
FEASIBILITY. (2) WAFER PROCESSING. THE  
FEASIBILITY OF USING 1 1/2 INCH WAFERS WITH SLURRY  
POLISH AND CHEMICAL ETCH WAS INVESTIGATED. (3)  
WAFER STORAGE. DEVICES WHICH HAD BEEN STORED IN  
N2 FOR 15 DAYS AT VARIOUS STEPS WERE PROCESSED AND  
EVALUATED. (4) ASSEMBLY PROCESSING. UNITS WERE  
CONSTRUCTED USING ULTRASONIC WIRE BONDING OF ALUMINUM  
WIRE TO BARE KOVAR POSTS AND DEIONIZED WATER BOILING  
PRIOR TO ENCAPSULATION. (5) RELIABILITY.  
COMPLETED UNITS WERE EVALUATED. (AUTHOR) (U)

UNCLASSIFIED

UDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-628 230 9/1 13/8  
MOTOROLA INC PHOENIX ARIZ SEMICONDUCTOR PRODUCTS DIV

PRODUCTION ENGINEERING MEASURE FOR SILICON OVERLAY  
TRANSISTORS. (U)

DESCRIPTIVE NOTE: QUARTERLY PROGRESS REPT. NO. 3, 1 JUL-  
30 SEP 65,  
SEP 65 32P KEARKUFF, THOMAS ; GREER, PAUL

CONTRACT: DA-36-039-AMC-06156(E),  
PROJ: DA-74001.

UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: SEE ALSO AD-625 317.

DESCRIPTORS: (TRANSISTORS, MANUFACTURING METHODS),  
(SILICON, TRANSISTORS), DOPING, GOLD, CHEMICAL  
MILLING, PRECISION FINISHING, PROCESSING,  
ENCAPSULATION, ULTRASONIC RADIATION, BONDING,  
WIRE, ASSEMBLING, RELIABILITY(ELECTRONICS) (U)

PROGRESS DURING THE REPORTING PERIOD CONSISTED OF  
THE FOLLOWING: (1) DIFFUSION SYSTEMS. WORK WAS  
COMPLETED ON THE BBR3 BASE DIFFUSION SYSTEM, AND  
SYSTEM FEASIBILITY WAS DETERMINED. THE EMITTER-  
GOLD EMITTER DIFFUSION SYSTEM WAS ALSO EVALUATED FOR  
FEASIBILITY. (2) WAFER PROCESSING. THE  
FEASIBILITY OF USING 1 1/2 INCH WAFERS WITH SLURRY  
POLISH AND CHEMICAL ETCH WAS INVESTIGATED. (3)  
WAFER STORAGE. DEVICES WHICH HAD BEEN STORED IN  
N2 FOR 15 DAYS AT VARIOUS STEPS WERE PROCESSED AND  
EVALUATED. (4) ASSEMBLY PROCESSING. UNITS WERE  
CONSTRUCTED USING ULTRASONIC WIRE BONDING OF ALUMINUM  
WIRE TO BARE KOVAR POSTS AND DEIONIZED WATER BOILING  
PRIOR TO ENCAPSULATION. (5) RELIABILITY.  
COMPLETED UNITS WERE EVALUATED. (AUTHOR) (U)

UNCLASSIFIED

UDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD#631 952 13/8  
NAVAL AIR ENGINEERING CENTER PHILADELPHIA PA AERONAUTICAL  
MATERIALS LAB

CHEMICAL MILLING OF ALLOY STEELS, (U)

MAR 66 23P KETCHAM, SARA J. ;  
REPT. NO. NAEC-AML-2418;  
PROJ: HRMA-02-011/200-1/F020-01-01

UNCLASSIFIED REPORT

DESCRIPTORS: (\*CHEMICAL MILLING, \*STEEL), HYDROGEN  
EMBRITTEMENT, STRESS CORROSION,  
FRACTURE (METALLURGY), SURFACE PROPERTIES (U)  
IDENTIFIERS: STEEL H-11, STEEL 4340, STAINLESS  
STEEL 17-7PH (U)

EXPERIMENTS WERE CONDUCTED TO DETERMINE THE EFFECT  
OF CHEMICAL MILLING ON SUSCEPTIBILITY OF HIGH  
STRENGTH STEELS TO HYDROGEN EMBRITTEMENT AND STRESS  
CORROSION CRACKING. ALLOYS STUDIED INCLUDED H-  
11, 4340 AND 17-7 PH. RESULTS INDICATED THAT THE  
ACID BATHS USED FOR CHEMICAL MILLING DO INITIALLY  
EMBRITTE THESE ALLOYS, BUT RECOVERY OF DUCTILITY  
TAKES PLACE AT ROOM TEMPERATURE WITHIN ONE WEEK IF  
THERE IS NO BARRIER TO THE ESCAPE OF HYDROGEN (SUCH  
AS A PLATING). A RECOVERY TREATMENT OF 48 HOURS AT  
ROOM TEMPERATURE FOLLOWED BY 4 HOURS AT 375F IS  
RECOMMENDED. A HIGH STRENGTH STEEL WITH A CHEM-  
MILLED SURFACE IS MORE SUSCEPTIBLE TO STRESS  
CORROSION CRACKING THAN ONE WITH A MACHINE GROUND  
SURFACE. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-634 075 13/8 11/6 13/9  
BATTELLE MEMORIAL INST COLUMBUS OHIO

MACHINING AND GRINDING OF NICKEL-AND COBALT-BASE  
ALLOYS.

(U)

APR 66 146P OLOFSON, C. T. ; GURKLIS, J. A.  
; BOULGER, F. W. ;  
CONTRACT: DA-01-021-AMC-11651(Z),  
MONITOR: NASA ,RSIC TM-X-53446 ,482

UNCLASSIFIED REPORT

DESCRIPTORS: (\*NICKEL ALLOYS, MATERIAL REMOVAL),  
(\*COBALT ALLOYS, MATERIAL REMOVAL), (\*MATERIAL  
REMOVAL, STATE-OF-THE-ART REVIEWS), MACHINING,  
GRINDERS, CHEMICAL MILLING, ELECTROEROSIVE  
MACHINING, CUTTING, CUTTING TOOLS, DRILLING,  
MACHINE SHOP PRACTICE, MACHINE TOOLS, MILLING  
MACHINES, REAMERS, LATHES, CUTTING FLUIDS,  
DRILLING MACHINES, PRECISION FINISHING, ABRASIVES,  
GRINDING, ELECTROLYTES, CLEANING, FRICTION,  
HEAT-RESISTANT METALS + ALLOYS, CORROSION-  
RESISTANT ALLOYS, MECHANICAL PROPERTIES, COPPER  
ALLOYS, IRON ALLOYS, CHROMIUM ALLOYS, CASTING  
ALLOYS

(U)

THE REPORT COVERS THE STATE OF THE ART OF METAL-  
REMOVAL OPERATIONS FOR NICKEL AND COBALT-BASE  
ALLOYS. IT DESCRIBES THE METHODS CURRENTLY  
EMPLOYED FOR CONVENTIONAL MACHINING, GRINDING,  
ELECTROLYTIC, AND CHEMICAL-MACHINING PROCESSES, THE  
PRECAUTIONS THAT SHOULD BE TAKEN TO AVOID TROUBLES  
RESULTING FROM THE CHARACTERISTICS TYPICAL OF THESE  
ALLOYS ARE POINTED OUT. NINE MACHINING, TWO  
GRINDING, TWO CUTTING, AND TWO UNCONVENTIONAL METAL-  
REMOVAL OPERATIONS ARE DISCUSSED SEPARATELY. OTHER  
SECTIONS DISCUSS THE CLASSIFICATION OF THESE ALLOYS  
AND THEIR GENERAL RESPONSE TO MACHINING VARIABLES.  
(AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-634 392 13/8 20/2  
NAVAL ORDNANCE LAB WHITE OAK MD

POLISHES AND ETCHES FOR TIN TELLURIDE, LEAD SULFIDE,  
LEAD SELENIDE, AND LEAD TELLURIDE: SUPPLEMENT. (U)

DESCRIPTIVE NOTE: FINAL REPT. JUN 63-FEB 66,  
MAR 66 ISP NORR, MARRINER K. ;  
REPT. NO. NOLTR-66-32.  
PROJ: FR-46,

UNCLASSIFIED REPORT

DESCRIPTORS: (\*CHEMICAL MILLING, CRYSTALS),  
(\*ETCHING, CRYSTALS), (\*ELECTROLYTIC POLISHING,  
CRYSTALS), (\*CRYSTALS, PRECISION FINISHING), TIN  
ALLOYS, TELLURIUM ALLOYS, LEAD ALLOYS, LEAD  
COMPOUNDS, SULFIDES, SELENIUM ALLOYS,  
INTERMETALLIC COMPOUNDS, CRYSTAL LATTICE  
DEFECTS (U)  
IDENTIFIERS: ETCHES, POLISHES, TIN TELLURIDE,  
LEAD SULFIDE, LEAD SELENIDE, LEAD TELLURIDE (U)

THIS REPORT IS A CONTINUATION OF NOLTR 63-156  
(AD-423 367). TOGETHER, THE TWO REPORTS PRESENT A  
REVIEW OF CHEMICAL AND ELECTROLYTIC POLISHES AND  
DISLOCATION ETCHES FOR SNTE, PBS, PBSE,  
AND PHTE, COVERING THE PERIOD FROM 1907 THROUGH  
1965. THE PRESENT REPORT ALSO DESCRIBES A NEW  
POLISH AND A NEW DISLOCATION ETCH FOR TIN TELLURIDE,  
AS WELL AS TESTS ON AND IMPROVEMENTS IN SOME OF THE  
POLISHES REPORTED IN EARLIER PUBLICATION.  
(AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-635 814 9/1 13/8  
MOTOROLA INC PHOENIX ARIZ SEMICONDUCTOR PRODUCTS DIV

PRODUCTION ENGINEERING MEASURE FOR SILICON OVERLAY  
TRANSISTORS. (U)

DESCRIPTIVE NOTE: QUARTERLY PROGRESS REPT. NO. 4, 1 OCT-  
31 DEC 65.

DEC 65 37P CASSIDY, MICHAEL ; GREER, PAUL

CONTRACT: DA-36-039-AMC-06156(E),  
PROJ: DA-7401,

UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: SEE ALSO AD-635 118.

DESCRIPTORS: (\*TRANSISTORS, MANUFACTURING METHODS),  
(\*SILICON, TRANSISTORS), DISKS, PREPARATION,  
BONDING, DIFFUSION, STORAGE,  
RELIABILITY (ELECTRONICS), ULTRASONIC WELDING,  
CHEMICAL MILLING, ETCHING, ELECTRIC TERMINALS (U)

PROGRESS DURING THE PAST QUARTER HAS CONSISTED OF  
THE FOLLOWING: (1) WAFER PREPARATION:  
PROCESSING OF 1 1/2-INCH SLURRY-POLISHED AND  
CHEMICALLY ETCHED WAFERS USING THE NEW PREGHMIC TWO-  
STEP PHOTORESIST PROCESS. (2) MASK RESOLUTION  
AND ALIGNMENT: VERTICAL AND HORIZONTAL  
DIMENSIONAL INSPECTION OF MASKS TO ELIMINATE MASK  
VARIATIONS. (3) DEIONIZED WATER BOIL:  
EVALUATION OF ULTRASONICALLY WIRE-BONDED DEVICES  
AFTER SUBJECTION TO DEIONIZED WATER BOIL. (4)  
WIRE BONDING: EVALUATION OF UNITS FABRICATED  
USING A SONO BOND ULTRASONIC BONDER. (5)  
DIFFUSION SYSTEMS: FINAL EVALUATION OF THE  
BCL3 SYSTEM. EMITTER DIFFUSION EMPLOYING A  
CONTROLLED POCL3 SOURCE TEMPERATURE. (6)  
RELIABILITY EVALUATION: EVALUATION OF COMPLETED  
UNITS. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-639 454 13/8 13/9  
BATTELLE MEMORIAL INST COLUMBUS OHIO

MACHINING AND GRINDING OF ULTRAHIGH-STRENGTH STEELS  
AND STAINLESS STEEL ALLOYS. (U)

OCT 65 214P OLOFSON, C. T. ; GURKLIS, J. A. ;  
BOULGER, F. W. ;  
CONTRACT: DA-01-021-AMC-11651(Z),  
MONITOR: NASA ,RSIC TM-X-53433 ,501

UNCLASSIFIED REPORT

DESCRIPTORS: (\*STEEL, \*MATERIAL REMOVAL),  
(\*MACHINING, STEEL), (\*GRINDING, STEEL),  
STAINLESS STEEL, STATE-OF-THE-ART REVIEWS, CHEMICAL  
MILLING, MACHINE TOOLS, CUTTING FLUIDS, CUTTING  
TOOLS, SMALL TOOLS (U)

THE REPORT COVERS THE STATE OF THE ART OF METAL-  
REMOVAL OPERATIONS FOR STAINLESS AND ULTRAHIGH-  
STRENGTH STEELS. IT DESCRIBES THE METHODS  
CURRENTLY EMPLOYED FOR CONVENTIONAL MACHINING,  
GRINDING, ELECTROLYTIC, ELECTRIC-DISCHARGE, AND  
CHEMICAL-MACHINING PROCESSES. THE PRECAUTIONS THAT  
SHOULD BE TAKEN TO AVOID TROUBLES RESULTING FROM THE  
CHARACTERISTICS TYPICAL OF THESE ALLOYS ARE POINTED  
OUT. NINE MACHINING, TWO GRINDING, TWO CUTTING,  
AND THREE UNCONVENTIONAL METAL-REMOVAL OPERATIONS ARE  
DISCUSSED SEPARATELY. OTHER SECTIONS DISCUSS THE  
CLASSIFICATION OF THESE ALLOYS AND THEIR GENERAL  
RESPONSE TO MACHINING VARIABLES. (AUTHOR) (U)

UNCLASSIFIED

DOC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-648 980 13/8  
NAVAL AIR MATERIAL CENTER PHILADELPHIA PA AERONAUTICAL  
MATERIALS LAB

CHEMICAL MILLING OF METALS AND ALLOYS; ITS EFFECT ON  
STRESS CORROSION SUSCEPTIBILITY AND HYDROGEN  
EMBRITTELEMENT. (U)

MAY 61 4P KETCHAM, S. J. ;  
REPT. NO. NAMC-AML-1236

UNCLASSIFIED REPORT

DESCRIPTORS: (\*CHEMICAL MILLING, \*ALUMINUM  
ALLOYS), (\*STEEL, CHEMICAL MILLING),  
(\*CORROSION-RESISTANT ALLOYS, TITANIUM),  
DEGRADATION, HYDROGEN EMBRITTELEMENT, TEMPERATURE,  
SOLUTIONS, SURFACE PROPERTIES (U)  
IDENTIFIERS: ALUMINUM ALLOY 2024, ALUMINUM ALLOY  
7075, ALUMINUM ALLOY X2020 (U)

THE PAPER CONTAINS SPECIFICATIONS TO CONTROL THE  
SOLUTIONS AND PROCESSES FOR THE VARIOUS METALS AND  
ALLOYS. A METHOD FOR DETERMINING WHETHER ANY STEP  
IN THE PROCESS CAN ACCELERATE STRESS CORROSION IN  
ALUMINUM ALLOYS AND CORROSION RESISTING STEELS, OR  
CAUSE HYDROGEN EMBRITTELEMENT IN STEEL AND TITANIUM  
ALLOYS SUSCEPTIBLE TO SUCH EMBRITTELEMENT, IS DESIRED  
FOR INCORPORATION INTO THE SPECIFICATION AS WELL AS  
ESTABLISHMENT OF CRITERIA FOR ASSESSING THE SEVERITY  
OF SUCH EFFECTS. THE PROJECT CONTAINS:  
ALUMINUM ALLOYS; STEELS; TITANIUM ALLOYS.  
(AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-674 066 11/6 13/8  
BATTELLE MEMORIAL INST COLUMBUS OHIO DEFENSE METALS  
INFORMATION CENTER

A REVIEW OF METALLOGRAPHIC PREPARATION PROCEDURES FOR  
BERYLLIUM AND BERYLLIUM ALLOYS, (U)

JUN 68 ZUP PRICE, C. W. MCCALL, J.

L. ;

REPT. NO. DMIC-MEMO-237  
CONTRACT: F33615-68-C-1325

UNCLASSIFIED REPORT

DESCRIPTORS: (\*BERYLLIUM, METALLOGRAPHY),  
(\*BERYLLIUM ALLOYS, METALLOGRAPHY), REVIEWS,  
ELECTRON MICROSCOPY, FINISHES + FINISHING,  
GRINDING, ETCHING, CUTTING, MACHINING,  
CHEMICAL MILLING (U)

THE MEMORANDUM IS DIVIDED INTO FOUR TOPICS:  
(1) GRINDING, (2) POLISHING, (3)  
ETCHING, AND (4) THINNING FOR TRANSMISSION  
ELECTRON MICROSCOPY. PROCEDURES REVIEWED ARE ALSO  
LISTED IN TABULAR FORM FOR READY REFERENCE. IN  
ADDITION TO REVIEWING PUBLISHED REFERENCES, THE  
AUTHORS HAVE INCLUDED A CONSIDERABLE AMOUNT OF  
PREVIOUSLY UNPUBLISHED DATA BASED ON THEIR OWN  
EXPERIENCE AND PRIVATE COMMUNICATION WITH ASSOCIATES  
IN THE FIELD. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-677 066 11/6 13/8  
GENERAL DYNAMICS/CONVAIR SAN DIEGO CALIF

REDUCING HAND STRAIGHTENING BY CHEM-MILLING 7075  
AND 7178 ALUMINUM ALLOY IN THE 'W' (OR  
NATURALLY AGED) CONDITION. (U)

DESCRIPTIVE NOTE: FINAL REPT.,  
OCT 60 23P WHITING, H. A. (PLUMMER, C.  
E. I.  
REPT. NO. GDC-PR919

UNCLASSIFIED REPORT

DESCRIPTORS: (+ALUMINUM ALLOYS, +CHEMICAL  
MILLING), ETCHING, SURFACE ROUGHNESS, FINISHES  
+ FINISHING, AGING (MATERIALS),  
PANELS (STRUCTURAL), MECHANICAL WORKING,  
TOLERANCES (MECHANICS) (U)  
IDENTIFIERS: ALUMINUM ALLOY 7075, ALUMINUM ALLOY  
7185 (U)

THE OBJECTIVE AND PURPOSE OF THE PROJECT WAS TO  
ETCH 7075 AND 7178 ALUMINUM ALLOYS, 0.125 IN. THICK,  
IN THE 'W' (OR NATURALLY AGED CONDITION). A  
MAXIMUM SURFACE ROUGHNESS (RMS) OF 125 MICROINCHES  
WAS NOT TO BE EXCEEDED. (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZDML6

AD-677 494

11/6

13/8

GENERAL DYNAMICS/ASTRONAUTICS SAN DIEGO CALIF

STRIPPING PT201 THERMOSETTING RESIN COATINGS FROM  
321 ANNEALED STAINLESS STEEL SURFACES,  
(PROPELLANT UTILIZATION MANOMETER HOUSINGS).

(U)

SEP 61

15P

SHIWANOV, E. J

REPT. NO. GDA-AN6IAMR4062

UNCLASSIFIED REPORT

DESCRIPTORS: (\*STAINLESS STEEL, \*CHEMICAL  
MILLING), THERMOSETTING PLASTICS, SULFURIC ACID,  
ULTRASONIC RADIATION, STAINLESS STEEL, REMOVAL,  
SURFACES, MANOMETERS, CLEANING, PLASTIC COATINGS

(U)

THE REPORT DISCUSSES THE DEVELOPMENT OF A NEW  
CHEMICAL STRIPPER. IT WAS FOUND THAT THE USE OF  
SULFURIC ACID IN COMBINATION WITH ULTRASONIC  
VIBRATION (40KC.) WAS AN EFFICIENT METHOD TO  
STRIP AND DISINTEGRATE PT201 THERMOSETTING RESIN  
FROM THE SURFACE OF MANOMETER HOUSINGS. THREE SUCH  
HOUSINGS WERE EFFECTIVELY CLEANED BY THIS METHOD  
WITHIN A PERIOD OF TEN MINUTES AND WERE IN ACCORDANCE  
WITH THE REQUIREMENTS OF MS 60.148A.  
MAINTENANCE CLEANING OF PROPELLANT  
UTILIZATION MANOMETERS. (AUTHOR)

(U)

UNCLASSIFIED

DUC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AU-678 154 13/8 13/13 11/6  
GENERAL DYNAMICS/CONVAIR SAN DIEGO CALIF

CHEM-MILL PROCESS FOR CONTOURING ALUMINUM  
HONEYCOMB CORE.

(U)

DESCRIPTIVE NOTE: FINAL REPT.,  
NOV 60 77P GLENSK, F. J. ;  
REPT. NO. GDC-PR-920

UNCLASSIFIED REPORT

DESCRIPTORS: (\*HONEYCOMB CORES, \*CHEMICAL  
MILLING), (\*ALUMINUM ALLOYS, CHEMICAL MILLING),  
BONDING, PRESSURE, THICKNESS,  
PANELS (STRUCTURAL), SANDWICH CONSTRUCTION,  
COSTS, FLEXURAL STRENGTH, SPECIFICATIONS,  
MASKING, FEASIBILITY STUDIES

(U)

CONTOURING ALUMINUM HONEYCOMB CORE BY MECHANICAL  
MEANS IS DIFFICULT AND EXPENSIVE. A REVOLUTIONARY  
METHOD OF CONTOURING BY CHEMICAL MILLING HAS BEEN  
INVENTED. THIS PROCESS HAS BEEN SUCCESSFULLY  
APPLIED TO 1/4 INCH CELL-SIZED CORES. THE PROBLEM  
WAS TO CONTOUR 1/8 INCH CELL-SIZED CORES, SINCE THIS  
IS A PRODUCTION ITEM. THIS PROJECT WAS AN ATTEMPT  
TO ADAPT THE PROCESS TO 1/8 INCH CELL-SIZED CORES.  
(AUTHOR)

(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-680 561 13/8  
FOREIGN TECHNOLOGY DIV WRIGHT-PATTERSON AFB OHIO

CHEMICAL MILLING (DEEP CONTOUR ETCHING), (U)

MAY 68 14P TARASOVA, V. A. 1  
REPT. NO. FTD-HT-23-1225-67

UNCLASSIFIED REPORT

PORTIONS OF THIS DOCUMENT ARE ILLEGIBLE. SEE  
INTRODUCTION SECTION OF THIS ANNOUNCEMENT JOURNAL FOR CFST  
ORDERING INSTRUCTIONS.

SUPPLEMENTARY NOTE: UNEDITED ROUGH DRAFT TRANS. OF MONO.  
SPRAVOCHNIK MASHINOSTROITEL'YA (REFERENCE BOOK FOR  
THE MECHANICAL ENGINEER) N.P., 1963 V5 BK. 1 P387-393,  
BY E. HARTER.

DESCRIPTORS: (CHEMICAL MILLING, REVIEWS),  
INORGANIC ACIDS, CLEANING, MASKING, ETCHING,  
LIQUID IMMERSION TESTS, ALUMINUM ALLOYS, TITANIUM  
ALLOYS, STAINLESS STEEL, TABLES, POLYVINYL  
CHLORIDE, USSR (U)

IDENTIFIERS: TRANSLATIONS (U)

FOR THE SHAPING OF PARTS, INSTEAD OF MECHANICAL  
REMOVING OF MATERIAL TO OBTAIN A GIVEN FORM THERE IS  
DESCRIBED A METHOD OF ETCHING THE MATERIAL AWAY WITH  
CHEMICALS. THERE ARE FOUR OPERATIONS INVOLVED IN  
THIS PROCESS. THE MATERIAL NOT TO BE REMOVED IS  
PROTECTED BY PAINTS AND VARNISHES, PREFERABLY  
CHLORINATED-POLYVINYL-CHLORIDE LACQUERS AND ENAMELS.  
ADHESIVE TAPES AND RUBBER ARE ALSO USED. THE  
SURFACE HAS TO BE PREPARED BEFOREHAND. NOT MORE  
THAN 24 HOURS SHOULD ELAPSE BETWEEN THE APPLYING OF  
THESE PROTECTIONS AND THE ETCHING WORK. WEAKENING  
AND WARPING IS AVOIDED BY USING CHEMICALS INSTEAD OF  
MACHINING. EXTENSIVE TABLES ARE ATTACHED GIVING  
DIRECTIONS FOR THE PREPARING AND APPLYING THE  
COATINGS TO PROTECT MATERIAL NOT TO BE REMOVED AND  
FOR REMOVING THE COATING AFTERWARDS. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD#681 765 11/6  
GENERAL DYNAMICS/ASTRONAUTICS SAN DIEGO CALIF

A NEW APPROACH TO BEND TESTING FOR THE DETERMINATION  
OF HYDROGEN EMBRITTLEMENT SUSCEPTIBILITY OF SHEET  
MATERIALS. (U)

JUN 61 31P JONES, R. L. ;  
REPT. NO. GDA-MRG-235

UNCLASSIFIED REPORT

DESCRIPTORS: (\*METAL PLATES, HYDROGEN  
EMBRITTLEMENT), (\*HYDROGEN EMBRITTLEMENT, TEST  
METHODS), STEEL, BENDING, COMPRESSIVE  
PROPERTIES, CHEMICAL MILLING, ELECTROPLATING,  
CADMIUM, FAILURE(MECHANICS), DUCTILITY,  
STRESSES, HYDROGEN, DIFFUSION, STRESS  
RELIEVING (U)  
IDENTIFIERS: STEEL 4340 (U)

A SERIES OF EXPERIMENTAL PROGRAMS WERE CARRIED OUT  
TO DETERMINE THE SUITABILITY AND SENSITIVITY OF A NEW  
TEST TECHNIQUE FOR THE DETERMINATION OF HYDROGEN  
EMBRITTLEMENT SUSCEPTIBILITY OF MATERIALS. A  
SIMPLE BEND TEST WAS USED TO STUDY THE EFFECT OF  
CHEMICAL MILLING AND CADMIUM PLATING ON HYDROGEN  
EMBRITTLEMENT OF HIGH STRENGTH 4340 STEEL SHEET.  
THE BEND TEST CONSISTED OF LOADING A COUPON IN THE  
FORM OF A SLENDER COLUMN IN COMPRESSION AT A SERIES  
OF FIXED BENDING SPEEDS. BEND DUCTILITY WAS  
MEASURED AS THE DEPRESSION OF COLUMN HEIGHT AT  
FRACTURE AND ALL DATA WERE REFERRED BACK TO A BASE  
LINE CONDITION (NON-EMBRITLED) FOR COMPARISON.  
(AUTHOR) (U)

UNCLASSIFIED

DOC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD-683 661 13/6 11/6  
BOEING CO RENTON WASH COMMERCIAL AIRPLANE DIV

DETERMINATION OF RESIDUAL STRESS PROFILES BY X-RAY  
DIFFRACTION AND STRAIN GAGE METHODS FOR BRAKE-PRESS  
FORMED TI-6AL-4V. (U)

DEC 68 41P ESQUIVEL, A. L. ;  
REPT. NO. D6-23737

UNCLASSIFIED REPORT

DESCRIPTORS: (\*TITANIUM ALLOYS, STRESSES),  
(\*NON-DESTRUCTIVE TESTING, TITANIUM ALLOYS), X-  
RAY DIFFRACTION ANALYSIS, STRAIN GAGES, COLD  
WORKING, STRESS RELIEVING, CHEMICAL MILLING,  
METAL-FORMING BRAKES (U)  
IDENTIFIERS: TITANIUM ALLOY 6AL 4V, \*RESIDUAL  
STRESS (U)

THE RESIDUAL STRESS PROFILES (STRESS VERSUS  
DEPTH) FROM BRAKE-PRESS FORMED TI-6AL-4V  
(ANNEALED) RIGHT ANGLE BENDS WERE DETERMINED BY  
THE TWO-EXPOSURE X-RAY DIFFRACTION METHOD AND A  
STRESS RELAXATION STRAIN GAGE METHOD USING EITHER  
CONTINUOUS OR STEPWISE (INCREMENTAL) CHEM-  
MILLING. RESULTS FROM THE STRAIN GAGE METHOD WERE  
TESTED ON FOUR AVAILABLE STRESS FORMULATIONS. THE  
HAIGH EQUATION (COMPUTER PROGRAM: NORS) WAS  
FOUND MOST SUITABLE AND IS RECOMMENDED FOR FUTURE  
USE. A REASONABLE CORRESPONDENCE WAS FOUND BETWEEN  
THE RESIDUAL STRESSES CALCULATED FROM X-RAY PEAK  
SHIFT DATA AND THOSE FROM STRAIN GAGE DATA.  
RESIDUAL STRESSES OBTAINED BY THE STRAIN GAGE  
METHOD UTILIZING CHEM-MILLING WERE FOUND REPRODUCIBLE  
TO WITHIN 3 TO 5 KSI. RESIDUAL STRESS PROFILES OF  
THE BRAKE-PRESS FORMED BENDS INDICATE COMPRESSIVE  
STRESS (-30 KSI) NEAR THE OUTSIDE BEND SURFACE  
AND TENSILE STRESSES (40 TO 50 KSI) ON THE INSIDE  
BEND SURFACE. DEPTH OF THE COMPRESSIVE STRESSES  
VARIED FROM 0.008 TO 0.012 INCH. NO SIGNIFICANT  
DIFFERENCES WERE FOUND BETWEEN THE RESIDUAL STRESS  
PROFILES OF BENDS 0.045-INCH THICK AND THOSE 0.050-  
INCH THICK. (AUTHOR) (U)

100

UNCLASSIFIED

/ZOML6

UNCLASSIFIED

UDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AU-725 614 13/8 5/2  
NAVAL MATERIAL INDUSTRIAL RESOURCES OFFICE PHILADELPHIA  
PA

NAVMIRO MANUFACTURING TECHNOLOGY BULLETIN.  
NUMBERS 1 THRU 12, DECEMBER 1969-NOVEMBER  
1970.

(U)

NOV 7U 79P

UNCLASSIFIED REPORT

DESCRIPTORS: (•MANUFACTURING METHODS, REVIEWS),  
MACHINE SHOP PRACTICE, PRECISION FINISHING,  
LASERS, POWDER METALLURGY, SINTERING, EXPLOSIVE  
FORMING, ULTRASONIC WELDING, COMPOSITE MATERIALS,  
CUTTING TOOLS, COOLING, CHEMICAL MILLING,  
ELECTRON BEAM MELTING, SPARK MACHINING, FORGING,  
NON-DESTRUCTIVE TESTING, CASTING  
IDENTIFIERS: COMPUTER AIDED DESIGN

(U)

(U)

THE DOCUMENT IS A COMPILATION OF MANUFACTURING  
TECHNIQUES THAT CAN BE EMPLOYED IN VARIED INDUSTRIES(U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZDML6

AD-727 620 :3/8  
GRUMMAN AEROSPACE CORP BETHPAGE N Y

ADVANCED CHEMICAL MILLING PROCESSES. (U)

DESCRIPTIVE NOTE: FINAL TECHNICAL REPT. 1 JUL 69-31  
DEC 70.

MAR 71 213P STAEBLER, CHRISTIAN J., JR  
CONTRACT: F33615-69-C-1840  
PROJ: AF-705-9  
MONITOR: AFML TR-71-44

UNCLASSIFIED REPORT

DESCRIPTORS: (\*CHEMICAL MILLING, \*TITANIUM  
ALLOYS), AUTOMATION, INORGANIC ACIDS, MASKING,  
ETCHING, HEAT TREATMENT, MECHANICAL WORKING, AIR  
POLLUTION (U)  
IDENTIFIERS: HYDROFLUORIC ACID (U)

THE PROGRAM OBJECTIVE WAS TO IMPROVE THE  
CAPABILITY, RELIABILITY, AND COST EFFECTIVENESS OF  
CHEMICAL MILLING WHEN APPLIED TO SELECTED AEROSPACE  
STRUCTURAL MATERIALS. A COMPLETELY AUTOMATED,  
CENTRIFUGAL REGENERATION SYSTEM FOR TITANIUM  
HYDROFLUORIC ACID ETCHANT WAS DESIGNED, FABRICATED,  
AND TESTED. THIS SYSTEM AUTOMATICALLY ANALYZES THE  
ETCHANT, ADDS FRESH ACID, DETERMINES THE TITANIUM  
CONCENTRATION, AND ACTIVES A CENTRIFUGE WHICH REMOVES  
PRECIPITATED TITANIUM AND RECLAIMS THE ETCHANT. A  
NEW, STYRENE-BUTADIENE MASKANT WAS DEVELOPED THAT  
GIVES EXCELLENT LINE DEFINITION ON TITANIUM  
SUBSTRATES AND THAT CAN BE MANUFACTURED FOR ABOUT  
ONE-HALF THE COST OF COMMERCIALY AVAILABLE MASKANTS.  
THE FEASIBILITY OF USING A LASER-DRILLED, HIGH-  
ENERGY WATER JET TO SCRIBE CHEM-MILLING MASKANTS WAS  
ESTABLISHED. OPTIMUM CHEM-MILLING/FORMING  
METHODIZING SEQUENCES WERE ESTABLISHED THAT MINIMIZE  
DISTORTION OF TITANIUM ALLOY DETAIL PARTS. SAMPLING  
AND ANALYTICAL TECHNIQUES WERE ESTABLISHED FOR THE  
MAJOR POLLUTANTS EMITTED BY CHEM-MILLING OPERATIONS.  
AIR POLLUTION CONTROL AGENCIES AND EQUIPMENT  
MANUFACTURERS WERE SURVEYED. (AUTHOR) (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /ZOML6

AD#738 271 13/8  
BATTELLE COLUMBUS LABS OHIO METALS AND CERAMICS  
INFORMATION CENTER

NONTRADITIONAL MACHINING OF BERYLLIUM, (U)

JAN 72 91P GURKLIS, JOHN A. ;  
REPT. NO. MCIC-72-03

UNCLASSIFIED REPORT

SUPPLEMENTARY NOTE: LIBRARY OF CONGRESS CATALOG CARD NO.  
78-190407.

DESCRIPTORS: (\*ELECTROEROSIVE MACHINING,  
BERYLLIUM); (\*CHEMICAL MILLING, BERYLLIUM);  
(\*BERYLLIUM, MACHINING); MACHINE TOOLS (U)  
IDENTIFIERS: \*ELECTROCHEMICAL MACHINING (U)

THE REPORT DEALS WITH ELECTRICHEMICAL MACHINING  
(ECM), CHEMICAL MILLING, AND ELECTRIC-DISCHARGE  
MACHINING (EDM). THE GENERAL CHARACTERISTICS OF  
THESE PROCESSES AND THEIR APPLICATIONS TO THE  
PROCESSING OF BERYLLIUM PARTS ARE PRESENTED AND  
COVERED IN DETAIL. (U)

UNCLASSIFIED

DDC REPORT BIBLIOGRAPHY SEARCH CONTROL NO. /Z0HL6

AD-870 146 13/8 11/6 1/3  
METCUT RESEARCH ASSOCIATES INC CINCINNATI OHIO

SURFACE INTEGRITY OF MACHINED STRUCTURAL  
COMPONENTS.

(U)

DESCRIPTIVE NOTE: FINAL TECHNICAL REPT. 1 FEB 68-30  
NOV 69;

MAR 70 361P KOSTER, WILLIAM P. FIELD;  
MICHAEL KAHLES, JOHN F. FRITZ, LOUIS J. I  
GATTO, LUCIANO R. I  
REPT. NO. 970-11700  
CONTRACT: F33615-68-C-1003  
PROJ: AF-721-B  
MONITOR: AFML TR-70-11

UNCLASSIFIED REPORT

DESCRIPTORS: (AIRFRAMES, STRUCTURAL PARTS),  
(MATERIAL REMOVAL, EFFECTIVENESS), MILLING  
MACHINES, GRINDING, DRILLING, ELECTROLYTIC  
POLISHING, ELECTROEROSIVE MACHINING, CHEMICAL  
MILLING, MICROSTRUCTURE, MARTENSITE,  
DEFECTS (MATERIALS), SURFACE ROUGHNESS, STRESS  
CORROSION, FATIGUE (MECHANICS),  
AGING (MATERIALS)

(U)

IDENTIFIERS: NICKEL ALLOY INCONEL 718, TITANIUM  
ALLOY 6AL 4V, STEEL 4340, ELECTROCHEMICAL  
MACHINING, ELECTRICAL DISCHARGE MACHINING,  
CHEMICAL MACHINING

(U)

A PROGRAM HAS BEEN RUN TO EVALUATE THE EFFECTS OF  
DIFFERENT METAL REMOVAL METHODS AND VARIATIONS OF  
THESE METHODS ON SURFACE INTEGRITY. THREE ALLOYS  
WERE STUDIED: BETA ROLLED TI-6AL-4V; AISI  
4340, QUENCHED AND TEMPERED, 50 RC; AND INCONEL  
718, SOLUTION TREATED AND AGED. VARIOUS GRINDING  
PROCEDURES CAUSED THE TITANIUM ALLOY TO EXHIBIT A  
FATIGUE STRENGTH RANGE OF 13 TO 62 KSI. THE  
FATIGUE STRENGTH OF 4340 DUE TO GRINDING VARIABLES  
RANGED FROM 62 TO 102 KSI, WHILE INCONEL 718 SHOWED  
A RANGE OF 24 TO 60 KSI. ABUSIVE GRINDING  
CONDITIONS ALWAYS RESULTED IN FATIGUE STRENGTHS AT  
THE MINIMUM OF THESE RANGES. MILLING VARIABLES  
EXHIBITED A FATIGUE STRENGTH RANGE OF 32 TO 72 KSI IN  
THE BETA ROLLED TITANIUM ALLOY. EDM AND ECM ON  
INCONEL 718 YIELDED 22 AND 39 KSI, RESPECTIVELY,  
COMPARED TO 60 KSI FOR GENTLE GRINDING. GUIDELINES  
FOR PROCESSING AEROSPACE HARDWARE CONSIDERING SURFACE  
INTEGRITY REQUIREMENTS ARE PRESENTED IN THE REPORT. (U)

UNCLASSIFIED

CORPORATE AUTHOR - MONITORING AGENCY

•AEROJET-GENERAL CORP SACRAMENTO  
CALIF

•••  
STRUCTURAL TESTS OF A  
CHEMICALLY MILLED LAGISH D-6AC  
STEEL SECOND-STAGE MINUTEHAN AF1  
CLOSURE  
AD-261 959

•AERONAUTICAL SYSTEMS DIV WRIGHT-  
PATTERSON AFB OHIO

•••  
ASD-IR7 727  
500 C SILICON CARBIDE RECTIFIER  
PROGRAM.  
AD-420 775

•••  
ASD-IR7 865 V6  
SILICON SEMICONDUCTOR NETWORKS  
MANUFACTURING METHODS  
AD-291 600

•••  
ASD-TR63 730  
THE DESIGN AND EVALUATION OF  
PERFORATED ION EMITTERS.  
AD-418 226

•••  
ASD-TR7 648 V1  
CHEMICAL COMPOUNDS FOR METAL  
SHAPING  
AD-271 526

•••  
ASD-TR7 648 V3  
CHEMICAL COMPOUNDS FOR METAL  
SHAPING  
AD-295 752

•••  
ASD-TR61 350  
INVESTIGATION OF SINGLE-CRYSTAL  
AND POLYCRYSTALLINE TITANIUM  
DIBORIDE: METALLOGRAPHIC PROCEDURES  
AND FINDINGS  
AD-271 965

•••  
ASD-TR61 706 V2  
BERYLLIUM COMPOSITE STRUCTURES.  
VOLUME II, MATERIALS AND PROCESSES  
AD-278 526

•••  
ASD-TR617 576  
TITANIUM DEVELOPMENT PROGRAM.

VOLUME IV,  
AD-264 685

•AERONCA MFG CORP MIDDLETOWN OHIO

•••  
TR61 706 V2  
BERYLLIUM COMPOSITE STRUCTURES.  
VOLUME II, MATERIALS AND PROCESSES  
(ASD-TR61 706 V2)  
AD-278 526

•AEROSPACE RESEARCH LABS WRIGHT-  
PATTERSON AFB OHIO

•••  
ARL-65-111  
RESEARCH ON PHOTOVOLTAIC CELLS.  
AD-621 454

•AIR FORCE CAMBRIDGE RESEARCH LABS L &  
HANSCOM FIELD MASS

•••  
729  
A NOTE ON SEMICONDUCTOR DEVICE  
FABRICATION  
AD-268 033

•••  
AFCL-1111  
CHEMICAL COMPOUNDS FOR METAL  
SHAPING  
AD-282 720

•AIR FORCE MACHINABILITY DATA CENTER  
CINCINNATI OHIO

•••  
AFMDC-66-2  
MACHINING DATA FOR BERYLLIUM  
METAL,  
AD-485 297

•AIR FORCE MATERIALS LAB WRIGHT-  
PATTERSON AFB OHIO

•••  
AFML-TR-70-11  
SURFACE INTEGRITY OF MACHINED  
STRUCTURAL COMPONENTS.  
AD-870 146

•••  
AFML-TR-71-44  
ADVANCED CHEMICAL MILLING  
PROCESSES.  
AD-727 620

0-1  
UNCLASSIFIED

AIR-BAT

•AIR FORCE OFFICE OF SCIENTIFIC  
RESEARCH ARLINGTON VA

• • •  
AFOSR-2-74  
RESEARCH IN THE GENERAL FIELD  
OF SUBSTRUCTURE AND DISLOCATION  
NETWORKS IN METALLIC CRYSTALS.  
AD-610 424

• • •  
AFOSR-TR-71-2489  
ULTRAVIOLET ABSORPTION SPECTRA  
OF TRANSITION METAL ATOMS IN RARE-  
GAS MIXTURES,  
AD-730 200

•ALLOY ENGINEERING AND CASTING CO  
CHAMPAIGN ILL

• • •  
A FUNDAMENTAL STUDY OF ROLLING  
CONTACT FATIGUE  
AD-276 887

• • •  
A FUNDAMENTAL STUDY OF ROLLING  
CONTACT FATIGUE  
AD-285 085

•ARMY ELECTRONICS LABS FORT MONMOUTH NJ

• • •  
TR-2318  
DESIGN CONSIDERATIONS FOR  
MICROWAVE GERMANIUM TUNNEL DIODES  
AD-294 788

• • •  
TR-2339  
TECHNOLOGY FOR PNP PLANAR  
SILICON TRANSISTORS: SWITCHING AND  
AMPLIFYING,  
AD-408 190

•ARMY MATERIALS RESEARCH AGENCY  
WATERTOWN MASS

• • •  
AMRA-TR-64-4,  
THE METALLOGRAPHY OF PYROLITIC  
GRAPHITE,  
AD-613 643

•ARMY MISSILE COMMAND REDSTONE  
ARSENAL AL: ARMY INERTIAL  
GUIDANCE AND CONTROL LAB AND CENTER

• • •  
RG-TR-62-20

MISSILE-BORNE TRACKING ANTENNA,  
AD-426 922

•BATTELLE COLUMBUS LABS OHIO METALS  
AND CERAMICS INFORMATION CENTER

• • •  
MCIC-72-07  
NONTRADITIONAL MACHINING OF  
BERYLLIUM,  
AD-728 271

•BATTELLE MEMORIAL INST COLUMBUS OHIO

• • •  
MACHINING AND GRINDING OF  
NICKEL-AND COBALT-BASE ALLOYS,  
(NASA-TM-X-52446)  
AD-624 075

• • •  
MACHINING AND GRINDING OF  
ULTRAHIGH-STRENGTH STEELS AND  
STAINLESS STEEL ALLOYS,  
(NASA-TM-X-52423)  
AD-629 654

•BATTELLE MEMORIAL INST COLUMBUS OHIO

• • •  
MACHINING AND GRINDING OF  
TITANIUM AND ITS ALLOYS,  
(NASA-TM-X-52312)  
AD-620 508

•BATTELLE MEMORIAL INST COLUMBUS OHIO  
DEFENSE METALS INFORMATION CENTER

• • •  
A SURVEY OF THE COMPARATIVE  
COSTS OF FABRICATING AIRFRAME FROM  
ALUMINUM AND FROM TITANIUM,  
AD-609 249

• • •  
DMIC-213  
METAL REMOVAL BY  
ELECTROCHEMICAL METHODS AND ITS  
EFFECTS ON MECHANICAL PROPERTIES OF  
METALS,  
AD-613 261

• • •  
DMIC-MEMO-227  
A REVIEW OF METALLOGRAPHIC  
PREPARATION PROCEDURES FOR

BERYLLIUM AND BERYLLIUM ALLOYS,  
AD-674 066

• • •  
M144  
A REVIEW OF RECENT DEVELOPMENTS  
IN TITANIUM AND TITANIUM ALLOY  
TECHNOLOGY  
AD-269 209

• BELL TELEPHONE LABS INC WHIPPANY N J  
• • •  
12  
ENGINEERING SERVICES ON  
TRANSISTORS.  
AD-422 492

• BOEING CO RENTON WASH COMMERCIAL  
AIRPLANE DIV  
• • •  
D6-23737  
DETERMINATION OF RESIDUAL  
STRESS PROFILES BY X-RAY  
DIFFRACTION AND STRAIN GAGE METHODS  
FOR BRAKE-PRESS FORMED TI-6AL-4V,  
AD-683 041

• BOEING CO WICHITA KANS WICHITA DIV  
• • •  
BOEING-WICHITA MATERIALS AND  
RESEARCH DEVELOPMENT PROGRAMS, 1957-  
1961  
AD-271 167

• CRYSTALONICS INC CAMBRIDGE MASS  
• • •  
PRODUCTION ENGINEERING MEASURE  
TO IMPROVE PRODUCTION TECHNIQUES  
AND TO INSURE THE RELIABILITY OF  
THE C600 SERIES FIELD EFFECT  
TRANSISTORS.  
AD-426 356  
• • •

PRODUCTION ENGINEERING MEASURE  
TO IMPROVE PRODUCTION TECHNIQUES  
AND TO INSURE THE RELIABILITY OF  
THE C600 SERIES FIELD EFFECT  
TRANSISTORS.  
AD-606 477

• • •  
PRODUCTION ENGINEERING MEASURE  
TO IMPROVE PRODUCTION TECHNIQUES  
AND TO INSURE THE RELIABILITY OF  
THE C600 SERIES FIELD EFFECT  
TRANSISTORS.  
AD-613 068

• DOUGLAS AIRCRAFT CO INC LONG BEACH  
CALIF

• • •  
CHEMICAL COMPOUNDS FOR METAL  
SHAPING  
(ASD-TR7 643 V1)  
AD-271 526

• • •  
1111  
CHEMICAL COMPOUNDS FOR METAL  
SHAPING  
(AFCRL-1111)  
AD-282 920

• • •  
TR7 648 V2  
CHEMICAL COMPOUNDS FOR METAL  
SHAPING  
(ASD-TR7 648 V2)  
AD-295 752

• ESTABLISHMENT HALVERN (ENGLAND)

• • •  
RSIC-409  
MACHINING AND GRINDING OF  
TITANIUM AND ITS ALLOYS.  
AD-620 908

• • •  
RSIC-482  
MACHINING AND GRINDING OF  
NICKEL-AND COBALT-BASE ALLOYS,  
AD-634 075

• • •  
RSIC-501  
MACHINING AND GRINDING OF  
ULTRAHIGH-STRENGTH STEELS AND  
STAINLESS STEEL ALLOYS,  
AD-639 654

FOR-GEN

•FOREIGN TECHNOLOGY DIV WRIGHT-  
PATTERSON AFB OHIO

•••  
ELECTRIC AND CHEMICO-MECHANICAL  
METHODS OF WORKING METALS (CHAPTER  
VII)  
AD-265 701

•••  
FTD-MT-23-1225-67  
CHEMICAL MILLING (DEEP CONTOUR  
ETCHING),  
AD-680 561

•••  
FTD-TT-65-885  
CHEMICAL MILLING,  
(TT-65-62694)  
AD-618 628

•••  
FTD-TT-65-1539  
SECONDARY ELECTRONIC EMISSION,  
OF COPPER AND OF CERTAIN COATINGS,  
(TT-66-61136)  
AD-631 855

•FRANKLIN INST PHILADELPHIA PA LABS  
FOR RESEARCH AND DEVELOPMENT

•••  
F-A2400  
RESEARCH IN THE GENERAL FIELD  
OF SUBSTRUCTURE AND DISLOCATION  
NETWORKS IN METALLIC CRYSTALS.  
(AFOSR-2574)  
AD-610 424

•GENERAL DYNAMICS/ASTRONAUTICS SAN  
DIEGO CALIF

•••  
GDA-AN61AMR4062  
STRIPPING PT201 THERMOSETTING  
RESIN COATINGS FROM 321 ANNEALED  
STAINLESS STEEL SURFACES,  
(PROPELLANT UTILIZATION MANOMETER  
HOUSINGS),  
AD-677 494

•••  
GDA-MRG-235  
A NEW APPROACH TO BEND TESTING  
FOR THE DETERMINATION OF HYDROGEN  
EMBRIEMENT SUSCEPTIBILITY OF  
SHEET MATERIALS,  
AD-681 765

•GENERAL DYNAMICS/CONVAIR SAN DIEGO  
CALIF

•••  
TITANIUM DEVELOPMENT PROGRAM,  
VOLUME IV,  
(ASD-TR617 576)  
AD-264 685

•••  
GDC-PR919  
REDUCING HAND STRAIGHTENING BY  
CHEM-MILLING 7075 AND 7178 ALUMINUM  
ALLOY IN THE 'W' (OR NATURALLY  
AGED) CONDITION,  
AD-677 866

•••  
GDC-PR-920  
CHEM-MILL PROCESS FOR  
CONTOURING ALUMINUM HONEYCOMB CORE,  
AD-678 154

•GENERAL DYNAMICS/FORT WORTH TEX

•••  
ERR FW35  
DEVELOPMENT OF CHEMICAL MILLED  
WAFFLE GRID BERYLLIUM STRUCTURAL  
PANEL,  
AD-423 282

•••  
FGT 2100  
NING - ALUMINUM SHEET AND PLATE  
- DYNAMIC ETCHED OR CHEM-MILLED -  
MECHANICAL PROPERTIES -  
DETERMINATION OF  
AD-286 074

•••  
FGT 2510  
MATERIALS - HONEYCOMB CORE  
RIBBON RELATIONSHIP BETWEEN FLOW  
CHARACTERISTICS OF BRAZING ALLOY  
AND OXIDE FILM FORMATIONS OF -  
DETERMINATION OF  
AD-272 227

•••  
FTDM 3068  
MATERIAL BERYLLIUM WAFFLE  
PANEL. CHEMICAL MILLED, SHEAR TEST  
OF,  
AD-428 128

•GENERAL DYNAMICS/POMONA CALIF

- 8926 142  
EFFECT OF SURFACE FINISHES ON  
FATIGUE LIFE  
AD-402 164
- GENERAL ELECTRIC CO IRMC S C  
• • •  
SOLID ELECTROLYTE TANTALUM FOIL  
CAPACITOR.  
AD-423 225
- GENERAL ELECTRIC CO SCHENECTADY N Y  
• • •  
SILICON PLANAR EPITAXIAL  
TRANSISTOR TYPE 2N2192  
AD-286 886
- • •  
SILICON PLANAR EPITAXIAL  
TRANSISTOR TYPE 2N2192.  
AD-404 185
- GENERAL ELECTRIC CO SYRACUSE N Y  
• • •  
MATRIX CONTROLLED DISPLAY  
DEVICE.  
AD-418 684
- GENERAL MOTORS CORP KOKOMO IND DELCO  
RADIO DIV  
• • •  
PRODUCTION ENGINEERING MEASURE  
TO IMPROVE PRODUCTION TECHNIQUES  
AND INCREASE THE RELIABILITY OF THE  
2N1258A TRANSISTOR  
AD-286 872
- GRUMMAN AEROSPACE CORP BETHPAGE N Y  
• • •  
ADVANCED CHEMICAL MILLING  
PROCESSES.  
(AFML-TR-71-44)  
AD-727 620
- HARRY DIAMOND LABS WASHINGTON D C  
• • •  
TR-1052  
MICROCIRCUITRY BY CHEMICAL  
DEPOSITION,  
AD-281 842
- MARSHAW CHEMICAL CO CLEVELAND OHIO
- • •  
INVESTIGATION OF THIN FILM  
CADMIUM SULFIDE SOLAR CELLS.  
AD-609 425
- • •  
RESEARCH ON PHOTOVOLTAIC CELLS.  
(ARL-A2-111)  
AD-621 454
- HONEYWELL RESEARCH CENTER HOPKINS  
MINN  
• • •  
THIN FILM IMAGE CONVERTER.  
AD-452 855
- IIT RESEARCH INST CHICAGO ILL  
• • •  
B241 3  
FIBER-REINFORCED METALS AND  
ALLOYS  
AD-287 594
- • •  
B241 4  
FIBER-REINFORCED METALS AND  
ALLOYS  
AD-292 259
- INNSBRUCK UNIV (AUSTRIA)  
• • •  
DISLOCATION MOBILITY IN ZINC  
SINGLE CRYSTALS  
AD-292 445
- JOHNS HOPKINS UNIV SILVER SPRING MD  
APPLIED PHYSICS LAB  
• • •  
YG-675  
THE MINISTICK PROCESS FOR  
PACKAGING INTEGRATED CIRCUIT FLAT  
PACKS.  
AD-468 271
- KELSEY-HAYES CO ANOMLUS MICH  
• • •  
THE DESIGN AND EVALUATION OF  
PERFORATED ION EMITTERS.  
(ASD-TDR67 750)  
AD-418 226
- LEAR SIEGLER INC SANTA MONICA CALIF  
• • •

LIN-HOT

- SEMICONDUCTOR THIN FILMS.  
AD-412 841
- LINDEN LABS INC STATE COLLEGE PA  
•••  
MACHINING HIGH PURITY ALUMINA.  
AD-611 467
- LOCKHEED MISSILES AND SPACE CO  
SUNNYVALE CALIF  
•••  
R5622 3 80 61 41  
PACKAGING MINIATURIZATION.  
CHARGE NUMBERS 31-8027-0201-D, 31-  
8027-0901 AND RES 2 AND 4,  
AD-422 113
- MARTIN CO BALTIMORE MD  
•••  
THE EFFECT OF SURFACE-ACTIVE  
AGENTS ON THE MECHANICAL PROPERTIES  
OF METALS. PART II. THE EFFECT OF  
SURFACE-ACTIVE AGENTS ON THE  
MECHANICAL BEHAVIOR OF ALUMINUM  
SINGLE CRYSTALS.  
(AADO-TR-61-58-PT-2)  
AD-292 017
- MARTIN CO DENVER COLO  
•••  
WDD-M-41-57-60  
MANUAL AND REPAIR WELDING OF  
CHEMICALLY MILLED 2014-T6 ALUMINUM  
SHEETING,  
AD-606 819
- MCDONNELL AIRCRAFT CORP ST LOUIS MO  
•••  
MOLYBDENUM STRUCTURAL COMPONENT  
PROGRAM  
AD-272 526  
•••  
A239  
CHEMICAL MILLING OF NARROW  
CLOSE TOLERANCE SLOTS IN ALUMINUM  
AND STAINLESS STEEL.  
AD-425 102  
•••  
A473  
DETERMINATION OF MECHANICAL  
PROPERTIES AND SURFACE CONDITION OF
- CHEM-MILLED CB-3Zr COLUMBIUM ALLOY  
SAMPLES,  
AD-421 617  
•••  
A478  
ELECTROCHEMICAL DEBURTING OF  
MOLYBDENUM, ALUMINUM AND STAINLESS  
STEEL.  
AD-421 602
- METAL HYDRIDES INC BEVERLY MASS  
•••  
AD-267 806  
•••  
INVESTIGATION OF SINGLE-CRYSTAL  
AND POLYCRYSTALLINE TITANIUM  
DIBORIDE; METALLOGRAPHIC PROCEDURES  
AND FINDINGS  
(ASD-TR61 390)  
AD-271 965
- METCUT RESEARCH ASSOCIATES INC  
CINCINNATI OHIO  
•••  
970-11700  
SURFACE INTEGRITY OF MACHINED  
STRUCTURAL COMPONENTS.  
(AFML-TR-70-11)  
AD-820 146
- MOTOROLA INC PHOENIX ARIZ  
•••  
PRODUCTION ENGINEERING MEASURE.  
HIGH SPEED SEMICONDUCTOR SWITCH  
(TWO TERMINAL) HIGH SPEED  
SEMICONDUCTOR SWITCH (GATE).  
AD-602 660
- MOTOROLA INC PHOENIX ARIZ  
SEMICONDUCTOR PRODUCTS DIV  
•••  
PRODUCTION ENGINEERING MEASURE  
FOR SILICON OVERLAY TRANSISTORS.  
AD-619 295  
•••  
PRODUCTION ENGINEERING MEASURE  
FOR SILICON OVERLAY TRANSISTORS.  
AD-625 317  
•••  
PRODUCTION ENGINEERING MEASURE

- FOR SILICON OVERLAY TRANSISTORS.  
AD-628 220  
\* \* \*  
PRODUCTION ENGINEERING MEASURE  
FOR SILICON OVERLAY TRANSISTORS.  
AD-635 814
- \* NATIONAL AERONAUTICS AND SPACE  
ADMINISTRATION WASHINGTON D C  
\* \* \*  
NASA-TH-X-52312  
MACHINING AND GRINDING OF  
TITANIUM AND ITS ALLOYS.  
AD-620 508  
\* \* \*  
NASA-TH-X-52433  
MACHINING AND GRINDING OF  
ULTRAHIGH-STRENGTH STEELS AND  
STAINLESS STEEL ALLOYS.  
AD-639 654  
\* \* \*  
NASA-TH-X-52446  
MACHINING AND GRINDING OF  
NICKEL-AND COBALT-BASE ALLOYS.  
AD-634 075
- \* NATIONAL SEMICONDUCTOR CORP DANBURY  
CONN  
\* \* \*  
PRODUCTION ENGINEERING MEASURE  
TO IMPROVE PRODUCTION TECHNIQUES  
AND INCREASE THE RELIABILITY OF  
THE 2N228A TRANSISTOR.  
AD-614 823
- \* NAVAL AIR ENGINEERING CENTER  
PHILADELPHIA PA AERONAUTICAL  
MATERIALS LAB  
\* \* \*  
NAEC-AML-1909  
STUDY OF SIZE EFFECT IN FINE  
BERYLLIUM WIRE PHASE II,  
AD-438 478  
\* \* \*  
NAEC-AML-2418  
CHEMICAL MILLING OF ALLOY  
STEELS,  
AD-631 922  
\* \* \*  
NAEC-AML-2441  
INFLUENCE OF SOME PROCESSING
- VARIABLES UPON THE ELEVATED AND  
ROOM TEMPERATURE STRENGTH OF  
ULTRAFINE BERYLLIUM WIRES,  
AD-622 992
- \* NAVAL AIR MATERIAL CENTER  
PHILADELPHIA PA AERONAUTICAL  
MATERIALS LAB  
\* \* \*  
NAAC-AML-1226  
CHEMICAL MILLING OF METALS AND  
ALLOYS; ITS EFFECT ON STRESS  
CORROSION SUSCEPTIBILITY AND  
HYDROGEN EMBRITTLEMENT,  
AD-648 980
- \* NAVAL MATERIAL INDUSTRIAL RESOURCES  
OFFICE PHILADELPHIA PA  
\* \* \*  
NAVMIRO MANUFACTURING  
TECHNOLOGY BULLETIN. NUMBERS 1  
THRU 12, DECEMBER 1969-NOVEMBER  
1970.  
AD-725 614
- \* NAVAL ORDNANCE LAB WHITE OAK MD  
\* \* \*  
NOLTR-43-126  
POLISHES AND ETCHES FOR TIN  
TELLURIDE, LEAD SULFIDE, LEAD  
SELENIDE, AND LEAD TELLURIDE,  
AD-422 267  
\* \* \*  
NOLTR-66-72  
POLISHES AND ETCHES FOR TIN  
TELLURIDE, LEAD SULFIDE, LEAD  
SELENIDE, AND LEAD TELLURIDE:  
SUPPLEMENT.  
AD-634 242
- \* NORTHROP AIRCRAFT INC HAWTHORNE  
CALIF  
\* \* \*  
NOR 61 199  
DEVELOPMENT OF IMPROVED  
METHODS, PROCESSES, AND TECHNIQUES  
FOR PRODUCING STEEL EXTRUSIONS  
AD-262 104
- \* PENNSYLVANIA STATE UNIV UNIVERSITY  
PARK

PHI-TEX

• • •  
 INFLUENCE OF DISPLACIVE-  
 SHEARING STRESSES ON THE KINETICS  
 OF RECONSTRUCTIVE TRANSFORMATIONS  
 EFFECTED BY PRESSURE IN THE RANGE 0-  
 100,000 BARS  
 AD-256 351

•PHILCO CORP LANSDALE PA

• • •  
 R 222 I  
 PEM FOR TRANSISTOR  
 MANUFACTURING PROCESS IMPROVEMENT  
 AD-286 907

•PHOTOCIRCUITS CORP GLEN COVE N Y

• • •  
 MICROMINIATURE LAYERED PRINTED  
 WIRING  
 AD-291 876

• • •  
 MICROMINIATURE LAYERED PRINTED  
 WIRING  
 AD-400 722

•RADIO CORP OF AMERICA SUMMERVILLE N J

• • •  
 PRODUCTION ENGINEERING MEASURE  
 ON 2N1709 SILICON PLANAR EPITAXIAL  
 TRANSISTOR.  
 AD-409 537

• • •  
 PRODUCTION ENGINEERING MEASURE  
 ON 2N1708 SILICON PLANAR EPITAXIAL  
 TRANSISTOR.  
 AD-414 913

•RAYTHEON CO LEWISTON MAINE

• • •  
 PRODUCTION ENGINEERING MEASURE  
 ON SILICON ALLOY TRANSISTORS.  
 AD-422 940

•RENSSELAER POLYTECHNIC INST TROY N Y

• • •  
 TP-2  
 PRINCIPLES OF METALLOGRAPHIC  
 ETCHING.  
 AD-616 786

•ROME AIR DEVELOPMENT CENTER GRIFFISS

0-8  
 UNCLASSIFIED

APB N Y

• • •  
 RADG-TDR64 252  
 FAILURE MECHANISMS IN  
 MICROELECTRONICS.  
 AD-607 426

•SIGNETICS CORP SUNNYVALE CALIF

• • •  
 AN ECONOMICAL FLAT PACKAGE FOR  
 INTEGRATED CIRCUITS.  
 AD-450 549

•SILICON TRANSISTOR CORP GARDEN CITY  
 N Y

• • •  
 PRODUCTION ENGINEERING MEASURE  
 TO INCREASE THE RELIABILITY OF THE  
 TRANSISTOR TYPE 22N2024.  
 AD-606 191

•SPRAGUE ELECTRIC CO NORTH ADAMS MASS

• • •  
 PRODUCTION ENGINEERING MEASURE.  
 RELIABILITY IMPROVEMENT JCT ETCH  
 TRANSISTOR  
 AD-295 057

•SYLVANIA ELECTRIC PRODUCTS INC WOBURN  
 MASS

• • •  
 PRODUCTION ENGINEERING MEASURE  
 FOR GALLIUM ARSENIDE VARACTOR  
 DIODE.  
 AD-419 585

•TEXAS INSTRUMENTS INC DALLAS

• • •  
 RESEARCH AND DEVELOPMENT OF  
 HIGH TEMPERATURE SEMICONDUCTOR  
 DEVICES  
 AD-298 707

• • •  
 03-64-71  
 PRODUCTION ENGINEERING MEASURES  
 (PEM) FOR A GERMANIUM MICROWAVE  
 TRANSISTOR.  
 AD-612 617

• • •  
 IR7 065 V6  
 SILICON SEMICONDUCTOR NETWORKS

MANUFACTURING METHODS  
(ASD-1R7 865 V6)  
AD-291 600

MECHANICAL BEHAVIOR OF ALUMINUM  
SINGLE CRYSTALS.  
AD-282 017

•TRW SEMICONDUCTORS INC LANSDALE  
CALIF RESEARCH AND DEVELOPMENT  
DEPT

•XEROX CORP ROCHESTER N Y

•••  
59-RD-F  
TRANSISTOR, VHF, SILICON, POWER  
(10W-500MC).  
AD-622 879

•••  
LOW-COST MICROCIRCUITS FOR  
MICROASSEMBLIES.  
AD-433 891

•WATERVLIET ARSENAL N Y

•••  
NVT RI 60001 IRI 60001 I  
CHEMICAL MILLING  
AD-252 129

•WESTINGHOUSE DEFENSE AND SPACE CENTER  
BALTIMORE MD

•••  
WDSC-385A4  
FAILURE MECHANISMS IN  
MICROELECTRONICS.  
(RADC-TDR64 252)  
AD-607 426

•WESTINGHOUSE ELECTRIC CORP DAYTON  
OHIO

•••  
500 C SILI CARBIDE RECTIFIER  
PROGRAM.  
(ASD-1R7 727)  
AD-420 373

•WESTINGHOUSE ELECTRIC CORP YOUNGWOOD  
PA

•••  
MICROMINIATURE INTEGRATED  
CIRCUIT PACKAGE.  
AD-405 861

•WRIGHT AIR DEVELOPMENT DIV WRIGHT-  
PATTERSON AFB OHIO

•••  
WADD-TR-61-58-PT-2  
THE EFFECT OF SURFACE-ACTIVE  
AGENTS ON THE MECHANICAL PROPERTIES  
OF METALS. PART II. THE EFFECT OF  
SURFACE-ACTIVE AGENTS ON THE

## UNCLASSIFIED

## SUBJECT INDEX

- AIRFRAMES
  - DEVELOPMENT OF IMPROVED METHODS, PROCESSES, AND TECHNIQUES FOR PRODUCING STEEL EXTRUSIONS. AD-262 134
  - BOEING-WICHITA MATERIALS AND RESEARCH DEVELOPMENT PROGRAMS, 1957-1961. AD-271 167
- COSTS
  - COMPARATIVE COSTS OF FABRICATING AIRFRAME FROM ALUMINUM AND FROM TITANIUM. AD-609 349
- STRUCTURAL PARTS
  - SURFACE INTEGRITY OF MACHINED STRUCTURAL COMPONENTS. AD-870 146
- ALLOYS
  - TITANIUM DEVELOPMENT PROGRAM. VOLUME IV. AD-264 685
  - CHEMICAL COMPOUNDS FOR METAL SHAPING. AD-271 536
- ALUMINA
  - MACHINING
    - MACHINING HIGH PURITY ALUMINA. AD-614 467
- ALUMINUM
  - CHEMICAL MILLING
    - CHEMICAL MILLING OF NARROW CLOSE TOLERANCE SLOTS IN ALUMINUM AND STAINLESS STEEL. AD-425 102
- ALUMINUM ALLOYS
  - EFFECTS OF CHEMICAL MILLING ON MECHANICAL PROPERTIES OF 2024, 7075, AND 7079 AL ALLOYS. TENSILE AND FATIGUE SPECIMENS PREPARED FROM SHEETS REDUCED IN THICKNESS BY MACHINING OR CHEMICAL MILLING INCLUDING ALCLAD 2024-T86 AL, BARE 2024-T86AL, BARE 7075-T6 AL, BARE 7079-T6 AL. SOME LOSS OF
- DUCTILITY WITH ALL METALS, GENERALLY. AD-236 074
- AIRFRAMES
  - COMPARATIVE COSTS OF FABRICATING AIRFRAME FROM ALUMINUM AND FROM TITANIUM. AD-609 349
- CHEMICAL MILLING
  - CHEMICAL MILLING OF METALS AND ALLOYS; ITS EFFECT ON STRESS CORROSION SUSCEPTIBILITY AND HYDROGEN ENBRITTLMENT. AD-648 980
  - REDUCING HAND STRAIGHTENING BY CHEM-MILLING 7075 AND 7178 ALUMINUM ALLOY IN THE 'W' (OR NATURALLY AGED) CONDITION. AD-677 065
  - CHEM-MILL PROCESS FOR CONTOURING ALUMINUM HONEYCOMB CORE. AD-678 154
- WELDING
  - MANUAL AND REPAIR WELDING OF CHEMICALLY MILLED 2014-T3 ALUMINUM SHEETING. AD-606 819
- BERYLLIUM
  - MACHINING
    - MACHINING DATA FOR BERYLLIUM METAL. AD-485 297
    - NONTRADITIONAL MACHINING OF BERYLLIUM. AD-738 271
- METAL PLATES
  - DEVELOPMENT OF CHEMICAL MILLED WAFFLE GRID BERYLLIUM STRUCTURAL PANEL. AD-423 338
- METALLOGRAPHY
  - A REVIEW OF METALLOGRAPHIC PREPARATION PROCEDURES FOR BERYLLIUM AND BERYLLIUM ALLOYS. AD-674 066

C-1  
UNCLASSIFIED

BEF-CHE

- PANELS (STRUCTURAL)  
SHEAR TEST OF CHEMICAL MILLED  
BERYLLIUM WAFFLE PANEL.  
AD-438 138
- WIRE  
STUDY OF SIZE EFFECT IN FINE  
BERYLLIUM WIRE PHASE II, •  
AD-438 478  
INFLUENCE OF SOME PROCESSING  
VARIABLES UPON THE ELEVATED AND  
ROOM TEMPERATURE STRENGTH OF  
ULTRAFINE BERYLLIUM WIRES, •  
AD-633 992
- BERYLLIUM ALLOYS  
MACHINING  
MACHINING DATA FOR BERYLLIUM  
METAL.  
AD-485 297
- METALLOGRAPHY  
A REVIEW OF METALLOGRAPHIC  
PREPARATION PROCEDURES FOR  
BERYLLIUM AND BERYLLIUM ALLOYS, •  
AD-674 066
- BORIDES  
INVESTIGATION OF SINGLE-CRYSTAL  
AND POLYCRYSTALLINE TITANIUM  
DIBORIDE; METALLOGRAPHIC PROCEDURES  
AND FINDINGS •  
AD-271 965
- BRAZING  
MATERIALS - HONEYCOMB CORE  
RIBBON RELATIONSHIP BETWEEN FLOW  
CHARACTERISTICS OF BRAZING ALLOY  
AND OXIDE FILM FORMATIONS OF -  
DETERMINATION OF •  
AD-272 227
- CADMIUM COMPOUNDS,  
SULFIDES  
INVESTIGATION OF THIN FILM  
CADMIUM SULFIDE SOLAR CELLS.  
AD-605 425
- CESIUM  
IONIZATION  
FEASIBILITY OF UTILIZING
- EMITTERS OF PERFOJATED SOLID SHEET  
RATHER THAN A SINTERED POWDER  
STRUCTURE IN ION ENGINE  
APPLICATIONS.  
AD-418 224
- CHEMICAL MILLING  
CHEMICAL MILLING •  
AD-252 129  
INFLUENCE OF DISPLACIVE-SHEARING  
STRESSES ON THE KINETICS OF  
RECONSTRUCTIVE TRANSFORMATIONS  
EFFECTED BY PRESSURE IN THE RANGE 0-  
100,000 BARS •  
AD-276 351  
STRUCTURAL TESTS OF A CHEMICALLY  
MILLED LADISH D-6AC STEEL SECOND-  
STAGE MINUTEMAN AFT CLOSURE •  
AD-261 959  
CHEMICAL COMPOUNDS FOR METAL  
SHAPING •  
AD-271 526  
ETCH MILLING BY LIQUID AND NON-  
LIQUID ETCHANTS ON STAINLESS  
STEEL PLATES AND HONEYCOMB CORES.  
AD-282 920  
EFFECTS OF CHEMICAL MILLING ON  
MECHANICAL PROPERTIES OF 2024,  
7075, AND 7079 AL ALLOYS.  
TENSILE AND FATIGUE SPECIMENS  
PREPARED FROM SHEETS REDUCED IN  
THICKNESS BY MACHINING OR CHEMICAL  
MILLING INCLUDING ALCLAD 2024-T86  
AL, BARE 2024-T86AL, BARE 7075-T6  
AL, BARE 7079-T6 AL. SOME LOSS OF  
DUCTILITY WITH ALL METALS,  
GENERALLY.  
AD-286 074
- ALLOYS  
PRINCIPLES OF METALLOGRAPHIC  
ETCHING.  
AD-616 786
- ALUMINUM ALLOYS  
CHEMICAL MILLING OF METALS AND  
ALLOYS; ITS EFFECT ON STRESS  
CORROSION SUSCEPTIBILITY AND  
HYDROGEN EMBRITTLEMENT, •  
AD-648 980  
REDUCING HAND STRAIGHTENING BY

CHEM-MILLING 7075 AND 7178 ALUMINUM ALLOY IN THE 'W' (OR NATURALLY AGED) CONDITION. •  
AD-677 066

BERYLLIUM  
NONTRADITIONAL MACHINING OF BERYLLIUM. •  
AD-738 271

CRYSTALS  
POLISHES AND ETCHES FOR TIN TELLURIDE, LEAD SULFIDE, LEAD SELENIDE, AND LEAD TELLURIDE. •  
AD-423 367

POLISHES AND ETCHES FOR TIN TELLURIDE, LEAD SULFIDE, LEAD SELENIDE, AND LEAD TELLURIDE: SUPPLEMENT. •  
AD-634 392

FLUIDS  
CHEMICAL MILLING OF NARROW CLOSE TOLERANCE SLOTS IN ALUMINUM AND STAINLESS STEEL. •  
AD-425 102

HONEYCOMB CORES  
CHEM-MILL PROCESS FOR CONTOURING ALUMINUM HONEYCOMB CORE. •  
AD-678 154

MANUFACTURING METHODS  
TRANSLATION OF RUSSIAN RESEARCH: CHEMICAL MILLING. •  
AD-618 628

METALS  
METAL REMOVAL BY ELECTROCHEMICAL METHODS AND ITS EFFECTS ON MECHANICAL PROPERTIES OF METALS. •  
AD-613 261

REVIEWS  
CHEMICAL MILLING (DEEP CONTOUR ETCHING)--TRANSLATION. •  
AD-680 561

STAINLESS STEEL  
STRIPPING PT201 THERMOSETTING RESIN COATINGS FROM 321 ANNEALED

STAINLESS STEEL SURFACES, (PROPELLANT UTILIZATION MANOMETER HOUSINGS). •  
AD-677 494

STEEL  
CHEMICAL MILLING OF ALLOY STEELS. •  
AD-631 952

TITANIUM ALLOYS  
ADVANCED CHEMICAL MILLING PROCESSES. •  
AD-727 620

WIRE  
INFLUENCE OF SOME PROCESSING VARIABLES UPON THE ELEVATED AND ROOM TEMPERATURE STRENGTH OF ULTRAFINE BERYLLIUM WIRES. •  
AD-633 992

•CIRCUITS  
MICROCIRCUITRY DEVELOPED BY CHEMICALLY DEPOSITING NI ALLOY FILMS ON INSULATING SUBSTRATES AND CHEMICAL ETCHING PATTERNS IN THIN CU CONDUCTORS. RESISTIVE AND CONDUCTIVE PARTS MADE OF NI ALLOY FILMS OF APPROX. 500 OHMS PER SQUARE WERE USED. •  
AD-281 843

•COATINGS  
MOLYBDENUM STRUCTURAL COMPONENT PROGRAM. •  
AD-272 526

•COBALT ALLOYS  
MATERIAL REMOVAL MACHINING AND GRINDING OF NICKEL- AND COBALT-BASE ALLOYS. •  
AD-634 073

•COMPOSITE MATERIALS  
DEVELOPMENT OF FIBER-REINFORCED METALS AND ALLOYS; PREPARATION OF BE FIBER-AG ALLOY MATRIX COMPOSITES. •  
AD-267 594  
DEVELOPMENT OF FIBER-REINFORCED

COP-ELE

- METALS AND ALLOYS WITH HIGH STRENGTH-TO-WEIGHT RATIOS, HIGH ELASTIC MODULUS; HOT EXTRUSION; FABRICATION; AL-BE ALLOYS.  
AD-293 259
- COPPER ALLOYS  
SECONDARY EMISSION  
TRANSLATION OF RUSSIAN ARTICLE: SECONDARY ELECTRONIC EMISSION OF COPPER AND OF CERTAIN COATINGS.  
AD-631 855
- CORROSION-RESISTANT ALLOYS  
TITANIUM  
CHEMICAL MILLING OF METALS AND ALLOYS; ITS EFFECT ON STRESS CORROSION SUSCEPTIBILITY AND HYDROGEN EMBRITTLEMENT.\*  
AD-648 980
- CRYSTAL RECTIFIERS  
SILICON ALLOYS  
500 C SILICON CARBIDE RECTIFIER PROGRAM.\*  
AD-420 375
- CRYSTAL STRUCTURE  
METALLIC CRYSTALS  
SUBSTRUCTURE AND DISLOCATION NETWORKS IN METALLIC CRYSTALS.  
AD-610 434
- CRYSTALS  
INVESTIGATION OF SINGLE-CRYSTAL AND POLYCRYSTALLINE TITANIUM DIBORIDE; METALLOGRAPHIC PROCEDURES AND FINDINGS.  
AD-271 965  
PREPARATION OF LIF CRYSTALS FOR ROLLING CONTACT STUDIES: CLEAVAGE, POLISHING, AND ETCHING OF CRYSTALS. ELECTRON BEAM IRRADIATION; RADIATION EFFECTS.  
AD-276 887
- PRECISION FINISHING  
POLISHES AND ETCHES FOR TIN TELLURIDE, LEAD SULFIDE, LEAD SELENIDE, AND LEAD TELLURIDE.\*
- AD-423 267  
POLISHES AND ETCHES FOR TIN TELLURIDE, LEAD SULFIDE, LEAD SELENIDE, AND LEAD TELLURIDE: SUPPLEMENT.\*  
AD-634 392
- DEFORMATION  
FUNDAMENTAL STUDY OF ROLLING CONTACT FATIGUE. NYLON AND TEFLON BALLS ROLLED UNDER LOAD UPON A PREPARED (001) SURFACE OF LIF LEFT A DISTINCTIVE DISLOCATION TRACE AS REVEALED BY AN ETCH PITTING TREATMENT.  
AD-285 085  
DISLOCATION MOBILITY IN ZN SINGLE CRYSTALS. DISLOCATION DENSITY AND CONFIGURATION WERE DETERMINED BEFORE AND AFTER STATIC LOADING AND STRESS PULSE LOADING.  
AD-293 445
- DIODES  
MICROWAVE GERMANIUM TUNNEL DIODES. DESIGN CONSIDERATIONS AND FABRICATION TECHNIQUES.  
AD-294 788
- DIODES (SEMICONDUCTORS)  
SILICON ALLOYS  
500 C SILICON CARBIDE RECTIFIER PROGRAM.\*  
AD-420 375
- DISPLAY SYSTEMS  
ELECTRONIC RECORDING SYSTEMS  
MATRIX CONTROLLED DISPLAY DEVICE USING TECHNIQUES CALLED IN-AIR SURFACE DEFORMATION RECORDING AND TIRF (TOTAL INTERNAL REFLECTION PRISM) PROJECTION.  
AD-418 684
- ELECTROEROSIVE MACHINING  
BERYLLIUM  
NONTRADITIONAL MACHINING OF BERYLLIUM.\*  
AD-738 271

- METALS**  
METAL REMOVAL BY ELECTROCHEMICAL METHODS AND ITS EFFECTS ON MECHANICAL PROPERTIES OF METALS.  
AD-612 261
- ELECTROLYTIC POLISHING**  
**CRYSTALS**  
POLISHES AND ETCHES FOR TIN TELLURIDE, LEAD SULFIDE, LEAD SELENIDE, AND LEAD TELLURIDE.  
AD-423 267  
POLISHES AND ETCHES FOR TIN TELLURIDE, LEAD SULFIDE, LEAD SELENIDE, AND LEAD TELLURIDE: SUPPLEMENT.  
AD-634 392
- METALS**  
METAL REMOVAL BY ELECTROCHEMICAL METHODS AND ITS EFFECTS ON MECHANICAL PROPERTIES OF METALS.  
AD-612 261
- ELECTRONIC RECORDING SYSTEMS**  
**GEOMETRIC FORMS**  
MATRIX CONTROLLED DISPLAY DEVICE USING TECHNIQUES CALLED IN-AIR SURFACE DEFORMATION RECORDING AND TIRP (TOTAL INTERNAL REFLECTION PRISM) PROJECTION.  
AD-418 684
- ELECTRONIC SWITCHES**  
**SEMICONDUCTOR DEVICES**  
PRODUCTION ENGINEERING MEASURE. HIGH SPEED SEMICONDUCTOR SWITCH (TWO TERMINAL) HIGH SPEED SEMICONDUCTOR SWITCH (GATE).  
AD-603 660
- ETCHING**  
**CRYSTALS**  
POLISHES AND ETCHES FOR TIN TELLURIDE, LEAD SULFIDE, LEAD SELENIDE, AND LEAD TELLURIDE: SUPPLEMENT.  
AD-634 392
- EXTRUSION**  
DEVELOPMENT OF IMPROVED METHODS,
- PROCESSES, AND TECHNIQUES FOR PRODUCING STEEL EXTRUSIONS.  
AD-262 184
- FAILURE (MECHANICS)**  
**MICROMINIATURIZATION (ELECTRONICS)**  
**FAILURE MECHANISMS IN MICROELECTRONICS.**  
AD-607 426
- FATIGUE (MECHANICS)**  
PREPARATION OF LIF CRYSTALS FOR ROLLING CONTACT STUDIES CLEAVAGE, POLISHING, AND ETCHING OF CRYSTALS, ELECTRON BEAM IRRADIATION; RADIATION EFFECTS.  
AD-276 887  
FUNDAMENTAL STUDY OF ROLLING CONTACT FATIGUE, NYLON AND TEFLON BALLS ROLLED UNDER LOAD UPON A PREPARED (001) SURFACE OF LIF LEFT A DISTINCTIVE DISLOCATION TRACE AS REVEALED BY AN ETCH PITTING TREATMENT.  
AD-285 085
- FIBERS**  
DEVELOPMENT OF FIBER-REINFORCED METALS AND ALLOYS WITH HIGH STRENGTH-TO-WEIGHT RATIOS, HIGH ELASTIC MODULI; HOT EXTRUSION; FABRICATION; AL-BE ALLOYS.  
AD-293 259
- FIXED CAPACITORS**  
**MICROMINIATURIZATION (ELECTRONICS)**  
LOW-COST MICROCIRCUITS FOR MICROASSEMBLIES.  
AD-433 891
- FIXED RESISTORS**  
**MICROMINIATURIZATION (ELECTRONICS)**  
LOW-COST MICROCIRCUITS FOR MICROASSEMBLIES.  
AD-433 891
- FLUORIDES**  
PREPARATION OF LIF CRYSTALS FOR ROLLING CONTACT STUDIES CLEAVAGE, POLISHING, AND ETCHING OF

## GEL-ION

- CRYSTALS, ELECTRON BEAM IRRADIATION; RADIATION EFFECTS.  
AD-276 687
- GELS  
ETCH MILLING BY LIQUID AND NON-LIQUID ETCHANTS ON STAINLESS STEEL PLATES AND HONEYCOMB CORES.  
AD-282 920
- GERMANIUM TRANSISTORS  
PRODUCTION ENGINEERING MEASURES (PEM) FOR A GERMANIUM MICROWAVE TRANSISTOR.  
AD-612 617
- GRINDING STEEL  
MACHINING AND GRINDING OF ULTRAHIGH-STRENGTH STEELS AND STAINLESS STEEL ALLOYS.  
AD-639 654
- GUIDED MISSILE ANTENNAS  
ELEC TRONIC SCANNERS  
ELECTRONICALLY STEERABLE, AUTOMATICALLY SELF-DIRECTING, MISSILEBORNE ANTENNAS.  
AD-426 922
- HONEYCOMB CORES  
MATERIALS - HONEYCOMB CORE RIBBON RELATIONSHIP BETWEEN FLOW CHARACTERISTICS OF BRAZING ALLOY AND OXIDE FILM FORMATIONS OF - DETERMINATION OF.  
AD-272 227  
ELECTROLYTIC ETCHING OF STAINLESS STEEL PLATES AND HONEYCOMB CORES; VARIOUS CHEMICAL COMPOUNDS USED FOR METAL SHAPING; PROCESSING OF AIRCRAFT MATERIALS.  
AD-295 752
- CHEMICAL MILLING  
CHEM-MILL PROCESS FOR CONTOURING ALUMINUM HONEYCOMB CORE.  
AD-678 194
- HYDROGEN EMBRITTLEMENT TEST METHODS  
A NEW APPROACH TO BEND TESTING FOR THE DETERMINATION OF HYDROGEN EMBRITTLEMENT SUSCEPTIBILITY OF SHEET MATERIALS.  
AD-681 765
- INFRARED IMAGES  
SEMICONDUCTING FILMS  
THIN FILM IMAGE CONVERTER.  
AD-453 855
- INTEGRATED CIRCUITS  
AN INVESTIGATION TO DEVELOP A .225 X .225-INCH SQUARE PLANAR, HERMETIC, INTEGRATED CIRCUIT PACKAGE FOR MOUNTING ON .310-INCH SQUARE MICROMODULE WAFERS.  
AD-405 861
- PACKAGING  
AN ECONOMICAL FLAT PACKAGE FOR INTEGRATED CIRCUITS.  
AD-450 549  
THE MINISTICK PROCESS FOR PACKAGING INTEGRATED CIRCUIT FLAT PACKS.  
AD-468 278
- TRANSISTORS  
ENGINEERING SERVICES ON TRANSISTORS.  
AD-422 492
- ION ENGINES  
ION SOURCES  
FEASIBILITY OF UTILIZING EMITTERS OF PERFOJATED SOLID SHEET RATHER THAN A SINTERED POWDER STRUCTURE IN ION ENGINE APPLICATIONS.  
AD-418 226
- ION SOURCES  
CESIUM  
FEASIBILITY OF UTILIZING EMITTERS OF PERFOJATED SOLID SHEET RATHER THAN A SINTERED POWDER STRUCTURE IN ION ENGINE APPLICATIONS.

- AD-418 226
- JOINTS  
TITANIUM DEVELOPMENT PROGRAM.  
VOLUME IV. •  
AD-264 685
- LITHIUM COMPOUNDS  
PREPARATION OF LIF CRYSTALS FOR  
ROLLING CONTACT STUDIES CLEAVAGE,  
POLISHING, AND ETCHING OF  
CRYSTALS. ELECTRON BEAM  
IRRADIATION; RADIATION EFFECTS.  
AD-276 887
- FUNDAMENTAL STUDY OF ROLLING  
CONTACT FATIGUE. NYLON AND  
TEFLON BALLS ROLLED UNDER LOAD  
UPON A PREPARED (001)  
SURFACE OF LIF LEFT A DISTINCTIVE  
DISLOCATION TRACE AS REVEALED BY AN  
ETCH PITTING TREATMENT.  
AD-285 085
- MANUFACTURING METHODS  
VARACTOR DIODES  
PRODUCTION ENGINEERING MEASURE  
FOR GALLIUM ARSENIDE VARACTOR  
DIODES.  
AD-419 585
- MACHINING  
ALUMINA  
MACHINING HIGH PURITY ALUMINA.  
AD-614 467
- BERYLLIUM ALLOYS  
MACHINING DATA FOR BERYLLIUM  
METAL.  
AD-485 297
- STEEL  
MACHINING AND GRINDING OF  
ULTRAHIGH-STRENGTH STEELS AND  
STAINLESS STEEL ALLOYS. •  
AD-629 654
- MANUFACTURING METHODS  
TITANIUM DEVELOPMENT PROGRAM.  
VOLUME IV. •  
AD-264 685  
THE RELIABILITY OF THE 2N1758A  
TRANSISTOR BY IMPROVEMENT OF  
MANUFACTURING TECHNIQUES INCLUDING  
EQUIPMENT AND PROCESS  
MODIFICATIONS, RELIABILITY TEST,  
FAILURE ANALYSIS AND ANALYTICAL-  
EMPIRICAL SURFACE STUDY.  
AD-284 872
- PRODUCTION ENGINEERING MEASURE  
TO INCREASE THE RELIABILITY  
FOR THE JET ETCH TRANSISTOR TYPE  
2N501A. MAXIMUM OPERATING  
FAILURE RATE OF 0.018/1000 HR AT A  
90% CONFIDENCE LEVEL AT 25 C.  
AD-286 907
- SPRAY ETCHING FOR PRODUCING THIN  
LINES, AND LAMINATING TECHNIQUES  
FOR MULTILAYER PRINTED  
CIRCUITS IN A  
MICROMINIATURIZATION PROGRAM.  
AD-291 876
- MICROWAVE GERMANIUM TUNNEL  
DIODES. DESIGN CONSIDERATIONS  
AND FABRICATION TECHNIQUES.  
AD-294 788
- PRODUCTION ENGINEERING MEASURE  
RELIABILITY IMPROVEMENT OF JET ETCH  
TRANSISTOR TYPE 2N1500.  
AD-295 057
- MANUFACTURING IMPROVEMENTS ON  
THE 2N1708 PLANAR EPITAXIAL  
TRANSISTOR.  
AD-404 537
- MODULES (ELECTRONIC)  
PACKAGING MINIATURIZATION.  
CHARGE NUMBERS 31-8027-0201-01, 31-  
8027-0901 AND RES 2 AND 4. •  
AD-422 115
- REVIEWS  
NAVMIRO MANUFACTURING TECHNOLOGY  
BULLETIN. NUMBERS 1 THRU 12,  
DECEMBER 1969-NOVEMBER 1970. •  
AD-725 614
- TRANSISTORS  
MANUFACTURING IMPROVEMENTS ON  
THE 2N1708 SILICON PLANAR  
EPITAXIAL TRANSISTOR.  
AD-414 912

## MAT-MET

- TRANSISTORS  
PRODUCTION ENGINEERING MEASURE  
ON SILICON ALLOY TRANSISTORS. •  
AD-422 940
- MATERIAL REMOVAL  
EFFECTIVENESS  
SURFACE INTEGRITY OF MACHINED  
STRUCTURAL COMPONENTS. •  
AD-870 146
- ELECTROCHEMISTRY  
INVESTIGATION OF ELECTROCHEMICAL  
TECHNIQUES AND SOLUTIONS FOR  
OCCURRING SHARP EDGES RESULTING  
FROM CHEMICAL MILLING AND BLANKING  
MOLYBDENUM, ALUMINUM ALLOYS, AND  
STAINLESS STEEL.  
AD-431 602
- STATE-OF-THE-ART REVIEWS  
MACHINING AND GRINDING OF NICKEL-  
AND COBALT-BASE ALLOYS. •  
AD-634 075
- STEEL  
MACHINING AND GRINDING OF  
ULTRAHIGH-STRENGTH STEELS AND  
STAINLESS STEEL ALLOYS. •  
AD-639 654
- TITANIUM  
MACHINING AND GRINDING OF  
TITANIUM AND ITS ALLOYS.  
AD-520 908
- MATERIALS  
BOEING-WICHITA MATERIALS AND  
RESEARCH DEVELOPMENT PROGRAMS, 1957-  
1961. •  
AD-271 167
- MECHANICAL PROPERTIES  
NIOBIUM ALLOYS  
MECHANICAL PROPERTIES AND  
SURFACE CONDITION OF CHEMICALLY  
MILLED SPECIMENS OF CB-5ZR NIOBIUM  
ALLOY.  
AD-431 617
- METAL FILMS
- MICROCIRCUITRY DEVELOPED BY  
CHEMICALLY DEPOSITING NI ALLOY  
FILMS ON INSULATING SUBSTRATES AND  
CHEMICAL ETCHING PATTERNS  
IN THIN CU CONDUCTORS.  
RESISTIVE AND CONDUCTIVE PARTS MADE  
OF NI ALLOY FILMS OF APPROX. 500  
OHMS PER SQUARE WERE USED.  
AD-281 843
- METAL PLATES  
CHEMICAL MILLING  
DEVELOPMENT OF CHEMICALLY MILLED  
WAFFLE GRID BERYLLIUM STRUCTURAL  
PANEL. •  
AD-423 788
- HYDROGEN EMBRITTLEMENT  
A NEW APPROACH TO BEND TESTING  
FOR THE DETERMINATION OF HYDROGEN  
EMBRITTLEMENT SUSCEPTIBILITY OF  
SHEET MATERIALS. •  
AD-681 765
- METALLIC CRYSTALS  
THE EFFECT OF SURFACE-ACTIVE  
AGENTS ON THE MECHANICAL PROPERTIES  
OF METALS. PART II. THE EFFECT OF  
SURFACE-ACTIVE AGENTS ON THE  
MECHANICAL BEHAVIOR OF ALUMINUM  
SINGLE CRYSTALS. •  
AD-282 017
- CRYSTAL STRUCTURE  
SUBSTRUCTURE AND DISLOCATION  
NETWORKS IN METALLIC CRYSTALS.  
AD-610 424
- METALLIC TEXTILES  
BERYLLIUM  
STUDY OF SIZE EFFECT IN FINE  
BERYLLIUM WIRE PHASE II. •  
AD-428 478
- METALLOGRAPHY  
CHEMICAL MILLING  
PRINCIPLES OF METALLOGRAPHIC  
ETCHING.  
AD-616 786
- METALLURGY

A REVIEW OF RECENT DEVELOPMENTS  
IN TITANIUM AND TITANIUM ALLOY  
TECHNOLOGY\*  
AD-269 209

•METALS

ELECTRIC AND CHEMICO-MECHANICAL  
METHODS OF WORKING METALS (CHAPTER  
VII)\*

AD-269 701

CHEMICAL COMPOUNDS FOR METAL  
SHAPING\*

AD-271 524

ETCH MILLING BY LIQUID AND NON-  
LIQUID ETCHANTS ON STAINLESS  
STEEL PLATES AND HONEYCOMB CORES.

AD-282 920

DEVELOPMENT OF FIBER-REINFORCED  
METALS AND ALLOYS; PREPARATION OF  
DE FIBER-AG ALLOY MATRIX  
COMPOSITES.

AD-287 594

DEVELOPMENT OF FIBER-REINFORCED  
METALS AND ALLOYS WITH HIGH  
STRENGTH-TO-WEIGHT RATIOS, HIGH  
ELASTIC MODULI; HOT  
EXTRUSION; FABRICATION; AL-BE  
ALLOYS.

AD-292 259

MATERIAL REMOVAL

INVESTIGATION OF ELECTROCHEMICAL  
TECHNIQUES AND SOLUTIONS FOR  
DEBURRING SHARP EDGES RESULTING  
FROM CHEMICAL MILLING AND BLANKING  
MOLYBDENUM, ALUMINUM ALLOYS, AND  
STAINLESS STEEL.

AD-431 602

•MICROMINIATURIZATION (ELECTRONICS)

AN INVESTIGATION TO DEVELOP A  
.225 X .225-INCH SQUARE PLANAR,  
HERMETIC, INTEGRATED CIRCUIT  
PACKAGE FOR MOUNTING ON .310-INCH  
SQUARE MICROMODULE WAFERS.

AD-405 841

•MICROMINIATURIZATION (ELECTRONICS)

MICROCIRCUITRY DEVELOPED BY  
CHEMICALLY DEPOSITING NI ALLOY  
FILMS ON INSULATING SUBSTRATES AND  
CHEMICAL ETCHING PATTERNS  
IN THIN CU CONDUCTORS.

RESISTIVE AND CONDUCTIVE PARTS MADE  
OF NI ALLOY FILMS OF APPROX. 500  
OHMS PER SQUARE WERE USED.

AD-281 842

SPRAY ETCHING FOR PRODUCING THIN  
LINES, AND LAMINATING TECHNIQUES  
FOR MULTILAYER PRINTED  
CIRCUITS IN A

MICROMINIATURIZATION PROGRAM.

AD-291 876

FAILURE (MECHANICS)

FAILURE MECHANISMS IN  
MICROELECTRONICS.

AD-607 426

MANUFACTURING METHODS

LOW-COST MICROCIRCUITS FOR  
MICROASSEMBLIES.\*

AD-432 891

•MICROWAVE EQUIPMENT

TRANSISTORS

PRODUCTION ENGINEERING MEASURES  
(PEM) FOR A GERMANIUM MICROWAVE  
TRANSISTOR.

AD-612 617

•MODULES (ELECTRONIC)

MANUFACTURING METHODS

PACKAGING MINIATURIZATION;  
CHARGE NUMBERS J1-8027-0201-01, J1-  
8027-0901 AND RES 2 AND 4.\*

AD-432 115

•MOLYBDENUM ALLOYS

MOLYBDENUM STRUCTURAL COMPONENT  
PROGRAM\*

AD-272 526

•NICKEL ALLOYS

MATERIAL REMOVAL

MACHINING AND GRINDING OF NICKEL-

- AND COBALT-BASE ALLOYS.  
AD-634 075
- NIOBIUM ALLOYS.  
MECHANICAL PROPERTIES  
MECHANICAL PROPERTIES AND  
SURFACE CONDITION OF CHEMICALLY  
MILLED SPECIMENS OF C8-52R NIOBIUM  
ALLOY.  
AD-431 617
- NON-DESTRUCTIVE TESTING  
TITANIUM ALLOYS  
DETERMINATION OF RESIDUAL STRESS  
PROFILES BY X-RAY DIFFRACTION AND  
STRAIN GAGE METHODS FOR BRAKE-PRESS  
FORMED TI-6AL-4V.  
AD-693 061
- PACKAGING  
INTEGRATED CIRCUITS  
AN ECONOMICAL FLAT PACKAGE FOR  
INTEGRATED CIRCUITS.  
AD-450 549
- PANELS (STRUCTURAL)  
BERYLLIUM  
SHEAR TEST OF CHEMICALLY MILLED  
BERYLLIUM WAFFLE PANEL.  
AD-438 138
- PHASE STUDIES  
INFLUENCE OF DISPLACIVE-SHEARING  
STRESSES ON THE KINETICS OF  
RECONSTRUCTIVE TRANSFORMATIONS  
EFFECTED BY PRESSURE IN THE RANGE 0-  
100,000 BARS.  
AD-236 351
- PRINTED CIRCUITS  
SPRAY ETCHING FOR PRODUCING THIN  
LINES, AND LAMINATING TECHNIQUES  
FOR MULTILAYER PRINTED  
CIRCUITS IN A  
MICROMINIATURIZATION PROGRAM.  
AD-291 876
- PACKAGING  
THE MINISTICK PROCESS FOR  
PACKAGING INTEGRATED CIRCUIT FLAT  
PACKS.
- AD-468 378
- PROCESSING  
ELECTRIC AND CHEMICO-MECHANICAL  
METHODS OF WORKING METALS (CHAPTER  
VII).  
AD-269 701
- PYROLITIC GRAPHITE  
MICROSTRUCTURE  
MICROSTRUCTURE OF PYROLITIC  
GRAPHITE.  
AD-612 643
- RADOMES  
BOEING-WICHITA MATERIALS AND  
RESEARCH DEVELOPMENT PROGRAMS, 1957-  
1961.  
AD-271 167
- REFRACTORY MATERIALS  
CHEMICAL COMPOUNDS FOR METAL  
SHAPING.  
AD-271 336
- REINFORCING MATERIALS  
DEVELOPMENT OF FIBER-REINFORCED  
METALS AND ALLOYS; PREPARATION OF  
BE FIBER-AG ALLOY MATRIX  
COMPOSITES.  
AD-287 594
- DEVELOPMENT OF FIBER-REINFORCED  
METALS AND ALLOYS WITH HIGH  
STRENGTH-TO-WEIGHT RATIOS, HIGH  
ELASTIC MODULI; HOT  
EXTRUSION; FABRICATION; AL-BE  
ALLOYS.  
AD-293 259
- RELIABILITY (ELECTRONICS)  
TRANSISTORS  
PRODUCTION ENGINEERING MEASURE  
TO IMPROVE PRODUCTION TECHNIQUES  
AND TO INSURE THE RELIABILITY OF  
THE C600 SERIES FIELD EFFECT  
TRANSISTORS.  
AD-606 477
- PRODUCTION ENGINEERING MEASURE  
TO IMPROVE PRODUCTION TECHNIQUES  
AND TO INSURE THE RELIABILITY OF  
THE C600 SERIES FIELD EFFECT

- TRANSISTORS.  
AD-613 048
- RESISTORS  
MICROCIRCUITRY DEVELOPED BY CHEMICALLY DEPOSITING NI ALLOY FILMS ON INSULATING SUBSTRATES AND CHEMICAL ETCHING PATTERNS IN THIN CU CONDUCTORS.  
RESISTIVE AND CONDUCTIVE PARTS MADE OF NI ALLOY FILMS OF APPROX. 500 OHMS PER SQUARE WERE USED.  
AD-281 843
- RIVETS  
MOLYBDENUM STRUCTURAL COMPONENT PROGRAM.  
AD-272 926
- ROCKET CASES  
STRUCTURAL TESTS OF A CHEMICALLY MILLED LADISH D-6AC STEEL SECOND-STAGE MINUTEMAN AFT CLOSURE.  
AD-261 999
- SANDWICH PANELS  
MATERIALS - HONEYCOMB CORE RIBBON RELATIONSHIP BETWEEN FLOW CHARACTERISTICS OF BRAZING ALLOY AND OXIDE FILM FORMATIONS OF - DETERMINATION OF.  
AD-272 227
- SECONDARY EMISSION  
COPPER ALLOYS  
TRANSLATION OF RUSSIAN ARTICLE: SECONDARY ELECTRONIC EMISSION OF COPPER AND OF CERTAIN COATINGS.  
AD-631 855
- SEMICONDUCTING FILMS  
SEMICONDUCTOR THIN FILM STUDIES.  
AD-412 841
- INFRARED IMAGES  
THIN FILM IMAGE CONVERTER.  
AD-453 855
- SOLAR CELLS  
RESEARCH ON PHOTOVOLTAIC CELLS.  
AD-621 454
- SEMICONDUCTOR DEVICES  
MANUFACTURING METHODS  
PRODUCTION ENGINEERING MEASURE.  
HIGH SPEED SEMICONDUCTOR SWITCH (TWO TERMINAL) HIGH SPEED SEMICONDUCTOR SWITCH (GATE).  
AD-603 660
- SEMICONDUCTORS  
PROCESSES AND TECHNIQUES FOR MANUFACTURING SILICON SEMICONDUCTOR NETWORKS; SUBMINIATURE ELECTRONIC EQUIPMENT; METHODS AND PILOT-LINE EQUIPMENT.  
AD-291 660
- MICROWAVE GERMANIUM TUNNEL DIODES. DESIGN CONSIDERATIONS AND FABRICATION TECHNIQUES.  
AD-274 788
- SHEEYS  
A REVIEW OF RECENT DEVELOPMENTS IN TITANIUM AND TITANIUM ALLOY TECHNOLOGY.  
AD-269 209
- SILICON  
PROCESSES AND TECHNIQUES FOR MANUFACTURING SILICON SEMICONDUCTOR NETWORKS; SUBMINIATURE ELECTRONIC EQUIPMENT; METHODS AND PILOT-LINE EQUIPMENT.  
AD-291 600
- TRANSISTORS  
PRODUCTION ENGINEERING MEASURE FOR SILICON OVERLAY TRANSISTORS.  
AD-619 295
- PRODUCTION ENGINEERING MEASURE FOR SILICON OVERLAY TRANSISTORS.  
AD-625 317
- PRODUCTION ENGINEERING MEASURE FOR SILICON OVERLAY TRANSISTORS.  
AD-628 230
- PRODUCTION ENGINEERING MEASURE FOR SILICON OVERLAY TRANSISTORS.  
AD-635 814
- SILICON ALLOYS  
CRYSTAL RECTIFIERS  
500 C SILICON CARBIDE RECTIFIER

SIN-SUB

PROGRAM.  
AD-420 375

## \*SINGLE CRYSTALS

INVESTIGATION OF SINGLE-CRYSTAL  
AND POLYCRYSTALLINE TITANIUM  
DIBORIDE: METALLOGRAPHIC PROCEDURES  
AND FINDINGS.

AD-271 955

THE EFFECT OF SURFACE-ACTIVE  
AGENT: ON THE MECHANICAL PROPERTIES  
OF METALS. PART II. THE EFFECT OF  
SURFACE-ACTIVE AGENTS ON THE  
MECHANICAL BEHAVIOR OF ALUMINUM  
SINGLE CRYSTALS.

AD-282 017

DISLOCATION MOBILITY IN ZN  
SINGLE CRYSTALS. DISLOCATION  
DENSITY AND CONFIGURATION  
WERE DETERMINED BEFORE AND AFTER  
STATIC LOADING AND STRESS PULSE  
LOADING.

AD-293 445

\*SOLAR CELLS  
FILMSINVESTIGATION OF THIN FILM  
CADMIUM SULFIDE SOLAR CELLS.

AD-605 425

## SEMICONDUCTING FILMS

RESEARCH ON PHOTOVOLTAIC CELLS.

AD-621 454

## \*STAINLESS STEEL

MATERIALS - HONEYCOMB CORE  
RIBBON RELATIONSHIP BETWEEN FLOW  
CHARACTERISTICS OF BRAZING ALLOY  
AND OXIDE FILM FORMATIONS OF -  
DETERMINATION OF.

AD-272 227

ETCH MILLING BY LIQUID AND NON-  
LIQUID ETCHANTS ON STAINLESS  
STEEL PLATES AND HONEYCOMB CORES.

AD-282 920

ELECTROLYTIC ETCHING OF  
STAINLESS STEEL PLATES AND  
HONEYCOMB CORES; VARIOUS  
CHEMICAL COMPOUNDS USED FOR METAL  
SHAPING; PROCESSING OF AIRCRAFT  
MATERIALS.

AD-295 752

## CHEMICAL MILLING

CHEMICAL MILLING OF NARROW CLOSE  
TOLERANCE SLOTS IN ALUMINUM AND  
STAINLESS STEEL.

AD-425 102

STRIPPING PT201 THERMOSETTING  
RESIN COATINGS FROM 321 ANNEALED  
STAINLESS STEEL SURFACES,  
(PROPELLANT UTILIZATION MANOMETER  
HOUSINGS).

AD-677 494

## \*STEEL

DEVELOPMENT OF IMPROVED METHODS,  
PROCESSES, AND TECHNIQUES FOR  
PRODUCING STEEL EXTRUSIONS.

AD-362 184

## CHEMICAL MILLING

CHEMICAL MILLING OF ALLOY  
STEELS.

AD-671 992

CHEMICAL MILLING OF METALS AND  
ALLOYS; ITS EFFECT ON STRESS  
CORROSION SUSCEPTIBILITY AND  
HYDROGEN EMBRITTLEMENT.

AD-648 980

## MATERIAL REMOVAL

MACHINING AND GRINDING OF  
ULTRAHIGH-STRENGTH STEELS AND  
STAINLESS STEEL ALLOYS.

AD-639 654

## \*SUBMINIATURE ELECTRONIC EQUIPMENT

MICROCIRCUITRY DEVELOPED BY  
CHEMICALLY DEPOSITING NI ALLOY  
FILMS ON INSULATING SUBSTRATES AND  
CHEMICAL ETCHING PATTERNS  
IN THIN CU CONDUCTORS.  
RESISTIVE AND CONDUCTIVE PARTS MADE  
OF NI ALLOY FILMS OF APPROX. 500

- OHMS PER SQUARE WERE USED.  
AD-281 843  
PROCESSES AND TECHNIQUES FOR  
MANUFACTURING SILICON SEMICONDUCTOR  
NETWORKS; SUBMINIATURE ELECTRONIC  
EQUIPMENT; METHODS AND PILOT-LINE  
EQUIPMENT.  
AD-291 600
- SWITCHING CIRCUITS  
MODULES (ELECTRONIC)  
PACKAGING MINIATURIZATION.  
CHARGE NUMBERS 31-8027-0201-01, 31-  
8027-0901 AND RES 2 AND 4.  
AD-422 115
- TANTALUM CAPACITORS  
FOILS  
SOLID ELECTROLYTE TANTALUM FOIL  
CAPACITOR.  
AD-423 325
- TITANIUM  
MATERIAL REMOVAL  
MACHINING AND GRINDING OF  
TITANIUM AND ITS ALLOYS.  
AD-620 908
- TITANIUM ALLOYS  
TITANIUM DEVELOPMENT PROGRAM.  
VOLUME IV.  
AD-264 685  
A REVIEW OF RECENT DEVELOPMENTS  
IN TITANIUM AND TITANIUM ALLOY  
TECHNOLOGY.  
AD-269 209
- AIRFRAMES  
COMPARATIVE COSTS OF FABRICATING  
AIRFRAME FROM ALUMINUM AND FROM  
TITANIUM.  
AD-609 349
- CHEMICAL MILLING  
ADVANCED CHEMICAL MILLING  
PROCESSES.  
AD-727 620
- MATERIAL REMOVAL  
MACHINING AND GRINDING OF  
TITANIUM AND ITS ALLOYS.
- AD-620 908
- STRESSES.  
DETERMINATION OF RESIDUAL STRESS  
PROFILES BY X-RAY DIFFRACTION AND  
STRAIN GAGE METHODS FOR BRAKE-PRESS  
FORMED Ti-6AL-4V.  
AD-602 061
- TITANIUM COMPOUNDS  
INVESTIGATION OF SINGLE-CRYSTAL  
AND POLYCRYSTALLINE TITANIUM  
DIBORIDE; METALLOGRAPHIC PROCEDURES  
AND FINDINGS.  
AD-271 965
- TRANSFORMATIONS  
INFLUENCE OF DISPLACIVE-SHEARING  
STRESSES ON THE KINETICS OF  
RECONSTRUCTIVE TRANSFORMATIONS  
EFFECTED BY PRESSURE IN THE RANGE 0-  
100,000 BARS.  
AD-296 751
- TRANSISTORS  
THE RELIABILITY OF THE 2N1358A  
TRANSISTOR BY IMPROVEMENT OF  
MANUFACTURING TECHNIQUES INCLUDING  
EQUIPMENT AND PROCESS  
MODIFICATIONS, RELIABILITY TEST,  
FAILURE ANALYSIS AND ANALYTICAL-  
EMPIRICAL SURFACE STUDY.  
AD-286 872  
PRODUCTION OF SILICON, PLANAR,  
EPITAXIAL TRANSISTOR TYPE 2N2193.  
MANUFACTURING METHODS, PROCESSES  
AND TEST RESULTS.  
AD-286 886  
PRODUCTION ENGINEERING MEASURE  
TO INCREASE THE RELIABILITY  
FOR THE JET ETCH TRANSISTOR TYPE  
2N501A. MAXIMUM OPERATING  
FAILURE RATE OF 0.01%/1000 HR AT A  
90% CONFIDENCE LEVEL AT 25 C.  
AD-286 907  
WELDING MACHINE INSTALLATION,  
IMPROVED KPR RESOLUTION,  
DIFFUSION, INTERCONNECTIONS,  
RELIABILITY MEASUREMENT.  
AD-404 185

VAR-ZIN

MANUFACTURING METHODS  
FABRICATION TECHNOLOGY FOR PNP  
PLANAR SILICON TRANSISTORS.

AD-408 190

MANUFACTURING IMPROVEMENTS ON  
THE 2N1708 SILICON PLANAR  
EPITAXIAL TRANSISTOR.

AD-414 913

ENGINEERING SERVICES ON  
TRANSISTORS.

AD-422 492

PRODUCTION ENGINEERING MEASURE  
TO IMPROVE PRODUCTION TECHNIQUES  
AND TO INSURE THE RELIABILITY OF  
THE C600 SERIES FIELD EFFECT  
TRANSISTORS.

AD-606 477

PRODUCTION ENGINEERING MEASURES  
(PEM) FOR A GERMANIUM MICROWAVE  
TRANSISTOR.

AD-612 617

PRODUCTION ENGINEERING MEASURE  
TO IMPROVE PRODUCTION TECHNIQUES  
AND TO INSURE THE RELIABILITY OF  
THE C600 SERIES FIELD EFFECT  
TRANSISTORS.

AD-613 068

PRODUCTION ENGINEERING MEASURE  
TO IMPROVE PRODUCTION TECHNIQUES  
AND INCREASE THE RELIABILITY OF THE  
2N228A TRANSISTOR.

AD-614 823

PRODUCTION ENGINEERING MEASURE  
FOR SILICON OVERLAY TRANSISTORS.

AD-619 295

PRODUCTION ENGINEERING MEASURE  
FOR SILICON OVERLAY TRANSISTORS.

AD-625 317

PRODUCTION ENGINEERING MEASURE  
FOR SILICON OVERLAY TRANSISTORS.

AD-628 230

PRODUCTION ENGINEERING MEASURE  
FOR SILICON OVERLAY TRANSISTORS.

AD-635 814

PRODUCTION

PRODUCTION ENGINEERING MEASURE  
ON SILICON ALLOY TRANSISTORS.

AD-422 940

PRODUCTION ENGINEERING MEASURE  
TO IMPROVE PRODUCTION TECHNIQUES

AND TO INSURE THE RELIABILITY OF  
THE C600 SERIES FIELD EFFECT  
TRANSISTORS.

AD-426 356

RELIABILITY (ELECTRONICS)

PRODUCTION ENGINEERING MEASURE  
TO INCREASE THE RELIABILITY OF THE  
TRANSISTOR TYPE 2N2034.

AD-606 191

SILICON

TRANSISTOR, VHF, SILICON, POWER  
(10W-500MC).

AD-622 879

•VARACTOR DIODES

PRODUCTION

PRODUCTION ENGINEERING MEASURE  
FOR GALLIUM ARSENIDE VARACTOR  
DIODES.

AD-419 585

•WELDING

ALUMINUM ALLOYS

MANUAL AND REPAIR WELDING OF  
CHEMICALLY MILLED 2014-T6 ALUMINUM  
SHEETING.

AD-606 819

•WIRE

TENSILE PROPERTIES

INFLUENCE OF SOME PROCESSING  
VARIABLES UPON THE ELEVATED AND  
ROOM TEMPERATURE STRENGTH OF  
ULTRAFINE BERYLLIUM WIRES.

AD-633 992

•ZINC

DISLOCATION MOBILITY IN ZN

SINGLE CRYSTALS. DISLOCATION  
DENSITY AND CONFIGURATION  
WERE DETERMINED BEFORE AND AFTER  
STATIC LOADING AND STRESS PULSE  
LOADING.

AD-243 445

D-14

UNCLASSIFIED

UNCLASSIFIED

TITLE INDEX

ADVANCED CHEMICAL MILLING PROCESSES. (U) •CHEMICAL MILLING	AD-727 620	ALUMINUM AND STAINLESS STEEL. (U) •STAINLESS STEEL	
BERYLLIUM COMPOSITE STRUCTURES, VOLUME II. MATERIALS AND PROCESSES (U) •AEROSPACE CRAFT	AD-270 524	CHEMICAL MILLING (U) •CHEMICAL MILLING	AD-292 129
BOEING-WICHITA MATERIALS AND RESEARCH PROGRAMS, 1957-1961 (U) •AIRFRAMES	AD-271 147	CHEMICAL MILLING (U) •CHEMICAL MILLING	AD-610 620
300 C SILICON CARBIDE RECTIFIER PROGRAM. (U) •CRYSTAL RECTIFIERS	AD-420 375	THE DESIGN AND EVALUATION OF PERFORATED ION EMITTERS. (U) •ION ENGINES	AD-418 226
CHEM-MILL PROCESS FOR CONTOURING ALUMINUM HONEYCOMB CORE. (U) •HONEYCOMB CORES	AD-670 154	DESIGN CONSIDERATIONS FOR MICROWAVE GERMANIUM TUNNEL DIODES (U) •DIODES	AD-294 788
CHEMICAL COMPOUNDS FOR METAL SHAPING (U) •ALLOYS	AD-271 526	DETERMINATION OF MECHANICAL PROPERTIES AND SURFACE CONDITION OF CHEM-MILLED CB-5ZR COLUMBIUM ALLOY SAMPLES. (U) •NIObIUM ALLOYS	AD-421 617
CHEMICAL COMPOUNDS FOR METAL SHAPING (U) •CHEMICAL MILLING	AD-282 920	DETERMINATION OF RESIDUAL STRESS PROFILES BY X-RAY DIFFRACTION AND STRAIN GAGE METHODS FOR BRAKE-PRESS FORMED Ti-6AL-4V. (U) •TITANIUM ALLOYS	AD-683 061
CHEMICAL COMPOUNDS FOR METAL SHAPING (U) •HONEYCOMB CORES	AD-295 752	DEVELOPMENT OF CHEMICAL MILLED WAFFLE GRID BERYLLIUM STRUCTURAL PANEL. (U) •BERYLLIUM	AD-422 288
CHEMICAL MILLING (DEEP CONTOUR ETCHING). (U) •CHEMICAL MILLING	AD-680 561	DEVELOPMENT OF IMPROVED METHODS, PROCESSES, AND TECHNIQUES FOR PRODUCING STEEL EXTRUSIONS (U) •AIRFRAMES	AD-262 184
CHEMICAL MILLING OF ALLOY STEELS. (U) •CHEMICAL MILLING	AD-671 952	DISLOCATION MOBILITY IN ZINC SINGLE CRYSTALS (U) •DEFORMATION	AD-293 445
CHEMICAL MILLING OF METALS AND ALLOYS—ITS EFFECT ON STRESS CORROSION SUSCEPTIBILITY AND HYDROGEN EMBRITTELEMENT. (U) •CHEMICAL MILLING	AD-640 980	AN ECONOMICAL FLAT PACKAGE FOR INTEGRATED CIRCUITS. (U) •PACKAGING	AD-450 549
CHEMICAL MILLING OF NARROW CLOSE TOLERANCE SLOTS IN	AD-425 102	THE EFFECT OF SURFACE-	AD-282 017

T-1

UNCLASSIFIED

- ACTIVE AGENTS ON THE MECHANICAL PROPERTIES OF METALS. PART II. THE EFFECT OF SURFACE-ACTIVE AGENTS ON THE MECHANICAL BEHAVIOR OF ALUMINUM SINGLE CRYSTALS.(U)  
•METALLIC CRYSTALS)
- EFFECT OF SURFACE FINISHES ON FATIGUE LIFE(U)  
•ALLOYS AD-402 164
- ELECTRIC AND CHEMICO-MECHANICAL METHODS OF WORKING METALS (CHAPTER VII)(U)  
•METALS AD-269 701
- ELECTROCHEMICAL DEBURRING OF MOLYBDENUM, ALUMINUM AND STAINLESS STEEL.(U)  
•METALS AD-431 402
- ENGINEERING SERVICES ON TRANSISTORS.(U)  
•TRANSISTORS AD-422 492
- FAILURE MECHANISMS IN MICROELECTRONICS.(U)  
•MICROMINIATURIZATION (ELECTRONICS) AD-607 426
- FIBER-REINFORCED METALS AND ALLOYS(U)  
•COMPOSITE MATERIALS AD-297 994
- FIBER-REINFORCED METALS AND ALLOYS(U)  
•COMPOSITE MATERIALS AD-293 289
- A FUNDAMENTAL STUDY OF ROLLING CONTACT FATIGUE(U)  
•CRYSTALS AD-276 887
- A FUNDAMENTAL STUDY OF ROLLING CONTACT FATIGUE(U)  
•DEFORMATION AD-289 089
- INFLUENCE OF DISPLACIVE-SHEARING STRESSES ON THE KINETICS OF RECONSTRUCTIVE TRANSFORMATIONS EFFECTED BY PRESSURE IN THE RANGE 0-100,000 BARS(U)  
•CHEMICAL MILLING AD-286 351
- INFLUENCE OF SOME PROCESSING VARIABLES UPON THE ELEVATED AND ROOM TEMPERATURE STRENGTH OF ULTRAFINE BERYLLIUM WIRES.(U)  
•CHEMICAL MILLING AD-622 992
- INVESTIGATION OF SINGLE-CRYSTAL AND POLYCRYSTALLINE TITANIUM DIBORIDE: METALLOGRAPHIC PROCEDURES AND FINDINGS(U)  
•BORIDES AD-271 969
- INVESTIGATION OF THIN FILM CADMIUM SULFIDE SOLAR CELLS.(U)  
•SOLAR CELLS AD-609 429
- LOW-COST MICROCIRCUITS FOR MICROASSEMBLIES.(U)  
•MICROMINIATURIZATION (ELECTRONICS) AD-423 891
- MACHINING AND GRINDING OF NICKEL-AND COBALT-BASE ALLOYS.(U)  
•NICKEL ALLOYS AD-624 079
- MACHINING AND GRINDING OF TITANIUM AND ITS ALLOYS.(U)  
•TITANIUM AD-620 989
- MACHINING AND GRINDING OF ULTRAHIGH-STRENGTH STEELS AND STAINLESS STEEL ALLOYS.(U)  
•STEEL AD-629 694
- MACHINING DATA FOR BERYLLIUM METAL.(U)  
•BERYLLIUM ALLOYS AD-489 297
- MACHINING HIGH PURITY ALUMINA.(U)  
•MACHINING AD-614 467
- MANUAL AND REPAIR WELDING OF CHEMICALLY MILLED 2014-T6 ALUMINUM SHEETING.(U)  
•ALUMINUM ALLOYS AD-604 819
- MATERIAL BERYLLIUM WAFFLE PANEL. CHEMICAL MILLED. AD-428 128

SHEAR TEST OF (U)  
•BERYLLIUM

MATERIALS - HONEYCOMB AD-272 227  
CORE RIBBON RELATIONSHIP BETWEEN  
FLOW CHARACTERISTICS OF BRAZING  
ALLOY AND OXIDE FILM FORMATIONS OF -  
DETERMINATION OF (U)

•BRAZING

MATRIX CONTROLLED AD-418 889  
DISPLAY DEVICE (U)

•DISPLAY SYSTEMS

METAL REMOVAL BY AD-612 261  
ELECTROCHEMICAL METHODS AND ITS  
EFFECTS ON MECHANICAL PROPERTIES OF  
METALS (U)

•ELECTROEROSIVE MACHINING

THE METALLOGRAPHY OF AD-612 649  
PYROLITIC GRAPHITE (U)

•PYROLITIC GRAPHITE

MICROCIRCUITRY BY AD-281 849  
CHEMICAL DEPOSITION (U)

•CIRCUITS

MICROMINIATURE AD-409 861  
INTEGRATED CIRCUIT PACKAGE (U)  
•MICROMINIATURIZATION (ELEC TRONICS)

MICROMINIATURE LAYERED AD-291 876  
PRINTED WIRING (U)

•MANUFACTURING METHODS

MICROMINIATURE LAYERED AD-400 732  
PRINTED WIRING (U)

•CHEMICAL MILLING

THE MINISTICK PROCESS AD-468 378  
FOR PACKAGING INTEGRATED CIRCUIT  
FLAT PACKS (U)

•INTEGRATED CIRCUITS

MISSILE-BORNE TRACKING AD-426 932  
ANTENNA (U)

•GUIDED MISSILE ANTENNAS

MOLYBDENUM STRUCTURAL AD-272 926  
COMPONENT PROGRAM (U)

•COATINGS

NAVYMANUFACTURING AD-729 614  
TECHNOLOGY BULLETIN. NUMBERS 1  
THRU 12, DECEMBER 1969-NOVEMBER  
1970 (U)

•MANUFACTURING METHODS

A NEW APPROACH TO BEND AD-681 769  
TESTING FOR THE DETERMINATION OF  
HYDROGEN EMBRITTLEMENT  
SUSCEPTIBILITY OF SHEET  
MATERIALS (U)

•METAL PLATES

NO UNCLASSIFIED TITLE AD-267 806

NONTRADITIONAL AD-798 271  
MACHINING OF BERYLLIUM (U)

•ELECTROEROSIVE MACHINING

A NOTE ON SEMICONDUCTOR AD-368 039  
DEVICE FABRICATION (U)

•ALLOYS

PACKAGING MINIATURIZATION AD-499 119  
N. CHARGE NUMBERS 21-8027-0201-01,  
21-8027-0901 AND RES 2 AND 4 (U)

•MODULES (ELECTRONIC)

PEN FOR TRANSISTOR AD-286 907  
MANUFACTURING PROCESS  
IMPROVEMENT (U)

•TRANSISTORS

POLISHES AND ETCHES FOR AD-624 392  
TIN TELLURIDE, LEAD SULFIDE, LEAD  
SELENIDE, AND LEAD TELLURIDE  
SUPPLEMENT (U)

•CHEMICAL MILLING

POLISHES AND ETCHES FOR AD-423 367  
TIN TELLURIDE, LEAD SULFIDE, LEAD  
SELENIDE, AND LEAD TELLURIDE (U)

•CHEMICAL MILLING

PRINCIPLES OF AD-616 786  
METALLOGRAPHIC ETCHING (U)

•CHEMICAL MILLING

PRODUCTION ENGINEERING AD-419 985

PRO-RES

MEASURE FOR GALLIUM ARSENIIDE  
VARACTOR DIODE.(U)  
•VARACTOR DIODES

PRODUCTION ENGINEERING AD-619 295  
MEASURE FOR SILICON OVERLAY  
TRANSISTORS.(U)  
•TRANSISTORS

PRODUCTION ENGINEERING AD-629 217  
MEASURE FOR SILICON OVERLAY  
TRANSISTORS.(U)  
•TRANSISTORS

PRODUCTION ENGINEERING AD-628 230  
MEASURE FOR SILICON OVERLAY  
TRANSISTORS.(U)  
•TRANSISTORS

PRODUCTION ENGINEERING AD-638 814  
MEASURE FOR SILICON OVERLAY  
TRANSISTORS.(U)  
•TRANSISTORS

PRODUCTION ENGINEERING AD-603 660  
MEASURE. HIGH SPEED SEMICONDUCTOR  
SWITCH (TWO TERMINAL) HIGH SPEED  
SEMICONDUCTOR SWITCH (GATE).(U)  
•ELECTRONIC SWITCHES

PRODUCTION ENGINEERING AD-404 927  
MEASURE ON 2N1708 SILICON PLANAR  
EPITAXIAL TRANSISTOR. (U)  
•MANUFACTURING METHODS

PRODUCTION ENGINEERING AD-414 913  
MEASURE ON 2N1708 SILICON PLANAR  
EPITOXIAL TRANSISTOR.(U)  
•TRANSISTORS

PRODUCTION ENGINEERING AD-422 940  
MEASURE ON SILICON ALLOY  
TRANSISTORS.(U)  
•TRANSISTORS

PRODUCTION ENGINEERING AD-299 057  
MEASURE RELIABILITY IMPROVEMENT JET  
ETCH TRANSISTOR(U)  
•MANUFACTURING METHODS

PRODUCTION ENGINEERING AD-614 823

MEASURE TO IMPROVE PRODUCTION  
TECHNIQUES AAND INCREASE THE  
RELIABILITY OF THE 2N229A  
TRANSISTOR.(U)  
•TRANSISTORS

PRODUCTION ENGINEERING AD-286 872  
MEASURE TO IMPROVE PRODUCTION  
TECHNIQUES AND INCREASE THE  
RELIABILITY OF THE 2N1398A  
TRANSISTOR(U)  
•MANUFACTURING METHODS

PRODUCTION ENGINEERING AD-426 356  
MEASURE TO IMPROVE PRODUCTION  
TECHNIQUES AND TO INSURE THE  
RELIABILITY OF THE C600 SERIES  
FIELD EFFECT TRANSISTORS.(U)  
•TRANSISTORS

PRODUCTION ENGINEERING AD-606 477  
MEASURE TO IMPROVE PRODUCTION  
TECHNIQUES AND TO INSURE THE  
RELIABILITY OF THE C600 SERIES  
FIELD EFFECT TRANSISTORS.(U)  
•TRANSISTORS

PRODUCTION ENGINEERING AD-613 068  
MEASURE TO IMPROVE PRODUCTION  
TECHNIQUES AND TO INSURE THE  
RELIABILITY OF THE C400 SERIES  
FIELD EFFECT TRANSISTORS.(U)  
•TRANSISTORS

PRODUCTION ENGINEERING AD-606 191  
MEASURE TO INCREASE THE RELIABILITY  
OF THE TRANSISTOR TYPE 22N2024.(U)  
•TRANSISTORS

PRODUCTION ENGINEERING AD-612 617  
MEASURES (PCM) FOR A GERMANIUM  
MICROWAVE TRANSISTOR.(U)  
•TRANSISTORS

REDUCING HAND AD-677 066  
STRAIGHTENING BY CHEM-HILLING 7075  
AND 7178 ALUMINUM ALLOY IN THE 'W'  
(OR NATURALLY AGED) CONDITION.(U)  
•ALUMINUM ALLOYS

RESEARCH AND AD-298 707

DEVELOPMENT OF HIGH TEMPERATURE SEMICONDUCTOR DEVICES (U)  
 • ARSENIDES

RESEARCH IN THE GENERAL AD-610 434  
 FIELD OF SUBSTRUCTURE AND  
 DISLOCATION NETWORKS IN METALLIC  
 CRYSTALS (U)  
 • METALLIC CRYSTALS

RESEARCH ON AD-621 484  
 PHOTOVOLTAIC CELLS (U)  
 • SOLAR CELLS

A REVIEW OF AD-674 066  
 METALLOGRAPHIC PREPARATION  
 PROCEDURES FOR BERYLLIUM AND  
 BERYLLIUM ALLOYS (U)  
 • BERYLLIUM

A REVIEW OF RECENT AD-269 209  
 DEVELOPMENTS IN TITANIUM AND  
 TITANIUM ALLOY TECHNOLOGY (U)  
 • METALLURGY

SECONDARY ELECTRONIC AD-671 825  
 EMISSION OF COPPER AND OF CERTAIN  
 COATINGS (U)  
 • COPPER ALLOYS

SEMICONDUCTOR THIN AD-212 841  
 FILMS (U)  
 • SEMICONDUCTING FILMS

SILICON PLANAR AD-286 886  
 EPITAXIAL TRANSISTOR TYPE 2N2193 (U)  
 • TRANSISTORS

SILICON PLANAR AD-404 185  
 EPITAXIAL TRANSISTOR TYPE 2N2193 (U)  
 • TRANSISTORS

SILICON SEMICONDUCTOR AD-291 600  
 NETWORKS MANUFACTURING METHODS (U)  
 • SEMICONDUCTORS

SOLID ELECTROLYTE AD-423 225  
 TANTALUM FOIL CAPACITOR (U)  
 • TANTALUM CAPACITORS

STRIPPING PT201 AD-677 494

THERMOSETTING RESIN COATINGS FROM  
 221 ANNEALED STAINLESS STEEL  
 SURFACES; (PROPELLANT UTILIZATION  
 MANOMETER HOUSINGS) (U)  
 • STAINLESS STEEL

STRUCTURAL TESTS OF A AD-261 989  
 CHEMICALLY MILLED LADISH D-6AC  
 STEEL SECOND-STAGE MINUTEHAN AFT  
 CLOSURE (U)  
 • CHEMICAL MILLING

STUDY OF SIZE EFFECT IN AD-438 478  
 FINE BERYLLIUM WIRE PHASE II (U)  
 • BERYLLIUM

SURFACE INTEGRITY OF AD-670 146  
 MACHINED STRUCTURAL COMPONENTS (U)  
 • AIRFRAMES

A SURVEY OF THE AD-609 349  
 COMPARATIVE COSTS OF FABRICATING  
 AIRFRAME FROM ALUMINUM AND FROM  
 TITANIUM (U)  
 • TITANIUM ALLOYS

TECHNOLOGY FOR RNP AD-408 190  
 PLANAR SILICON TRANSISTORS:  
 SWITCHING AND AMPLIFYING (U)  
 • TRANSISTORS

THIN FILM IMAGE AD-452 885  
 CONVERTER (U)  
 • SEMICONDUCTING FILMS

TITANIUM DEVELOPMENT AD-254 685  
 PROGRAM. VOLUME IV (U)  
 • ALLOYS

TRANSISTOR, VHF, AD-622 879  
 SILICON, POWER (10W-500MC) (U)  
 • TRANSISTORS

---

WING - ALUMINUM SHEET AD-286 074  
 AND PLATE - DYNAMIC ETCHED OR CHEM-  
 MILLED - MECHANICAL PROPERTIES -

RES-WIN

UNCLASSIFIED

DETERMINATION OF (U)  
•ALUMINUM ALLOYS

T-6  
UNCLASSIFIED

## UNCLASSIFIED

## PERSONAL AUTHOR INDEX

- ABE, SHIRO . . .  
PACKAGING MINIATURIZATION. CHARGE  
NUMBERS 31-8027-0201-01, 31-8027-  
0901 AND RES 2 AND 4,  
AD-433 115
- ADAMS, K.H . . .  
DISLOCATION MOBILITY IN ZINC SINGLE  
CRYSTALS  
AD-293 445
- AGRICOLA, K. R. . . .  
MANUAL AND REPAIR WELDING OF  
CHEMICALLY MILLED 2014-T6 ALUMINUM  
SHEETING,  
AD-606 819
- ARNOLD, S. R. . . .  
ENGINEERING SERVICES ON  
TRANSISTORS,  
AD-422 492
- BARBARC, E.P. . . .  
MICROMINIATURE INTEGRATED CIRCUIT  
PACKAGE,  
AD-405 861
- BELT, R. F. . . .  
INVESTIGATION OF THIN FILM CADMIUM  
SULFIDE SOLAR CELLS,  
AD-605 425
- BERMAN, I . . . .  
A NOTE ON SEMICONDUCTOR DEVICE  
FABRICATION  
AD-268 033
- BOULGER, F. W. . . .  
MACHINING AND GRINDING OF TITANIUM  
AND ITS ALLOYS,  
AD-620 500
- BOULGER, F. W. . . .  
MACHINING AND GRINDING OF NICKEL-  
AND COBALT-BASE ALLOYS,  
AD-634 075
- BROWER, W.C . . . .  
MACHINING AND GRINDING OF ULTRAHIGH-  
STRENGTH STEELS AND STAINLESS STEEL  
ALLOYS,  
AD-639 654
- BROWER, W.C . . . .  
SILICON SEMICONDUCTOR NETWORKS  
MANUFACTURING METHODS  
AD-291 600
- BURLINGAME, B. G. . . .  
PRODUCTION ENGINEERING MEASURE,  
HIGH SPEED SEMICONDUCTOR SWITCH  
(TWO TERMINAL) HIGH SPEED  
SEMICONDUCTOR SWITCH (GATE),  
AD-603 660
- CADY, J.R . . . .  
CHEMICAL COMPOUNDS FOR METAL  
SHAPING  
AD-282 920
- CASSIDY, MICHAEL . . . .  
PRODUCTION ENGINEERING MEASURE FOR  
SILICON OVERLAY TRANSISTORS,  
AD-625 317
- CASSIDY, MICHAEL . . . .  
PRODUCTION ENGINEERING MEASURE FOR  
SILICON OVERLAY TRANSISTORS,  
AD-635 814
- CHANG, H. C. . . . .  
500 C SILICON CARBIDE RECTIFIER  
PROGRAM,  
AD-420 375

CHR-FAR

- CHRISTENSEN, L.M.  
 . . .  
 DEVELOPMENT OF IMPROVED METHODS,  
 PROCESSES, AND TECHNIQUES FOR  
 PRODUCING STEEL EXTRUSIONS  
 AD-262 184
- CHURCHON, STUART  
 . . .  
 PACKAGING MINIATURIZATION. CHARGE  
 NUMBERS 31-8027-0201-01, 31-8027-  
 0901 AND RES 2 AND 4,  
 AD-423 115
- CLARKE, R. H.  
 . . .  
 TRANSISTOR, VPF, SILICON, POWER  
 (10W-500MC).  
 AD-622 879
- COCKING, J.  
 . . .  
 PRODUCTION ENGINEERING MEASURE TO  
 INCREASE THE RELIABILITY OF THE  
 TRANSISTOR TYPE 22N2034.  
 AD-606 191
- COURIER, J.  
 . . .  
 PRODUCTION ENGINEERING MEASURE TO  
 INCREASE THE RELIABILITY OF THE  
 TRANSISTOR TYPE 22N2034.  
 AD-606 191
- CRISHAL, J.  
 . . .  
 TRANSISTOR, VHF, SILICON, POWER  
 (10W-500MC).  
 AD-622 879
- DACHILLE, FRANK  
 . . .  
 INFLUENCE OF DISPLACIVE-SHEARING  
 STRESSES ON THE KINETICS OF  
 RECONSTRUCTIVE TRANSFORMATIONS  
 EFFECTED BY PRESSURE IN THE RANGE 0-  
 100,000 BARS  
 AD-254 351
- DAHIANO, V. V.  
 . . .
- RESEARCH IN THE GENERAL FIELD OF  
 SUBSTRUCTURE AND DISLOCATION  
 NETWORKS IN METALLIC CRYSTALS.  
 AD-610 424
- DAVIS, C.F.  
 . . .  
 PRODUCTION ENGINEERING MEASURE FOR  
 GALLIUM ARSENIDE VARACTOR DIODE.  
 AD-419 585
- DAVIS, R. E.  
 . . .  
 ENGINEERING SERVICES ON  
 TRANSISTORS.  
 AD-422 492
- DES ROCHES, F.  
 . . .  
 PRODUCTION ENGINEERING MEASURE TO  
 INCREASE THE RELIABILITY OF THE  
 TRANSISTOR TYPE 22N2034.  
 AD-606 191
- DIATROPTOV, D. B.  
 . . .  
 SECONDARY ELECTRONIC EMISSION OF  
 COPPER AND OF CERTAIN COATINGS,  
 AD-621 855
- DI PAOLA, R.  
 . . .  
 PRODUCTION ENGINEERING MEASURE TO  
 IMPROVE PRODUCTION TECHNIQUES AND  
 INCREASE THE RELIABILITY OF THE  
 2N208A TRANSISTOR.  
 AD-614 922
- ESQUIVEL, A. L.  
 . . .  
 DETERMINATION OF RESIDUAL STRESS  
 PROFILES BY X-RAY DIFFRACTION AND  
 STRAIN GAGE METHODS FOR BRAKE-PRESS  
 FORMED TI-6AL-4V,  
 AD-683 061
- FARNER, H.B.  
 . . .  
 WING - ALUMINUM SHEET AND PLATE -  
 DYNAMIC ETCHED OR CHEM-MILLED -  
 MECHANICAL PROPERTIES -

- DETERMINATION OF  
AD-286 074
- FEHRLE, A. C. . . .  
DEVELOPMENT OF CHEMICAL MILLED  
WAFFLE GRID BERYLLIUM STRUCTURAL  
PANEL,  
AD-423 388
- FELDMAN, E. J. . . .  
PRODUCTION ENGINEERING MEASURE FOR  
GALLIUM ARSENIDE VARACTOR DIODE.  
AD-419 585
- FIELD, MICHAEL . . . .  
SURFACE INTEGRITY OF MACHINED  
STRUCTURAL COMPONENTS.  
AD-870 146
- FOLSTER, J. H. D. . . . .  
PRODUCTION ENGINEERING MEASURE  
RELIABILITY IMPROVEMENT JET ETCH  
TRANSISTOR  
AD-295 057
- FRITZ, LOUIS J. . . . .  
SURFACE INTEGRITY OF MACHINED  
STRUCTURAL COMPONENTS.  
AD-870 146
- GAGNE, R. M. . . . .  
PRODUCTION ENGINEERING MEASURE  
RELIABILITY IMPROVEMENT JET ETCH  
TRANSISTOR  
AD-295 057
- GATTO, LUCIANO R. . . . .  
SURFACE INTEGRITY OF MACHINED  
STRUCTURAL COMPONENTS.  
AD-870 146
- GIBBONS, G. . . . .  
ENGINEERING SERVICES ON
- TRANSISTORS.  
AD-422 492
- GLENSKI, P. J. . . . .  
CHEM-MILL PROCESS FOR CONTOURING  
ALUMINUM HONEYCOMB CORE.  
AD-678 154
- GOLDING, WILLIAM H. . . . .  
INFLUENCE OF SOME PROCESSING  
VARIABLES UPON THE ELEVATED AND  
ROOM TEMPERATURE STRENGTH OF  
ULTRAFINE BERYLLIUM WIRES,  
AD-633 992
- GREEN, E. D. . . . .  
TITANIUM DEVELOPMENT PROGRAM.  
VOLUME IV.  
AD-264 685
- GREENE, NORBERT D. . . . .  
PRINCIPLES OF METALLOGRAPHIC  
ETCHING.  
AD-616 786
- GREER, PAUL . . . . .  
PRODUCTION ENGINEERING MEASURE FOR  
SILICON OVERLAY TRANSISTORS.  
AD-625 317
- PRODUCTION ENGINEERING MEASURE FOR  
SILICON OVERLAY TRANSISTORS.  
AD-628 230
- PRODUCTION ENGINEERING MEASURE FOR  
SILICON OVERLAY TRANSISTORS.  
AD-635 814
- GURKLIS, J. A. . . . .  
MACHINING AND GRINDING OF TITANIUM  
AND ITS ALLOYS.  
AD-620 508
- MACHINING AND GRINDING OF NICKEL-  
AND COBALT-BASE ALLOYS,

GUR-JEN

- AD-674 075  
 \* \* \*  
 MACHINING AND GRINDING OF ULTRAHIGH-  
 STRENGTH STEELS AND STAINLESS STEEL  
 ALLOYS,  
 AD-639 654
- \*GURKLIS, JOHN A.  
 \* \* \*  
 METAL REMOVAL BY ELECTROCHEMICAL  
 METHODS AND ITS EFFECTS ON  
 MECHANICAL PROPERTIES OF METALS,  
 AD-613 261
- \* \* \*  
 NONTRADITIONAL MACHINING OF  
 BERYLLIUM,  
 AD-738 271
- \*HARVEY, DONALD J.  
 \* \* \*  
 RESEARCH ON PHOTOVOLTAIC CELLS.  
 AD-621 454
- \*HEBB, EMMA LEE  
 \* \* \*  
 MICROCIRCUITRY BY CHEMICAL  
 DEPOSITION,  
 AD-281 843
- \*HERMAN, M.  
 \* \* \*  
 RESEARCH IN THE GENERAL FIELD OF  
 SUBSTRUCTURE AND DISLOCATION  
 NETWORKS IN METALLIC CRYSTALS.  
 AD-610 434
- \*MEYERDAHL, NORMAN E.  
 \* \* \*  
 RESEARCH ON PHOTOVOLTAIC CELLS.  
 AD-621 454
- \*HORDON, M. J.  
 \* \* \*  
 A FUNDAMENTAL STUDY OF ROLLING  
 CONTACT FATIGUE  
 AD-285 085
- \*HOWELL, JAMES E  
 \* \* \*  
 MISSILE-BORNE TRACKING ANTENNA.  
 AD-426 922
- \*HUGHES, D.  
 \* \* \*  
 PRODUCTION ENGINEERING MEASURE TO  
 INCREASE THE RELIABILITY OF THE  
 TRANSISTOR TYPE 22N2034.  
 AD-606 191
- \*HUMRICK, R. J.  
 \* \* \*  
 INVESTIGATION OF THIN FILM CADMIUM  
 SULFIDE SOLAR CELLS.  
 AD-608 425
- \*INFIELD, J. H.  
 \* \* \*  
 MACHINING HIGH PURITY ALUMINA.  
 AD-614 467
- \*JACKSON, RAYMOND  
 \* \* \*  
 TECHNOLOGY FOR PNP PLANAR SILICON  
 TRANSISTORS: SWITCHING AND  
 AMPLIFYING,  
 AD-408 190
- \*JACOBUS, H.  
 \* \* \*  
 DETERMINATION OF MECHANICAL  
 PROPERTIES AND SURFACE CONDITION OF  
 CHEM-MILLED CB-5ZR COLUMBIUM ALLOY  
 SAMPLES,  
 AD-431 617
- \*JAMIESON, J. L.  
 \* \* \*  
 CHEMICAL COMPOUNDS FOR METAL  
 SHAPING  
 AD-271 536
- \* \* \*  
 CHEMICAL COMPOUNDS FOR METAL  
 SHAPING  
 AD-282 920
- \* \* \*  
 CHEMICAL COMPOUNDS FOR METAL  
 SHAPING  
 AD-298 752
- \*JENNINGS, V. J.  
 \* \* \*  
 500 C SILICON CARBIDE RECTIFIER  
 PROGRAM.

- AD-420 275  
 •JENNY, A. L.  
 . . .  
 SOLID ELECTROLYTE TANTALUM FOIL  
 CAPACITOR.  
 AD-420 225
- JOHNSON, S.O.  
 . . .  
 SILICON PLANAR EPITAXIAL TRANSISTOR  
 TYPE 2N2173  
 AD-286 886
- JONES, R. L.  
 . . .  
 A NEW APPROACH TO BEND TESTING FOR  
 THE DETERMINATION OF HYDROGEN  
 EMBRITTLEMENT SUSCEPTIBILITY OF  
 SHEET MATERIALS.  
 AD-681 765
- JONES, R. W.  
 . . .  
 PRODUCTION ENGINEERING MEASURE ON  
 SILICON ALLOY TRANSISTORS.  
 AD-422 940
- KAHLES, JOHN F.  
 . . .  
 MACHINING DATA FOR BERYLLIUM METAL,  
 AD-485 297
- KEARKUFF, THOMAS  
 . . .  
 SURFACE INTEGRITY OF MACHINED  
 STRUCTURAL COMPONENTS.  
 AD-870 146
- KEARKUFF, THOMAS  
 . . .  
 PRODUCTION ENGINEERING MEASURE FOR  
 SILICON OVERLAY TRANSISTORS.  
 AD-619 295
- KEARKUFF, THOMAS  
 . . .  
 PRODUCTION ENGINEERING MEASURE FOR  
 SILICON OVERLAY TRANSISTORS.  
 AD-628 230
- KETCHAM, S. J.  
 . . .  
 CHEMICAL MILLING OF METALS AND  
 ALLOYS; ITS EFFECT ON STRESS
- CORROSION SUSCEPTIBILITY AND  
 HYDROGEN EMBRITTLEMENT,  
 AD-643 980
- KETCHAM, SARA J.  
 . . .  
 CHEMICAL MILLING OF ALLOY STEELS,  
 AD-631 952
- KIRSHENBAUM, N.W.  
 . . .  
 A FUNDAMENTAL STUDY OF ROLLING  
 CONTACT FATIGUE  
 AD-276 887
- KJELBY, A.S.  
 . . .  
 BERYLLIUM COMPOSITE STRUCTURES.  
 VOLUME II. MATERIALS AND PROCESSES  
 AD-278 526
- KLOHN, K  
 . . .  
 DESIGN CONSIDERATIONS FOR MICROWAVE  
 GERMANIUM TUNNEL DIODES  
 AD-294 788
- KOCSIS, J.  
 . . .  
 ENGINEERING SERVICES ON  
 TRANSISTORS.  
 AD-422 492
- KOSTER, WILLIAM P.  
 . . .  
 SURFACE INTEGRITY OF MACHINED  
 STRUCTURAL COMPONENTS.  
 AD-870 146
- KRANTZ, J.E.  
 . . .  
 PRODUCTION ENGINEERING MEASURE  
 RELIABILITY IMPROVEMENT JET ETCH  
 TRANSISTOR  
 AD-295 057
- KRAUSS, J.J.  
 . . .  
 THE DESIGN AND EVALUATION OF  
 PERFORATED ION EMITTERS.  
 AD-418 226

- KROKO, L. J.  
 •••  
 500 C SILICON CARBIDE RECTIFIER  
 PROGRAM.  
 AD-420 375
- KRUSE, PAUL W.  
 •••  
 THIN FILM IMAGE CONVERTER.  
 AD-457 855
- KRUSOS, J.N.  
 •••  
 BERYLLIUM COMPOSITE STRUCTURES.  
 VOLUME II. MATERIALS AND PROCESSES  
 AD-278 526
- KUHNS, J.C.  
 •••  
 PRODUCTION ENGINEERING MEASURE TO  
 IMPROVE PRODUCTION TECHNIQUES AND  
 INCREASE THE RELIABILITY OF THE  
 2N1358A TRANSISTOR  
 AD-286 872
- LANGLOIS, A.P.  
 •••  
 TITANIUM DEVELOPMENT PROGRAM.  
 VOLUME IV.  
 AD-264 685
- LAROCQUE, ARMOND P.  
 •••  
 TECHNOLOGY FOR PNP PLANAR SILICON  
 TRANSISTORS: SWITCHING AND  
 AMPLIFYING,  
 AD-408 190
- LATHROP, J.W.  
 •••  
 SILICON SEMICONDUCTOR NETWORKS  
 MANUFACTURING METHODS  
 AD-291 600
- LEE, LINDA  
 •••  
 PRINCIPLES OF METALLOGRAPHIC  
 ETCHING.  
 AD-616 786
- LINDENEAU, G.D.
- EFFECT OF SURFACE FINISHES ON  
 FATIGUE LIFE  
 AD-402 164
- LOCKMART, F.J.  
 •••  
 CHEMICAL COMPOUNDS FOR METAL  
 SHAPING  
 AD-271 536
- LOVE, T. S.  
 •••  
 DEVELOPMENT OF CHEMICAL MILLED  
 WAFFLE GRID BERYLLIUM STRUCTURAL  
 PANEL,  
 AD-423 308
- LYNCH, C.T.  
 •••  
 INVESTIGATION OF SINGLE-CRYSTAL AND  
 POLYCRYSTALLINE TITANIUM DIBORIDE:  
 METALLOGRAPHIC PROCEDURES AND  
 FINDINGS  
 AD-271 965
- MALAKELIS, ELIAS  
 •••  
 CHEMICAL MILLING OF NARROW CLOSE  
 TOLERANCE SLOTS IN ALUMINUM AND  
 STAINLESS STEEL.  
 AD-423 102
- MARSHALL, P. A., JR.  
 •••  
 MACHINING HIGH PURITY ALUMINA.  
 AD-614 467
- HARTERSTECK, K. E.  
 •••  
 ENGINEERING SERVICES ON  
 TRANSISTORS.  
 AD-422 492

- MARTIN, E. . . .  
 PRODUCTION ENGINEERING MEASURE TO  
 INCREASE THE RELIABILITY OF THE  
 TRANSISTOR TYPE 22N2034.  
 AD-606 191
- HAY, J. . . .  
 MATERIAL BERYLLIUM WAFFLE PANEL.  
 CHEMICAL MILLED. SHEAR TEST OF,  
 AD-438 138
- MCCALL, J. L. . . .  
 A REVIEW OF METALLOGRAPHIC  
 PREPARATION PROCEDURES FOR  
 BERYLLIUM AND BERYLLIUM ALLOYS,  
 AD-674 066
- MCCAW, R. . . .  
 MICROMINIATURE LAYERED PRINTED  
 WIRING  
 AD-291 876
- MICROMINIATURE LAYERED PRINTED  
 WIRING  
 AD-400 732
- HESSNER, G. . . .  
 MICROMINIATURE LAYERED PRINTED  
 WIRING  
 AD-291 876
- MICROMINIATURE LAYERED PRINTED  
 WIRING  
 AD-400 732
- MURPHY, J.F. . . .  
 TITANIUM DEVELOPMENT PROGRAM.  
 VOLUME IV.  
 AD-264 685
- MYTYCH, C. . . .  
 LOW-COST MICROCIRCUITS FOR  
 MICROASSEMBLIES.  
 AD-433 891
- NEWMAN, H. L. . . .  
 PACKAGING MINIATURIZATION. CHARGE  
 NUMBERS 31-8027-0201-01, 31-8027-  
 0901 AND RES 2 AND 4,  
 AD-433 115
- NORR, HARRINER K. . . .  
 POLISHES AND ETCHES FOR TIN  
 TELLURIDE, LEAD SULFIDE, LEAD  
 SELENIDE, AND LEAD TELLURIDE,  
 AD-423 367
- POLISHES AND ETCHES FOR TIN  
 TELLURIDE, LEAD SULFIDE, LEAD  
 SELENIDE, AND LEAD TELLURIDE:  
 SUPPLEMENT.  
 AD-634 392
- NOYES, CARLTON F. . . .  
 THE MINISTICK PROCESS FOR PACKAGING  
 INTEGRATED CIRCUIT FLAT PACKS.  
 AD-468 378
- OLOFSON, C. T. . . .  
 MACHINING AND GRINDING OF TITANIUM  
 AND ITS ALLOYS.  
 AD-620 508
- MACHINING AND GRINDING OF NICKEL-  
 AND COBALT-BASE ALLOYS,  
 AD-634 075
- MACHINING AND GRINDING OF ULTRAHIGH-  
 STRENGTH STEELS AND STAINLESS STEEL  
 ALLOYS,  
 AD-629 654
- OSTROSKI, J. . . .  
 500 C SILICON CARBIDE RECTIFIER  
 PROGRAM.  
 AD-420 275
- PALUSZEK, M. . . .  
 MICROMINIATURE LAYERED PRINTED  
 WIRING

PAR-R18

- AD-291 876  
MICROMINIATURE LAYERED PRINTED  
WIRING  
AD-400 732
- PARIKH, N.H.  
FIBER-REINFORCED METALS AND ALLOYS  
AD-287 594
- FIBER-REINFORCED METALS AND ALLOYS  
AD-293 259
- PARTRIDGE, E.G.  
CHEMICAL COMPOUNDS FOR METAL  
SHAPING  
AD-295 752
- PETRICK, E.N.  
THE DESIGN AND EVALUATION OF  
PERFORATED ION EMITTERS.  
AD-418 226
- PETRITZ, R.L.  
RESEARCH AND DEVELOPMENT OF HIGH  
TEMPERATURE SEMICONDUCTOR DEVICES  
AD-298 707
- PLUMMER, C. E.  
REDUCING HAND STRAIGHTENING BY CHEM-  
MILLING 7075 AND 7178 ALUMINUM  
ALLOY IN THE 'W' (OR NATURALLY  
AGED) CONDITION.  
AD-677 066
- POE, A.H.  
BOEING-WICHITA MATERIALS AND  
RESEARCH DEVELOPMENT PROGRAMS, 1957-  
1961  
AD-271 167
- POPILOV, L. YA.  
ELECTRIC AND CHEMICO-MECHANICAL  
METHODS OF WORKING METALS (CHAPTER
- VII)  
AD-265 701
- POSSEMATO, L.R.  
PRODUCTION ENGINEERING MEASURE ON  
2N1708 SILICON PLANAR EPITAXIAL  
TRANSISTOR.  
AD-404 537
- PRODUCTION ENGINEERING MEASURE ON  
2N1708 SILICON PLANAR EPITAXIAL  
TRANSISTOR.  
AD-414 917
- PRATT, W.H.  
MATERIALS - HONEYCOMB CORE RIBBON  
RELATIONSHIP BETWEEN FLOW  
CHARACTERISTICS OF BRAZING ALLOY  
AND OXIDE FILM FORMATIONS OF -  
DETERMINATION OF  
AD-272 227
- PRIBBLE, FRED C.  
THIN FILM IMAGE CONVERTER.  
AD-453 855
- PRICE, C. W.  
A REVIEW OF METALLOGRAPHIC  
PREPARATION PROCEDURES FOR  
BERYLLIUM AND BERYLLIUM ALLOYS,  
AD-674 066
- RAU, R. R.  
PRODUCTION ENGINEERING MEASURE TO  
IMPROVE PRODUCTION TECHNIQUES AND  
INCREASE THE RELIABILITY OF THE  
2N220A TRANSISTOR.  
AD-614 823
- RIBLE, VINCENT E.  
TECHNOLOGY FOR PNP PLANAR SILICON  
TRANSISTORS: SWITCHING AND  
AMPLIFYING,  
AD-408 190

- ROGEL, ALEX  
TECHNOLOGY FOR PNP PLANAR SILICON  
TRANSISTORS: SWITCHING AND  
AMPLIFYING,  
AD-408 190
- ROGERS, C. W.  
DEVELOPMENT OF CHEMICAL MILLED  
WAFFLE GRID BERYLLIUM STRUCTURAL  
PANEL,  
AD-423 388
- ROSE, C-H  
CHEMICAL MILLING  
AD-252 129
- ROSER, W  
DEVELOPMENT OF IMPROVED METHODS,  
PROCESSES, AND TECHNIQUES FOR  
PRODUCING STEEL EXTRUSIONS  
AD-262 184
- ROY, RUSTUH  
INFLUENCE OF DISPLACIVE-SHEARING  
STRESSES ON THE KINETICS OF  
RECONSTRUCTIVE TRANSFORMATIONS  
EFFECTED BY PRESSURE IN THE RANGE 0-  
100,000 BARS  
AD-256 351
- RUDAN, PETER S.  
PRINCIPLES OF METALLOGRAPHIC  
ETCHING.  
AD-616 786
- RYBAK, P. T.  
CHEMICAL MILLING,  
AD-618 628
- SANDERS, J  
PEM FOR TRANSISTOR MANUFACTURING  
PROCESS IMPROVEMENT  
AD-286 907
- SAVICH, V. V.  
CHEMICAL MILLING,  
AD-618 628
- SCHAEFER, J. C.  
INVESTIGATION OF THIN FILM CADMIUM  
SULFIDE SOLAR CELLS.  
AD-605 425
- SCHULZE, RICHARD G.  
THIN FILM IMAGE CONVERTER.  
AD-453 055
- SKIGLEY, H.E  
BOEING-WICHITA MATERIALS AND  
RESEARCH DEVELOPMENT PROGRAMS, 1957-  
1961  
AD-271 147
- SHIHANOV, E.  
STRIPPING PT201 THERMOSETTING RESIN  
COATINGS FROM 721 ANNEALED  
STAINLESS STEEL SURFACES,  
(PROPELLANT UTILIZATION MANOMETER  
HOUSINGS),  
AD-677 494
- SHIDER, ROBERT E.  
MACHINING DATA FOR BERYLLIUM METAL,  
AD-485 297
- SOLTIS, PAUL  
STUDY OF SIZE EFFECT IN FINE  
BERYLLIUM WIRE PHASE II,  
AD-438 478
- STAEBLER, CHRISTIAN J., JR  
ADVANCED CHEMICAL MILLING  
PROCESSES.  
AD-727 620
- TARASOVA, V. A.

TAR-#15

CHEMICAL MILLING (DEEP CONTOUR  
ETCHING),  
AD-680 561

•TARPINIAN, ARAM

THE METALLOGRAPHY OF PYROLITIC  
GRAPHITE,  
AD-617 647

•THOMAS, R.W

STRUCTURAL TESTS OF A CHEMICALLY  
MILLED LADISH D-6AC STEEL SECOND-  
STAGE MINUTEMAN AFT CLOSURE  
AD-261 959

•THORNBURG, D. R.

500 C SILICON CARBIDE RECTIFIER  
PROGRAM,  
AD-420 375

•TINT, G. S.

RESEARCH IN THE GENERAL FIELD OF  
SUBSTRUCTURE AND DISLOCATION  
NETWORKS IN METALLIC CRYSTALS.  
AD-610 424

•VAHLDIK, F.W

INVESTIGATION OF SINGLE-CRYSTAL AND  
POLYCRYSTALLINE TITANIUM DIBORIDE:  
METALLOGRAPHIC PROCEDURES AND  
FINDINGS  
AD-271 965

•VRELAND, T. JR

DISLOCATION MOBILITY IN ZINC SINGLE  
CRYSTALS  
AD-297 445

•WANDINGER, L

DESIGN CONSIDERATIONS FOR MICROWAVE  
GERMANIUM TUNNEL DIODES  
AD-294 788

•WARREN, A.

•••  
PRODUCTION ENGINEERING MEASURE ON  
2N1708 SILICON PLANAR EPITOXIAL  
TRANSISTOR.  
AD-414 913

•WEEKS, ROBERT F.

•••  
CHEMICAL MILLING OF NARROW CLOSE  
TOLERANCE SLOTS IN ALUMINUM AND  
STAINLESS STEEL.  
AD-425 102

•WHITING, H. A.

•••  
REDUCING HAND STRAIGHTENING BY CHEM-  
MILLING 7075 AND 7172 ALUMINUM  
ALLOY IN THE 'R' (OR NATURALLY  
AGED) CONDITION.  
AD-677 066

•WILLIAMS, JOHN R.

•••  
PRODUCTION ENGINEERING MEASURE TO  
IMPROVE PRODUCTION TECHNIQUES AND  
TO INSURE THE RELIABILITY OF THE  
C600 SERIES FIELD EFFECT  
TRANSISTORS.  
AD-426 756

•••  
PRODUCTION ENGINEERING MEASURE TO  
IMPROVE PRODUCTION TECHNIQUES AND  
TO INSURE THE RELIABILITY OF THE  
C600 SERIES FIELD EFFECT  
TRANSISTORS.  
AD-606 477

•••  
PRODUCTION ENGINEERING MEASURE TO  
IMPROVE PRODUCTION TECHNIQUES AND  
TO INSURE THE RELIABILITY OF THE  
C600 SERIES FIELD EFFECT  
TRANSISTORS.  
AD-673 068

•WINSLOW, E.K

•••  
EFFECT OF SURFACE FINISHES ON  
FATIGUE LIFE  
AD-402 164

•WISE, W.E

• • •  
EFFECT OF SURFACE FINISHES ON  
FATIGUE LIFE  
AD-402 164

•WOOD, R.A.

• • •  
A REVIEW OF RECENT DEVELOPMENTS IN  
TITANIUM AND TITANIUM ALLOY  
TECHNOLOGY  
AD-269 209

•WOOLF, JAMES E.

• • •  
ELECTROCHEMICAL DEBURRING OF  
MOLYBDENUM, ALUMINUM AND STAINLESS  
STEEL.  
AD-431 602

•WURST, E.C.

• • •  
RESEARCH AND DEVELOPMENT OF HIGH  
TEMPERATURE SEMICONDUCTOR DEVICES  
AD-298 707

•YATSKO, ROBERT S.

• • •  
TECHNOLOGY FOR PNP PLANAR SILICON  
TRANSISTORS; SWITCHING AND  
AMPLIFYING,  
AD-408 190

UNCLASSIFIED

CONTRACT INDEX

•AF19 604 4556  
DOUGLAS AIRCRAFT CO INC LONG BEACH  
CALIF  
1111  
(AFCR1-1111)  
AD-282 920

•AF30 602 9017  
WESTINGHOUSE DEFENSE AND SPACE  
CENTER BALTIMORE MD  
WDSC-385A4  
(RADC-TDR64 252)  
F AD-607 426

•AF33 600 32841  
GENERAL DYNAMICS/FORT WORTH TEX  
FGT 2100  
AD-286 074

•AF33 600 34876  
GENERAL DYNAMICS/CONVAIR SAN DIEGO  
CALIF  
(ASD-TR617 576)  
F AD-264 685

•AF33 600 36350  
GENERAL DYNAMICS/FORT WORTH TEX  
FGT 2510  
AD-272 227

•AF33 600 36610  
AEROCJET-GENERAL CORP SACRAMENTO  
CALIF  
AD-261 959

•AF33 600 36713  
NORTHROP AIRCRAFT INC HAWTHORNE  
CALIF  
NOR 61 199  
AD-262 184

•AF33 600 42210  
TEXAS INSTRUMENTS INC DALLAS  
IR7 865 V6  
(ASD-IR7 865 V6)  
AD-291 600

•AF33 600 43027  
DOUGLAS AIRCRAFT CO INC LONG BEACH  
CALIF  
(ASD-TR7 648 V1)

AD-271 536  
TR7 648 V2  
(ASD-TR7 648 V2)  
AD-295 782

•AF33 615 1121  
BATTELLE MEMORIAL INST COLUMBUS  
OHIO DEFENSE METALS INFORMATION  
CENTER  
DHIC-212  
AD-612 261

•AF33 615 1248  
HARSHAW CHEMICAL CO CLEVELAND OHIO  
AD-605 425

•AF 33(615)-3262  
AIR FORCE MACHINABILITY DATA CENTER  
CINCINNATI OHIO  
AFMDC-66-3  
AD-485 297

•AF33 616 6220  
MARTIN CO BALTIMORE MD  
(WADD-TR-51-58-PT-2)  
AD-282 017

•AF33 616 7080  
AERONCA HFG CORP MIDDLETOWN OHIO  
TR61 706 V2  
(ASD-TR61 706 V2)  
F AD-278 926

•AF33 616 8141  
SOEING CO WICHITA KANS WICHITA  
DIV  
AD-271 167

•AF33 657 7027  
WESTINGHOUSE ELECTRIC CORP DAYTON  
OHIO  
(ASD-IR7 727)  
AD-420 375

•AF33 657 7623  
LEAR SIEGLER INC SANTA MONICA  
CALIF  
AD-412 841

•AF33 657 7916  
HARSHAW CHEMICAL CO CLEVELAND OHIO

C-1  
UNCLASSIFIED

AF3-DA3

(ARL-65-111)  
 F AD-621 454

•AF33 657 8638  
 KELSEY-HAYES CO. ROMULUS MICH  
 (ASD-TDR63-750)  
 F AD-418 226

•AF33 657 8923  
 GENERAL DYNAMICS/POHONA CALIF  
 8926 142  
 AD-402 164

•AF33 657 11214  
 GENERAL DYNAMICS/FORT WORTH TEX  
 ERR. FW135  
 AD-423 388

•AF33 657 11215  
 MCCOYNE AIRCRAFT CORP ST LOUIS  
 MO  
 A239  
 F AD-425 102  
 A476  
 F AD-431 603  
 A473  
 AD-431 617

•AF49 638 821  
 FRANKLIN INST PHILADELPHIA PA LABS  
 FOR RESEARCH AND DEVELOPMENT  
 F-A2400  
 (AFOSR-2574)  
 F AD-610 434

•DA-01-021-AHC-11651(2)  
 BATTELLE MEMORIAL INST COLUMBUS  
 OHIO  
 (NASA-TM-X-53446)  
 AD-634 075  
 (NASA-TM-X-53433)  
 AD-639 654  
 BATTELLE MEMORIAL INST COLUMBUS  
 OHIO  
 (NASA-TM-X-53312)

AD-620 508

•DA36 039AMCO1475E  
 MOTOROLA INC PHOENIX ARIZ  
 AD-603 660

•DA36 039AMCO1480E  
 NATIONAL SEMICONDUCTOR CORP DANBURY  
 CONN  
 F AD-614 823

•DA36 039AMCO1482E  
 SILICON TRANSISTOR CORP GARDEN  
 CITY N Y  
 AD-606 151

•DA36 039AMCO1487E  
 CRYSTALONICS INC CAMBRIDGE MASS  
 AD-426 256  
 AD-606 477  
 AD-613 668

•DA36 039AMCO2227  
 BELL TELEPHONE LABS INC WHIPPANY N  
 J  
 12  
 AD-422 492

•DA36 039AMCO2189E  
 TRW SEMICONDUCTORS INC LAWDALE  
 CALIF RESEARCH AND DEVELOPMENT  
 DEPT  
 59-RD-F  
 F AD-622 879

•DA36 039AMCO2257E  
 XEROX CORP ROCHESTER N Y  
 AD-433 801

•DA36 039AMCO2622E  
 TEXAS INSTRUMENTS INC DALLAS  
 03-64-73  
 AD-612 617

•DA36 039AMCO2634E  
 LINDEN LABS INC STATE COLLEGE PA  
 AD-614 467

•DA36 039AMCO6156E  
 MOTOROLA INC PHOENIX ARIZ  
 SEMICONDUCTOR PRODUCTS DIV

C-2

UNCLASSIFIED

AD-619 295  
AD-625 317  
AD-628 230  
AD-635 814

•DA36 039SC86720  
PHILCO CORP LANSDALE PA  
R 272 1  
AD-286 907

•DA36 039SC86725  
GENERAL MOTORS CORP KOKOMO IND  
DELCO RADIO DIV.  
AD-286 872

•DA36 039SC86727  
GENERAL ELECTRIC CO SCHENECTADY N  
Y  
AD-286 886  
AD-404 185

•DA36 039SC86729  
RADIO CORP OF AMERICA SOHERVILLE N  
J  
AD-404 837  
AD-414 913

•DA36 039SC86736  
SYLVANIA ELECTRIC PRODUCTS INC  
40BURN MASS  
AD-419 585

•DA36 039SC86744  
RAYTHEON CO LEWISTON MAINE  
AD-422 940

•DA-36-039-5C-90763  
PHOTOCIRCUITS CORP GLEN COVE N Y  
AD-291 876  
AD-400 732

•DA36 039SC90850  
WESTINGHOUSE ELECTRIC CORP  
YOUNGWOOD PA  
AD-405 861

•DA44 009AMC168T  
HONEYWELL RESEARCH CENTER HOPKINS  
MINN  
AD-453 855

•DA91 591EUC1722  
METAL HYDRIDES INC BEVERLY MASS  
AD-267 806

•F22615-68-C-1003  
METCUT RESEARCH ASSOCIATES INC  
CINCINNATI OHIO  
970-11700  
(AFHL-TR-70-11)  
F AD-870 146

•F22615-68-C-1225  
BATTELLE MEMORIAL INST COLUMBUS  
OHIO DEFENSE METALS INFORMATION  
CENTER  
DMIC-MEMO-237  
AD-674 066

•F22615-69-C-1840  
GRUMMAN AEROSPACE CORP BETHPAGE N  
Y  
(AFHL-TR-71-44)  
F AD-727 620

•NO8SR85424  
TEXAS INSTRUMENTS INC DALLAS  
AD-298 707

•NO8SR89334  
GENERAL ELECTRIC CO SYRACUSE N Y  
AD-418 684

•NO8SR89380  
GENERAL ELECTRIC CO IRMO S C  
AD-423 225

•NO8SR91298  
SIGNETICS CORP SUNNYVALE CALIF  
AD-450 544

•NONR22027  
INNSBRUCK UNIV (AUSTRIA)  
F AD-293 445

•NONR59117  
RENSELAER POLYTECHNIC INST TROY N  
Y  
TR-2  
AD-616 786

•NOW-61-0653

NOW-NOW

UNCLASSIFIED

MCDONNELL AIRCRAFT CORP ST LOUIS  
MO  
AD-272 526

•NOW-61-0656  
ALLOY ENGINEERING AND CASTING CO  
CHAMPAIGN ILL  
AD-275 807  
AD-285 085

•NOW62 06042  
JOHNS HOPKINS UNIV SILVER SPRING  
MD APPLIED PHYSICS LAB  
TG-675  
AD-468 378

•NOW-62-0680  
FIT RESEARCH INST CHICAGO ILL  
8241 3  
AD-287 594  
8241 4  
AD-293 257

C-4  
UNCLASSIFIED

## UNCLASSIFIED

## REPORT NUMBER INDEX

07-64-73 AD-612 617	ARL-69-111 AD-621 454
12 AD-422 492	ASD-IR7 727 AD-420 373
59-RD-F AD-622 679	ASD-IR7 865 V6 AD-291 600
729 AD-268 033	ASD-TDR63 750 AD-418 226
970-11700 AD-870 146	ASD-TR7 648 V1 AD-271 536
1111 AD-282 920	ASD-TR7 648 V2 AD-295 752
8926 142 AD-462 164	ASD-TR61 730 AD-271 965
A229 AD-425 103	ASD-TR61 706 V2 AD-278 526
A473 AD-431 617	ASD-TR617 376 AD-264 685
A478 AD-431 602	B241 3 AD-287 594
AFCRL-1111 AD-282 920	B241 4 AD-293 259
AFMDC-66-3 AD-485 297	D6-23737 AD-683 061
AFML-TR-70-11 AD-870 146	DMIC-213 AD-613 261
AFML-TR-71-44 AD-777 620	DMIC-HEMO-237 AD-674 066
AFOSR-2574 AD-610 424	ERR FW135 AD-423 388
AFOSR-TR-71-2489 AD-730 200	F-A2400 AD-610 424
AMRA-TR-64-41 AD-613 643	FGT 2100 AD-286 074

R-1  
UNCLASSIFIED

FTT 2510 AD-272 227	NASA-TM-X-53433 AD-639 654
FTD-HT-23-1225-67 AD-610 561	NASA-TM-X-53446 AD-634 075
FTD-TT-65-865 AD-618 623	NOLTR-63-156 AD-423 367
FTD-TT-65-1525 AD-621 855	NOLTR-66-32 AD-634 392
FTDM 3068 AD-438 138	NOR 61 199 AD-262 184
GDA-AN61AMR4062 AD-677 494	R 232 1 AD-286 907
GDA-MRG-235 AD-681 765	R5832 3 80 61 N1 AD-433 115
GDC-PR919 AD-677 066	RADC-TDR64 232 AD-607 426
GDC-PR-920 AD-678 154	RS-TR-63-20 AD-426 932
IR7 865 VA AD-291 600	TG-675 AD-468 378
I:144 AD-269 209	TR-2 AD-616 786
MCIC-72-03 AD-739 271	TR7 648 V3 AD-295 752
NAEC-AHL-1909 AD-438 478	TR61 706 V2 AD-278 526
NAEC-AHL-2418 AD-631 952	TR-1052 AD-281 843
NAEC-AHL-2441 AD-633 992	TR2718 AD-294 788
NAMC-AHL-1236 AD-648 980	TR-2339 AD-408 190
NASA-TM-X-53312 AD-620 508	TT-65-62694 AD-618 628

FST 2510 AD-272 227	NASA-TM-X-53433 AD-639 654
FTD-HT-23-1225-67 AD-610 561	NASA-TM-X-53446 AD-634 075
FTD-TT-65-865 AD-618 623	NOLTR-63-156 AD-423 367
FTD-TT-65-1523 AD-621 855	NOLTR-66-32 AD-634 392
FTDM 3068 AD-438 138	NOR 61 199 AD-262 184
GDA-AN61AMR4062 AD-677 494	R 232 1 AD-286 907
GDA-MRG-235 AD-681 765	R5832 3 80 61 41 AD-433 115
GDC-PR919 AD-677 066	RADC-TDR64 232 AD-607 426
GDC-PR-920 AD-678 154	RS-TR-63-20 AD-426 932
IR7 865 V6 AD-291 600	TG-675 AD-468 378
M144 AD-269 209	TR-2 AD-616 786
HCIC-72-03 AD-739 271	TR7 648 V3 AD-295 752
NAEC-AHL-1909 AD-438 478	TR61 706 V2 AD-278 526
NAEC-AHL-2418 AD-631 952	TR-1052 AD-281 843
NAEC-AHL-2441 AD-633 992	TR2318 AD-294 788
NAMC-AHL-1236 AD-648 980	TR-2339 AD-408 190
NASA-TM-X-53312 AD-620 508	TT-65-62694 AD-618 628

R-2  
UNCLASSIFIED