

UNCLASSIFIED

AD NUMBER

AD815579

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors;  
Administrative/Operational Use; 06 JUN 1967.  
Other requests shall be referred to Air Force Technical Applications Center, Washington, DC.

AUTHORITY

USAF ltr 28 Feb 1972

THIS PAGE IS UNCLASSIFIED

AD815579

# THE DETECTION THRESHOLD AT THE MONTANA L A S A

6 JUNE 1967

Prepared For

AIR FORCE TECHNICAL APPLICATIONS CENTER  
Washington, D. C.

By

E.F. CHIBURIS  
R.A. HARTENBERGER  
TELEDYNE, INC.

Under

Project VELA UNIFORM

Sponsored By

ADVANCED RESEARCH PROJECTS AGENCY  
Nuclear Test Detection Office  
ARPA Order No. 624

THE DETECTION THRESHOLD AT THE MONTANA LASA

6 June 1967

SEISMIC DATA LABORATORY REPORT NO. 185

AFTAC Project No.:	VELA T/6702
Project Title:	Seismic Data Laboratory
ARPA Order No.:	624
ARPA Program Code No.:	5810
Name of Contractor:	TELEDYNE, INC.
Contract No.:	F 33657-67-C-1313
Date Of Contract:	3 March 1967
Amount of Contract:	\$ 1,735,617
Contract Expiration Date:	2 March 1968
Project Manager	William C. Dean (703) 836-7644

P. O. Box 334, Alexandria, Virginia

AVAILABILITY

This document is subject to special export controls and each transmittal to foreign governments or foreign national may be made only with prior approval of Chief, AFTAC.

This research was supported by the Advanced Research Projects Agency, Nuclear Test Detection Office, under Project VELA-UNIFORM and accomplished under the technical direction of the Air Force Technical Applications Center under Contract F 33657-67-C-1313.

Neither the Advanced Research Projects Agency nor the Air Force Technical Applications Center will be responsible for information contained herein which may have been supplied by other organizations or contractors, and this document is subject to later revision as may be necessary.

TABLE OF CONTENTS

	Page No.
ABSTRACT	
1. INTRODUCTION	1
2. PROCEDURE	2
2.1 Signal and Noise	2
2.2 Minimum Detectable Signal	2
2.3 Magnitude Determinations	3
3. RESULTS	3
4. CONCLUSIONS	4
REFERENCES	

LIST OF ILLUSTRATIONS

	<u>Follows</u> <u>Page No.</u>
<u>Figure</u>	
1. Probability that noise will be less than a given amplitude on a LASA beamformed output trace.	3
2. Probability that noise on a LASA beamformed trace will be less than a given amplitude.	4
3. Magnitude comparisons.	4
4. LASA beamformed seismograms.	4
<u>Table</u>	<u>Follows</u> <u>Page No.</u>
1. Event Magnitudes.	2

### ABSTRACT

Short-period P arrivals on LASA beamformed traces for 56 teleseismic events were used to compute event magnitudes and corresponding threshold magnitudes.

The average event magnitude reported by the USC&GS differed by less than 0.1 from the average magnitude computed at LASA. Threshold magnitudes varied from 3.2 to 4.0; the average, 3.6, is biased downward about 0.1, because of the magnitude factors (B) for deep foci, and an additional 0.1 - 0.2 because only night-recorded events were available for analysis.

## 1. INTRODUCTION

Early in 1966 several studies were undertaken by the Seismic Data Laboratory in support of the Vela Seismological Center's evaluation of the LARGE APERTURE SEISMIC ARRAY (LASA) in Montana. Since June 1966, reports have been written which relate directly to the detection and identification capability of the LASA system. Included in these reports are three by Chiburis (1966) which describe travel-time anomalies for various epicentral regions, three by Chiburis and Hartenberger (1966) concerning signal-to-noise ratio improvement by beamforming LASA seismograms, and three by Flinn, Hartenberger, and McCowan (1966) which review maximum-likelihood filtering techniques. The analysis of travel-time anomalies has relied upon visual inspection of 16 mm film, whereas the remaining studies have utilized digital seismograms. In all studies to date, we have been concerned only with the P phase and associated band-limited noise.

The present study is an attempt to determine a detection threshold at the LASA for events originating at teleseismic distances. We note that any such magnitude value is highly generalized since it depends not only on the epicentral distance and azimuth, depth of the hypo-center, and the source mechanism, but also on the precision of the beamforming process and the type of pre-filtering used. Moreover, it is undoubtedly a function of the recording period. By this we mean that the nighttime noise level is lower than that recorded during the daylight hours, and our detection threshold estimates will be lower than that obtained from a similar set of events recorded during the day. Our basic procedure will be to use LASA beamformed outputs to compute event magnitudes and corresponding threshold values.

Our data are 56 beamformed traces, i.e., phased sums of the subarray phased sums (hereafter referred to as PPA traces) for the teleseismic events shown in Table 1. These events were recorded during the night at the Montana LASA, because of the operational procedure used at that site. Forty-one of these events were discussed in SDL Report Nos. 164 and 173. Events numbered 15 and 53 through 56 are included to test the validity of the theoretical threshold values.

For details regarding the various stages of data processing required to produce beamformed traces, i.e., demultiplexing, detrending, demagnifying, time-shifting, and summing of array and subarray data, the reader is referred to SDL Report No. 164.

## 2. PROCEDURE

### 2.1 Signal and Noise

For the purpose of computing event magnitudes, the "signal" is considered to be half the maximum peak-to-trough deflection, in  $m\mu$ , occurring in the first few seconds of the P signature as it appears on the prefiltered PPA trace. "Noise" is defined as the rms nighttime level achieved on the prefiltered PPA traces for a data sample of 40 seconds before the onset of each signal.

### 2.2 Minimum Detectable Signal

In order to define the minimum detectable signal (MDS) on the PPA trace, we must first describe the rms background noise field within which the signal will appear. We know from previous analyses that the average measured rms noise level on the PPA traces is  $\bar{\sigma} = \pm 0.2 m\mu$ . If the noise is Gaussian with mean zero and variance  $\bar{\sigma}^2$ , 95% of the noise amplitudes on the beamformed

EVENT	<sup>m</sup> C & GS	<sup>m</sup> <sub>1</sub>	<sup>m</sup> <sub>0</sub>	EVENT	<sup>m</sup> C & GS	<sup>m</sup> <sub>1</sub>	<sup>m</sup> <sub>0</sub>
1.	4.1	4.3	3.4	29.	3.9	4.1	3.3
2.	4.3	4.4	3.5	30.	5.0	5.0	3.6
3.	4.3	4.3	3.4	31.	4.9	4.8	3.2
4.	5.7	5.7	3.4	32.	5.2	5.6	3.5
5.	5.2	5.0	3.8	33.	5.1	5.2	3.6
6.	5.1	5.4	3.6	34.	4.1	4.2	3.2
7.	5.1	4.9	3.7	35.	4.4	4.6	3.6
8.	4.7	4.6	3.7	36.	5.6	5.3	3.9
9.	4.7	5.1	3.6	37.	4.8	5.0	3.6
10.	4.9	4.6	3.5	38.	6.0	5.5	3.7
11.	5.0	4.8	3.6	39.	4.6	4.9	3.8
12.	5.1	5.0	3.7	40.	6.3	6.1	3.9
13.	5.2	5.6	3.8	41.	4.8	5.3	3.7
14.	4.5	4.8	3.8	42.	5.8	5.8	3.8
15.	*3.9	3.9	3.7	43.	6.3	6.3	3.9
16.	3.9	4.1	3.3	44.	*5.8	6.2	3.8
17.	4.9	5.0	3.2	45.	4.9	4.9	3.9
18.	4.8	4.7	3.2	46.	5.5	5.6	3.8
19.	4.9	4.7	3.4	47.	5.7	5.5	3.8
20.	5.3	5.4	3.3	48.	4.8	4.6	3.8
21.	4.3	4.6	3.4	49.	5.0	5.1	3.7
22.	5.0	5.5	3.5	50.	5.2	5.6	3.9
23.	4.5	4.3	3.5	51.	4.8	4.8	3.3
24.	4.9	4.7	3.5	52.	*3.9	4.3	3.9
25.	4.3	4.5	3.7	53.	*4.8	5.3	4.0
26.	4.6	3.9	3.4	54.	*3.7	3.9	3.3
27.	3.8	4.3	3.3	55.	*3.3	3.4	3.4
28.	4.6	4.9	3.7	56.	*4.0	-	-
AVERAGES					4.91	4.96	3.6

\*NON C & GS MAGNITUDE (Not included in average)

Table 1. Event Magnitudes

traces would be expected to lie in the interval  $0 \pm 2\bar{\sigma} = 0 \pm 0.4 \text{ m}\mu$ . This means that about one noise cycle in twenty should exceed  $\pm 0.4 \text{ m}\mu$ , and that signals which are greater than or equal to  $0.4 \text{ m}\mu$ , would be larger than 95% of the noise amplitudes. Moreover, the amplitude interval which includes 99% of the noise would be  $0 \pm 3\bar{\sigma} = 0 \pm 0.6 \text{ m}\mu$  and signals  $\geq 0.6 \text{ m}\mu$  would be larger than the background noise level 99% of the time. If we assume an MDS amplitude on the PPA trace equal to  $\pm 0.6 \text{ m}\mu$ , we must input an average signal amplitude of  $\pm 0.8 \text{ m}\mu$ , because of signal losses accompanying the beamforming process.

### 2.3 Magnitude Determinations

LASA magnitude ( $m_1$ ) for each event was computed in the following manner:

$$m_1 = \log A_{\text{PPA}}/T_{\text{PPA}} + \beta$$

where  $A_{\text{PPA}}$  = signal amplitude from the PPA trace,

$T_{\text{PPA}}$  = signal period from the PPA trace,

$\beta$  = magnitude factor for distance and depth.

The threshold magnitude ( $m_0$ ) for each event was determined using the following relationship:

$$m_0 = m_1 - \log X$$

in which

$$X = A_{\text{PPA}}/\text{MDS} = A_{\text{PPA}}/0.8$$

### 3. RESULTS

Table 2 of SDL Report No. 164 lists the rms noise levels achieved on 41 LASA beamformed traces filtered 0.4 - 3.0 cps. These values form the basis for Figure 1 in this report which shows the probability that seismic noise will be less than a given amplitude on a beamformed trace. As shown in Figure 1, the probability that the noise level will be less than  $0.2 \text{ m}\mu$  is 0.5;




Figure 1. Probability that noise will be less than a given amplitude on a LASA beamformed output trace

this is the value reported by Romney (1966) which was based on the analysis of 19 teleseismic events recorded at the Montana LASA. Figure 2 illustrates the log normal distribution of the same 41 noise values.

Table 1 summarizes the results of this analysis and shows C&GS magnitude, LASA Magnitude, LASA threshold magnitude, and averages for the 56 events analyzed to date. These data illustrate two important points. First, the average C&GS magnitude differs from the average LASA magnitude by less than 0.1, even though LASA computations were based on data taken from beamformed output traces. Figure 3 further illustrates this point. Second, threshold magnitudes vary from 3.2 to 4.0 and average 3.6: this magnitude, 3.6, represents our estimate of the overall detection capability of the Montana LASA if the array is beamed precisely at the source, and if the distance distribution of events correctly samples the teleseismic zone. It will be lower than the threshold computed for bombs or shallow quakes, since the magnitude corrections which were applied for deep events bias the threshold downward about 0.1. It will furthermore be lower than a magnitude based on daytime recordings. Beamformed seismograms for five relatively small teleseismic events are shown in Figure 4. First arrivals are plainly visible on four of the five traces; in the case of the magnitude 4.0 event, however, the beamforming and filtering processes failed to produce a recognizable P signature. The output trace second from the top of Figure 4 is particularly interesting because the LASA magnitude and the threshold magnitude are the same, 3.4.

#### 4. CONCLUSIONS

The following conclusions are based on a study of beamformed outputs (filtered 0.4 - 3.0 cps) for 56 teleseismic events recorded




Figure 2. Probability that noise on a LASA beamformed trace will be less than a given amplitude




Figure 3. Magnitude comparisons








Figure 4. LASA beamford seismograms

during the night at the Montana LASA in the period November 1965 to June 1966:

1. LASA magnitudes based on data taken from the beamformed traces differ from those computed by the USC&GS by less than 0.1.
2. The Montana LASA should be able to detect a mixture of shallow and deep events of average magnitude 3.6 as a result of the beamforming process. For bombs and shallow quakes, the threshold would be 0.1 higher because of the correction factor for deep foci. For daytime recordings we estimate that it would be an additional 0.1 - 0.2 higher because of higher noise levels. Obviously, this magnitude, 3.6, is highly generalized since it is a function of several parameters which include epicentral distance and azimuth, source mechanism, beamforming precision, and type of bandpass filter used.

## REFERENCES

1. Romney, C. F., (1966), The Large Aperture Seismic Array: Its Capabilities and Worldwide System Implications, AFTAC Tech Memo No. 218, 25 August 1966.
2. Chiburis, E. F., (1966), Relative Travel-Time Anomalies at LASA and The Location of Epicenters Using "Shift", SDL Report No. 147.
3. Chiburis, E. F., (1966), LASA Travel-Time Anomalies For Various Epicentral Regions, SDL Report No. 159.
4. Chiburis, E. F. and Ahner, R. O., (1966), LASA Travel-Time Data at the SDL, SDL Report No. 172.
5. Flinn, E. A., Hartenberger, R. A., and McCowan, D. W., (1966), Two Examples of Maximum-Likelihood Filtering of LASA Seismograms, SDL Report No. 148.
6. Flinn, E. A., Hartenberger, R. A., and McCowan, D. W., (1966), Maximum-Likelihood Filtering of LASA Noise Seismograms, SDL Report No. 149.
7. Flinn, E. A., Hartenberger, R. A., and McCowan, D. W., (1966), The Crosswise Sum Method for Maximum-Likelihood Filtering of LASA Seismograms, SDL Report No. 150.
8. Chiburis, E. F. and Hartenberger, R. A., (1966), LASA Signal and Noise Amplitudes for Three Teleseismic Events, SDL Report No. 151.
9. Chiburis, E. F., and Hartenberger, R. A., (1966), Signal-To-Noise Ratio Improvement by Time-Shifting and Summing LASA Seismograms, SDL Report No. 164.
10. Chiburis, E. F., and Hartenberger, R. A., (1966), Signal-To-Noise Ratio Improvement by Beamforming LASA Seismograms, SDL Report No. 173.

Unclassified

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author)  TELEDYNE, INC. ALEXANDRIA, VIRGINIA	2a. REPORT SECURITY CLASSIFICATION <b>Unclassified</b>
	2b. GROUP -----

3. REPORT TITLE  
  
THE DETECTION THRESHOLD AT THE MONTANA LASA

4. DESCRIPTIVE NOTES (Type of report and inclusive dates)  
Scientific

5. AUTHOR(S) (Last name, first name, initial)  
  
Chiburis, Edward F. and Hartenberger, Royal A.

6. REPORT DATE June 6, 1967	7a. TOTAL NO. OF PAGES 13	7b. NO. OF REFS 10
--------------------------------	------------------------------	-----------------------

8a. CONTRACT OR GRANT NO. F 33657-67-C-1313  a. PROJECT NO. VELA T/6702  c. ARPA Order No. 624  d. ARPA Program Code No. 5810	8b. ORIGINATOR'S REPORT NUMBER(S) 185
	8c. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) ---

10. AVAILABILITY/LIMITATION NOTICES  
This document is subject to special export controls and each transmittal to foreign governments or foreign national may be made only with prior approval of Chief, AFTAC.

11. SUPPLEMENTARY NOTES ---	12. SPONSORING MILITARY ACTIVITY ADVANCED RESEARCH PROJECTS AGENCY NUCLEAR TEST DETECTION OFFICE WASHINGTON, D. C.
--------------------------------	---

13. ABSTRACT

Short-period P arrivals on LASA beamformed traces for 56 teleseismic events were used to compute event magnitudes and corresponding threshold magnitudes.

The average event magnitude reported by the USC&GS differed by less than 0.1 from the average magnitude computed at LASA. Threshold magnitudes varied from 3.2 to 4.0; the average, 3.6, is biased downward about 0.1, because of the magnitude factors (B) for deep foci, and an additional 0.1-0.2 depending upon night-day noise fluctuations at the LASA.

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
LASA  threshold  minimum detectable signal  magnitude						

**INSTRUCTIONS**

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2e. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Title in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7c. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through \_\_\_\_\_."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through \_\_\_\_\_."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through \_\_\_\_\_."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.