UNCLASSIFIED

AD NUMBER

AD825614

NEW LIMITATION CHANGE

TO

Approved for public release, distribution unlimited

FROM

Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; JAN 1968. Other requests shall be referred to Atmospheric Sciences Lab., White Sands Missile Range, NM.

AUTHORITY

USAEC ltr, 13 Sep 1971

THIS PAGE IS UNCLASSIFIED

DR-286
January 1968
AD

AD825614

METEOROLOGICAL DATA REPORT

NIKE-HYDAC STV SR 069
(11 December 1967)

BY

GORDON L. DUNAWAY

STATEMENT #2 UNCLASSIFIED

This document is subject to special [illegible] controls and each transmittal to foreign governments [illegible] nationals may be made only with prior approval of [illegible]

ATMOSPHERIC SCIENCES LABORATORY
WHITE SANDS MISSILE RANGE, NEW MEXICO

ECOM
UNITED STATES ARMY ELECTRONICS COMMAND

DDC
RECEIVED
JAN 25 1968
D

37

Best
Available
Copy

DISPOSITION INSTRUCTIONS

Destroy this report when it is no longer needed. Do not return it to the originator.

DISCLAIMER

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The citation of trade names and names of manufacturers in this report is not to be construed as official Government indorsement or approval of commercial products or services referenced herein.

METEOROLOGICAL DATA REPORT

NIKE-HYDAC STV SR 069
(11 December 1967)

By

Gordon L. Dunaway

DR-286 January 1968

DA Task IV650212A127-02

ATMOSPHERIC SCIENCES LABORATORY
WHITE SANDS MISSILE RANGE, NEW MEXICO

[redacted]

ABSTRACT

Meteorological data gathered for the launching of Nike-Bydac STV (SR 069) are presented for the Space and Missile Systems Organization and for ballistic studies. The data appear, along with calculated ballistic data, in tabular form.

CONTENTS

	PAGE
ABSTRACT	iii
INTRODUCTION	1
DISCUSSION	2
REFERENCES	3
TABLES	
I. Theoretical Rocket Performance Values	4
II. Ballistic Factors	5
III. Anemometer Wind Speed and Direction	6
IV. Pilot-Balloon-Measured Wind Data	7
V. Rawinsonde-Measured Wind Data	9
VI. Significant Level Data (Release Time: 1055 MST)	10
VII. Upper Air Data (Release Time: 1055 MST)	11
VIII. Mandatory Levels (Release Time: 1055 MST)	18
IX. Significant Level Data (Release Time: 1540 MST)	19
X. Upper Air Data (Release Time: 1540 MST)	21
XI. Mandatory Levels (Release Time: 1540 MST)	29
XII. Impact Prediction Data	30

INTRODUCTION

Nike-Hydac STV (SR 069) was launched from Launch Complex 33, L-361, White Sands Missile Range (WSMR), New Mexico, at 1456 hours MST, 11 December 1967.

Meteorological data used in conjunction with theoretical calculations to predict rocket impact were collected by the Meteorological Support Division, Atmospheric Sciences Laboratory (ASL), WSMR, New Mexico. The Ballistic Meteorologists for this firing were Gordon L. Dunaway and George Fugate.

DISCUSSION

Wind data for the first 216 feet above the surface were obtained from a system composed of 5 Aerovanes mounted on a 200-foot tower and cabled to component wind indicators.

From 216 to 4,000 feet above the surface, wind data were obtained from an automatic pilot-balloon wind measuring system (1,2) utilizing a T-9 radar tracker. Pilot-balloons released at the launch site were equipped with light-weight corner reflectors to improve the reflected signal and permit radar tracking. Acquisition of the target was accomplished by means of a boresight television camera. An analog computer converted azimuth and elevation angles and the slant range data into horizontal components of position with respect to the radar as reference. Changes of these components per unit time were converted into East-West and North-South wind components values which were then displaced on two plotters with a specially designed wind velocity ballistic chart. It is possible to read directly from the chart both the mean wind component values and the mean ballistic wind components in the various ballistic layers.

Temperature, pressure, and humidity data, along with upper wind data from 4,000 to 69,331 feet above the surface, were obtained from standard rawinsonde observations.

Mean wind component values in each ballistic zone were determined from vertical cross sections by the equal-area method.

Theoretical rocket performance values and ballistic factors as a function of altitude were provided by Atmospheric Sciences Laboratory, White Sands Missile Range, New Mexico, and are the basis for data appearing in Table XII.

REFERENCES

1. Engineering Division, "Pilot-Balloon Radar Tracker at White Sands Missile Range", Atmospheric Sciences Laboratory, U. S. Army Electronics Command, White Sands Missile Range, New Mexico.

2. Kubinski, S. F., April 1967: "A Comparative Evaluation of the Automatic Tracking Pilot-Balloon Wind Measuring System". Meteorological Support Division, Atmospheric Sciences Laboratory, U. S. Army Electronics Command, White Sands Missile Range, New Mexico, ECOM-5121.

PAYLOAD		215	Pounds
CORIOLIS DISPLACEMENT	WEST	4.9	Miles
SECOND-STAGE IGNITION	TIME	20.0	Seconds
	ALTITUDE	35,767	Feet MSL
PEAK	TIME	236	Seconds
	ALTITUDE	715,900	Feet MSL
UNIT WIND EFFECT	HEAD	2.1575	Miles/MPH
	CROSS	2.2444	Miles/MPH
	TAIL	2.1672	Miles/MPH
TOWER TILT EFFECT		14.53	Miles/Degree

TABLE I. THEORETICAL ROCKET PERFORMANCE VALUES
NIKE-HYDAC STV SR 069

LAYERS IN FEET ABOVE GROUND	BALLISTIC FACTORS
11- 60	.1256
60- 108	.0842
108- 148	.0533
148- 184	.0408
184- 216	.0262
216- 300	.0620
300- 400	.0580
400- 600	.0720
600- 800	.0580
800-1000	.0390

LAYERS IN FEET ABOVE GROUND	BALLISTIC FACTORS
1000- 1400	.0630
1400- 2000	.0662
2000- 2500	.0350
22500- 3000	.0277
3000- 3500	.0142
3500- 4000	.0052
4000- 4160	-.0026
4160- 9000	-.0141
9000-15000	-.0168
15000-21000	-.0156

LAYERS IN FEET ABOVE GROUND	BALLISTIC FACTORS
21000-26000	-.0132
26000-31767	-.0162
31767-36000	.1310
36000-41000	.0566
41000-46000	.0260
46000-51000	.0154
51000-56000	.0101
56000-61000	.0063
61000-66000	.0040
66000-69331	.0009

TABLE II. BALLISTIC FACTORS
NIKE-HYDAC STV SR 069

AERO-VANE NO. *	MEAN WIND COMPONENTS IN MILES PER HOUR									
	1 1230 MST		2 1300 MST		3 1330 MST		4 1345 MST		5 1400 MST	
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
1	C	C	C	C	C	C	C	C	C	C
2	C	C	C	C	C	C	C	C	C	C
3	C	C	C	C	C	C	C	C	C	C
4	C	C	C	C	C	C	C	C	C	C
5	C	C	C	C	C	C	C	C	C	C

AERO-VANE NO. *	MEAN WIND COMPONENTS IN MILES PER HOUR									
	6 1415 MST		7 1433 MST		8 1443 MST		9 1456 MST			
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
1	3.0S	0.0	4.0S	0.0	3.0S	0.0	8.0S	0.0		
2	3.0	0.0	4.0	0.0	3.0	0.0	7.0	0.0		
3	3.0	0.0	4.0	0.0	3.0	0.0	7.0	0.0		
4	3.0	0.0	4.0	0.0	3.0	0.0	7.0	0.0		
5	3.0	0.0	4.0	0.0	3.0	0.0	6.0	0.0		

TABLE III. ANEMOMETER WIND SPEED AND DIRECTION
NIKE-HYDAC STV SR 069

C = CALM

* Heights corresponding to Aerovane Numbers: 1 = 35 Feet 2 = 88 Feet 3 = 128 Feet 4 = 168 Feet 5 = 200 Feet

LAYERS IN FEET ABOVE GROUND	MEAN WIND COMPONENTS IN MILES PER HOUR									
	1 1230 MST		2 1300 MST		3 1330 MST		4 1345 MST		5 1400 MST	
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
216- 300	1.5S	0.0	2.0N	1.0E	0.0	0.0	1.0S	1.0W	3.0S	1.0E
300- 400	1.0N	0.0	2.0	0.0	2.0S	0.0	1.0	0.0	4.0	0.0
400- 600	0.5	1.5W	2.0	1.0W	2.0	1.0W	1.0	1.0W	3.0	0.0
600- 800	0.5	2.0	1.0S	2.0	1.0	2.0	3.0	1.0	4.0	2.0W
800-1000	1.5S	1.5E	2.0	3.0	0.0	3.0	1.0	5.0	4.0	1.0
1000-1400	0.5	2.5W	2.0	4.0	1.5N	3.0	0.0	7.0	0.0	4.0
1400-2000	3.0N	10.0	3.0N	12.0	3.0	9.0	1.0N	10.0	2.0N	8.0
2000-2500	8.5	12.0	6.0	14.0	7.0	12.0	6.0	13.0	6.0	15.0
2500-3000	13.5	10.0	10.0	12.0	12.0	14.0	6.0	12.0	10.0	17.0
3000-3500	17.0	8.5	18.0	8.0	18.0	15.0	6.0	15.0	20.0	18.0
3500-4000	23.0	11.0	28.0	16.0	18.0	17.0	10.0	15.0	31.0	18.0

TABLE IV. PILOT-BALLOON-MEASURED WIND DATA
T-9 RADAR TRACKER METHOD
NIKE-HYDAC STV SR 069

LAYERS IN FEET ABOVE GROUND	MEAN WIND COMPONENTS IN MILES PER HOUR									
	6 1415 MST		7 1433 MST		8 1443 MST		9 1456 MST			
	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W
216- 300	5.0S	0.0	7.0S	0.0	0.0	1.0W	7.0S	0.0		
300- 400	6.0	2.0W	6.0	1.0E	3.0S	2.0	7.5	0.0		
400- 600	7.0	2.0	5.0	0.0	9.0	1.0	8.0	1.0W		
600- 800	5.0	3.0	5.0	1.0W	5.0	3.0	8.0	2.0		
800-1000	4.0	4.0	5.0	0.0	6.0	4.0	7.0	2.0		
1000-1400	0.0	6.0	3.0	1.0W	6.0	6.0	8.0	5.0		
1400-2000	3.0N	14.0	2.0N	7.0	5.0	6.0	0.0	12.0		
2000-2500	8.0	14.0	5.0	14.0	2.0N	15.0	4.0N	14.0		
2500-3000	16.0	17.0	16.0	18.0	12.0	17.0	13.0	19.0		
3000-3500	25.0	23.0	27.0	24.0	24.0	24.0	25.0	25.0		
3500-4000	32.0	22.0	32.0	20.0	31.0	22.0	28.0	24.0		

TABLE IV. PILOT-BALLOON-MEASURED WIND DATA (CONT)
T-9 RADAR TRACKER METHOD
NIKE-HYDAC STV SR 069

LAYERS IN FEET ABOVE GROUND	MEAN WIND COMPONENTS IN KNOTS					
	1 1055 MST		2* 1300 MST		3 1540 MST	
	N-S	E-W	N-S	E-W	N-S	E-W
4000- 4160	22.5N	4.0W	18.0N	11.5W	22.5N	13.0W
4160- 9000	30.0	11.0	28.0	10.5	27.5	16.0
9000-15000	40.5	7.0	38.5	14.0	32.0	18.5
15000-21000	36.0	13.0	35.0	12.5	25.5	21.0
21000-26000	38.5	14.0	30.5	25.5	28.5	16.5
26000-31767	37.0	21.5	34.5	29.0	34.0	19.5
31767-36000	44.0	16.0	44.0	25.5	23.5	40.5
36000-41000	34.5	20.0	22.5	27.0	22.0	38.0
41000-46000	40.5	23.5	34.5	29.0	33.0	27.5
46000-51000	28.0	10.0	18.5	15.5	22.0	18.5
51000-56000	17.0	6.0	9.5	11.5	13.0	11.0
56000-61000	14.0	5.0	14.0	2.5	8.0	4.5
61000-66000	10.5	4.0	14.0	5.0E	7.0	4.0
66000-69331	11.5	4.0	11.5	4.0	10.5	6.0

TABLE V. RAWINSONDE-MEASURED WIND DATA
NIKE-HYDAC STV SR 069

*Rawin, Telecompute data not available.

STATION ALTITUDE 3989.0 FEET MSL
11 DEC. 67 1055 HRS MST
ASCENSION NO. 991

SIGNIFICANT LEVEL DATA
0055003901
WHITE SANDS SITE
TABLE VI

MSYK SITE COORDINATES
E 488.500 FEET
N 185.045 FEET

PRESSURE MILLIBARS	GEOMETRIC ALTITUDE MSL FEET	TEMPERATURE AIR DEGREES	TEMPERATURE DEWPOINT CENTIGRADE	REL. HUM. PERCENT
874.1	3989.0	7.0	-11.2	26.0
859.0	4917.2	3.4	-14.3	24.0
839.0	5146.4	5.2	-12.3	27.0
775.0	7283.9	2.9	-15.2	25.0
751.0	8103.0	4.9	-16.9	19.0
714.0	9457.2	5.6	-17.6	17.0
625.0	13004.2	2.5	-21.0	17.0
452.0	21275.3	-17.7	-34.4	16.0
342.0	27911.2	-14.6	-50.3	19.0
317.0	29646.1	-37.3	0.	-0. **
280.0	32431.5	-43.5	0.	-0. **
249.0	35373.0	-44.9	0.	-0. **
229.0	38856.3	-45.0	0.	-0. **
209.0	38856.6	-47.5	0.	-0. **
133.0	48278.7	-66.7	0.	-0. **
122.0	49994.4	-68.0	0.	-0. **
105.0	52970.8	-67.6	0.	-0. **
101.0	53748.7	-64.1	0.	-0. **
85.0	57209.2	-66.9	0.	-0. **
77.0	59188.8	-65.0	0.	-0. **
73.0	60276.7	-59.4	0.	-0. **
61.0	63933.3	-65.7	0.	-0. **
45.0	70168.0	-54.8	0.	-0. **
26.0	81553.9	-60.1	0.	-0. **
14.5	93802.7	-53.6	0.	-0. **
10.0	101698.9	-54.5	0.	-0. **
8.8	104441.2	-49.8	0.	-0. **

** RELATIVE HUMIDITY NOT SUPPLIED. ZERO VALUE ASSUMED FOR COMPUTATIONS.

STATION ALTITUDE 3989.0 FEET MSL
11 DEC. 67 1055 HRS MST
ASCENSION NO. 991

UPPER AIR DATA
0055003901
WHITE SANDS SITE
TABLE VII

WSTM SITE COORDINATES
E 488,580 FEET
N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES	TEMPERATURE DEWPOINT CENTIGRADE	REL.HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES(TN)	WIND DATA SPEED KNOTS	INDEX OF REFRACTION
3989.0	876.1	7.0	-11.2	26.0	1088.4	652.1	0.	0.	1.000255
4000.0	875.7	6.9	-11.3	26.0	1088.2	652.0	359.8	0.1	1.000255
4500.0	859.6	3.5	-14.2	26.0	1081.5	648.0	349.9	2.8	1.000251
5000.0	843.6	4.8	-12.8	26.8	1056.5	649.5	340.1	5.5	1.000247
5500.0	828.0	4.8	-12.8	26.7	1036.7	649.5	330.3	8.2	1.000242
6000.0	812.6	4.3	-13.5	26.2	1019.5	648.9	320.4	11.0	1.000238
6500.0	797.5	3.7	-14.2	25.7	1002.8	648.2	322.6	14.1	1.000233
7000.0	782.7	3.2	-14.9	25.2	985.9	647.6	334.3	17.5	1.000229
7500.0	768.2	3.5	-15.6	23.3	966.7	647.9	338.7	20.5	1.000224
8000.0	753.9	4.7	-16.6	19.7	944.7	649.3	340.5	23.3	1.000219
8500.0	740.0	5.1	-17.1	18.4	925.8	649.8	340.0	24.5	1.000214
9000.0	726.3	5.4	-17.3	17.7	907.8	650.1	339.1	25.5	1.000210
9500.0	712.9	5.6	-17.6	17.0	890.4	650.3	337.7	25.9	1.000206
10000.0	699.6	5.0	-18.1	17.0	875.7	649.6	336.8	26.4	1.000202
10500.0	686.6	4.4	-18.6	17.0	861.2	648.9	340.6	28.4	1.000199
11000.0	673.8	3.8	-19.1	17.0	847.0	648.3	344.7	30.8	1.000195
11500.0	661.3	3.2	-19.5	17.0	833.0	647.6	349.8	34.2	1.000192
12000.0	649.0	2.7	-20.0	17.0	819.3	646.9	353.9	37.3	1.000189
12500.0	636.9	2.1	-20.5	17.0	805.7	646.2	356.6	39.8	1.000185
13000.0	625.1	1.5	-21.0	17.0	792.4	645.5	357.9	41.1	1.000182
13500.0	613.0	0.3	-21.9	17.1	780.4	644.2	358.1	41.4	1.000179
14000.0	601.1	-0.8	-22.8	17.1	768.5	642.8	356.5	40.9	1.000176
14500.0	589.4	-2.0	-23.7	17.2	756.9	641.4	354.0	39.8	1.000173
15000.0	578.0	-3.1	-24.7	17.2	745.4	640.0	351.4	38.8	1.000170
15500.0	566.8	-4.3	-25.6	17.3	734.1	638.6	348.9	37.8	1.000168
16000.0	555.8	-5.5	-26.5	17.4	723.0	637.2	345.9	37.5	1.000165
16500.0	545.0	-6.6	-27.4	17.4	712.1	635.8	342.8	37.5	1.000162
17000.0	534.4	-7.8	-28.4	17.5	701.4	634.4	339.4	37.8	1.000159
17500.0	524.1	-8.9	-29.3	17.5	690.8	633.0	336.0	37.4	1.000157
18000.0	513.9	-10.1	-30.2	17.6	680.4	631.6	332.7	36.5	1.000154

STATION ALTITUDE 3989.0 FEET MSL
11 DEC. 67 10:15 HRS MST
ASCENSION NO. 991

UPPER AIR DATA
0095003901
WHITE SANDS SITE
TABLE VII (Cont.)

MSTN SITE COORDINATES
E 488.580 FEET
N 185.045 FEET

GEOMETRIC ALTITUDE MSL (FEET)	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	TEMPERATURE DEWPOINT DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES (TN)	WIND DATA SPEED KNOTS	INDEX OF REFRACTION
18500.0	503.9	-11.3	-31.2	17.7	670.2	630.3	321.5	54.8	1.000152
19000.0	496.1	-12.4	-32.1	17.7	660.5	626.8	321.8	54.3	1.000149
19500.0	488.6	-13.5	-33.0	17.8	650.2	623.4	322.4	54.0	1.000147
20000.0	475.2	-14.7	-34.0	17.8	640.9	620.0	323.3	53.7	1.000145
20500.0	465.9	-15.9	-34.9	17.8	630.5	616.8	324.5	53.4	1.000142
21000.0	456.9	-17.1	-35.9	17.8	621.2	613.7	325.9	53.0	1.000140
21500.0	447.8	-18.3	-36.9	17.8	611.9	610.7	327.4	52.6	1.000138
22000.0	438.4	-19.5	-37.9	17.8	602.2	607.6	328.4	52.1	1.000135
22500.0	429.3	-20.6	-38.9	17.8	592.9	604.8	329.0	51.5	1.000133
23000.0	420.4	-21.8	-39.9	17.8	583.2	601.8	329.2	50.7	1.000131
23500.0	411.5	-23.0	-41.0	17.8	573.5	598.9	329.0	49.8	1.000129
24000.0	403.1	-24.8	-42.0	18.4	564.3	595.9	342.8	49.2	1.000127
24500.0	394.7	-25.9	-43.1	18.2	554.2	613.3	341.5	48.3	1.000125
25000.0	386.5	-27.2	-44.1	18.6	547.4	610.7	342.3	48.7	1.000123
25500.0	378.8	-28.5	-45.2	18.6	538.8	609.1	342.0	49.0	1.000121
26000.0	370.6	-29.7	-46.2	18.7	530.4	607.5	342.5	49.4	1.000119
26500.0	362.9	-31.0	-47.3	18.8	522.1	605.9	342.3	49.7	1.000117
27000.0	355.3	-32.3	-48.3	18.9	514.0	604.3	342.0	50.0	1.000115
27500.0	348.0	-33.6	-49.4	18.9	506.0	602.7	340.9	48.8	1.000113
28000.0	340.7	-34.7	-50.8	18.0**	497.8	601.2	339.3	46.9	1.000111
28500.0	333.3	-35.5	-54.5	12.6**	488.7	600.3	337.7	45.3	1.000109
29000.0	326.1	-36.3	-59.7	7.1**	479.7	599.3	336.2	43.8	1.000107
29500.0	319.0	-37.1	-71.0	1.6**	470.9	598.3	334.9	42.3	1.000105
30000.0	312.0	-38.1	0.	-0. **	462.5	597.0	333.5	41.2	1.000103
30500.0	305.2	-39.2	0.	-0. **	454.5	595.6	332.2	40.9	1.000101
31000.0	298.4	-40.3	0.	-0. **	446.6	594.2	331.5	40.4	1.000099
31500.0	291.9	-41.4	0.	-0. **	438.8	592.7	331.8	39.3	1.000098
32000.0	285.4	-42.5	0.	-0. **	431.2	591.3	331.4	38.6	1.000096
32500.0	279.1	-43.6	0.	-0. **	423.4	590.0	329.9	38.1	1.000094
33000.0	272.9	-44.0	0.	-0. **	414.8	589.5	328.8	38.6	1.000092

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
11 DEC. 67 1055 HRS MST
ASCENSION NO. 991

UPPER AIR DATA
005500390 1
WHITE SANDS SITE
TABLE VII (Cont).

WSTM SITE COORDINATES
E 488,580 FEET
N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES	TEMPERATURE DEWPOINT CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES(TN)	WIND DATA SPEED KNOTS	INDEX OF REFRACTION
33500.0	266.7	-44.4	0.	-0. **	406.2	589.0	328.3	40.2	1.000090
34000.0	260.8	-44.8	0.	-0. **	397.8	588.4	327.7	42.5	1.000089
34500.0	254.9	-45.2	0.	-0. **	389.6	587.9	327.2	45.5	1.000087
35000.0	249.2	-45.6	0.	-0. **	381.5	587.4	327.7	47.7	1.000085
35500.0	243.8	-45.8	0.	-0. **	373.3	587.1	328.7	49.6	1.000083
36000.0	238.1	-45.5	0.	-0. **	364.4	587.5	330.9	50.3	1.000081
36500.0	232.7	-45.2	0.	-0. **	355.8	587.9	333.3	50.9	1.000079
37000.0	227.5	-45.2	0.	-0. **	347.7	587.9	335.7	50.4	1.000077
37500.0	222.4	-45.8	0.	-0. **	340.8	587.1	338.2	49.9	1.000076
38000.0	217.3	-46.4	0.	-0. **	334.0	586.3	340.8	49.6	1.000074
38500.0	212.4	-47.1	0.	-0. **	327.4	585.5	343.5	49.4	1.000073
39000.0	207.6	-47.8	0.	-0. **	320.9	584.5	344.9	48.2	1.000071
39500.0	202.6	-48.8	0.	-0. **	314.7	583.2	346.1	47.0	1.000070
40000.0	197.8	-49.8	0.	-0. **	308.7	581.9	346.3	45.4	1.000069
40500.0	193.2	-50.8	0.	-0. **	302.7	580.6	346.2	43.8	1.000067
41000.0	188.6	-51.9	0.	-0. **	296.9	579.2	345.7	42.3	1.000066
41500.0	184.1	-52.9	0.	-0. **	291.2	577.9	344.9	40.9	1.000065
42000.0	179.7	-53.9	0.	-0. **	285.6	576.5	342.3	40.1	1.000064
42500.0	175.5	-54.9	0.	-0. **	280.2	575.2	338.4	39.7	1.000062
43000.0	171.3	-55.9	0.	-0. **	274.8	573.9	333.6	40.1	1.000061
43500.0	167.3	-57.0	0.	-0. **	269.6	572.5	328.2	41.1	1.000060
44000.0	163.3	-58.0	0.	-0. **	264.4	571.2	323.0	42.8	1.000059
44500.0	159.4	-59.0	0.	-0. **	259.4	569.8	317.9	44.9	1.000058
45000.0	155.7	-60.0	0.	-0. **	254.5	568.5	315.3	46.3	1.000057
45500.0	152.0	-61.0	0.	-0. **	249.6	567.1	314.8	47.3	1.000056
46000.0	148.4	-62.1	0.	-0. **	244.9	565.7	314.7	48.2	1.000055
46500.0	144.8	-63.1	0.	-0. **	240.2	564.4	315.5	48.6	1.000053
47000.0	141.4	-64.1	0.	-0. **	235.7	563.0	316.3	49.0	1.000052
47500.0	138.1	-65.1	0.	-0. **	231.2	561.6	317.9	48.9	1.000051
48000.0	134.8	-66.1	0.	-0. **	226.9	560.2	319.6	48.7	1.000051

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
11 DEC. 67 1055 HRS MST
ASCENSION NO. 991

UPPER AIR DATA
0035003901
WHITE SANDS SITE
TABLE VII (Cont)

MSTM SITE COORDINATES
E 488.580 FEET
N 185.045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES	TEMPERATURE DEWPOINT CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES(TN)	WIND DATA SPEED KNOTS	INDEX OF REFRACTION
48500.0	131.5	-66.9	0.	-0. **	222.2	559.2	321.5	49.2	1.000049
49000.0	128.3	-67.2	0.	-0. **	217.0	558.7	323.8	50.0	1.000048
49500.0	125.1	-67.6	0.	-0. **	212.0	558.2	325.7	50.3	1.000047
50000.0	122.0	-68.0	0.	-0. **	207.1	557.7	328.1	49.9	1.000046
50500.0	118.9	-67.9	0.	-0. **	201.9	557.8	330.4	49.4	1.000045
51000.0	116.0	-67.9	0.	-0. **	196.8	557.9	332.4	48.4	1.000044
51500.0	113.1	-67.8	0.	-0. **	191.9	558.0	334.4	47.3	1.000043
52000.0	110.3	-67.7	0.	-0. **	187.0	558.1	337.2	42.7	1.000042
52500.0	107.5	-67.7	0.	-0. **	182.3	558.2	340.4	36.2	1.000041
53000.0	104.8	-67.5	0.	-0. **	177.6	558.4	343.7	30.2	1.000040
53500.0	102.3	-65.2	0.	-0. **	171.4	561.5	347.7	26.1	1.000038
54000.0	99.7	-64.3	0.	-0. **	166.4	562.7	351.6	22.0	1.000037
54500.0	97.3	-64.7	0.	-0. **	162.6	562.2	359.4	18.1	1.000036
55000.0	94.9	-65.1	0.	-0. **	158.9	561.6	7.9	14.1	1.000035
55500.0	92.6	-65.5	0.	-0. **	155.3	561.1	10.1	12.0	1.000035
56000.0	90.3	-65.9	0.	-0. **	151.8	560.5	4.1	12.4	1.000034
56500.0	88.1	-66.3	0.	-0. **	148.3	560.0	358.3	12.8	1.000033
57000.0	85.9	-66.7	0.	-0. **	145.0	559.4	357.4	15.0	1.000032
57500.0	83.8	-66.6	0.	-0. **	141.3	559.6	356.6	17.2	1.000031
58000.0	81.7	-66.1	0.	-0. **	137.5	560.2	355.4	17.9	1.000031
58500.0	79.7	-65.7	0.	-0. **	133.8	560.9	354.1	17.7	1.000030
59000.0	77.7	-65.2	0.	-0. **	130.2	561.5	352.8	17.5	1.000029
59500.0	75.8	-63.4	0.	-0. **	126.0	563.9	351.4	17.2	1.000028
60000.0	74.0	-60.8	0.	-0. **	121.4	567.4	350.1	16.9	1.000027
60500.0	72.2	-59.8	0.	-0. **	117.9	568.8	346.7	14.7	1.000026
61000.0	70.5	-60.6	0.	-0. **	115.5	567.6	341.8	11.0	1.000026
61500.0	68.7	-61.5	0.	-0. **	113.2	566.5	337.4	7.9	1.000025
62000.0	67.1	-62.4	0.	-0. **	110.9	565.3	337.4	10.3	1.000025
62500.0	65.4	-63.2	0.	-0. **	108.6	564.2	337.4	12.7	1.000024
63000.0	63.9	-64.1	0.	-0. **	106.4	563.0	337.4	13.9	1.000024

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
11 DEC. 67 1055 HRS MST
ASCENSION NO. 991

UPPER AIR DATA
0035003901
WHITE SANDS SITE
TABLE VII (Cont)

WSTM SITE COORDINATES
E 488.580 FEET
N 185.045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES	TEMPERATURE DEWPOINT CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES(TN)	WIND DATA SPEED KNOTS	INDEX OF REFRACTION
63500.0	62.3	-65.0	0.	-0. **	104.3	561.8	337.4	14.3	1.000023
64000.0	60.8	-65.6	0.	-0. **	102.1	561.0	337.8	14.7	1.000023
64500.0	59.3	-64.9	0.	-0. **	99.3	561.9	339.7	14.8	1.000022
65000.0	57.9	-64.2	0.	-0. **	96.5	562.9	341.7	14.9	1.000021
65500.0	56.5	-63.5	0.	-0. **	93.9	563.8	350.3	14.7	1.000021
66000.0	55.1	-62.7	0.	-0. **	91.3	564.8	1.9	14.4	1.000020
66500.0	53.8	-62.0	0.	-0. **	88.8	565.8	12.5	14.4	1.000020
67000.0	52.5	-61.3	0.	-0. **	86.4	566.7	24.4	14.9	1.000019
67500.0	51.3	-60.6	0.	-0. **	84.0	567.7	36.4	15.4	1.000019
68000.0	50.0	-59.9	0.	-0. **	81.7	568.6	40.4	16.6	1.000018
68500.0	48.8	-59.2	0.	-0. **	79.5	569.6	42.1	17.9	1.000018
69000.0	47.6	-58.5	0.	-0. **	77.3	570.5	43.5	18.9	1.000017
69500.0	46.5	-57.8	0.	-0. **	75.2	571.5	62.6	17.5	1.000017
70000.0	45.4	-57.0	0.	-0. **	73.1	572.4	41.7	16.1	1.000016
70500.0	44.3	-56.9	0.	-0. **	71.4	572.6	40.6	14.5	1.000016
71000.0	43.2	-57.0	0.	-0. **	69.7	572.4	39.3	12.5	1.000016
71500.0	42.2	-57.2	0.	-0. **	68.1	572.2	38.0	10.5	1.000015
72000.0	41.2	-57.3	0.	-0. **	66.5	572.0	25.1	12.2	1.000015
72500.0	40.2	-57.5	0.	-0. **	65.0	571.8	9.8	14.6	1.000014
73000.0	39.3	-57.6	0.	-0. **	63.5	571.6	356.5	16.9	1.000014
73500.0	38.3	-57.8	0.	-0. **	62.0	571.5	355.4	18.3	1.000014
74000.0	37.4	-57.9	0.	-0. **	60.6	571.3	354.2	19.8	1.000013
74500.0	36.5	-58.1	0.	-0. **	59.2	571.1	354.3	22.3	1.000013
75000.0	35.7	-58.2	0.	-0. **	57.8	570.9	355.8	26.4	1.000013
75500.0	34.8	-58.3	0.	-0. **	56.5	570.7	357.3	30.4	1.000013
76000.0	34.0	-58.5	0.	-0. **	55.2	570.5	1.1	30.3	1.000012
76500.0	33.2	-58.6	0.	-0. **	53.9	570.3	7.0	26.1	1.000012
77000.0	32.4	-58.8	0.	-0. **	52.6	570.1	12.9	21.9	1.000012
77500.0	31.6	-58.9	0.	-0. **	51.4	569.9	15.9	19.1	1.000011
78000.0	30.9	-59.1	0.	-0. **	50.2	569.7	14.0	18.7	1.000011

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
11 DEC. 67 1055 HRS MST
ASCENSION NO. 991

UPPER AIR DATA
0055003901
WHITE SANDS SITE

TABLE VII (Cont)

WSTM SITE COORDINATES
E 488,580 FEET
N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	TEMPERATURE DEWPOINT DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES(TN)	WIND DATA SPEED KNOTS	INDEX OF REFRACTION
78500.0	30.1	-59.2	0.	-0. **	49.1	569.5	12.0	18.2	1.000011
79000.0	29.4	-59.4	0.	-0. **	47.9	569.3	10.8	17.4	1.000011
79500.0	28.7	-59.5	0.	-0. **	46.8	569.1	11.6	15.5	1.000010
80000.0	28.0	-59.6	0.	-0. **	45.8	569.0	12.4	13.7	1.000010
80500.0	27.4	-59.8	0.	-0. **	44.7	568.8	12.5	12.6	1.000010
81000.0	26.7	-59.9	0.	-0. **	43.7	568.6	7.1	16.5	1.000010
81500.0	26.1	-60.1	0.	-0. **	42.7	568.4	1.7	20.4	1.000009
82000.0	25.5	-59.9	0.	-0. **	41.6	568.7	356.3	24.4	1.000009
82500.0	24.9	-59.6	0.	-0. **	40.6	569.0	356.9	24.9	1.000009
83000.0	24.3	-59.3	0.	-0. **	39.6	569.4	357.7	25.3	1.000009
83500.0	23.7	-59.1	0.	-0. **	38.6	569.7	358.5	25.7	1.000009
84000.0	23.1	-58.8	0.	-0. **	37.6	570.1	356.4	25.5	1.000008
84500.0	22.6	-58.5	0.	-0. **	36.7	570.4	353.7	25.2	1.000008
85000.0	22.1	-58.3	0.	-0. **	35.8	570.8	351.0	24.9	1.000008
85500.0	21.5	-58.0	0.	-0. **	34.9	571.1	348.9	24.0	1.000008
86000.0	21.0	-57.7	0.	-0. **	34.0	571.5	347.1	22.9	1.000008
86500.0	20.5	-57.5	0.	-0. **	33.2	571.8	345.4	21.8	1.000007
87000.0	20.1	-57.2	0.	-0. **	32.4	572.2	343.9	20.6	1.000007
87500.0	19.6	-56.9	0.	-0. **	31.6	572.5	342.9	19.3	1.000007
88000.0	19.1	-56.7	0.	-0. **	30.8	572.9	341.8	18.0	1.000007
88500.0	18.7	-56.4	0.	-0. **	30.0	573.2	340.8	17.0	1.000007
89000.0	18.2	-56.2	0.	-0. **	29.3	573.6	340.8	18.7	1.000007
89500.0	17.8	-55.9	0.	-0. **	28.6	573.9	340.8	20.3	1.000006
90000.0	17.4	-55.6	0.	-0. **	27.8	574.3	340.8	21.9	1.000006
90500.0	17.0	-55.4	0.	-0. **	27.2	574.6	340.1	22.5	1.000006
91000.0	16.6	-55.1	0.	-0. **	26.5	575.0	339.1	22.3	1.000006
91500.0	16.2	-54.8	0.	-0. **	25.8	575.3	338.0	22.2	1.000006
92000.0	15.8	-54.6	0.	-0. **	25.2	575.7	336.7	22.1	1.000006
92500.0	15.4	-54.3	0.	-0. **	24.6	576.0	333.4	22.1	1.000005
93000.0	15.1	-54.0	0.	-0. **	24.0	576.4	330.2	22.1	1.000005

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
11 DEC. 67 1055 HRS MST
ASCENSION NO. 991

UPPER AIR DATA
0055003901
WHITE SANDS SITE
TABLE VII (Cont)

WSTM SITE COORDINATES
E 488,580 FEET
N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES	TEMPERATURE DEWPOINT CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES(TN)	WIND DATA SPEED KNOTS	INDEX OF REFRACTION
93500.0	14.7	-53.8	0.	-0. **	23.4	576.7	327.0	22.1	1.000005
94000.0	14.4	-53.6	0.	-0. **	22.8	576.9	324.1	21.9	1.000005
94500.0	14.0	-53.7	0.	-0. **	22.3	576.8	321.5	21.6	1.000005
95000.0	13.7	-53.7	0.	-0. **	21.8	576.8	318.9	21.4	1.000005
95500.0	13.4	-53.8	0.	-0. **	21.3	576.7	316.0	21.2	1.000005
96000.0	13.1	-53.9	0.	-0. **	20.8	576.6	311.4	21.6	1.000005
96500.0	12.8	-53.9	0.	-0. **	20.3	576.5	306.8	21.9	1.000005
97000.0	12.5	-54.0	0.	-0. **	19.8	576.5	302.2	22.3	1.000004
97500.0	12.2	-54.0	0.	-0. **	19.4	576.4	299.6	22.8	1.000004
98000.0	11.9	-54.1	0.	-0. **	18.9	576.3	298.1	23.5	1.000004
98500.0	11.6	-54.1	0.	-0. **	18.5	576.2	296.7	24.1	1.000004
99000.0	11.4	-54.2	0.	-0. **	18.1	576.2	295.1	24.8	1.000004
99500.0	11.1	-54.2	0.	-0. **	17.7	576.1	292.2	25.9	1.000004
100000.0	10.8	-54.3	0.	-0. **	17.2	576.0	289.4	27.1	1.000004
100500.0	10.6	-54.4	0.	-0. **	16.8	575.9	286.5	28.2	1.000004
101000.0	10.3	-54.4	0.	-0. **	16.5	575.9			1.000004
101500.0	10.1	-54.5	0.	-0. **	16.1	575.8			1.000004
102000.0	9.9	-54.0	0.	-0. **	15.7	576.4			1.000003
102500.0	9.8	-53.1	0.	-0. **	15.3	577.6			1.000003
103000.0	9.4	-52.3	0.	-0. **	14.8	578.7			1.000003
103500.0	9.2	-51.4	0.	-0. **	14.4	579.8			1.000003
104000.0	9.0	-50.6	0.	-0. **	14.1	580.9			1.000003

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
11 DEC. 67 1055 HRS MST
ASCENSION NO. 991

MANDATORY LEVELS
0055003901
WHITE SANDS SITE
TABLE VIII

WSTR SITE COORDINATES
E 4[illegible],580 FEET
N 1[illegible],045 FEET

PRESSURE MILLIBARS	GEOPOTENTIAL FEET	TEMPERATURE AIR DEGREES CENTIGRADE	TEMPERATURE DEWPOINT DEGREES CENTIGRADE	REL. HUM. PERCENT	WIND DATA DIRECTION DEGREES(TN)	WIND DATA SPEED KNOTS
850.0	4797.	4.2	-13.4	26.	344.1	4.4
800.0	6416.	3.8	-14.1	26.	320.7	13.5
750.0	8134.	4.9	-16.9	19.	340.7	23.8
700.0	9982.	5.0	-18.1	17.	336.7	26.3
650.0	11956.	2.7	-20.0	17.	353.7	37.1
600.0	14068.	-0.9	-22.9	17.	356.2	40.7
550.0	16324.	-6.1	-27.0	17.	343.8	37.5
500.0	18745.	-11.7	-31.5	18.	331.4	34.6
450.0	21361.	-18.0	-36.6	18.	343.0	39.2
400.0	24210.	-25.1	-42.4	18.	341.2	48.1
350.0	27341.	-33.2	-49.1	19.	341.2	49.3
300.0	30845.	-40.1	0.	-0.**	331.5	40.6
250.0	34869.	-45.5	0.	-0.**	327.6	47.4
200.0	39732.	-49.4	0.	-0.**	346.3	46.0
175.0	42567.	-55.0	0.	-0.**	337.2	39.6
150.0	45750.	-61.6	0.	-0.**	314.4	48.0
125.0	49393.	-67.6	0.	-0.**	325.8	50.3
100.0	53808.	-64.3	0.	-0.**	351.1	22.5
80.0	58255.	-65.7	0.	-0.**	354.3	17.7
70.0	60958.	-60.9	0.	-0.**	340.5	10.1
60.0	64064.	-65.2	0.	-0.**	338.8	14.8
50.0	67754.	-59.9	0.	-0.**	40.3	16.5
40.0	72373.	-57.5	0.	-0.**	6.0	15.2
30.0	78311.	-59.2	0.	-0.**	11.6	18.1
25.0	82051.	-59.7	0.	-0.**	356.7	24.8
20.0	86655.	-57.2	0.	-0.**	343.9	20.5
15.0	92670.	-54.0	0.	-0.**	329.7	22.1
10.0	101208.	-54.5	0.	-0.**		

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
11 DEC. 67 1540 HRS MST
ASCENSION NO. 993

SIGNIFICANT LEVEL DATA
0063003902
WHITE SANDS SITE
TABLE 2X

WSTM SITE COORDINATES
E 488,580 FEET
N 185,045 FEET

PRESSURE MILLIBARS	GEOMETRIC ALTITUDE MSL FEET	TEMPERATURE AIR DEGREES	TEMPERATURE DEWPOINT CENTIGRADE	REL.HUM. PERCENT
871.5	3989.0	13.0	-10.1	19.0
851.0	4641.7	10.3	-10.5	22.0
813.0	5883.0	7.8	-11.5	24.0
770.0	7358.3	9.8	-12.8	19.0
717.0	9286.6	5.5	-16.4	19.0
656.0	11666.1	4.0	-18.2	18.0
504.0	18497.4	-12.0	-31.6	18.0
441.0	21794.0	-21.7	-39.2	19.0
344.0	27665.5	-33.9	-49.7	19.0
273.0	32872.8	-45.0	0.	-0. **
250.0	34806.9	-45.5	0.	-0. **
243.0	35431.5	-44.8	0.	-0. **
213.0	38310.9	-48.4	0.	-0. **
171.0	42966.3	-58.5	0.	-0. **
152.0	45380.0	-63.2	0.	-0. **
131.0	48376.5	-65.0	0.	-0. **
125.0	49316.7	-65.4	0.	-0. **
115.0	50974.5	-69.2	0.	-0. **
111.0	51673.3	-68.4	0.	-0. **
104.0	52955.5	-70.4	0.	-0. **
95.0	54745.6	-66.5	0.	-0. **
82.0	57688.5	-65.9	0.	+0. **
76.0	59201.5	-68.4	0.	+0. **
72.0	60281.9	-64.[illegible]	0.	-0. **
65.0	62337.8	-66.0	0.	-0. **
60.0	63958.7	-61.5	0.	-0. **
50.0	67723.5	-57.8	0.	-0. **
47.0	69004.0	-60.7	0.	-0. **
40.0	72301.4	-63.0	0.	-0. **
36.0	74462.4	-59.5	0.	-0. **

** RELATIVE HUMIDITY NOT SUPPLIED. ZERO VALUE ASSUMED FOR COMPUTATIONS.

STATION ALTITUDE 3989.0 FEET MSL
11 DEC. 67 1540 HRS MST
ASCENSION NO. 993

SIGNIFICANT LEVEL DATA
0069003902
WHITE SANDS SITE
TABLE IX (Cont)

WSTN SITE COORDINATES
E 483,580 FEET
N 185,045 FEET

PRESSURE MILLIBARS	GEOMETRIC ALTITUDE MSL FEET	TEMPERATURE AIR DEGREES	TEMPERATURE DEWPOINT CENTIGRADE	REL. HUM. PERCENT
30.0	78211.6	-62.0	0.	-0. **
21.0	85583.2	-57.5	0.	-0. **
19.0	87688.6	-54.7	0.	-0. **
15.0	92639.4	-59.5	0.	-0. **
11.0	99124.5	-55.6	0.	-0. **
9.0	103408.7	-50.7	0.	-0. **
6.0	112159.3	-51.0	0.	-0. **
5.0	116147.8	-45.0	0.	-0. **

** RELATIVE HUMIDITY NOT SUPPLIED. ZERO VALUE ASSUMED FOR COMPUTATIONS.

STATION ALTITUDE 3989.0 FEET MSL
11 DEC. 67 1540 HRS MST
ASCENSION NO. 993

UPPER AIR DATA
0063003902
WHITE SANDS SITE
TABLE X

WSTM SITE COORDINATES
E 488.580 FEET
N 185.042 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES	TEMPERATURE DEWPOINT CENTIGRADE	REL.HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES(TN)	WIND DATA SPEED KNOTS	INDEX OF REFRACTION
3989.0	871.5	13.0	-10.1	19.0	1059.8	659.1	200.0	4.1	1.000249
4000.0	871.2	13.0	-10.1	19.1	1059.6	659.0	209.5	4.2	1.000249
4500.0	855.4	10.9	-10.4	21.1	1048.0	656.6	224.1	7.4	1.000247
5000.0	839.9	9.6	-10.8	22.6	1033.7	655.1	247.6	10.7	1.000243
5500.0	824.5	8.6	-11.2	23.4	1018.5	653.9	271.1	13.9	1.000239
6000.0	809.5	8.0	-11.6	23.6	1002.1	653.2	294.7	17.2	1.000235
6500.0	794.7	8.6	-12.0	21.9	981.5	654.0	309.1	19.9	1.000230
7000.0	780.2	9.3	-12.4	20.2	981.3	654.8	316.6	22.1	1.000225
7500.0	766.0	9.5	-13.0	19.0	943.2	655.0	323.0	23.3	1.000221
8000.0	751.9	8.4	-14.0	19.0	929.7	655.7	328.8	24.1	1.000217
8500.0	738.2	7.3	-14.9	19.0	916.3	652.3	333.6	25.0	1.000213
9000.0	724.6	6.1	-15.8	19.0	903.2	651.0	338.1	26.0	1.000210
9500.0	711.3	5.4	-16.5	18.9	889.0	650.1	338.4	28.3	1.000206
10000.0	698.1	5.1	-16.9	18.7	873.6	649.7	338.0	30.7	1.000203
10500.0	685.2	4.7	-17.3	18.5	858.4	649.4	335.9	32.8	1.000199
11000.0	672.5	4.4	-17.7	18.3	843.5	649.0	333.4	34.2	1.000195
11500.0	660.1	4.1	-18.1	18.1	828.6	648.6	330.3	34.8	1.000192
12000.0	647.6	3.2	-18.9	18.0	815.8	647.6	328.3	34.4	1.000189
12500.0	635.2	2.0	-19.9	18.0	803.6	646.2	326.9	34.2	1.000185
13000.0	623.1	0.9	-20.8	18.0	791.7	644.8	326.1	34.3	1.000182
13500.0	611.2	-0.3	-21.8	18.0	779.9	643.4	324.8	35.3	1.000179
14000.0	599.5	-1.5	-22.8	18.0	768.4	642.0	323.6	36.3	1.000176
14500.0	588.1	-2.6	-23.8	18.0	757.0	640.6	322.9	37.5	1.000173
15000.0	576.8	-3.8	-24.7	18.0	745.8	639.2	322.9	38.8	1.000170
15500.0	565.8	-5.0	-25.7	18.0	734.7	637.8	323.5	40.3	1.000168
16000.0	555.0	-6.2	-26.7	18.0	723.9	636.4	324.8	41.5	1.000165
16500.0	544.4	-7.3	-27.7	18.0	713.2	635.0	326.0	42.7	1.000162
17000.0	534.0	-8.5	-28.7	18.0	702.7	633.6	326.3	43.8	1.000160
17500.0	523.8	-9.7	-29.6	18.0	692.3	632.2	326.4	44.1	1.000157
18000.0	513.8	-10.8	-30.6	18.0	682.2	630.8	325.7	43.7	1.000155

STATION ALTITUDE 3989.0 FEET MSL
11 DEC. 67 1540 HRS MST
ASCENSION NO. 993

UPPER AIR DATA
0601003002
WHITE SANDS SITE
TABLE X. (Cont)

WSTN SITE COORDINATES
E 488,580 FEET
N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES	TEMPERATURE DEWPOINT CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES(TN)	WIND DATA SPEED KNOTS	INDEX OF REFRACTION
18500.0	503.9	-12.0	-31.6	18.0	672.1	629.3	324.5	41.4	1.000152
19000.0	493.8	-13.5	-32.7	18.2	662.4	627.5	323.1	39.0	1.000150
19500.0	483.9	-15.0	-33.9	18.3	652.9	625.8	320.8	36.0	1.000147
20000.0	474.2	-16.4	-35.1	18.5	643.4	624.0	319.3	33.5	1.000145
20500.0	464.7	-17.9	-36.2	18.6	634.2	622.2	319.0	31.6	1.000143
21000.0	455.4	-19.4	-37.4	18.8	625.1	620.4	319.8	31.3	1.000141
21500.0	446.3	-20.8	-38.6	18.9	616.1	618.6	321.3	31.2	1.000139
22000.0	437.2	-22.1	-39.6	19.0	606.7	617.0	324.3	30.8	1.000136
22500.0	428.0	-23.2	-40.5	19.0	596.5	615.7	325.9	30.6	1.000134
23000.0	419.1	-24.2	-41.4	19.0	586.4	614.4	326.6	30.4	1.000132
23500.0	410.3	-25.2	-42.3	19.0	576.6	613.1	326.1	30.3	1.000129
24000.0	401.7	-26.3	-43.1	19.0	566.9	611.8	325.0	30.8	1.000127
24500.0	393.3	-27.3	-44.0	19.0	557.4	610.5	323.6	31.4	1.000125
25000.0	385.1	-28.4	-44.9	19.0	548.0	609.2	323.2	31.8	1.000123
25500.0	377.0	-29.4	-45.8	19.0	538.8	607.9	323.2	32.2	1.000121
26000.0	369.1	-30.4	-46.7	19.0	529.8	606.6	324.1	32.4	1.000119
26500.0	361.4	-31.5	-47.6	19.0	521.0	605.3	326.0	32.0	1.000117
27000.0	353.8	-32.5	-48.5	19.0	512.3	604.0	328.8	31.1	1.000115
27500.0	346.4	-33.6	-49.4	19.0	503.7	602.7	331.9	30.6	1.000113
28000.0	338.9	-34.6	-50.8	17.8**	495.0	601.4	335.4	30.2	1.000111
28500.0	331.5	-35.7	-52.7	16.0**	486.3	600.1	338.0	30.6	1.000109
29000.0	324.2	-36.7	-54.6	14.1**	477.8	598.7	340.1	31.3	1.000107
29500.0	317.1	-37.8	-56.6	12.3**	469.4	597.3	339.5	33.7	1.000105
30000.0	310.1	-38.9	-58.7	10.5**	461.2	596.0	339.5	35.5	1.000103
30500.0	303.3	-39.9	-61.0	8.7**	453.2	594.6	340.4	36.2	1.000101
31000.0	296.7	-41.0	-63.7	6.8**	445.3	593.3	342.1	36.8	1.000099
31500.0	290.2	-42.1	-66.8	5.0**	437.5	591.9	344.6	37.4	1.000097
32000.0	283.8	-43.1	-70.7	3.2**	429.9	590.5	345.4	36.4	1.000096
32500.0	277.6	-44.2	-77.1	1.4**	422.4	589.2	345.6	35.0	1.000094
33000.0	271.4	-45.0	0.	-0. **	414.6	588.1	339.6	36.6	1.000092

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
11 DEC. 67 1540 HRS MST
ASCENSION NO. 993

UPPER AIR DATA
0063003902
WHITE SANDS SITE

TABLE X (Cont)

WSTM SITE COORDINATES
E 488,580 FEET
N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	TEMPERATURE DEWPOINT CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES (TN)	WIND DATA SPEED KNOTS	INDEX OF REFRACTION
33500.0	265.3	-45.2	0.	-0. **	405.5	587.9	332.9	38.3	1.000090
34000.0	259.4	-45.3	0.	-0. **	396.6	587.8	324.9	39.6	1.000088
34500.0	253.5	-45.4	0.	-0. **	387.9	587.6	317.9	41.4	1.000086
35000.0	247.8	-45.3	0.	-0. **	378.9	587.8	313.7	44.6	1.000084
35500.0	242.2	-44.9	0.	-0. **	369.7	588.3	310.0	46.5	1.000082
36000.0	236.8	-45.5	0.	-0. **	362.4	587.5	306.9	46.4	1.000081
36500.0	231.4	-46.1	0.	-0. **	355.2	586.7	305.1	46.9	1.000079
37000.0	226.2	-46.8	0.	-0. **	348.1	585.9	304.9	47.9	1.000078
37500.0	221.1	-47.4	0.	-0. **	341.1	585.1	304.3	48.5	1.000076
38000.0	216.1	-48.0	0.	-0. **	334.4	584.2	303.5	48.6	1.000074
38500.0	211.1	-48.8	0.	-0. **	327.9	583.2	303.3	48.5	1.000073
39000.0	206.2	-49.9	0.	-0. **	321.8	581.8	303.4	48.4	1.000072
39500.0	201.4	-51.0	0.	-0. **	315.8	580.4	303.1	48.2	1.000070
40000.0	196.7	-52.1	0.	-0. **	310.0	579.0	302.2	47.9	1.000069
40500.0	192.1	-53.1	0.	-0. **	304.2	577.5	301.2	47.3	1.000068
41000.0	187.6	-54.2	0.	-0. **	298.6	576.1	299.9	46.2	1.000067
41500.0	183.2	-55.3	0.	-0. **	293.1	574.7	299.3	45.5	1.000065
42000.0	179.0	-56.4	0.	-0. **	287.7	573.2	299.7	45.2	1.000064
42500.0	174.8	-57.5	0.	-0. **	282.4	571.8	299.5	44.4	1.000063
43000.0	170.7	-58.6	0.	-0. **	277.2	570.4	298.6	42.9	1.000062
43500.0	166.6	-59.5	0.	-0. **	271.7	569.1	299.4	42.0	1.000061
44000.0	162.8	-60.5	0.	-0. **	266.4	567.8	301.4	41.8	1.000059
44500.0	158.7	-61.5	0.	-0. **	261.2	566.5	303.2	41.6	1.000058
45000.0	154.8	-62.5	0.	-0. **	256.1	565.2	304.8	41.7	1.000057
45500.0	151.1	-63.3	0.	-0. **	250.9	564.1	307.9	42.9	1.000056
46000.0	147.4	-63.7	0.	-0. **	245.8	563.3	311.2	44.3	1.000055
46500.0	143.8	-64.1	0.	-0. **	239.6	562.0	313.6	44.5	1.000053
47000.0	140.3	-64.5	0.	-0. **	234.2	562.5	316.0	44.8	1.000052
47500.0	136.8	-64.9	0.	-0. **	228.9	561.9	318.9	43.5	1.000051
48000.0	133.5	-65.3	0.	-0. **	223.7	561.4	322.0	42.1	1.000050

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
11 DEC. 67 1540 HRS MST
ASCENSION NO. 993

UPPER AIR DATA
0063003902
WHITE SANDS SITE

MSTR SITE COORDINATES
E 408,580 FEET
N 185,045 FEET

TABLE X. (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	TEMPERATURE DEWPOINT DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES(TN)	WIND DATA SPEED KNOTS	INDEX OF REFRACTION
48500.0	130.2	-65.6	0.	-0. **	218.5	561.0	325.2	39.8	1.000049
49000.0	127.0	-65.5	0.	-0. **	213.0	561.1	328.5	36.9	1.000047
49500.0	123.9	-65.8	0.	-0. **	206.1	560.7	330.3	35.0	1.000046
50000.0	120.8	-67.0	0.	-0. **	204.1	559.1	330.7	34.1	1.000045
50500.0	117.8	-68.1	0.	-0. **	200.1	557.6	330.7	33.1	1.000045
51000.0	114.9	-69.2	0.	-0. **	196.2	556.1	329.5	32.2	1.000044
51500.0	112.0	-68.6	0.	-0. **	190.7	556.9	328.3	31.3	1.000042
52000.0	109.2	-68.9	0.	-0. **	186.2	556.5	325.1	31.6	1.000041
52500.0	106.4	-69.7	0.	-0. **	182.3	555.4	321.7	32.0	1.000041
53000.0	103.8	-70.3	0.	-0. **	178.2	554.6	315.5	30.2	1.000040
53500.0	101.2	-69.2	0.	-0. **	172.9	556.1	307.6	27.1	1.000038
54000.0	98.6	-68.1	0.	-0. **	167.6	557.5	300.5	25.2	1.000037
54500.0	96.2	-67.0	0.	-0. **	162.6	559.0	295.1	25.9	1.000036
55000.0	93.8	-66.4	0.	-0. **	158.1	559.8	289.7	26.6	1.000035
55500.0	91.5	-66.3	0.	-0. **	154.1	560.0	284.8	26.2	1.000034
56000.0	89.2	-66.2	0.	-0. **	150.2	560.1	279.9	25.8	1.000033
56500.0	87.0	-66.1	0.	-0. **	146.5	560.2	280.9	23.0	1.000033
57000.0	84.9	-66.0	0.	-0. **	142.8	560.4	283.4	19.5	1.000032
57500.0	82.8	-65.9	0.	-0. **	139.2	560.5	290.9	16.1	1.000031
58000.0	80.7	-66.4	0.	-0. **	136.1	559.9	303.0	12.9	1.000030
58500.0	78.7	-67.2	0.	-0. **	133.2	558.7	317.7	9.9	1.000030
59000.0	76.8	-68.1	0.	-0. **	130.4	557.6	344.5	7.9	1.000029
59500.0	74.9	-67.3	0.	-0. **	126.7	558.6	11.3	5.8	1.000028
60000.0	73.0	-65.5	0.	-0. **	122.5	561.1	5.6	7.8	1.000027
60500.0	71.2	-64.7	0.	-0. **	119.0	562.2	350.1	10.9	1.000026
61000.0	69.5	-65.0	0.	-0. **	116.3	561.7	338.8	12.6	1.000026
61500.0	67.8	-65.4	0.	-0. **	113.6	561.2	335.7	11.5	1.000025
62000.0	66.1	-65.8	0.	-0. **	111.0	560.8	332.8	10.4	1.000025
62500.0	64.5	-65.5	0.	-0. **	108.2	561.0	338.5	12.8	1.000024
63000.0	62.9	-64.2	0.	-0. **	104.9	562.9	345.4	15.5	1.000023

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
11 DEC. 67 1540 HRS MST
ASCENSION NO. 993

UPPER AIR DATA
0063003902
WHITE SANDS SITE

MSTN SITE COORDINATES
E 488,580 FEET
N 185,045 FEET

TABLE X (Cont)

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	TEMPERATURE DEWPOINT DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES(TN)	WIND DATA SPEED KNOTS	INDEX OF REFRACTION
63500.0	61.4	-62.8	0.	-0. **	101.6	564.8	355.6	17.5	1.000023
64000.0	59.9	-61.5	0.	-0. **	98.6	566.5	9.1	18.9	1.000022
64500.0	58.4	-61.0	0.	-0. **	96.0	567.2	21.2	20.1	1.000021
65000.0	57.0	-60.5	0.	-0. **	93.5	567.8	25.1	20.0	1.000021
65500.0	55.7	-60.0	0.	-0. **	91.0	568.5	29.1	20.0	1.000020
66000.0	54.4	-59.5	0.	-0. **	88.6	569.2	31.4	18.0	1.000020
66500.0	53.1	-59.0	0.	-0. **	86.3	569.8	33.2	15.3	1.000019
67000.0	51.8	-58.5	0.	-0. **	84.1	570.5	32.7	12.4	1.000019
67500.0	50.5	-58.0	0.	-0. **	81.9	571.1	27.4	9.0	1.000018
68000.0	49.3	-58.4	0.	-0. **	80.1	570.6	22.1	5.7	1.000018
68500.0	48.2	-59.6	0.	-0. **	78.6	569.1	10.7	6.0	1.000017
69000.0	47.0	-60.7	0.	-0. **	77.1	567.6	358.6	6.7	1.000017
69500.0	45.9	-61.0	0.	-0. **	75.4	567.1	352.1	7.9	1.000017
70000.0	44.8	-61.4	0.	-0. **	73.7	566.6	353.9	9.9	1.000016
70500.0	43.7	-61.7	0.	-0. **	72.0	566.2	355.7	11.9	1.000016
71000.0	42.6	-62.1	0.	-0. **	70.4	565.7	358.2	15.2	1.000016
71500.0	41.6	-62.4	0.	-0. **	68.8	565.2	1.1	19.1	1.000015
72000.0	40.6	-62.8	0.	-0. **	67.2	564.7	4.0	23.0	1.000015
72500.0	39.6	-62.7	0.	-0. **	65.6	564.9	7.7	23.5	1.000015
73000.0	38.7	-61.9	0.	-0. **	63.8	566.0	11.6	23.9	1.000014
73500.0	37.7	-61.1	0.	-0. **	62.0	567.1	15.0	23.9	1.000014
74000.0	36.8	-60.2	0.	-0. **	60.3	568.1	16.8	22.4	1.000013
74500.0	35.9	-59.5	0.	-0. **	58.6	569.1	18.6	20.9	1.000013
75000.0	35.1	-59.9	0.	-0. **	57.3	568.7	20.3	18.6	1.000013
75500.0	34.2	-60.2	0.	-0. **	56.0	568.2	21.8	15.3	1.000012
76000.0	33.4	-60.5	0.	-0. **	54.7	567.8	23.3	12.1	1.000012
76500.0	32.6	-60.9	0.	-0. **	53.5	567.3	15.8	12.1	1.000012
77000.0	31.8	-61.2	0.	-0. **	52.3	566.9	4.5	13.5	1.000012
77500.0	31.1	-61.5	0.	-0. **	51.1	566.4	353.3	14.9	1.000011
78000.0	30.3	-61.9	0.	-0. **	50.0	566.0	354.8	17.1	1.000011

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
11 DEC. '67 1540 HRS MST
ASCENSION NO. 993

UPPER AIR DATA
0063003902
WHITE SANDS SITE
TABLE X (Cont)

WSTR SITE COORDINATES
E 488,580 FEET
N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	TEMPERATURE DEWPOINT DEGREES CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES(TN)	WIND DATA SPEED KNOTS	INDEX OF REFRACTION
78500.0	29.8	-61.8	0.	-0. **	48.8	566.0	356.5	19.3	1.000011
79000.0	28.9	-61.5	0.	-0. **	47.5	566.5	358.4	21.5	1.000011
79500.0	28.2	-61.2	0.	-0. **	46.3	566.9	2.9	22.0	1.000010
80000.0	27.5	-60.9	0.	-0. **	45.2	567.3	7.4	22.4	1.000010
80500.0	26.9	-60.6	0.	-0. **	44.0	567.7	11.9	22.8	1.000010
81000.0	26.2	-60.3	0.	-0. **	42.9	568.1	13.0	23.4	1.000010
81500.0	25.6	-60.0	0.	-0. **	41.8	568.5	13.0	24.0	1.000009
82000.0	25.0	-59.7	0.	-0. **	40.8	568.9	13.1	24.7	1.000009
82500.0	24.4	-59.4	0.	-0. **	39.7	569.3	12.1	24.8	1.000009
83000.0	23.8	-59.1	0.	-0. **	38.7	569.7	10.5	24.5	1.000009
83500.0	23.2	-58.8	0.	-0. **	37.7	570.1	8.8	24.2	1.000008
84000.0	22.7	-58.5	0.	-0. **	36.8	570.5	6.2	24.3	1.000008
84500.0	22.1	-58.2	0.	-0. **	35.9	570.9	2.0	24.9	1.000008
85000.0	21.6	-57.9	0.	-0. **	35.0	571.3	357.8	25.5	1.000008
85500.0	21.1	-57.6	0.	-0. **	34.1	571.7	353.5	25.8	1.000008
86000.0	20.6	-56.9	0.	-0. **	33.2	572.5	349.1	24.0	1.000007
86500.0	20.1	-56.3	0.	-0. **	32.3	573.4	344.6	22.3	1.000007
87000.0	19.6	-55.6	0.	-0. **	31.4	574.3	340.2	20.6	1.000007
87500.0	19.2	-55.0	0.	-0. **	30.6	575.2	332.8	18.7	1.000007
88000.0	18.7	-55.0	0.	-0. **	29.9	575.1	325.1	16.8	1.000007
88500.0	18.3	-55.5	0.	-0. **	29.3	574.5	317.5	14.9	1.000007
89000.0	17.8	-56.0	0.	-0. **	28.6	573.8	312.4	14.8	1.000006
89500.0	17.4	-56.5	0.	-0. **	28.0	573.2	308.6	15.5	1.000006
90000.0	17.0	-56.9	0.	-0. **	27.4	572.5	304.8	16.3	1.000006
90500.0	16.6	-57.4	0.	-0. **	26.8	571.9	303.1	16.7	1.000006
91000.0	16.2	-57.9	0.	-0. **	26.3	571.3	304.3	16.5	1.000006
91500.0	15.8	-58.4	0.	-0. **	25.7	570.6	305.5	16.4	1.000006
92000.0	15.5	-58.9	0.	-0. **	25.1	570.0	306.6	16.7	1.000006
92500.0	15.1	-59.4	0.	-0. **	24.6	569.3	307.3	19.0	1.000005
93000.0	14.7	-59.3	0.	-0. **	24.0	569.4	308.1	21.3	1.000005

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
11 DEC. 67 1540 HRS MST
ASCENSION NO. 993

UPPER AIR DATA
0063003902
WHITE SANDS SITE
TABLE X (Cont).

WSTM SITE COORDINATES
E 488,580 FEET
N 185,045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES	TEMPERATURE DEWPOINT CENTIGRADE	REL.HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES(TN)	WIND DATA SPEED KNOTS	INDEX OF REFRACTION
93500.0	14.4	-59.0	0.	-0. **	23.4	569.8	308.9	23.6	1.000005
94000.0	14.1	-58.7	0.	-0. **	22.8	570.2	305.8	23.8	1.000005
94500.0	13.7	-58.4	0.	-0. **	22.3	570.6	302.6	23.8	1.000005
95000.0	13.4	-58.1	0.	-0. **	21.7	571.0	299.3	23.9	1.000005
95500.0	13.1	-57.8	0.	-0. **	21.2	571.4	296.7	23.9	1.000005
96000.0	12.8	-57.5	0.	-0. **	20.6	571.8	294.3	23.9	1.000005
96500.0	12.5	-57.2	0.	-0. **	20.1	572.2	291.9	23.8	1.000004
97000.0	12.2	-56.9	0.	-0. **	19.6	572.6	290.6	24.1	1.000004
97500.0	11.9	-56.6	0.	-0. **	19.1	573.0	291.6	24.9	1.000004
98000.0	11.6	-56.3	0.	-0. **	18.6	573.4	292.6	25.8	1.000004
98500.0	11.3	-56.0	0.	-0. **	18.2	573.8	293.6	26.6	1.000004
99000.0	11.1	-55.7	0.	-0. **	17.7	574.2	294.9	28.0	1.000004
99500.0	10.8	-55.2	0.	-0. **	17.3	574.9	296.3	29.6	1.000004
100000.0	10.6	-54.6	0.	-0. **	16.8	575.6	297.7	31.2	1.000004
100500.0	10.3	-54.0	0.	-0. **	16.4	576.4	298.2	33.1	1.000004
101000.0	10.1	-53.5	0.	-0. **	16.0	577.1	296.6	35.7	1.000004
101500.0	9.8	-52.9	0.	-0. **	15.6	577.9	295.1	38.3	1.000003
102000.0	9.6	-52.3	0.	-0. **	15.2	578.0	293.5	40.9	1.000003
102500.0	9.4	-51.7	0.	-0. **	14.8	579.4	289.7	41.4	1.000003
103000.0	9.2	-51.2	0.	-0. **	14.4	580.1	285.2	41.4	1.000003
103500.0	9.0	-50.7	0.	-0. **	14.0	580.7	280.8	41.4	1.000003
104000.0	8.8	-50.7	0.	-0. **	13.7	580.7	276.6	41.4	1.000003
104500.0	8.6	-50.7	0.	-0. **	13.4	580.7	273.9	42.1	1.000003
105000.0	8.4	-50.8	0.	-0. **	13.1	580.7	271.1	42.7	1.000003
105500.0	8.2	-50.8	0.	-0. **	12.8	580.7	268.4	43.3	1.000003
106000.0	8.0	-50.8	0.	-0. **	12.5	580.6	267.5	43.5	1.000003
106500.0	7.8	-50.8	0.	-0. **	12.2	580.6	267.8	43.5	1.000003
107000.0	7.6	-50.8	0.	-0. **	11.9	580.6	268.0	43.4	1.000003
107500.0	7.4	-50.8	0.	-0. **	11.7	580.6	268.3	43.4	1.000003
108000.0	7.3	-50.9	0.	-0. **	11.4	580.5	270.1	45.0	1.000003

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
11 DEC. 67 1540 HRS MST
ASCENSION NO. 993

UPPER AIR DATA
0065003902
WHITE SANDS SITE

TABLE X (Cont)

WSTR SITE COORDINATES
E 448.380 FEET
N 185.045 FEET

GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMPERATURE AIR DEGREES CENTIGRADE	TEMPERATURE DEWPOINT CENTIGRADE	REL. HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION DEGREES(TN)	WIND DATA SPEED KNOTS	INDEX OF REFRACTION
108500.0	7.1	-50.9	0.	-0. **	11.1	580.5	271.9	44.5	1.000002
109000.0	6.9	-50.9	0.	-0. **	10.9	580.5	273.8	48.1	1.000002
109500.0	6.8	-50.9	0.	-0. **	10.6	580.5	274.9	49.8	1.000002
110000.0	6.6	-50.9	0.	-0. **	10.4	580.5	275.1	51.6	1.000002
110500.0	6.5	-50.9	0.	-0. **	10.2	580.4	275.3	53.4	1.000002
111000.0	6.3	-51.0	0.	-0. **	9.9	580.4	275.6	55.2	1.000002
111500.0	6.2	-51.0	0.	-0. **	9.7	580.4	275.0	56.3	1.000002
112000.0	6.0	-51.0	0.	-0. **	9.5	580.4	274.4	57.2	1.000002
112500.0	5.9	-50.5	0.	-0. **	9.2	581.0	273.7	58.2	1.000002
113000.0	5.8	-49.7	0.	-0. **	9.0	582.0			1.000002
113500.0	5.6	-49.0	0.	-0. **	8.8	583.0			1.000002
114000.0	5.5	-48.2	0.	-0. **	8.5	584.0			1.000002
114500.0	5.4	-47.5	0.	-0. **	8.3	584.9			1.000002
115000.0	5.3	-46.7	0.	-0. **	8.1	585.9			1.000002
115500.0	5.2	-46.0	0.	-0. **	7.9	586.9			1.000002
116000.0	5.0	-45.2	0.	-0. **	7.7	587.9			1.000002

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 3989.0 FEET MSL
11 DEC. 67 1540 HRS MST
ASCENSION NO. 993

MANDATORY LEVELS
0063003902
WHITE SANDS SITE
TABLE XI

WSTM SITE COORDINATES
E 488,580 FEET
N 185,045 FEET

PRESSURE MILLIBARS	GEOPOTENTIAL FEET	TEMPERATURE AIR DEGREES	TEMPERATURE DEWPOINT CENTIGRADE	REL. HUM. PERCENT	WIND DATA DIRECTION DEGREES(TN)	WIND DATA SPEED KNOTS
850.0	4673.	10.2	-10.5	22.	232.2	8.5
800.0	6317.	8.4	-11.8	23.	306.4	19.1
750.0	8069.	8.2	-14.1	19.	329.7	24.2
700.0	9924.	5.1	-16.9	19.	338.3	30.4
650.0	11903.	3.4	-18.7	18.	328.6	34.4
600.0	14013.	-1.4	-22.7	18.	323.6	36.4
550.0	16264.	-6.7	-27.2	18.	325.5	42.1
500.0	18679.	-12.6	-32.0	18.	324.0	40.6
450.0	21279.	-20.2	-38.1	19.	320.4	31.2
400.0	24105.	-26.5	-43.3	19.	324.6	30.9
350.0	27228.	-33.1	-48.9	19.	330.2	30.8
300.0	30730.	-40.5	-62.3	8.**	341.0	36.5
250.0	34746.	-45.5	0.	-0.**	315.4	43.4
200.0	39588.	-51.3	0.	-0.**	302.8	48.1
175.0	42396.	-57.4	0.	-0.**	299.5	44.5
150.0	45544.	-63.4	0.	-0.**	308.8	43.3
125.0	49195.	-65.4	0.	-0.**	330.2	35.4
100.0	53583.	-60.7	0.	-0.**	304.2	25.7
80.0	58013.	-66.7	0.	-0.**	307.3	11.7
70.0	60665.	-64.9	0.	-0.**	339.8	12.9
60.0	63755.	-61.5	0.	-0.**	7.7	18.8
50.0	67496.	-57.8	0.	-0.**	25.2	7.6
40.0	72042.	-63.0	0.	-0.**	6.1	23.4
30.0	77909.	-62.0	0.	-0.**	355.4	18.0
25.0	81629.	-59.7	0.	-0.**	13.1	24.6
20.0	86238.	-56.1	0.	-0.**	343.8	22.0
15.0	92219.	-49.5	0.	-0.**	307.5	19.6
10.0	100649.	-53.3	0.	-0.**	296.2	36.4
7.0	108258.	-50.9	0.	-0.**	273.1	47.6
5.0	115495.	-45.0	0.	-0.**		

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

RELEASE TIME (MST)		SECOND-STAGE IMPACT DISPLACEMENT IN MILES DUE TO WIND								AZIMUTH (DEGREES)	THEORETICAL IMPACT FROM LAUNCHER (IN MILES)		
		11-216 FT		216-4000 FT		4000-69331 FT		TOTAL					
RAWINSONDE	PIBAL	N-S	E-W	N-S	E-W	N-S	E-W	N-S	E-W		RANGE	N-S	E-W
1300	1230	0.0	0.0	2.7N	4.6W	15.6N	11.8W	17.3N	16.4W	355.5	72.0	71.8N	5.7W
1300	1300	0.0	0.0	2.8N	5.3W	14.6N	11.8W	17.4N	17.1W	354.9	72.2	71.9N	6.4W
1300	1330	0.0	0.0	1.9N	5.3W	14.6N	11.8W	16.5N	17.1W	354.8	71.3	71.0N	6.4W
1300	1345	0.0	0.0	0.5N	6.2W	14.6N	11.8W	15.1N	18.0W	354.0	70.0	69.6N	7.3W
1300	1400	0.0	0.0	0.2N	5.2W	14.6N	11.8W	14.8N	17.0W	354.8	69.6	69.3N	6.3W
1300	1415	2.2S	0.0	0.5S	7.2W	14.6N	11.8W	11.9N	19.0W	352.9	66.9	66.4N	8.3W
1300	1433	3.0S	0.0	1.2S	4.7W	14.6N	11.8W	10.4N	16.5W	354.9	65.2	64.9N	5.8W
1300	1443	2.2S	0.0	3.0S	6.8W	14.6N	11.8W	9.4N	18.6W	353.0	64.4	63.9N	7.9W
1540	1456	5.3S	0.0	3.8S	6.8W	8.6N	18.4W	0.5S	25.2W	345.0	55.9	54.0N	14.5W

	AZIMUTH (DEGREES)	MILES FROM LAUNCHER		
		RANGE	N-S	E-W
LAUNCHER SETTING (ELEVATION 86.1 DEGREES QE)	016.0	56.7	54.5N	15.6E
NO WIND IMPACT	011.1	55.5	54.5N	10.7E
PREDICTED SECOND-STAGE IMPACT	356.0	65.0	64.8N	4.5W
SECOND-STAGE IMPACT, RADAR TRACK	007.2	99.4	98.6N	12.4E
PREDICTED BOOSTER IMPACT	100.0	0.3	0.1S	0.3E
ACTUAL BOOSTER IMPACT	N/A	N/A	N/A	N/A

TABLE XII. IMPACT PREDICTION DATA
NIKE-HYDAC STV SR 069

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY *(Corporate author)* U.S. Army Electronics Command Ft. Monmouth, New Jersey	2a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED 2b. GROUP

3. REPORT TITLE

METEOROLOGICAL DATA REPORT, NIKE-HYDAC STV SR 069

4. DESCRIPTIVE NOTES *(Type of report and inclusive dates)*

5. AUTHOR(S) *(Last name, first name, initial)*

Dunaway, Gordon L.

6. REPORT DATE January 1968	7a. TOTAL NO. OF PAGES 37	7b. NO. OF REFS 2

8a. CONTRACT OR GRANT NO. b. PROJECT NO. c. DA Task IV650212A127-02 d.	9a. ORIGINATOR'S REPORT NUMBER(S) DR-286 9b. OTHER REPORT NO(S) *(Any other numbers that may be assigned this report)*

10. AVAILABILITY/LIMITATION NOTICES

[redacted].

11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY U.S. Army Electronics Command Atmospheric Sciences Laboratory White Sands Missile Range, New Mexico

13. ABSTRACT

Meteorological data gathered for the launching of Nike-Hydac STV (SR 069) are presented for the Space and Missile Systems Organization and for ballistic studies. The data appear, along with calculated ballistic data, in tabular form.

DD FORM 1 JAN 64 1473

UNCLASSIFIED

Security Classification

UNCLASSIFIED

Security Classification

14. KEY WORDS	LINK A ROLE	LINK A WT	LINK B ROLE	LINK B WT	LINK C ROLE	LINK C WT
1. Ballistics						
2. Meteorology						
3. Wind						

INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

(1) "Qualified requesters may obtain copies of this report from DDC."

(2) "Foreign announcement and dissemination of this report by DDC is not authorized."

(3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."

(4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."

(5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

UNCLASSIFIED

Security Classification