UNCLASSIFIED

## AD NUMBER

**AD839349**

## NEW LIMITATION CHANGE

TO

**Approved for public release, distribution unlimited**

FROM

**Distribution authorized to U.S. Gov't. agencies and their contractors; Administrative/Operational Use; JUL 1968. Other requests shall be referred to Naval Weapons Center, China Lake, CA.**

## AUTHORITY

**NWC ltr 24 Mar 1972**

THIS PAGE IS UNCLASSIFIED

NWC TP 4593 C.1
NWC TP 4593

Do not forward this copy to other activities without authorization of AVCOMSYSCOM(ORD-9)

RETURN TO
TECHNICAL LIBRARY BRANCH
NAVAL ORDNANCE SYSTEMS COMMAND
Dept. of Navy
D. C., 20360

# MEASUREMENT PROBLEMS RELATED TO SOLID ROCKET COMBUSTION INSTABILITY

by

H. B. Mathes

Research Department

ABSTRACT. A review is presented of the classes of instability, conditions favoring each class, experimental measurements recognized to diagnose each class, and problems in conducting such measurements.

NAVAL WEAPONS CENTER
CHINA LAKE, CALIFORNIA * JULY 1968

DISTRIBUTION STATEMENT
THIS DOCUMENT IS SUBJECT TO SPECIAL EXPORT CONTROLS AND EACH TRANSMITTAL TO FOREIGN GOVERNMENTS OR FOREIGN NATIONALS MAY BE MADE ONLY WITH PRIOR APPROVAL OF THE NAVAL WEAPONS CENTER.

NAVAL WEAPONS CENTER
AN ACTIVITY OF THE NAVAL MATERIAL COMMAND

M. R. Etheridge, Capt., USN ..... Commander
Thomas S. Amlie, Ph.D. ..... Technical Director

## FOREWORD

This report was written for the solid rocket propulsion engineer as a practical guide to measurement of solid propellant rocket motor instability. As such, it stresses aspects of instability and measurement problems that are likely to be encountered on the motor test stand rather than in a scientific laboratory research endeavor.

The information contained in this report was presented at the Fifth Annual Meeting of the Interagency Chemical Rocket Propulsion Group (ICRPG) Static Test Panel Working Group, 18-19 October 1967, in Sacramento, California (CPIA Publication No. 161). It is being released in its present form to provide wider distribution and to make it more accessible to persons responsible for solid propellant rocket motor development.

This report was prepared under sponsorship of Naval Ordnance Systems Command Task Assignment ORD-033 103/200 1/F009-06-01, PA #3.

This report is transmitted for information only. It does not represent the official views or final judgment of this Center.

Released by
J. E. CRUMP, Head (Acting)
Aerothermochemistry Division
23 July 1968

Under authority of
HUGH W. HUNTER, Head
Research Department

NWC Technical Publication 4593

Published by.....Research Department
Collation.....Cover, 12 leaves, DD Form 1473, abstract cards
First printing.....220 unnumbered copies
Security classification.....UNCLASSIFIED

CONTENTS

Introduction. . . . . 1

Nature of Combustion-Driven Gas Oscillations. . . . . 1
Acoustic Instability. . . . . 1
Longitudinal Oscillations . . . . . 2
Transverse Oscillations . . . . . 4
Nonacoustic Instability . . . . . 6

Characteristics and Classes of Instability. . . . . 7
High Frequency Instability (HFI). . . . . 8
Intermediate Frequency Instability (IFI). . . . . 8
Low Frequency Instability (LFI) . . . . . 9

Instability Measurement Problems. . . . . 10
Detection of Instability. . . . . 10
Signal Conditioning and Recording . . . . . 12
Methods of Analysis . . . . . 14

Conclusion. . . . . 15

References. . . . . 17

## INTRODUCTION

Combustion instability has hampered development of a variety of solid propellant motors over the past 25 years. It continues to be a problem today in spite of a great increase of knowledge regarding its causes and cures. At present, as in the past, motor design and test personnel are faced with the possibility that their next motor firing will be unstable. This is particularly the case following changes in motor or grain design or alteration of propellant composition.

The intent of this paper is to emphasize the importance of proper instability measurement and the methods used to attain that goal. The subject includes consideration of the nature of combustion instability, with particular attention being paid to the character of gas oscillations in the motor, the determination of proper transducers for detecting instability, and the choices to be made regarding signal conditioning and recording equipment. Other items of interest include the calculation of oscillation frequencies, conditions which favor particular modes and frequencies of instability, and methods used to analyze instability data.

## NATURE OF COMBUSTION-DRIVEN GAS OSCILLATIONS

Combustion instability is the result of an interaction between gas flow in the motor and energy release from the combustion zone such that small flow disturbances are amplified into larger ones (Ref. 1 and 2). The flow disturbances involve pressure and velocity variations in various parts of the motor which are usually, but not always, periodic. Two general classes of gas oscillation are observed: (1) acoustic oscillations in which the gas vibrates in one or more standing acoustic wave modes of the motor and (2) nonacoustic oscillations which are related to the gas discharge characteristics of the motor (Ref. 3 and 4).

### ACOUSTIC INSTABILITY

This class of instability is the type most often encountered in solid propellant rocket motors. The frequency of oscillation and distribution of the oscillating component of pressure and of velocity are determined by the internal motor dimensions, the "mode" of oscillation, and the speed of sound in the gas (Ref. 5). The environment imposed by pressure and velocity oscillations in the motor often result in significant deviations of motor pressure from the desired value due to the

burning rate being altered from its normal value as shown in Fig. 1 (Ref. 6 and 7). The burning rate is always increased in the region of velocity variations and it is always reduced in the region of pressure oscillations (Ref. 8 and 9). The net effect on the burning rate during instability may be positive, negative, or neutral, depending on the propellant composition, the placement of burning surfaces in the motor, and the structure of the gas oscillations. It is usually the motor pressure deviations that make instability unacceptable.




FIG. 1. Sketch of Rocket Motor Pressure-Time History Showing Typical Effect of Combustion Instability. Gas oscillations in the motor invariably accompany deviation of pressure from design value when instability is the cause of trouble.

Acoustic oscillations can be classified into two general categories: (1) longitudinal oscillations, in which the gas moves in a direction parallel to the motor axis and (2) transverse oscillations in which the gas moves perpendicularly to the motor axis (Ref. 5 and 10). One of the difficulties encountered in considering acoustic instability is the complex internal geometry characteristic of most rocket motors. In the following, therefore, it will be assumed that the motor interior can be approximated by a circular cylinder which is closed at both ends. The emphasis in the following will be on a qualitative description of the types of acoustic oscillation, means of calculating frequencies, and optimum locations for pressure transducers.

## LONGITUDINAL OSCILLATIONS

The simplest type of longitudinal oscillation, called the "first mode" or sometimes the "fundamental mode", consists of gas motion parallel to the motor axis with a maximum velocity (velocity antinode) at the

center of the motor and maxima in pressure (pressure antinodes) at the ends of the motor (Fig. 2). As is the case with all types of standing acoustic waves, the envelope of pressure oscillations varies continuously with distance and higher order modes are possible (Fig. 3), each of which has a particular pressure distribution and frequency.




FIG 2. Longitudinal (Axial Mode) Oscillations Involve Gas Motion Parallel to the Motor Axis. Regions of maximum pressure variation (pressure antinodes) alternately occur at the ends of the motor. Arrows indicate direction of gas motion in the region where gas velocity oscillations have maximum values.

The frequency of a longitudinal mode is calculated from the relation

$$f = \frac{\lambda a}{2L} ,$$

where f is the frequency, $\lambda$ is a positive integer (the mode number), a is the velocity of sound in the gas, and L is the length of the motor (Ref. 5). The various mode frequencies in real motors seldom bear a simple integral relationship to each other that is assumed here. The variations that are observed are due partly to complications induced by the geometry of real motors, and partly to the effects of oscillatory amplitudes much larger in magnitude than assumed by acoustic theory.

Optimum pressure transducer locations for measurement of this type of instability are at either end of the motor, since <u>every</u> longitudinal mode has a pressure antinode at these places. Generally, the head end is to be preferred since there are no net gas flow complications as are likely to be encountered in the nozzle region.




FIG. 3. Acoustic Pressure Distribution for Longitudinal Oscillations. Examples for the first three modes are shown. Small, heavy circles denote pressure antinode locations. Solid lines indicate the pressure distribution at an instant in time when the pressure at the head end is a maximum while the dashed line represents the distribution a half cycle later.

## TRANSVERSE OSCILLATIONS

Two types of transverse oscillations are possible in a cylindrical geometry: (1) radial oscillations in which the gas moves in and out along radii of the motor and (2) tangential oscillations which involve gas motion in a circumferential manner, as shown in Fig. 4 (Ref. 10). Radial and tangential oscillations are closely related but they can occur separately as well as in combination. Transverse mode frequencies can be calculated from the relation (Ref. 5 and 11)

$$f = \frac{(\alpha_{\rho\tau})a}{2R} ,$$

where f is the frequency, $\alpha_{\rho\tau}$ is a coefficient whose value is determined by the value of the radial mode number $\rho$ and the tangential mode number $\tau$, a is the velocity of sound in the gas, and R is the radius of the grain perforation. Values of the transverse mode frequency coefficient appear in Table 1.

Optimum placement of pressure transducers for detection of transverse mode oscillations presents a problem since the locations of the pressure antinodes follow the regression of the propellant web. The tangential mode is the most difficult to detect due to the difficulty in




(a) Radial Oscillations (b) Tangential Oscillations

FIG. 4. Transverse Mode Acoustic Oscillations Can Occur in Two Basic Modes. (a) Radial oscillations involve gas motion along radii as indicated by arrows. Locations of maximum pressure excursion are on the motor axis and the curved surface of the bounding cylinder. (b) Tangential oscillations involve circumferential gas motion indicated by arrows. Pressure maxima occur along lines on the cylindrical surface, which imposes stringent requirements for optimum pressure transducer locations.

TABLE 1. Values of the Transverse Mode Frequency Coefficient, $\alpha_{\rho\tau}$

| $\tau \downarrow$ $\rho \rightarrow$ | 0 | 1 | 2 | 3 |
|---|---|---|---|---|
| 0 | 0.000 | 1.220 | 2.233 | 3.238 |
| 1 | .586 | 1.697 | 2.714 | 3.726 |
| 2 | .972 | 2.135 | 3.173 | 4.192 |
| 3 | 1.337 | 2.551 | 3.611 | 4.643 |

predetermining its orientation in the motor, and the restricted distribution of the pressure antinodes. In addition, this mode may rotate in circular perforations, making analysis of data more difficult. The usual approach in choosing transducer locations is to arrange a pattern on the motor, such that one location will always be near a pressure

antinode. A modification of a pattern suggested for liquid instability measurement appears to be suitable as it permits determination of the tangential mode orientation as shown in Fig. 5 (Ref. 12).




FIG. 5. Suggested Transducer Distribution to Provide Information on Orientation of Tangential Mode Acoustic Oscillations. Comparison of outputs from the three transducers will identify acoustic oscillations of all three types and will indicate the speed and direction of rotation of the tangential mode, if that should occur.

A pressure transducer location on the motor axis should be avoided. While such a location is suitable for detecting <u>any</u> longitudinal or radial mode, an axial location theoretically cannot detect <u>any</u> tangential mode.

## NONACOUSTIC INSTABILITY

Nonacoustic instability (NAI) involves an interaction between the heated layer of the solid propellant, the combustion zone, and the gas discharge characteristics of the motor (Ref. 4 and 13). The frequencies encountered in this type of instability are generally below 100 cps, much lower than the frequencies of the natural acoustic modes of the motor. The pressure oscillations may be nonsinusoidal as in "chuffing" or they may be sinusoidal (Fig. 6). Nonacoustic theory treats only the sinusoidal oscillations. In both types of nonacoustic oscillation, the pressure fluctuations are a function of time only. There are no spacewise pressure variations. This class of instability poses little difficulty in measurement since the frequencies are low enough to be detected by the usual instrumentation and the location of pressure transducers is not critical.




FIG. 6. Sketch of Typical Nonacoustic Pressure-Time History. Pressure spikes due to "chuffing" and sinusoidal oscillations are possible. Nonacoustic theory refers to the latter behavior.

## CHARACTERISTICS AND CLASSES OF INSTABILITY

Knowledge of conditions under which particular classes of instability are likely to occur is helpful in anticipating the frequencies likely to be encountered in testing. Motor instability, however, depends on the relative magnitude of a number of factors which include ability of the combustion to amplify pressure and flow disturbances, effect of mean flow in generating or damping disturbances, energy losses induced by solid particles suspended in gas, the influence of the nozzle on acoustic losses, and the participation of the propellant grain in absorbing acoustic energy (Ref. 2, 14 & 15). Some of these factors can be calculated and several are being routinely evaluated in laboratory experiments but a reliable method of predicting motor instability behavior remains for the future (Ref. 16).

Laboratory test techniques that are available for rating instability characteristics include measurement of combustion amplification of flow disturbances and the effect of motor geometry on acoustic losses (Ref. 17-19). Combustion amplification tests are conducted in "T-burners" which normally test the pressure-coupled amplification characteristic (Ref. 20-22). A recent modification to the basic T-burner design permits investigation of velocity-coupled amplification (Ref. 23).

Although complete characterization of rocket motor instability behavior is not yet possible on a quantitative basis, classes of instability can be identified and a general discussion made on the basis of past experience and knowledge of the several definitive tests that are presently available (Ref. 2 and 15). For this purpose combustion instability will be classified into three regions on the basis of frequency.

## HIGH FREQUENCY INSTABILITY (HFI)

This class of instability involves frequencies from 1,000 to over 50,000 cps. It normally occurs in transverse acoustic modes but is readily stabilized by solid particles in the gas. High frequency instability is likely to be a problem in motors with circular (or nearly circular) grain perforations, with smokeless propellants, and with very high energy compositions. Stability may be achieved in these cases by introduction of a stabilizing rod or by designing the proper convolutions into the grain perforation, both of which will tend to interfere with the acoustic gas motion and will usually reduce or eliminate the instability. It should be noted that radial and mixed modes are rarely, if ever, seen in solid propellant rocket motors. Transverse oscillations occur most often in the first tangential mode.

Consideration of the interaction between the solid propellant web and transverse mode gas oscillations indicates that acoustic energy losses into the solid at certain times during burning can be large enough to damp instability (Ref. 24-26). This explains in part the observations concerning the appearance and disappearance of transverse modes at various times during a firing. Transverse modes are more likely to be encountered late in burning due to two other factors: (1) the star points have largely burned away and (2) stabilizing rods occupy a smaller percentage of the cavity.

## INTERMEDIATE FREQUENCY INSTABILITY (IFI)

Intermediate frequency instability includes the frequency range of 100 to 1,000 cps. It most commonly occurs as longitudinal (axial mode) oscillations and in rocket motors with large length to diameter ratios. This class of instability is also seen with heavily metallized propellants. Solid particle damping is relatively ineffective in the frequency ranges encountered and evidence suggests that the presence of metal in the combustion process may even contribute to this class of instability. The frequencies of oscillation are close to those calculated by assuming gas motion in a chamber closed at both ends. The influence of the nozzle is important in that it tends to stabilize axial instability. Acoustic tests in model rocket motors show that the nozzle losses vary in proportion to the nozzle throat-to-grain port area ratio (J). Observations in rocket motor firings indicate that motors which were stable early in burning may become unstable later in the firing, which appears to be due, at least in part, to a decrease in the J-factor (Ref. 27).

Another feature of axial mode IFI is the importance of velocity coupling, in contrast to pressure coupling which tends to dominate in the other ranges of instability. Velocity coupling causes a nonsinusoidal distortion of the pressure oscillations and it may be accompanied by a threshold velocity requirement such that a flow disturbance above a limiting level may be required in order for axial mode instability to persist

(Ref. 2, 15, 28, 29 and 30). Such behavior offers a perplexing situation to motor design and test personnel for an apparently stable motor may suddenly become unstable following any finite disturbance in the motor (Fig. 7).

Axial mode instability has only recently come under study. Much remains to be learned of this complex phenomenon.




FIG. 7. Sketch of Motor Pressure During Axial Mode Intermediate Frequency Instability. Requirement of a triggering pulse is sometimes encountered in this class of instability. Another characteristic is the presence of periodic, nonsinusoidal oscillations, which are caused by velocity-coupled combustion-flow interaction.

## LOW FREQUENCY INSTABILITY (LFI)

Low frequency instability generally occurs at frequencies below 100 cps and it includes nonacoustic and acoustic oscillations.

Nonacoustic instability depends on the relative thermal wave thickness in the propellant and the internal volume to nozzle throat area ratio (L*) (Ref. 4). This type of instability is most likely to occur in motors with a high propellant load ng factor and designed to operate at low pressure (low burning rate) (Ref. 2 and 15). Laboratory experiments with small motors that oscillate nonacoustically have provided stability limit data for metallized and nonmetallized propellants (Fig. 8) (Ref. 31). It remains to be determined, however, that the small motor data is capable of predicting larger motor behavior.

Interest in low frequency acoustic instability has grown recently due to the possibility of its occurrence in very large rocket motors. Present knowledge of this class of instability comes almost entirely from large T-burner tests (Ref. 32 and 33). It can occur with heavily metallized propellants since solid particle damping is ineffective at the low frequencies encountered. Instability with metallized propellants can also show a "preferred frequency" behavior in which instability occurs




FIG. 8. Nonacoustic Stability Data From a Small Research Motor. Comparison of this data with larger motor behavior may result in this information being useful in predicting conditions for stable motor operation.

over a narrow range of frequency at a given pressure (Ref. 34). Similarities in the mechanism between low frequency varieties of nonacoustic and acoustic instability has brought forth attempts to describe both aspects with a single theory.

The high cost of testing full scale motors of the sizes planned for boosting outer space missions puts great emphasis on development of laboratory techniques and theory which can be applied to prediction of LFI.

## INSTABILITY MEASUREMENT PROBLEMS

### DETECTION OF INSTABILITY

In a general sense, any physical property related to combustion-driven gas oscillations can be used to determine the presence of instability and to identify the modes. Motor case strain, acceleration of motor components, motor thrust variations, and measurement of the acoustic field outside the motor offer the possibility of detecting instability and of correlating the effect of instability on these aspects of motor behavior (Fig. 9) (Ref. 35). Detection of instability is better accomplished, however, by using pressure transducers chosen especially for that purpose. The pressure transducers routinely used on motor firings are seldom suitable for detecting pressure oscillations because they lack the frequency response. This is not too serious in detection




FIG. 9. Various Methods that can be Used to Detect Combustion Instability. Measurement of gas pressure oscillations is the most direct and the best developed of all methods.

of LFI but it becomes more acute when one encounters IFI and HFI where use of the proper transducer becomes a necessity if meaningful measurements are to be made (Ref. 36).

Pressure transducers are commercially available which permit measurements from dc to frequencies exceeding 50,000 cps. They characteristically feature an external mounting thread and a flush sensing diaphram (Fig. 10). Model variations are available that are either uncooled or water cooled. A relatively new type is available in which a flow of helium cools the transducer and serves to communicate between the gas in the motor and the sensing area in the transducer (Ref. 12). The preferred mounting of high frequency pressure transducers is an arrangement such that the sensing area is flush with the inner motor wall. While this is desirable from a frequency response standpoint, it is out of the question for uncooled transducers and may even be hazardous to those with cooling. The usual solution to the heating problem is to recess mount the transducer and utilize a grease or other insulating medium that will communicate the gas pressure to the sensing area. While solving the heating problem, recess mounting does affect the frequency response (Ref. 36 and 37). An alternate method of heat protection that may not cause the problem of frequency response degradation is the application of an ablative material to the face of the transducer. Synthetic rubber discs of thicknesses up to one-fourth inch have been used with apparent success.




FIG. 10. Typical High Frequency Response Pressure Transducers. External mounting threads and a flush sensing diaphram are characteristics of these devices. Water cooled transducer diaphram is a necessity for flush mounting in a rocket motor.

## SIGNAL CONDITIONING AND RECORDING

Problems of signal conditioning and recording include filtering and amplification of high frequency pressure transducer signals, choice of recording techniques and knowledge of frequencies likely to be encountered during the test.

The use of filters to provide high-pass, low-pass, and band-pass characteristics is nearly always required in HFI and IFI measurements (Fig. 11). High-pass filters are needed to block the dc signal component caused by mean pressure in the motor. This permits small amplitude signals from pressure oscillations to be amplified to a useable level, yet avoids saturating the recording equipment with an excessive dc signal. The low-pass filter is used to provide a "clean" pressure-time history from the high frequency transducer. The high-pass and low-pass signals can be advantageously recorded on a dual beam oscilloscope to provide a quick-look record within seconds after a motor firing (Fig. 12) (Ref. 35 and 36). Low-pass filters for such applications can be simple devices constructed from passive components with the cutoff frequency somewhat below the first longitudinal mode. Band-pass filters are useful in cases where several modes are present during a firing. Each band is set to pass a particular portion of the frequency spectrum so that




FIG. 11. Instrumentation of a Typical High Frequency Channel for Instability Measurement. Filters split the signal up into more easily handled and interpreted segments. Multiple band-pass filters are useful for dividing a complex signal into discrete frequency segments so that real-time recorded data can be analyzed for frequency and amplitude variations as a function of time during burning.




FIG. 12. Oscilloscope Camera Record Taken During a Motor Firing That Exhibited Axial Mode Intermediate Instability. Pulse fired into motor at 4.8 seconds initiated instability. This type of record is useful for quick-look purposes and provides a compact, conveniently handled and stored history of motor firings.

frequencies and amplitudes of the various modes are separately displayed (Ref. 36).

The use of filters requires some knowledge of the frequencies likely to be generated in the motor. The equations for acoustic vibrations (given in the section entitled Nature of Combustion-Driven Gas Oscillations) can be used but uncertainties often arise in judging the cavity dimensions of motors with complex internal geometries. The nature of this problem is that unexpected frequencies may be encountered because the gas oscillated in a different manner than predicted. Solution of this problem is to provide at least one channel with broad frequency response. This has the disadvantage that signals with widely varying amplitudes may be either saturated or lost in noise. Use of a logarithmic voltage compressor in such instances offers the possibility of recording a wide range of amplitudes without exceeding the recorder's limits.

Three types of recording devices that find application in other measurement work are utilized for gathering instability data. The major concern is to assure that the recorder does not unduly limit the frequency response. In the case of long sweep time on the oscilloscope, of course, frequency response is not really an issue as a resolution of about 50 lines per inch on the screen is the maximum capable of being observed. Recording oscillographs offer a convenient means of recording data and frequency response can be as high as 13,000 cps. All high frequency galvanometers, however, need the proper driver amplifier as they require more power than most instrumentation provides. Oscillographs have the disadvantage of requiring high paper speeds if high frequency response is to be achieved. Another disadvantage is that the data is in graphical form and the analysis of complex waveforms from such records is tedious if not impossible. Many of the objections to recording oscillographs are solved by magnetic tape recorders. In fact, these recorders exceed all others for frequency response and duration of recording time. Use of magnetic tape data is particularly desirable if any extensive analysis of high frequency data is to be done. Ability to reproduce the electrical signal also has advantages in that the signal can be played back, filtered, and re-recorded on an oscillograph. In this manner, information that was originally recorded incorrectly on the oscillograph can be retrieved.

## METHODS OF ANALYSIS

Analysis of data comprises determination of frequency and amplitude of the oscillatory component and the time of occurrence of particular oscillations during burning. Characteristics of several methods of analysis appear in Table 2. Analysis of graphical data acquired at low recording speed is limited to determination of amplitude and occurrence of oscillations as a function of time. No information concerning frequency is available from such records except possibly in the case of LFI. High speed oscillograph records, on the other hand, can be assessed for frequency but the degree of success in frequency-amplitude determination

TABLE 2. Methods of Analysis

| TYPE OF DATA & ANALYSIS | | CHARACTER OF INFORMATION |
|---|---|---|
| GRAPHIC RECORDS | LOW SPEED | AMPLITUDE & TIME – LOW FREQUENCY RESOLUTION |
| | HIGH SPEED | AMPLITUDE, TIME, & FREQUENCY TO ~ 12kc |
| MAGNETIC TAPE | TIME SCALING | SAME AS ABOVE – FREQ. DEPENDS ON SCALE FACTOR |
| | SPECTRUM ANAL. | AMPLITUDE & FREQUENCY – NO TIME RESOLUTION |
| | SONIC ANAL. | CONTOUR MAP OF AMPLITUDE, FREQUENCY & TIME |

depends on the complexity of the signal. Signals which are composed of several frequencies at various amplitudes are difficult to assess accurately. Graphical methods for attaining a frequency-amplitude analysis are available but archaic in light of modern methods utilizing magnetic tape and electronic instruments for the task.

Capability to recreate the electrical impulses generated during the test offers a variety of approaches for analysis of data. The methods used in analysis of instability data are similar to those used in acoustics and vibration studies and depend on magnetic tape playback of the test signal. Tape signals can be analyzed by octave or third octave band, multiple band-pass with oscillograph recording to provide time resolution, electronic spectrum (heterodyne analyzer), and sonic analyzer techniques (Ref. 35, 36 and 38). Some of these methods require costly, specialized equipment and their use depends to a great extent on the nature of the data, the speed with which detailed analysis is required, and the ultimate utilization of the information.

## CONCLUSION

Measurement of combustion instability manifestations presents a variety of problems ranging from selection of transducer locations to choice of data analysis methods. Success in making instability measurements depends largely on using a systematic approach which includes the following steps:

1. Expect instability on every motor firing, especially following motor design, grain design, or propellant composition changes.

2. Calculate frequencies of the first longitudinal and first tangential acoustic modes.

3. Provide instrumentation and transducer mountings that will detect and record signals through the first tangential frequency. A single broad frequency response channel is often adequate for instability monitoring purposes.

Unfortunately, not all rocket motor firings are equipped with instrumentation which is suitable for instability measurement. While it is recognized that instability is only one of a large number of problems facing motor development engineers, instability is encountered often enough that plans should be made to provide every motor firing with some capability for instability measurement. Such provision is insurance against having to refire a motor in order to determine whether or not instability was the cause of anomalous behavior and will usually pay for itself in the time and money saved.

## REFERENCES


1. Hart, R. W. and F. T. McClure. "Combustion Instability: Acoustic Interaction with a Burning Propellant Surface," J CHEM PHYS, Vol. 30 (June 1959), pp. 1501-14.

2. Price, E. W. "Review of the Combustion Instability Characteristics of Solid Propellants, 25th Meeting of the AGARD Combustion and Propulsion Panel, San Diego, Calif., 22-24 April 1965."

3. Princeton University, Department of Aerospace and Mechanical Sciences. Solid Propellant Combustion Instability: Oscillatory Burning of Solid Rocket Propellants, by R. H. Woodward Waesche and Martin Summerfield. Princeton, N. J., Princeton Univ., August 1965. (Aerospace and Mechanical Sciences Report No. 751, under AFOSR Grant - 448-63, Project Task No. 920F-3814.)

4. Beckstead, M. W., N. W. Ryan, and A. D. Baer. "Non-Acoustic Instability of Composite Propellant Combustion," AMER INST AERONAUT ASTRONAUT J, Vol. 4, No. 9 (September 1966), pp. 1622-28.

5. Morse, P. M. Vibration and Sound, 2nd ed., New York, McGraw-Hill, 1948.

6. Crump, J. E., and E. W. Price. "Effect of Acoustic Environment on the Burning Rate of Double-Base Solid Propellants," AMER ROCKET SOC, J, Vol. 31, No. 7 (July 1961), pp. 1026-29.

7. Crump, J. E., and E. W. Price. "Effect of Acoustic Environment on the Burning Rate of Solid Propellants, AMER INST AERONAUT ASTRONAUT J, Vol. 2, No. 7 (July 1964), pp. 1274-78.

8. Crump. J. E., and E. W. Price. "'Catastrophic' Changes in Burning Rate of Solid Propellants During Combustion Instability," AMER ROCKET SOC, J, Vol. 30, No. 7 (July 1960), pp. 705-07.

9. Eisel, J. L. "The Effect of Acoustic Pressure on the Burning Rates of Solid Rocket Propellants," PYRODYNAMICS, Vol. 1 (1964), pp. 61-70.

10. Princeton University. An Investigation of Transverse Mode Combustion Instability in Liquid Propellant Rocket Motors, by F. H. Reardon. Princeton, N. J., Princeton Univ., 1 June 1961. (Aeronautical Engineering Report No. 550; also Ph.D. thesis.)

11. Price, E. W. U. S. Naval Ordnance Test Station memorandum, Subj: Combustion Instability w/encl (1) Combustion Instability in Solid Propellant Rocket Motors: Part II. The Acoustical Problems, dated 31 May 1957.

12. Chemical Propulsion Information Agency. Selection of Instrumentation for Analyzing Combustion Instability in Liquid Propellant Rocket Engines, by the Committee on Instrumentation. Silver Spring, Md., CPIA, July 1967. CPIA Publ. No. 148.

13. Beckstead, M. W., and E. W. Price. "Nonacoustic Combustor Instability," AMER INST AERONAUT ASTRONAUT J, Vol. 5, No. 11 (November 1967), pp. 1989-96.

14. Hart, R. W., and F. T. McClure. "Theory of Acoustic Instability in Solid Propellant Rocket Combustion," in Tenth Symposium (International) on Combustion. Pittsburgh, Pa., Combustion Institute, 1965. Pp. 1016-19.

15. Price, E. W. "Experimental Solid Rocket Combustion Instability," in Tenth Symposium (International) on Combustion. Pittsburgh, Pa., Combustion Institute, 1965. Pp. 1067-82.

16. Friedman, R. "Experimental Techniques for Solid-Propellant Combustion Research," AMER INST AERONAUT ASTRONAUT J, Vol. 5, No. 7 (July 1967), pp. 1217-23.

17. Mathes, H. B. "Effect of Geometrical Variables on Losses in Motors as Determined by Cold-Flow Testing," in 1st Combustion Instability Conference, Interagency Chemical Rocket Propulsion Group," comp. and ed. by Chemical Propulsion Agency. Silver Spring, Md., CPIA, January 1965. CPIA Publ. No. 68, Vol. 1, pp. 443-51.

18. Buffum, F. G., G. L. Dehority, R. O. Slates, and E. W. Price. "Acoustic Attenuation Experiments on Subscale, Cold-Flow Rocket Motors," AMER INST AERONAUT ASTRONAUT J, Vol. 5, No. 2 (February 1967), pp. 272-80.

19. Slates, R. O., and F. G. Buffum. "Nozzle Attenuation of Resonant Model-Rocket Motors," in 3rd Combustion Conference, Interagency Chemical Rocket Propulsion Group, comp. and ed. by Chemical Propulsion Information Agency. Silver Spring, Md., CPIA, February 1967. CPIA Publ. No. 138, Vol. 1, pp. 429-40.

20. Coates, R. L., M. D. Horton, and N. W. Ryan. "T-Burner Method of Determining the Acoustic Admittance of Burning Propellants," AMER INST AERONAUT ASTRONAUT J, Vol. 2, No. 6, (June 1964), p. 1119.

21. Horton, M. D. "Use of the One-Dimensional T-Burner to Study Oscillatory Combustion," AMER INST AERONAUT ASTRONAUT J, Vol 2, No. 6 (June 1964), pp. 1112-18.

22. Horton, M. D., and D. W. Rice. "The Effect of Compositional Variables Upon Oscillatory Combustion of Solid Rocket Propellants," COMBUST AND FLAME, Vol. 8, No. 1 (March 1964), pp. 21-8.

23. Stepp, E. E. "Effect of Pressure and Velocity Coupling on Low Frequency Instability," AMER INST AERONAUT ASTRONAUT J, Vol. 5, No. 5 (May 1967), p. 945.

24. Bird, J. F., F. T. McClure, and R. W. Hart. "Acoustic Instability in the Transverse Modes of Solid Propellant Rockets," XIIth International Astronautical Congress. New York, Academic Press, 1963. P. 459.

25. Bird, J. F., L. Haar, R. W. Hart, and F. T. McClure. "Effect of Solid Propellant Compressibility on Combustion Instability," J CHEM PHYS, Vol. 32 (1960), p. 1423.

26. Ryan, N. W., and R. L. Coates. "Acoustic Instability: Influence of and On the Solid Phase," AMER INST AERONAUT ASTRONAUT J, Vol. 2, No. 6 (June 1964), p. 1130.

27. U. S. Naval Ordnance Test Station. Acoustic Losses of a Subscale, Cold-Flow Rocket Motor for Various "J" Values, by F. G. Buffum, G. L. Dehority, R. O. Slates, and E. W. Price, China Lake, Calif., NOTS, February 1966. (NAVWEPS Report 8971, NOTS TP 3932).

28. Price, E. W. "Evidence for Velocity Coupling," in Proceedings of the 1st Interagency Chemical Rocket Propulsion Group Combustion Instability Conference, comp. and ed. by Chemical Propulsion Information Agency. Silver Spring, Md., CPIA, January 1965. CPIA Publ. No. 68, Vol. 1, pp. 403-8.

29. Price, E. W., and G. L. Dehority. "Velocity Coupled Axial Mode Combustion Instability in Solid Propellant Rocket Motors, in ICRPG/AIAA 2nd Solid Propulsion Conference. New York, American Institute of Aeronautics and Astronautics, 1967. P. 213.

30. Culick, Fred E. C. "Acoustic Oscillations in Solid Propellant Rocket Chambers," ASTRONAUT ACTA, Vol. 12, No. 2 (March-April 1966), p. 113.

31. Beckstead, M. W. Private communication at Naval Weapons Center, China Lake, Calif., August 1967.

32. Horton, M. D., J. L. Eisel, and E. W. Price. "Low Frequency Acoustic Oscillatory Combustion," AMER INST AERONAUT ASTRONAUT J, Vol. 1, No. 11 (November 1963), pp. 2652-54.

33. Mathes, H. B., and E. W. Price. Measurement of Combustion Dynamics of Solid Propellants in the Low Frequency Range. New York, American Institute of Aeronautics and Astronautics, 1967. AIAA Paper No. 67-70, 7 pp.

34. Eisel, J. L., M. D. Horton, E. W. Price, and D. W. Rice. "Preferred Frequency Oscillatory Combustion of Solid Propellants," AMER INST AERONAUT ASTRONAUT J, Vol. 2, No. 7 (July 1964), pp. 1319-23.

35. Price, E. W. "Experimental Measurements in Solid Propellant Rocket Combustion Instability," in Experimental Methods in Combustion Research, 2nd Suppl. New York, Pergamon, 1964. P. 531.

36. Mathes, H. B. "Measurement Problems in Research on Unstable Combustion of Solid Rocket Propellants," in Eighth Symposium (International) on Combustion. Baltimore, Md., Williams and Wilkins, 1962.

37. Princeton University, Department of Aeronautical Engineering. Summary Technical Report on Transient Pressure Measuring Methods Research, by J. P. Layton, R. C. Knauer, and J. P. Thomas. Princeton, N. J., Princeton Univ., September 1963. (Aeronautical Engineering Report No. 595, under NASA Contract NASr-36.)

38. Beranek, Leo L. Acoustic Measurements. New York, Wiley, 1949.

## INITIAL DISTRIBUTION

11 Naval Air Systems Command
- AIR-03 (1)
- AIR-03B (1)
- AIR-310 (1)
- AIR-330 (1)
- AIR-330B (1)
- AIR-503 (1)
- AIR-536 (1)
- AIR-5366 (1)
- AIR-5367 (1)
- AIR-604 (2)

4 Chief of Naval Material
- NSP-00 (1)
- NSP-001 (1)
- NSP-20 (1)
- NSP-2733 (1)

5 Naval Ordnance Systems Command
- ORD-033 (1)
- ORD-03311 (1)
- ORD-03312 (1)
- ORD-9132 (2)

1 Office of Naval Research (Code 429)

2 Naval Ordnance Laboratory, White Oak
- Carl Boyars (1)
- Technical Library (1)

2 Naval Ordnance Station, Indian Head
- L. A. Dickinson (1)
- Technical Library (1)

3 Army Missile Command, Redstone Arsenal (Redstone Scientific Information Center, Chief Document Section)

2 Army Ballistics Research Laboratories, Aberdeen Proving Ground
- Interior Ballistics Laboratory
  - R. C. Strittmater (1)
- Technical Library (1)

2 Picatinny Arsenal
- J. Picard (1)
- Technical Library (1)

1 Sunflower Army Ammunition Plant (SMUSU-R)

1 Air Force Office of Scientific Research (Propulsion Division, Dr. Bernard T. Wolfson)

2 Air Force Rocket Propulsion Laboratory, Edwards (RPMCP)
  Capt. C. E. Payne (1)
  Richard Spann (1)
2 6593 Test Group, Edwards Air Force Base (Development, Don Hart)
1 Advanced Research Projects Agency (Technical Information Office)
20 Defense Documentation Center
1 Bureau of Mines, Pittsburgh (Explosive Research Center, I. Liebman)
19 National Aeronautics & Space Administration
  MGS, E. Hall (1)
  MTA, M. C. Waugh (1)
  NaPO, John J. Stashak (1)
  RC, J. L. Sloop (1)
  RF, R. D. Ginter (1)
  RP, A. O. Tischler (1)
  RPM, William Cohen (1)
  RPS, R. Ziem (5)
  RTA, R. V. Hensley (1)
  RTP, J. J. Phillips (1)
  RV, M. B. Ames (1)
  RV-1, R. W. May, Jr. (1)
  SV, V. L. Johnson (1)
  ATSS-AC, Technical Library (2)
1 George C. Marshall Space Flight Center (Technical Library)
1 Goddard Space Flight Center (Technical Library)
2 Langley Research Center
  Robert L. Swain (1)
  Technical Library (1)
4 Lewis Research Center
  Dr. Louis A. Povinelli (1)
  Dr. Richard J. Priem (1)
  James J. Kramer (1)
  Technical Library (1)
2 Manned Spacecraft Center
  J. G. Thibodaux (1)
  Technical Library (1)
1 NASA Scientific and Technical Information Facility, College Park, Md. (CRT)
1 Aerojet-General Corporation, Azusa, Calif. (Library), via NPRO
3 Aerojet-General Corporation, Sacramento, via AFPRO
  J. Wiegand (1)
  Department 4730 (1)
  Head, Technical Information Office (1)
1 Aerospace Corporation, Los Angeles (Library)
2 Allegany Ballistics Laboratory, Cumberland, Md.
  T. A. Angelus (1)
  Technical Library (1)
2 Applied Physics Laboratory, JHU, Silver Spring
  Dr. W. H. Avery (1)
  Dr. Robert H. Cantrell (1)

UNCLASSIFIED
Security Classification

## DOCUMENT CONTROL DATA - R&D

*(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)*

| | |
|---|---|
| 1. ORIGINATING ACTIVITY *(Corporate author)*<br>Naval Weapons Center<br>China Lake, California 93555 | 2a. REPORT SECURITY CLASSIFICATION<br>UNCLASSIFIED<br>2b GROUP |

3. REPORT TITLE

MEASUREMENT PROBLEMS RELATED TO SOLID ROCKET COMBUSTION INSTABILITY

4. DESCRIPTIVE NOTES *(Type of report and inclusive dates)*
Research Report

5. AUTHOR(S) *(Last name, first name, initial)*

Mathes, H. B.

| | | |
|---|---|---|
| 6. REPORT DATE<br>July 1968 | 7a. TOTAL NO. OF PAGES<br>22 | 7b. NO. OF REFS<br>38 |
| 8a. CONTRACT OR GRANT NO.<br>b. PROJECT NO.<br>c. ORD-033 103/200 1/F009-06-01, PA #3<br>d. | 9a. ORIGINATOR'S REPORT NUMBER(S)<br>NWC TP 4593<br>9b. OTHER REPORT NO(S) *(Any other numbers that may be assigned this report)* | |

10. AVAILABILITY/LIMITATION NOTICES
This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of the Naval Weapons Center.

| | |
|---|---|
| 11. SUPPLEMENTARY NOTES | 12. SPONSORING MILITARY ACTIVITY<br>Naval Ordnance Systems Command<br>Navy Material Command<br>Washington, D. C. 20360 |

13. ABSTRACT

A review is presented of the classes of instability, conditions favoring each class, experimental measurements recognized to diagnose each class, and problems in conducting such measurements.

DD FORM 1 JAN 64 1473 0101-807-6800

UNCLASSIFIED
Security Classification

UNCLASSIFIED

Security Classification

| 14. KEY WORDS | LINK A ROLE | LINK A WT | LINK B ROLE | LINK B WT | LINK C ROLE | LINK C WT |
|---|---|---|---|---|---|---|
| Solid propellant rockets<br>Combustion instability<br>Instability measurement | | | | | | |

## INSTRUCTIONS

1. ORIGINATING ACTIVITY: Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization *(corporate author)* issuing the report.

2a. REPORT SECURITY CLASSIFICATION: Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. GROUP: Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. REPORT TITLE: Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. DESCRIPTIVE NOTES: If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. AUTHOR(S): Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. REPORT DATE: Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. TOTAL NUMBER OF PAGES: The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. NUMBER OF REFERENCES: Enter the total number of references cited in the report.

8a. CONTRACT OR GRANT NUMBER: If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. PROJECT NUMBER: Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. ORIGINATOR'S REPORT NUMBER(S): Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. OTHER REPORT NUMBER(S): If the report has been assigned any other report numbers *(either by the originator or by the sponsor)*, also enter this number(s).

10. AVAILABILITY/LIMITATION NOTICES: Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

(1) "Qualified requesters may obtain copies of this report from DDC."

(2) "Foreign announcement and dissemination of this report by DDC is not authorized."

(3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."

(4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."

(5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. SUPPLEMENTARY NOTES: Use for additional explanatory notes.

12. SPONSORING MILITARY ACTIVITY: Enter the name of the departmental project office or laboratory sponsoring *(paying for)* the research and development. Include address.

13. ABSTRACT: Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as *(TS)*, *(S)*, *(C)*, or *(U)*.

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. KEY WORDS: Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.

UNCLASSIFIED

Security Classification

# ABSTRACT CARD

Naval Weapons Center
Measurement Problems Related to Solid Rocket Combustion Instability, by H. B. Mathes. China Lake, Calif., NWC, July 1968. 22 pp. (NWC TP 4593), UNCLASSIFIED.

ABSTRACT. A review is presented of the classes of instability, conditions favoring each class, experimental measurements recognized to diagnose each class, and problems in conducting such measurements.

1 card, 8 copies

Naval Weapons Center
Measurement Problems Related to Solid Rocket Combustion Instability, by H. B. Mathes. China Lake, Calif., NWC, July 1968. 22 pp. (NWC TP 4593), UNCLASSIFIED.

ABSTRACT. A review is presented of the classes of instability, conditions favoring each class, experimental measurements recognized to diagnose each class, and problems in conducting such measurements.

1 card, 8 copies

Naval Weapons Center
Measurement Problems Related to Solid Rocket Combustion Instability, by H. B. Mathes. China Lake, Calif., NWC, July 1968. 22 pp. (NWC TP 4593), UNCLASSIFIED.

ABSTRACT. A review is presented of the classes of instability, conditions favoring each class, experimental measurements recognized to diagnose each class, and problems in conducting such measurements.

1 card, 8 copies

Naval Weapons Center
Measurement Problems Related to Solid Rocket Combustion Instability, by H. B. Mathes. China Lake, Calif., NWC, July 1968. 22 pp. (NWC TP 4593), UNCLASSIFIED.

ABSTRACT. A review is presented of the classes of instability, conditions favoring each class, experimental measurements recognized to diagnose each class, and problems in conducting such measurements.

1 card, 8 copies

# ABSTRACT CARD

Naval Weapons Center
Measurement Problems Related to Solid Rocket Combustion Instability, by H. B. Mathes. China Lake, Calif., NWC, July 1968. 22 pp. (NWC TP 4593), UNCLASSIFIED.

ABSTRACT. A review is presented of the classes of instability, conditions favoring each class, experimental measurements recognized to diagnose each class, and problems in conducting such measurements.

1 card, 8 copies

Naval Weapons Center
Measurement Problems Related to Solid Rocket Combustion Instability, by H. B. Mathes. China Lake, Calif., NWC, July 1968. 22 pp. (NWC TP 4593), UNCLASSIFIED.

ABSTRACT. A review is presented of the classes of instability, conditions favoring each class, experimental measurements recognized to diagnose each class, and problems in conducting such measurements.

1 card, 8 copies

Naval Weapons Center
Measurement Problems Related to Solid Rocket Combustion Instability, by H. B. Mathes. China Lake, Calif., NWC, July 1968. 22 pp. (NWC TP 4593), UNCLASSIFIED.

ABSTRACT. A review is presented of the classes of instability, conditions favoring each class, experimental measurements recognized to diagnose each class, and problems in conducting such measurements.

1 card, 8 copies

Naval Weapons Center
Measurement Problems Related to Solid Rocket Combustion Instability, by H. B. Mathes. China Lake, Calif., NWC, July 1968. 22 pp. (NWC TP 4593), UNCLASSIFIED.

ABSTRACT. A review is presented of the classes of instability, conditions favoring each class, experimental measurements recognized to diagnose each class, and problems in conducting such measurements.

1 card, 8 copies

3 Atlantic Research Corporation, Alexandria, Va.
  Dr. Raymond Friedman (1)
  K. Woodcock (1)
  Technical Library (1)
1 Bermite Powder Company, Saugus, Calif.
1 Bolt, Beranek and Newman, Inc., Cambridge, Mass. (E. E. Unger)
1 Brigham Young University, Provo, Utah (R. L. Coates)
1 Bruce H. Sage Consultant, Pasadena
2 California Institute of Technology, Pasadena
  Dr. F. E. C. Culick (1)
  Dr. Frank E. Marble (1)
1 CETEC Corporation, Mountain View, Calif. (R. Anderson)
2 Chemical Propulsion Information Agency, Applied Physics Laboratory, Silver Spring
  T. W. Christian, III (1)
  Technical Library (1)
1 Columbia University, New York (Department of Mechanical Engineering, Dr. R. A. Gross)
1 Cornell Aeronautical Laboratory, Inc., Buffalo (Dr. G. H. Markstein)
1 Davidson Laboratory, Stevens Institute of Technology, Hoboken N. J. (R. F. McAlvey, III)
1 Defense Research Corporation, Santa Barbara (Dr. A. Berlad)
1 Georgia Institute of Technology, Atlanta (Dr. B. Zinn)
1 Hercules Incorporated, Bacchus, Utah (Technical Library)
1 Institute for Defense Analyses, Arlington (Technical Library)
3 Jet Propulsion Laboratory, CIT, Pasadena
  Dr. Leon Strand (1)
  Winston Gin (1)
  Technical Library (1)
1 Lockheed Missiles & Space Company, Palo Alto (C. A. Zimmerman)
2 Lockheed Propulsion Company, Redlands, Calif.
  Dr. M. W. Beckstead (1)
  Technical Library (1)
1 Marquardt Corporation, Van Nuys, Calif. (Technical Library)
1 Martin Company, Denver (R. Knoll)
1 Northern Research and Engineering Corporation, Cambridge, Mass. (K. Bastress)
1 Pennsylvania State University, University Park (Mechanical Engineering Department, G. M. Faeth)
2 Princeton University, Forrestal Campus Library
  Dr. Irvin Glassman (1)
  Dr. Martin Summerfield (1)
1 Purdue University, Lafayette, Ind. (School of Mechanical Engineering, Dr. John R. Osborn)
1 Rocket Research Corporation, Seattle (Technical Library)
3 Rocketdyne, Canoga Park, Calif.
  Dr. G. Lo (1)
  C. L. West (1)
  Library, Department 596-306 (1)

2 Rocketdyne, McGregor, Tex.
S. C. Britton (1)
Technical Library (1)
2 Rohm & Haas Company, Redstone Arsenal Research Division
Dr. William A. Wood (1)
Technical Library (1)
1 Sandia Corporation, Albuquerque (Dr. Lloyd S. Nelson)
2 Stanford Research Institute, Menlo Park, Calif.
Dr. M. Evans (1)
Dr. G. A. Marxman (1)
1 Texaco Experiment, Inc., Richmond, Va. (U. V. Henderson)
2 Thiokol Chemical Corporation, Elkton, Md.
E. E. Hackman (1)
Technical Library (1)
2 Thiokol Chemical Corporation, Huntsville Division, Huntsville, Ala.
Technical Director (1)
D. A. Flanigan (1)
2 Thiokol Chemical Corporation, Wasatch Division, Brigham City
Dr. R. Reed, Jr. (1)
Technical Library (1)
1 United Aircraft Corporation, East Hartford (Research Laboratories, Dr. R. Waesche)
3 United Technology Center, Sunnyvale, Calif.
Dr. R. S. Brown (1)
Dr. Robert W. Hermsen (1)
Technical Library (1)
2 University of California, Berkeley
Aeronautical Science Division, Dr. A. K. Oppenheim (1)
Chemistry Department, E. Peterson (1)
2 University of California, San Diego, La Jolla (Department of Aerospace Engineering )
Dr. Stanford S. Penner (1)
F. A. Williams (1)
1 University of Denver, Denver Research Institute (James Kottenstette)
2 University of Utah, Salt Lake City (Department of Chemical Engineering)
Prof. A. Baer (1)
Prof. N. W. Ryan (1)