AD-A041 854

TECHNICAL LIBRARY

AD

BRL MR 2

BRL

MEMORANDUM REPORT NO. 2757

SHOCK WAVE ATTENUATION BY PERFORATED PLATES WITH VARIOUS HOLE SIZES

Charles Kingery
Richard Pearson
George Coulter

June 1977

Approved for public release; distribution unlimited.

DTIC QUALITY INSPECTED 3

USA ARMAMENT RESEARCH AND DEVELOPMENT COMMAND
USA BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

Destroy this report when it is no longer needed.
Do not return it to the originator.

Secondary distribution of this report by originating or sponsoring activity is prohibited.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, Springfield, Virginia 22151.

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE

READ INSTRUCTIONS BEFORE COMPLETING FORM

1. REPORT NUMBER
BRL Memorandum Report No. 2757

2. GOVT ACCESSION NO.

3. RECIPIENT'S CATALOG NUMBER

4. TITLE (and Subtitle)
SHOCK WAVE ATTENUATION BY PERFORATED PLATES WITH VARIOUS HOLE SIZES

5. TYPE OF REPORT & PERIOD COVERED
Final

6. PERFORMING ORG. REPORT NUMBER

7. AUTHOR(s)
Charles Kingery
Richard Pearson
George Coulter

8. CONTRACT OR GRANT NUMBER(s)

9. PERFORMING ORGANIZATION NAME AND ADDRESS
USA Ballistic Research Laboratory
Aberdeen Proving Ground, Maryland 21005

10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS

11. CONTROLLING OFFICE NAME AND ADDRESS
US Army Materiel Development & Readiness Command
5001 Eisenhower Avenue
Alexandria, Virginia 22304

12. REPORT DATE
JUNE 1977

13. NUMBER OF PAGES
71

14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)

15. SECURITY CLASS. (of this report)
Unclassified

15a. DECLASSIFICATION/DOWNGRADING SCHEDULE

16. DISTRIBUTION STATEMENT (of this Report)
Approved for public release; distribution unlimited.

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES
The work reported here was performed for, and funded by PA, A4932 MM&T Project No. 5751264, Advanced Technology for Suppressive Shielding of Hazardous Production and Supply Operations for Production Base Modernization and Expansion (Program)

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

Blast Attenuation	Shock Tube Tests
Flow Restrictions	Shock Waves
Panel Venting	Suppressive Structures
Perforated Plates	

20. ABSTRACT (Continue on reverse side if necessary and identify by block number) (1jc)

Results are presented for a set of experiments designed to determine the attenuation of shock waves passing through perforated plates as a function of peak overpressure and hole size for a given percentage of plate area vented. The venting hole size was varied from 1/8 inch (0.32 cm) to 2-13/16 inches (7.14 cm) as the vented area was varied from 5-50 percent open. The perforated plates were exposed to shock waves in a 4-inch (10.2 cm) shock tube over a range of peak shock overpressures from 200 psi (1379 kPa) down to 48 psi (331 kPa).

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

TABLE OF CONTENTS

		Page
	LIST OF FIGURES	5
	LIST OF TABLES	7
	AUTHORS' COMMENTS	9
I.	INTRODUCTION	11
	A. Background	11
	B. Objectives	11
II.	EXPERIMENT	11
	A. Instrumentation	11
	B. Plate Design	12
III.	RESULTS	12
	A. Shock Tube Calibration	12
	B. Transmitted Pressure	19
	C. Pressure Transmission Ratio	26
IV.	CONCLUSIONS	27
	APPENDIX - PRESSURE-TIME DATA	45
	LIST OF SYMBOLS	61
	DISTRIBUTION LIST	63

LIST OF FIGURES

Figure		Page
1.	Shock Tube Test Setup	13
2.	Arrangement of Holes in the Test Plates	15
3.	Input Pressure P_I versus Transmitted Pressure P_T for A_v of 100 Percent	20
4.	Pressure versus Time Recorded at Stations 3 and 6 for an Input Pressure of 50 PSI (345 kPa)	21
5.	Pressure versus Time Recorded at Stations 3 and 6 for an Input Pressure of 119 PSI (830 kPa)	22
6.	Pressure versus Time Recorded at Stations 3 and 6 for an Input Pressure of 195 PSI (1344 kPa)	23
7.	Pressure versus Time at Stations 3 and 6 for Input Pressure of 50 PSI - 25 Percent Open	24
8.	Transmitted Pressure versus Input Pressure for Different Percentages of Area Vented	25
9.	Pressure Transmission Ratio as a Function of Percent of Area Vented	42
10.	Percent Pressure Attenuation as a Function of Percent of Area Vented	43
A-1	Pressure-Time Traces Recorded at Stations 3 and 6 - 4.69 Percent Open	47
A-2	Pressure-Time Traces Recorded at Stations 3 and 6 - 5.1 Percent Open	48
A-3	Pressure-Time Traces Recorded at Stations 3 and 6 - 7.8 Percent Open	49
A-4	Pressure-Time Traces Recorded at Stations 3 and 6 - 9.37 Percent Open	50
A-5	Pressure-Time Traces Recorded at Stations 3 and 6 - 10.2 Percent Open	51
A-6	Pressure-Time Traces Recorded at Stations 3 and 6 - 25 Percent Open, 1/2-Inch Holes	52

LIST OF FIGURES (Cont'd)

Figure		Page
A-7	Pressure-Time Traces Recorded at Stations 3 and 6 - 25 Percent Open, 1/8-Inch Holes	53
A-8	Pressure-Time Traces Recorded at Stations 3 and 6 - 26.6 Percent Open	54
A-9	Pressure-Time Traces Recorded at Stations 3 and 6 - 30 Percent Open	55
A-10	Pressure-Time Traces Recorded at Stations 3 and 6 - 38.2 Percent Open	56
A-11	Pressure-Time Traces Recorded at Stations 3 and 6 - 41.0 Percent Open	57
A-12	Pressure-Time Traces Recorded at Stations 3 and 6 - 49.4 Percent Open	58
A-13	Pressure-Time Traces Recorded at Stations 3 and 6 - 50 Percent Open	59

LIST OF TABLES

Table		Page
I.	Test Plates	14
II.	Pressure Attenuation, Plate 1 - 3, 1/2-Inch Holes - 4.69 Percent Open	28
III.	Pressure Attenuation, Plate 2 - 52, 1/8-Inch Holes - 5.1 Percent Open	29
IV.	Pressure Attenuation, Plate 3 - 5, 1/2-Inch Holes - 7.8 Percent Open	30
V.	Pressure Attenuation, Plate 4 - 6, 1/2-Inch Holes - 9.37 Percent Open	31
VI.	Pressure Attenuation, Plate 5 - 105, 1/8-Inch Holes - 10.2 Percent Open	32
VII.	Pressure Attenuation, Plate 6 - 16, 1/2-Inch Holes - 25 Percent Open	33
VIII.	Pressure Attenuation, Plate 7 - 256, 1/8-Inch Holes - 25 Percent Open	34
IX.	Pressure Attenuation, Plate 8 - 68, 1/4-Inch Holes - 26.6 Percent Open	35
X.	Pressure Attenuation, Plate 9 - 307, 1/8-Inch Holes - 30 Percent Open	36
XI.	Pressure Attenuation, Plate 10 - 392, 1/8-Inch Holes - 38.2 Percent Open	37
XII.	Pressure Attenuation, Plate 11 - 105, 1/4-Inch Holes - 41.0 Percent Open	38
XIII.	Pressure Attenuation, Plate 12 - 1, 2-13/16-Inch Hole - 49.4 Percent Open	39
XIV.	Pressure Attenuation, Plate 13 - 32, 1/2-Inch Holes - 50 Percent Open	40
XV.	Pressure Attenuation versus Area Vented	41
A-I.	Data for Pressure-Time Records	46

AUTHORS' COMMENTS

Both the English system of units and SI units have been used in this report with the exception of the data tables where the gage calibrations and computer output for overpressure are in pounds per square inch. Dual scales were not used because the primary objective of the tables is to determine ratios and percentages of input pressure and transmitted pressure which would be the same in either system of units.

There is also a need to keep continuity of the present results with previously published results (Reference 1) conceived with the same subject matter. All equations developed in this report satisfy both systems of units.

I. INTRODUCTION

This is the second* in a series of reports which define the parameters affecting the attenuation of shock waves passing through vented wall plates. Results are reported here for the attenuation of shock waves through single perforated plates as a function of the number and size of vent holes in a plate.

A. Background

Under the US Army's Production Base Modernization (PBM) program for munition processing facilities, a two-phase program has been initiated to develop suppressive shields. One phase, the Category Shield program, will produce a series of shields for specific munition applications.

For the second phase, the Applied Technology Development Phase, a major responsibility has been given to the Ballistic Research Laboratory (BRL). The basic requirement of this phase is to develop a general technology base for suppressive shields. The basic design criteria require containment of fragments and attenuation of the blast wave from accidental explosions in munition processing plants. This report is concerned with the blast attenuation part of the requirement.

B. Objectives

1. Define and determine the suppressive structure parameters which affect the attenuation of the blast wave.

2. Develop an understanding of blast wave suppression so as to design an efficient blast suppressor.

The objective of this report is to present results obtained from a study of pressure attenuation of shock waves passing through perforated plates. The variables were hole size, number of holes, and incident peak overpressure.

II. EXPERIMENT

This section describes the experimental equipment and design of the perforated plates.

A. Instrumentation

The shock waves were generated inside a 4-inch (10.2 cm) inside diameter shock tube. The driver section used was 12 inches (30.48 cm)

**The first report is entitled, "Shock Wave Attenuation by Single Perforated Plates," Charles Kingery and George Coulter, BRL Memorandum Report 2664, August 1976.*

long; driver gas was helium. The test station was located 100 inches (254 cm) from the diaphragm at the driver section. Another 200 inches (508 cm) of tube was added downstream of the test station to delay the return of reflections from the closed end.

The short driver section was chosen so as to form a peaked decaying shock wave similar to that produced by a high explosive detonation. Calibrated aluminum and copper diaphragm materials were used to contain the driver gas in the compression chamber until the desired pressure was obtained. Figure 1 shows a sketch of the shock tube.

Pressure-time profiles of the shock waves were recorded at the locations shown in the sketch. The transducers were tourmaline crystal type, Model ST-4, manufactured by Susquehanna Instruments Company. They were threaded into the shock tube wall as nearly flush as possible. Charge amplifiers, Kistler Model 506; and oscilloscopes, Tektronix Model 502-A; completed the recording instrumentation.

B. Plate Design

The perforated plates were designed to investigate the effect of number of holes and hole size on shock wave attenuation for different incident peak overpressures*. Several vent areas, A_v, in the range from 5-50 percent were chosen for testing. The number and diameter of the holes were varied for each of the several percentages of area vented.

Single steel plates, 0.25 inch (0.64 cm) thick, were bolted between the flanges of the shock tube at the point shown in Figure 1. The number, diameter, and size of the holes in the various plates are listed in Table I. Sketches of the plates are shown in Figure 2.

III. RESULTS

The test results are presented in three sections covering the shock tube calibration, the transmitted pressure, and the pressure transmission ratio.

A. Shock Tube Calibration

The shock tube was calibrated by measuring the attenuation of the shock waves with distance along the shock tube when no plates were installed; i.e., when A_v = 100 percent open.

This was done by measuring a series of shock over-pressure levels between gage Station 3 and Station 6. The earlier work, as noted in

All pressures discussed in this report are overpressures, not absolute values.



Figure 1. Shock Tube Test Setup

Table I. Test Plates

Plate No.	No. of Holes	Hole Diameter inches	Hole Diameter (cm)	Hole Area $inches^2$	Hole Area (cm^2)	A_v Area Vented Percent
1	3	0.50	(1.27)	0.196	(1.267)	4.69
2	52	0.125	(0.32)	0.012	(0.080)	5.1
3	5	0.50	(1.27)	0.196	(1.267)	7.81
4	6	0.50	(1.27)	0.196	(1.267)	9.37
5	105	0.125	(0.32)	0.012	(0.080)	10.2
6	16	0.50	(1.27)	0.196	(1.267)	25.0
7	256	0.125	(0.32)	0.012	(0.080)	25.0
8	68	0.25	(0.64)	0.049	(0.322)	26.6
9	307	0.125	(0.32)	0.012	(0.080)	30.0
10	392	0.125	(0.32)	0.012	(0.080)	38.2
11	105	0.25	(0.64)	0.049	(0.322)	41.0
12	1	2.81	(7.14)	6.202	(40.04)	49.4
13	32	0.50	(1.27)	0.196	(1.267)	50.0
-	1	4.0	(10.2)	12.566	(81.073)	100.

$$A_v = \frac{\text{Hole Area x Number of Holes}}{\text{Cross-Section Area of Shock Tube}} \times 100$$



PLATE 1 - 4.69 % OPEN
3 HOLES, 1/2" DIA.



PLATE 2 - 5.1 % OPEN
52 HOLES, 1/8" DIA.



PLATE 3 - 7.81 % OPEN
5 HOLES, 1/2" DIA.



PLATE 4 - 9.37 % OPEN
6 HOLES, 1/2" DIA.

Figure 2. Arrangement of Holes in the Test Plates



PLATE 5 - 10.2% OPEN
105 HOLES, 1/8" DIA.



PLATE 6 - 25% OPEN
16 HOLES, 1/2" DIA.



PLATE 7 - 25% OPEN
256 HOLES, 1/8" DIA.



PLATE 8 - 26.6% OPEN
68 HOLES, 1/4" DIA.

Figure 2. (Cont'd) Arrangement of Holes in the Test Plates



PLATE 9 - 30 % OPEN
308 HOLES, 1/8" DIA.



PLATE 10 - 38.2 % OPEN
392 HOLES, 1/8" DIA.



PLATE 11 - 41 % OPEN
105 HOLES, 1/4" DIA.



PLATE 12 - 49.4 % OPEN
1 HOLE, 2-13/16" DIA.

Figure 2. (Cont'd) Arrangement of Holes in the Test Plates



PLATE 13 - 50 % OPEN
32 HOLES, 1/2" DIA.

Figure 2. (Cont'd) Arrangement of Holes in the Test Plates

Reference 1, determined a calibration curve for the shock tube over a range of overpressure from 45 psi (310 kPa) to 218 psi (1503 kPa). This curve with data points is presented in Figure 3. The straight line fit is represented by Equation 1,

$$P_T\ 100 = 0.7855\ P_I \tag{1}$$

when P_T 100 is the transmitted pressure for A_v = 100 percent and P_I is the input pressure.

The peak overpressure measured at Station 6 when a perforated plate is in the shock tube will be compared to the value calculated from Equation 1 for the input pressure of a given shot.

Figures 4 through 6 show typical record traces within the calibrated range of the shock tube. The upper traces are the input condition at Station 3 and the lower traces are attenuated pressures recorded at Station 6 for the unobstructed shock tube.

B. Transmitted Pressure

Section A described the pressure transmitted down the unobstructed shock tube. This section will deal with the pressure transmitted down the shock tube when plates with various vented areas are inserted in the tube. Presented in Figure 7 is a typical set of traces from the shock tube when obstructed by a perforated plate. Other representative pressure-time traces are grouped in the Appendix.

Tables II through XIV list the attenuation results of the shock wave-plate interactions. Columns 2 and 3 of the tables list the input pressure (P_I) at Station 3 and the attenuated, transmitted pressure (P_T) at Station 6, respectively. Column 5 lists the transmitted pressure for the unobstructed no-plate case (A_v = 100%) as calculated from Equation 1 above.

Figure 8 shows how the transmitted pressure (P_T) varies with input pressure (P_I) for various percentages of vented plate area. The family of curves (the solid lines) for the control plates with half-inch holes may be represented by the equation:

$$P_T = C\ P_I \tag{2}$$

[1] *Charles Kingery and George Coulter, "Shock Wave Attenuation by Single Perforated Plates," BRL Memorandum Report 2664, August 1976.* (AD #B013764L)



Figure 3. Input Pressure P_I versus Transmitted Pressure P_T for A_V of 100 Percent



(A) INPUT PRESSURE



(B) TRANSMITTED PRESSURE

Figure 4. Pressure versus Time Recorded at Station 3 and 6 for an Input Pressure of 50 psi (345 kPa)



(A) INPUT PRESSURE



(B) TRANSMITTED PRESSURE

Figure 5. Pressure versus Time Recorded at Station 3 and 6 for an Input Pressure of 119 psi (820 kPa)



(A) INPUT PRESSURE



(B) TRANSMITTED PRESSURE

Figure 6. Pressure versus Time Recorded at Station 3 and 6 for an Input Pressure of 195 psi (1344 kPa)



PLATE 6 - INPUT PRESSURE



PLATE 6 - TRANSMITTED PRESSURE

Figure 7. Pressure versus Time at Stations 3 and 6 for Input Pressure of 50 PSI - 25 Percent Open



Figure 8. Transmitted Pressure versus Input Pressure for Different Percentages of Area Vented

where C is a function of the plate area vented. Values of C were calculated from a simple ratio of the data P_T for x percent opening (Column 3) divided by P_I (Column 2). The C values are listed in Column 4 of Tables II through XIV.

It can be seen from the average values of C listed in Tables II through XIV that there is no significant effect of the hole size or number of holes in a plate with the exception of Plate 2 and Plate 5 both with 1/8-inch diameter holes consisting of 52 and 105 in number.

C. Pressure Transmission Ratio

The last two columns of Tables II through XIV contain quantities that are helpful in defining the effectiveness of a perforated plate attenuator. The first quantity is defined as the transmission ratio (P_{TR}). It is defined as

$$P_{TR} = \frac{P_T \text{ with vented plate}}{P_T \text{ 100 without a plate}}, \tag{3}$$

where P_T is the transmitted pressure in each case.

A second quantity, the percentage of attenuation may be more helpful in some cases. It is equal simply to $(1 - P_{TR}) \times 100$. The average values listed of these quantities in Tables II through XIV are summarized in Table XV.

An equation of the form

$$P_{TR} = B\ A_V^{\ N} \tag{4}$$

was used to fit the data for the transmission ratio (P_{TR}) as a function of area vented (A_V). B and N have the values of 0.1094 and 0.5135, respectively, for plates with half-inch holes for area vented below 50 percent.

The data from the new plates listed in Table XV show little scatter from the values established from plates with the one-half inch diameter holes.

For a given A_V and P_I the value of P_T can be determined by calculating P_{TR} from Equation 4 and P_T 100 from Equation 1 and substituting in to Equation 3 to obtain

$$P_T = (0.7855\ P_I)\ P_{TR} \tag{5}$$

It also follows that by dividing both sides of Equation 5 by P_I, one obtains from Equation 2,

$$C = 0.7855\ P_{TR}, \text{ and} \tag{6}$$

if C is determined from Tables II through XIV then

$$P_{TR} = C/0.7855. \tag{7}$$

A direct comparison of the experimental values of the Pressure Transmission Ratio (P_{TR}) and the percent of pressure attenuation listed in Tables II through XIV has been made with values calculated using Equation 4. These comparisons are made in Table XV.

The values of pressure transmission ratio and pressure attenuation percent from Table XV have been plotted in Figures 9 and 10, respectively. The solid line represents the calculated values from Equation 4 which was established from the experimental values obtained from the plates with half-inch (1.27 cm) holes. The symbols indicate how well the data compare when obtained from plates with different hole sizes. The data from a A_V of 5.1 and 10.2 percent differ most from the trend established from previous tests. It should be noted in Table XV that when plates with a similar A_V are tested the values of attenuation percent are also similar.

IV. CONCLUSIONS

Based upon the experimental results obtained, a perforated plate did not change appreciably its ability to attenuate shock waves when the hole size was changed. It was only at the small values of A_V with 1/8 hole size that a deviation from the established trend was noted.

There was no trend established for pressure transmission ratio or attenuation percent as a function of input pressure (P_I) for a given A_V. The expression

$$P_T = C\ P_I$$

appears to be valid for range of pressures and vent areas tested.

Table II. Pressure Attenuation Plate 1, 3, 1/2-Inch Holes - 4.69 Percent Open

Shot Number	Input Pressure (P_I) psi	Transmitted Pressure (P_T) A_v = 4.69% psi	Ratio (C) P_T 4.69/P_I	Transmitted Pressure (P_T) A_v = 100%	Ratio (P_{TR}) P_T 4.69/P_T 100	Attenuation Percent
18	197.0	35.8	0.182	154.5	0.232	76.8
19	192.0	38.9	0.203	150.6	0.258	74.2
20	120.9	20.4	0.169	94.8	0.215	78.5
21	123.3	23.8	0.193	96.8	0.246	75.4
22	127.0	21.7	0.171	99.6	0.218	78.2
23	49.3	9.8	0.199	38.6	0.254	74.6
24	49.1	9.3	0.189	38.5	0.242	75.8
25	51.2	9.2	0.180	40.1	0.229	77.1
	Average		0.185		0.237	76.3

NOTE: Psi x 6.894757 = kPa.

Table III. Pressure Attenuation, Plate 2, 52, 1/8-Inch Holes - 5.1 Percent Open

Shot Number	Input Pressure (P_I) psi	Transmitted Pressure (P_T) A_v = 5.1% psi	Ratio C P_T 5.1/P_I	Transmitted Pressure (P_T) A_v = 100%	Ratio (P_{TR}) P_T 5.1/P_T 100	Attenuation Percent
77	193.6	30.9	0.160	152.1	0.203	79.7
78	199.1	33.5	0.168	156.4	0.214	78.6
79	126.1	22.3	0.177	99.1	0.225	77.5
80	126.1	16.6	0.132	99.1	0.168	83.2
81	128.3	18.1	0.141	100.8	0.180	82.0
82	46.5	7.2	0.155	36.5	0.197	80.3
83	47.6	7.2	0.151	37.4	0.193	80.7
84	46.5	6.8	0.146	36.5	0.186	81.4
	Average		0.154		0.196	80.4

Table IV. Pressure Attenuation, Plate 3,
5, 1/2-Inch Holes - 7.81 Percent Open

Shot Number	Input Pressure (P_I) psi	Transmitted Pressure (P_T) A_V = 7.81% psi	Ratio C P_T 7.8/P_I	Transmitted Pressure (P_T) A_V = 100%	Ratio (P_{TR}) P_T 7.81/P_T 100	Attenuation Percent
296	197.6	47.8	0.242	155.0	0.308	69.2
297	196.4	53.3	0.271	154.1	0.345	65.4
282	67.9	17.0	0.250	53.2	0.319	68.0
283	70.2	16.1	0.229	55.0	0.293	70.7
	Average		0.248		0.317	68.3

Table V. Pressure Attenuation, Plate 4, 6, 1/2-Inch Holes - 9.37 Percent Open

Shot Number	Input Pressure (P_I) psi	Transmitted Pressure (P_T) A_V = 9.37% psi	Ratio C P_T 9.3/P_I	Transmitted Pressure (P_T) A_V = 100%	Ratio (P_{TR}) P_T 9.37 P_T 100	Attenuation Percent
14	210.0	65.0	0.309	164.8	0.394	60.5
30	194.8	57.5	0.295	152.8	0.376	62.4
31	191.0	54.0	0.283	149.9	0.360	64.0
15	121.0	30.2	0.250	94.9	0.318	68.1
28	120.9	31.1	0.257	94.9	0.328	67.2
29	124.5	31.2	0.251	97.9	0.319	68.1
16	50.5	13.5	0.267	39.6	0.341	65.9
26	49.3	13.6	0.276	38.6	0.352	64.8
27	48.8	14.2	0.291	38.2	0.372	62.8
		Average	0.276		0.351	64.9

Table VI. Pressure Attenuation, Plate 5, 105, 1/8-Inch Holes - 10.2 Percent Open

Shot Number	Input Pressure (P_I) psi	Transmitted Pressure (P_T) A_V = 10.2% psi	Ratio (C) P_T 10.2/P_I	Transmitted Pressure (P_T) A_V = 100%	Ratio (P_{TR}) P_T 10.2/P_T 100	Attenuation Percent
75	216.8	53.2	0.245	170.3	0.312	68.8
76	185.1	52.4	0.283	145.4	0.360	64.0
72	128.9	30.9	0.240	101.2	0.305	69.5
73	129.4	33.0	0.255	101.6	0.325	67.5
74	122.8	31.9	0.260	96.5	0.331	66.9
71	47.2	13.4	0.284	37.1	0.361	63.9
		Average	0.261		0.332	66.8

Table VII. Pressure Attenuation, Plate 6, 16, 1/2-Inch Holes - 25 Percent Open

Shot Number	Input Pressure (P_I) psi	Pressure (P_T) A_v = 25% psi	Ratio (C) P_T 25/P_I	Transmitted Pressure (P_T) A_v = 100%	Ratio (P_{TR}) P_T 25/P_T 100	Attenuation Percent
11	205.0	99.0	0.483	160.9	0.615	38.5
32	195.0	94.5	0.486	153.0	0.617	38.2
33	191.0	93.3	0.488	149.9	0.622	37.8
12	121.0	53.8	0.445	94.9	0.567	43.3
34	123.8	56.0	0.452	97.1	0.576	42.3
35	118.6	55.3	0.466	93.1	0.594	40.6
13	51.2	22.4	0.438	40.1	0.559	44.1
36	49.8	22.6	0.454	38.3	0.590	41.0
37	49.3	21.7	0.440	38.6	0.562	43.8
		Average	0.461		0.589	41.1

Table VIII. Pressure Attenuation, Plate 7, 256, 1/8-Inch Holes - 25 Percent Open

Shot Number	Input Pressure (P_I) psi	Pressure (P_T) A_v = 25% psi	Ratio (C) P_T 25/P_I	Transmitted Pressure (P_T) A_v = 100%	Ratio (P_{TR}) P_T 25/P_T 100	Attenuation Percent
158	187.7	88.9	0.474	147.4	0.603	39.7
162	194.5	91.1	0.468	152.8	0.596	40.4
160	132.7	65.5	0.494	104.2	0.628	37.2
161	128.2	64.4	0.502	100.7	0.640	36.0
163	48.3	20.0	0.414	37.9	0.527	47.3
164	48.3	20.0	0.414	37.0	0.527	47.3
		Average	0.459		0.587	41.3

Table IX. Pressure Attenuation, Plate 8, 68, 1/4-Inch Holes - 26.6 Percent Open

Shot Number	Input Pressure (P_I) psi	Transmitted Pressure (P_T) A_v = 26.6% psi	Ratio (C) P_T 26.6/P_I	Transmitted Pressure (P_T) A_v = 100%	Ratio (P_{TR}) P_T 26.6/P_T 100	Attenuation Percent
61	195.2	89.4	0.458	153.3	0.583	41.7
62	197.5	92.7	0.469	155.1	0.597	40.2
63	116.2	55.3	0.476	91.1	0.607	39.3
64	118.4	53.2	0.449	93.0	0.572	42.8
65	118.4	51.1	0.432	93.0	0.549	45.0
66	47.2	20.8	0.441	37.1	0.561	43.9
67	48.2	21.9	0.454	37.9	0.578	42.1
68	48.8	23.4	0.479	38.3	0.610	38.9
		Average	0.457		0.582	41.8

Table X. Pressure Attenuation, Plate 9, 308, 1/8-Inch Holes - 30 Percent Open

Shot Number	Input Pressure (P_I) psi	Pressure (P_T) A_v = 30% psi	Ratio (C) P_T 30/P_I	Transmitted Pressure (P_T) A_v = 100%	Ratio (P_{TR}) P_T 30/P_T 100	Attenuation Percent
156	188.8	101.1	0.535	148.3	0.682	31.8
157	187.7	102.2	0.544	147.4	0.693	30.7
153	130.9	68.1	0.520	102.8	0.662	33.8
154	135.0	71.1	0.527	106.0	0.670	33.0
155	130.4	67.8	0.520	102.4	0.662	33.8
150	49.2	22.6	0.459	38.6	0.585	41.5
151	51.2	23.1	0.449	40.5	0.571	42.9
152	51.0	22.6	0.443	40.0	0.564	43.6
		Average	0.500		0.636	36.4

Table XI. Pressure Attenuation, Plate 10
392, 1/8-Inch Holes - 38.2 Percent Open

Shot Number	Input Pressure (P_I) psi	Pressure (P_T) A_v = 38.2% psi	Ratio (C) P_T 38.2/P_I	Transmitted Pressure (P_T) A_v = 100%	Ratio (P_{TR}) P_T 38.2/P_T 100	Attenuation Percent
165	206.0	111.1	0.539	161.8	0.687	31.3
166	200.2	108.9	0.544	157.2	0.693	30.8
167	132.7	80.0	0.603	104.2	0.767	23.2
168	135.0	76.7	0.568	106.0	0.723	27.6
169	51.3	28.9	0.563	40.3	0.717	28.3
170	50.6	28.3	0.559	39.7	0.712	28.8
		Average	0.563		0.716	28.3

Table XII. Pressure Attenuation, Plate 11, 105, 1/4-Inch Holes - 41.0 Percent Open

Shot Number	Input Pressure (P_I) psi	Pressure (P_T) A_v = 41% psi	Ratio (C) P_T 41/P_I	Transmitted Pressure (P_T) A_v = 100%	Ratio (P_{TR}) P_T 41/P_T 100	Attenuation Percent
58	201.5	110.6	0.549	158.3	0.699	30.1
59	193.0	105.5	0.547	151.6	0.696	30.4
60	197.4	110.6	0.560	155.1	0.713	28.7
55	120.6	67.0	0.556	94.7	0.707	29.3
56	118.4	66.0	0.557	93.0	0.710	29.0
67	122.8	64.9	0.529	96.5	0.673	32.7
52	49.3	28.7	0.582	38.7	0.741	25.9
53	48.8	28.2	0.578	38.3	0.736	26.4
54	47.7	28.7	0.602	37.5	0.766	23.4
		Average	0.562		0.716	28.4

Table XIII. Pressure Attenuation, Plate 12, 1, 2-13/16-Inch Hole - 49.4 Percent Open

Shot Number	Input Pressure (P_I) psi	Pressure (P_T) A_V = 49.4% psi	Ratio (C) P_T 49.4/P_I	Transmitted Pressure (P_T) A_V = 100%	Ratio (P_{TR}) P_T 49.4/P_T 100	Attenuation Percent
43	188.6	116.1	0.616	148.1	0.784	21.6
44	195.4	122.6	0.627	153.5	0.799	20.1
45	193.4	122.0	0.631	151.9	0.803	19.7
46	115.9	71.0	0.613	91.0	0.780	22.0
47	117.1	71.0	0.606	92.0	0.772	22.8
48	117.0	73.1	0.625	91.9	0.795	20.5
49	46.9	29.8	0.635	36.8	0.809	19.1
50	48.2	30.9	0.641	37.9	0.816	18.4
51	48.2	30.3	0.629	37.9	0.800	20.0
		Average	0.625		0.795	20.5

Table XIV. Pressure Attenuation, Plate 13, 32, 1/2-Inch Holes - 50 Percent Open

Shot Number	Input Pressure (P_I) psi	Pressure (P_T) A_v = 50% psi	Ratio (C) P_T 50/P_I	Transmitted Pressure (P_T) A_v = 100%	Ratio (P_{TR}) P_T 50/P_T 100	Attenuation Percent
4	198.0	114.0	0.575	155.3	0.734	26.6
5	200.0	127.0	0.635	156.9	0.809	19.1
42	195.5	116.1	0.594	153.4	0.757	24.3
6	121.0	74.2	0.613	94.9	0.782	21.8
40	113.6	77.4	0.681	89.1	0.869	13.1
41	117.0	76.3	0.652	91.8	0.831	16.9
7	49.2	30.0	0.610	38.6	0.778	22.2
38	50.0	31.2	0.624	39.2	0.796	20.4
39	50.0	31.2	0.624	31.2	0.796	20.4
		Average	0.623		0.795	20.5

Table XV. Pressure Attenuation versus Area Vented

Plate Number	Number of Holes	A_V Area Vented Percent	P_{TR} Transmission Ratio Experimental	P_{TR} Transmission Ratio Calculated	Attenuation Percent Experimental	Attenuation Percent Calculated
1	3*	4.69	0.237	0.242	73.6	75.8
2	52***	5.10	0.196	0.253	80.4	74.7
3	5*	7.81	0.317	0.314	68.3	68.6
4	6*	9.37	0.351	0.345	64.9	65.5
5	105***	10.2	0.332	0.360	66.8	64.0
6	16*	25.0	0.589	0.571	41.1	42.9
7	256***	25.0	0.587	0.571	41.3	42.9
8	68**	26.6	0.582	0.590	41.8	41.0
9	308***	30.0	0.636	0.627	36.4	37.3
10	392***	38.2	0.716	0.710	28.3	29.0
11	105**	41.0	0.716	0.737	28.4	26.3
12	1	49.4	0.795	0.810	20.5	19.0
13	32*	50.0	0.795	0.815	20.5	18.5

*Hole Diameter 0.50 in. (1.27 cm).
**Hole Diameter 0.25 in. (0.64 cm).
***Hole Diameter 0.125 in. (0.32 cm).

Pressure Transmission Ratio (P_{TR}) = $0.1094\ A_V^{0.5135}$ $\qquad A_V < 55$

Pressure Attenuation Percent = $(1 - P_{TR}) \times 100$



Figure 9. Pressure Transmission Ratio as a Function of Percent of Area Vented



Figure 10. Percent Pressure Attenuation as a Function of Percent of Area Vented

APPENDIX

PRESSURE-TIME DATA

This Appendix shows a selection of records which represent the pressure as a function of time at Station 3 (CH3) and Station 6 (CH6). Station 3 was located 0.75 tube diameter upstream from the target plate. Station 6 was located 7 tube diameters downstream of the target plate - a distance sufficient to allow the transmitted shock wave (P_T) to reform after passing the perforated plate.

Table A-I presents data for the target plates. Plate number, shot number, area vented, and hole diameter describe the target plates.

The pressure-time records are listed according to percent of area open. The upper trace (CH3) is the input record (P_I). The initial peak is the side-on value; the second peak is the portion of the shock wave reflected upstream from the target plate. The lower trace is the transmitted pressure at Station 6 (CH6).

Table A-I. Data for Pressure-Time Records

Plate No.	Shot No.	Area Vented Percent	Hole Diameter inches
1	22	4.69	1/2
2	81	5.1	1/8
3	297	7.81	1/2
4	29	9.37	1/2
5	76	10.2	1/8
6	32	25.0	1/2
7	160	25.0	1/8
8	63	26.6	1/4
9	153	30.0	1/8
10	168	38.2	1/8
11	66	41.0	1/4
12	51	49.4	2-13/16
13	7	50.0	1/2



PLATE I -INPUT PRESSURE



PLATE I -TRANSMITTED PRESSURE

Figure A-1. Pressure-Time Traces Recorded at Stations 3 and 6 - 4.69 Percent Open



PLATE 2 - INPUT PRESSURE



PLATE 2 - TRANSMITTED PRESSURE

Figure A-2. Pressure-Time Traces Recorded at Stations 3 and 6 - 5.1 Percent Open



PLATE 3 - INPUT PRESSURE



PLATE 3-TRANSMITTED PRESSURE

Figure A-3. Pressure-Time Traces Recorded at Stations 3 and 6 - 7.8 Percent Open



PLATE 4 - INPUT PRESSURE



PLATE 4 - TRANSMITTED PRESSURE

Figure A-4. Pressure-Time Traces Recorded at Stations 3 and 6 - 9.37 Percent Open



PLATE 5-INPUT PRESSURE



PLATE 5-TRANSMITTED PRESSURE

Figure A-5. Pressure-Time Traces Recorded at Stations 3 and 6 - 10.2 Percent Open



PLATE 6-INPUT PRESSURE



PLATE 6-TRANSMITTED PRESSURE

Figure A-6. Pressure-Time Traces Recorded at Stations 3 and 6 - 25 Percent Open, 1/2-Inch Holes



PLATE 7 - INPUT PRESSURE



PLATE 7-TRANSMITTED PRESSURE

Figure A-7. Pressure-Time Traces Recorded at Stations 3 and 6 - 25 Percent Open, 1/8-Inch Holes



PLATE 8-INPUT PRESSURE



PLATE 8-TRANSMITTED PRESSURE

Figure A-8. Pressure-Time Traces Recorded at Stations 3 and 6 - 26.6 Percent Open



PLATE 9 - INPUT PRESSURE



PLATE 9 - TRANSMITTED PRESSURE

Figure A-9. Pressure-Time Traces Recorded at Stations 3 and 6 - 30 Percent Open



PLATE 10 - INPUT PRESSURE



PLATE 10 - TRANSMITTED PRESSURE

Figure A-10. Pressure-Time Traces Recorded at Stations 3 and 6 - 38.2 Percent Open



PLATE II - INPUT PRESSURE



PLATE II - TRANSMITTED PRESSURE

Figure A-11. Pressure-Time Traces Recorded at Stations 3 and 6 - 41.0 Percent Open



PLATE 12 - INPUT PRESSURE



PLATE 12 - TRANSMITTED PRESSURE

Figure A-12. Pressure-Time Traces Recorded at Stations 3 and 6 - 49.4 Percent Open



PLATE 13 - INPUT PRESSURE



PLATE 13 - TRANSMITTED PRESSURE

Figure A-13. Pressure-Time Traces Recorded at Stations 3 and 6 - 50 Percent Open

LIST OF SYMBOLS

A_v	Percent of plate vented = $\frac{\text{area vented}}{\text{area of tube}} \times 100$
P_I	Input peak overpressure
P_T	Transmitted peak overpressure
P_T 100	Transmitted peak overpressure for unobstructed tube
P_{TR}	Pressure transmission ratio = $\frac{P_T \text{ for Plate}}{P_T\ 100}$
Psi	Pounds force per square inch
Pa	Pascal (newtons per square metre)

NOTE: Psi x 6.894757 = kPa.

DISTRIBUTION LIST

No. of Copies	Organization
12	Commander Defense Documentation Center ATTN: DDC-TCA Cameron Station Alexandria, Virginia 22314
1	Director Defense Advanced Research Projects Agency 1400 Wilson Boulevard Arlington, Virginia 22209
1	Director Weapons Systems Evaluation Group ATTN: CPT Donald E. McCoy Washington, DC 20305
3	Director Institute for Defense Analyses ATTN: Dr. J. Menkes Dr. J. Bengston Tech Info Ofc 400 Army-Navy Drive Arlington, Virginia 22202
1	Assistant to the Secretary of Defense (Atomic Energy) ATTN: Document Control Washington, DC 20301
1	Director of Defense Research and Engineering ATTN: Mr. J. Persh, Staff Specialist Materials and Structures Washington, DC 20301
2	Chairman Joint Chiefs of Staff ATTN: J-3, Operations J-5, Plans & Policy (R&D Division) Washington, DC 20301
1	Chairman Department of Defense Explosives Safety Board Forrestal Building, GB-270 Washington, DC 20314
2	Director Defense Nuclear Agency ATTN: Mr. J. F. Moulton, SPAS Dr. E. Sevin, SPSS Washington, DC 20305
4	Director Defense Nuclear Agency ATTN: SPTL Tech Lib (2 cys) SPSI (ARCHIVES) STSP Washington, DC 20305
1	Commander Field Command Defense Nuclear Agency ATTN: Tech Lib, FCWS-SC Kirtland AFB New Mexico 87115
1	Chief Las Vegas Liaison Office Field Command TD, DNA P.O. Box 2702 ATTN: Document Control Las Vegas, Nevada 89104
1	DNA Information and Analysis Center TEMPO, General Electric Co. Center for Advanced Studies ATTN: DASIAC 816 State Street Santa Barbara, California 93102
1	Director Defense Communications Agency ATTN: NMCSSC (Code 510) Washington, DC 20305

DISTRIBUTION LIST

No. of Copies	Organization
2	Director Defense Intelligence Agency ATTN: DT-1C, Dr. J. Vorona DT-2 Washington, DC 20301
1	Commander US Army Materiel Development and Readiness Command ATTN: DRCDMA-ST 5001 Eisenhower Avenue Alexandria, VA 22333
1	Commander US Army Materiel Development and Readiness Command ATTN: DRCPM-CS 5001 Eisenhower Avenue Alexandria, VA 22333
1	Commander US Army Construction Engineering Research Laboratory P. O. Box 4005 Champaign, IL 61820
1	Commander US Army Aviation Systems Command ATTN: DRSAV-E 12th and Spruce Streets St. Louis, MO 63166
1	Director US Army Air Mobility Research and Development Laboratory Ames Research Center Moffett Field, CA 94035
1	Commander US Army Electronics Command ATTN: DRSEL-RD Fort Monmouth, NJ 07703
5	Commander US Army Missile Research and Development Command ATTN: DRDMI-R DRDMI-AOA, Lib DRDMI-RSS, Mr. B. Cobb DRDMI-RX, Mr. W. Thomas DRDMI-RR, Mr. L. Lively Redstone Arsenal, AL 35809
2	Commander US Army Tank Automotive Development Command ATTN: DRDTA DRDTA-RWL Warren, MI 48090
2	Commander US Army Mobility Equipment Research & Development Command ATTN: Tech Docu Cen, Bldg. 315 DRSME-RZT Fort Belvoir, VA 22060
2	Commander US Army Armament Materiel Readiness Command ATTN: DRSAR-RDN DRSAR-MT Rock Island, IL 61202
3	Commander US Army Armament Materiel Readiness Command ATTN: DRSAR-SC, C. Hudson DRSAR-SF, R. Young DRSAR-PPI, CPT Burnsteel Rock Island, IL 61202
3	Commander US Army Armament Materiel Readiness Command ATTN: Joint Army-Navy-Air Force Conventional Ammunition Prod Coord Gp/E. Jordan Rock Island, IL 61202

DISTRIBUTION LIST

No. of Copies	Organization
1	Commander US Army Frankford Arsenal ATTN: SARFA-L6100, P. Flynn Philadelphia, PA 19137
4	Commander US Army Armament Research and Development Command ATTN: SARPA-V Mr. G. Demitrack Mr. M. Weinstein SARPA-MT-F Mr. John Canavan Mr. L. Saffian Mr. P. Price DRCPM-PBM-E, Mr. Dybacki Dover, NJ 07801
1	Commander US Army Rock Island Arsenal Rock Island, IL 61202
1	Commander US Army Dugway Proving Ground ATTN: STEDP-TO-H, Mr. Miller Dugway, UT 84022
1	Commander US Army Watervliet Arsenal Watervliet, NY 12189
1	Commander Pine Bluff Arsenal Pine Bluff, AR 71601
1	Commander Cornhusker Army Ammunition Plant Grand Island, NE 68801
1	Commander Indiana Army Ammunition Plant Charlestown, IN 47111
1	Commander Iowa Army Ammunition Plant Burlington, IA 52502
1	Commander Joliet Army Ammunition Plant Joliet, IL 60436
1	Commander Kansas Army Ammunition Plant Parsons, KS 67357
1	Commander Lone Star Army Ammunition Plant Texarkana, TX 75502
1	Commander Longhorn Army Ammunition Plant Marshall, TX 75671
1	Commander Louisiana Army Ammunition Plant Shreveport, LA 71102
1	Commander Milan Army Ammunition Plant Milan, TN 38358
1	Commander Radford Army Ammunition Plant Radford, VA 24141
1	Commander Ravenna Army Ammunition Plant Ravenna, OH 44266
1	Director US Army Engineer School Fort Belvoir, VA 22060

DISTRIBUTION LIST

No. of Copies	Organization
1	Commander US Army Harry Diamond Labs ATTN: DRXDO-TI 2800 Powder Mill Road Adelphi, MD 20783
1	Commander US Army Materials and Mechanics Research Center ATTN: DRXMR-ATL Watertown, MA 02172
1	Commander US Army Natick Research and Development Command ATTN: DRXRE, Dr. D. Sieling Natick, MA 01762
1	Commander US Army Foreign Science and Technology Center ATTN: Rsch & Data Branch Federal Office Building 220 7th Street, NE Charlottesville, VA 22901
1	Director DARCOM Field Safety Activity ATTN: DRXOS-ES Charlestown, IN 47111
1	Director DARCOM, ITC ATTN: Dr. Chiang Red River Depot Texarkana, TX 75501
1	Commander US Army TRADOC Systems Analysis Activity ATTN: ATAA-SA White Sands Missile Range NM 88002
2	HQDA (DAMA-AR; NCL Div) Washington, DC 20310
1	Commander U.S. Army Research Office P.O. Box 12211 Research Triangle Park North Carolina 27709
1	Director U.S. Army Advanced BMD Technology Center ATTN: M. Whitfield Huntsville, Alabama 35807
1	Commander U.S. Army Ballistic Missile Defense Systems Command ATTN: J. Veeneman P.O. Box 1500, West Station Huntsville, Alabama 35807
1	HQDA (DAEM-MCE-D/Mr. R. Wright) Washington, DC 20314
1	HQDA (DAEN-MCC-D/Mr. L. Foley) Washington, DC 20314
1	Director US Army Engineer Waterways Experiment Station P.O. Box 631 Vicksburg, MS 39180
1	Division Engineer U.S. Army Engineer Division Fort Belvoir, VA 22060
1	U.S. Army Eng Div ATTN: Mr. Char P. O. Box 1600 Huntsville, AL 35809

DISTRIBUTION LIST

No. of Copies	Organization
2	Director Joint Strategic Target Planning Staff ATTN: JLTW JPTP Offutt AFB Omaha, Nebraska 68113
4	Chief of Naval Operations ATTN: OP-03EG OP-97 OP-754 OP-985FZ Department of the Navy Washington, DC 20350
1	Assistant Secretary of the Navy (Research & Development) Navy Department Washington, DC 20350
1	Chief of Naval Material Navy Department ATTN: Code 418, Dr. T. Quinn Arlington, Virginia 22217
1	Commander Bureau of Naval Weapons ATTN: Code F121 Mr. H. Roylance Department of the Navy Washington, DC 20360
1	Commander Naval Ordnance Systems Command ATTN: Code ORD 43B Mr. Fernandes Washington, DC 20360
2	Commander David W. Taylor Naval Ship Research & Development Ctr ATTN: Mr. A. Wilner, Code 1747 Dr. W.W.Murray, Code 17 Bethesda, MD 20084
3	Commander U.S. Naval Surface Weapons Center ATTN: Mr. F. Sancher Mr. J. C. Talley Dr. W. Soper Dahlgren, Virginia 22448
3	Commander U.S. Naval Surface Weapons Center ATTN: Dr. Leon Schindel Dr. Victor Dawson Dr. P. Huang Silver Spring, Maryland 20910
2	Commander Naval Surface Weapons Center ATTN: Code 241 (Mr. Proctor) (Mr. Kushner) Silver Spring, Maryland 20910
1	Commander U.S. Naval Weapons Center ATTN: Code 6031 Dr. W. Stronge China Lake, California 93555
1	Commander Naval Ammunition Depot ATTN: ORD-04M/B/X-5/L. Leonard Crane, IN 47522
1	Commander Naval Explosive Ord Disposal Facility ATTN: Code 501/L. Wolfson Indianhead, MD 20640
1	Commander US Naval Ship Research and Development Center Facility ATTN: Mr. Lowell T. Butt Underwater Explosions Research Division Portsmouth, VA 23709

DISTRIBUTION LIST

No. of Copies	Organization
1	Commander US Naval Weapons Evaluation Facility ATTN: Document Control Kirtland AFB Albuquerque, NM 87117
1	Commander US Naval Civil Engineering Lab ATTN: J. Tancreto Port Hueneme, CA 93041
1	Commander US Naval Research Laboratory ATTN: Code 2027, Tech Washington, DC 20375
2	Superintendent US Naval Postgraduate School ATTN: Tech Rpts Sec Code 57, Prof. R. Ball Monterey, CA 93940
1	HQ USAF (AFNIE-CA) Washington, DC 20330
4	HQ USAF (AFRDQ; AFRDOSM; AFRDPM; AFRD) Washington, DC 20330
1	AFSC (DSCPSL) Andrews AFB Washington, DC 20331
1	HQ AFSC Andrews AFB Washington, DC 20334
1	AFRDL (M. Raleigh) Edwards AFB, CA 93523
2	AFATL (ATRD, R. Brandt) Eglin AFB, FL 32542
1	ADTC (ADBPS-12) Eglin AFB, FL 32542
1	USAFTAWC (OA) Eglin AFB, FL 32542
1	Ogden ALC/MMWRE (Mr. Ted E. Comins) Hill AFB, UT 84406
3	AFWL (WLA; WLD; WLRP, LTC H. C. McClammy) Kirtland AFB, NM 87117
4	AFWL (SYT, MAJ W.A. Whitaker; SRR; WSUL; SR) Kirtland AFB, NM 87117
1	AFCEC/DE, LTC Walkup Tyndall AFB Panama City, FL 32401
2	AFLC (MMWM/CPT D. Rideout; IGYE/K. Shopker) Wright-Patterson AFB, OH 45433
2	AFFDL/FDTR (Dr. F.J. Banik, Jr.; Dr. R. M. Bader) Wright-Patterson AFB, OH 45433
3	AFML (MAMD, Dr. T. Nicholas; MANC, Mr. D. Schmidt; MAX, Dr. A. M. Lovelace) Wright-Patterson AFB, OH 45433
2	FTD (TDPTN; TDFBD, J.D.Pumphrey) Wright-Patterson AFB, OH 45433
1	Headquarters Energy Research and Development Administration Dept of Military Applications Washington, DC 20545
1	Energy Research and Development Administration Deputy Manager of Engineering ATTN: W. H. Jackson P. O. Box E Oak Ridge, TN 37830

DISTRIBUTION LIST

No. of Copies	Organization
1	Director ATTN: J. Nall P. O. Box 1925 Washington, DC 20505
2	Director National Aeronautics and Space Administration Lewis Research Center ATTN: Frank Belles G. Pinkas 21000 Brook Park Road Cleveland, OH 44135
2	National Aeronautics and Space Administration Aerospace Safety Research and Data Institute ATTN: Mr. S. Weiss Mail Stop 6-2 Mr. R. Kemp Mail Stop 6-2 Lewis Research Center Cleveland, OH 44135
1	Director National Aeronautics and Space Administration Scientific and Technical Information Facility P. O. Box 8757 Baltimore/Washington International Airport, MD 21240
1	Director Lawrence Livermore Laboratory Technical Information Division P. O. Box 808 Livermore, CA 94550
1	Director Los Alamos Scientific Lab ATTN: Dr. J. Taylor P. O. Box 1663 Los Alamos, NM 87544
1	National Academy of Sciences ATTN: Mr. D. G. Groves 2101 Constitution Avenue, NW Washington, DC 20418
1	Aeronautical Research Associates of Princeton, Inc. ATTN: Dr. C. Donaldson 50 Washington Road Princeton, New Jersey 08540
1	Aerospace Corporation ATTN: Dr. Harris Mayer P.O. Box 95085 Los Angeles, California 90045
2	AVCO Corporation Structures and Mechanics Dept. ATTN: Dr. William Broding Mr. J. Gilmore Wilmington, Massachusetts 01887
2	The Boeing Company Aerospace Group ATTN: Dr. Peter Grafton Dr. D. Strome Mail Stop 8C-68 Seattle, Washington 98124
1	Dr. J. C. Shang General American Research Div General American Transportation Corp 7449 N. Natchez Avenue Niles, Illinois 60648
1	Hercules, Inc. ATTN: Billings Brown Box 93 Magna, UT 84044
1	J. G. Engineering Research Associates 3831 Menlo Drive Baltimore, Maryland 21215

DISTRIBUTION LIST

No. of Copies	Organization
2	Kaman-Avidyne ATTN: Dr. N. P. Hobbs Mr. S. Criscione 83 Second Avenue Northwest Industrial Park Burlington, Massachusetts 01803
3	Kaman Sciences Corporation ATTN: Dr. F. H. Shelton Dr. D. Sachs Dr. R. Keefe 1500 Garden of the Gods Road Colorado Springs, Colorado 80907
1	Knolls Atomic Power Lab. ATTN: Dr. R. A. Powell Schenectady, New York 12309
2	Martin Marietta Laboratories ATTN: Dr. P. F. Jordan Mr. R. Goldman 1450 S. Rolling Road Baltimore, Maryland 21227
1	McDonnell Douglas Astronautics Western Division ATTN: Mr. Samuel D. Mihara 3000 Ocean Park Blvd. Santa Monica, California 90406
1	Monsanto Research Corporation Mound Laboratory ATTN: Frank Neff Miamisburg, OH 45342
1	Physics International ATTN: Dr. G. Richard Fowles San Leandro, California 94577
1	R&D Associates ATTN: Mr. John Lewis P.O. Box 9695 Marina del Rey, CA 90291
2	Sandia Laboratories ATTN: Infor Distr Division Dr. W. A. von Riesemann Albuquerque, New Mexico 87115
2	Battelle Columbus Laboratories ATTN: Dr. L. E. Hulbert Mr. J. E. Backofen, Jr. 505 King Avenue Columbus, Ohio 43201
1	Brown University Division of Engineering ATTN: Prof. R. Clifton Providence, Rhode Island 02912
1	Georgia Institute of Technology ATTN: Dr. S. Atluri 225 North Avenue, N. W. Atlanta, Georgia 30332
1	Massachusetts Institute of Technology Aeroelastic and Structures Research Laboratory ATTN: Dr. E. A. Witmer Cambridge, Massachusetts 02139
1	Ohio State University Department of Engineering Mechanics ATTN: Prof. K. K. Stevens Columbus, Ohio 43210
3	Southwest Research Institute ATTN: Dr. H. N. Abramson Dr. W. E. Baker Dr. U. S. Lindholm 8500 Culebra Road San Antonio, Texas 78228

DISTRIBUTION LIST

No. of Copies	Organization
1	Stanford Research Institute ATTN: Dr. W. Reuland 306 Wynn Drive, NW Huntsville, Alabama 35805
1	Texas A & M University Department of Aerospace Engineering ATTN: Dr. James A. Stricklin College Station, Texas 77843
1	University of Alabama ATTN: Dr. T. L. Cost P.O. Box 2908 University, Alabama 35486
1	University of Delaware Department of Mechanical and Aerospace Engineering ATTN: Prof. J. R. Vinson Newark, Delaware 19711

Aberdeen Proving Ground

Marine Corps Ln Ofc
Dir, USAMSAA
ATTN: Dr. J. Sperrazza
Mr. R. Norman, GWD

Cdr, APG
ATTN: STEAP-AD-R/RHA

Cdr, USAEA
ATTN: SAREA-MT-T
Mr. R. Thresher
Dr. D. Katsanis
Mr. B. Jezek
Mr. J. McKivrigan