

12

NSWC TR-80-491

LEVEL II

AD A102366

SCALING UNDERWATER EXPLOSION SHOCK WAVES FOR DIFFERENCES IN AMBIENT SOUND SPEED AND DENSITY

BY JOHN F. GOERTNER

RESEARCH AND TECHNOLOGY DEPARTMENT

18 DECEMBER 1980

DTIC ELECTE
AUG 03 1981

Approved for public release, distribution unlimited

10 F 3-354
USF3



NAVAL SURFACE WEAPONS CENTER

Dehlgren, Virginia 22448 • Silver Spring, Maryland 20910

NSWC FILE COPY

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER NSWC TR 80-491	2. GOVT ACCESSION NO. AD-A102366	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Scaling Underwater Explosion Shock Waves for Differences in Ambient Sound Speed and Density	5. TYPE OF REPORT & PERIOD COVERED Final	
	6. PERFORMING ORG. REPORT NUMBER	
7. AUTHOR(s) John F. Goertner	8. CONTRACT OR GRANT NUMBER(s)	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Surface Weapons Center White Oak, Silver Spring, Maryland 20910	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 62633N; F33354 ; SF-33354391; R15JC	
11. CONTROLLING OFFICE NAME AND ADDRESS	12. REPORT DATE 18 December 1980	
	13. NUMBER OF PAGES 25	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)	15. SECURITY CLASS. (of this report) UNCLASSIFIED	
	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE	
15. DISTRIBUTION STATEMENT (of this Report) Approved for public release, distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Underwater Explosions Shock Waves Shock Wave Measurements Scaling		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) The underwater explosion shock wave similitude equations which describe the variation of peak pressure, decay constant, impuise and energy flux density with distance are rederived to include the effects of ambient sound speed and density. The resulting equations are found to be in good agreement with experimental measurements.		

DD FORM 1473

1 JAN 73


EDITION OF 1 NOV 65 IS OBSOLETE
S/N 0102-LF-014-6601

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)



UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

FOREWORD

Significant differences in underwater shock wave peak pressure and decay constant have been measured when identical explosive charges have been fired at different test sites. This "Key West Effect" has resulted in uncertainties in interpreting explosion test data. This report presents a method for quantitatively describing these and other changes in underwater explosion shock wave parameters in terms of the sound speed and density of the ambient water.

This work is part of the Explosives Development, Effects, and Safety Program of the Naval Sea Systems Command and was supported by Task Area SF-33-354-391.

J. F. Proctor
 J. F. PROCTOR
 By direction

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/ _____	
Availability Codes	
Dist	Avail and/or Special
A	

CONTENTS

<u>Section</u>		<u>Page</u>
1	INTRODUCTION.....	5
2	SIMILITUDE EQUATIONS.....	12
	Generalized Similitude Equations.....	14
3	RESULTS.....	16
4	DISCUSSION.....	17
	APPENDIX.....	A-1

ILLUSTRATIONS

<u>Figure</u>		<u>Page</u>
1.1	Generalized Similitude Equation Scaling of Peak Pressure....	6
1.2	Generalized Similitude Equation Scaling of Decay Constant...	7
1.3	Generalized Similitude Equation Scaling of Impulse.....	8
1.4	Generalized Similitude Equation Scaling of Energy Flux Density.....	9

TABLES

<u>Table</u>		<u>Page</u>
1.1	Key West vs Dahlgren Differences (Average Values for 2 Sites).....	11

SCALING UNDERWATER EXPLOSION SHOCK WAVES FOR DIFFERENCES
IN AMBIENT SOUND SPEED AND DENSITY

1. INTRODUCTION

In the measurement of underwater explosion shock waves it has generally been assumed that local ambient water conditions have a negligible effect on the recorded pressure signature.¹ The exception to this is when distortions due to refraction occur. A recent set of data shows that even with no refraction, the shock wave pressure signature may be strongly dependent on the temperature and salinity of the water.

In an underwater explosions field test conducted by the Naval Surface Weapons Center (NSWC) the test site had to be moved from one location to another in mid-program. After a number of shots had been fired in the Potomac River at Dahlgren, Virginia, in January of 1979, the operation was suspended due to environmental considerations. The remaining shots were fired in the Atlantic Ocean near Key West, Florida, in June of 1979.

The program consisted of a number of different explosives fired in 100-lb charges. Duplicate shots of four different charges were fired at the two sites. There was a consistent pattern of variation in measured pressures between the two sites. This is shown by the pairs of curves on the left hand side of Figures 1.1 through 1.4. These curves are the familiar power law fits* made by the method of ¹Cole, Robert H., 1948, "Underwater Explosions," Princeton University Press

*Reference 1, p 238




FIGURE 1.1 GENERALIZED SIMILITUDE EQUATION SCALING OF PEAK PRESSURE




FIGURE 1.2 GENERALIZED SIMILITUDE EQUATION SCALING OF DECAY CONSTANT




FIGURE 1.3 GENERALIZED SIMILITUDE EQUATION SCALING OF IMPULSE




FIGURE 1.4 GENERALIZED SIMILITUDE EQUATION SCALING OF ENERGY FLUX DENSITY

least squares to the experimental data for peak pressure, decay constant, impulse and energy flux density from four different types of explosive charges--each fired at the two sites. They show that in moving from Dahlgren (solid curves) to Key West (dashed curves) the peak pressure increased about 12%, the decay constant decreased about 14%, the impulse decreased about 4%, and the energy flux density was not significantly changed. Differences between the Key West and Dahlgren test conditions are summarized in Table 1.1.

Gaspin and Lehto² have shown that this "Key West Effect" is real and that it can be approximately accounted for by differences between the two sites in the sound speed, c_0 , and the bulk modulus, $K_0 = \rho_0 c_0^2$, where ρ_0 is the ambient water density. From an approximate physical model they estimated the effect on peak overpressure, PMAX, and on decay constant, $\hat{\epsilon}$, at a fixed distance from the charge to be

$$\frac{PMAX_2}{PMAX_1} = \left(\frac{K_{02}}{K_{01}} \right)^{0.56} \quad (14,500 > PMAX > 1450 \text{ psi}) \quad (1.1)$$

$$\frac{\hat{\epsilon}_2}{\hat{\epsilon}_1} = \frac{c_{01}}{c_{02}} \quad (1.2)$$

Equation 1.1 is in good agreement with the experimental data shown in Figure 1.1, while Equation 1.2 partially corrects for the change in decay constant shown in Figure 1.2. Lehto and Gaspin do not give results for the effects on impulse and energy flux density.

The purpose of this note is to demonstrate the possibility of accounting for changes in the peak pressure, decay constant, impulse, and energy flux density

²Gaspin, J. B. and Lehto, D. L., "Effects of Water Temperature and Salinity on Underwater Explosion Shock waves," NSWC Report to be published

Table 1.1 Key West vs Dahlgren Differences
(Average Values for 2 Sites)

	<u>Dahlgren</u>	<u>Key West</u>	<u>Change</u>
Water Temperature (Deg. C)	2.3	27.8	+ 25.5
Salinity (‰)	7.6	36.5	+ 28.9
Sound Speed (ft/sec)	4668	5048	+ 8.1%
Water Density (gm/cc)	1.006	1.024	+ 1.8%
Bulk Modulus (lb/ft ²)	42.54 E6	50.66 E6	+19.1%
Peak Pressure	—	—	+12%
Decay Constant	—	—	-14%
Impulse	—	—	-4%
Energy Flux Density	—	—	0%

(P_{MAX}, θ , I, and E) due to variations in c_0 and c_o by simply rederiving the dimensionless variables used to formulate the underwater explosion shock wave similitude equations--and not discarding c_0 and c_o . The pairs of curves shown on the right-hand side of Figures 1.1 through 1.4 show the results of this effort.

2. SIMILITUDE EQUATIONS

The similitude equations for the underwater explosion shock wave¹

$$P_{MAX} = k \left(\frac{W^{1/3}}{R} \right)^a \quad (2.1)$$

$$\theta = \lambda W^{1/3} \left(\frac{R}{W^{1/3}} \right)^R \quad (2.2)$$

$$I = m W^{1/3} \left(\frac{W^{1/3}}{R} \right)^Y \quad (2.3)$$

$$E = n W^{1/3} \left(\frac{W^{1/3}}{R} \right)^\delta \quad (2.4)$$

are specific expressions (power curve fits, $y = ax^b$) of a general scaling expressed by

$$p(R, t) = F \left(\frac{R}{W^{1/3}}, \frac{t}{W^{1/3}} \right) \quad (2.5)$$

We now proceed to rederive Equation 2.5 from dimensional considerations but retaining the dependence on c_0 and c_o . The significant variables for the problem are:

$p = p(t)$ = shock wave overpressure

R = radial distance from center of charge

t = time

Y_0 = total chemical energy released upon detonation

ρ_0 = ambient water density

c_0 = ambient sound speed.

Thus, we are in effect assuming that the overpressure, p , is a function of R , t , Y_0 , ρ_0 , and c_0 or that

$$f(p, R, t, Y_0, \rho_0, c_0) = 0 \quad (2.6)$$

where f is some unknown function. These six variables in Equation 2.6 can be expressed in terms of three dimensions--mass, length, and time. By Buckingham's π -theorem³, the problem can be reformulated in terms of three dimensionless groups or π 's and the solution must be of the form

$$F(\pi_1, \pi_2, \pi_3) = 0 \quad (2.7)$$

A convenient set of π 's for considering this problem is the following*

$$\pi_1 = \frac{p}{\rho_0 c_0^2} = \frac{p}{K_0} \quad (2.8)$$

$$\pi_2 = \frac{(\rho_0 c_0^2)^{1/3} R}{Y_0^{1/3}} = \frac{K_0^{1/3} R}{Y_0^{1/3}} \quad (2.9)$$

$$\pi_3 = \frac{c_0 (\rho_0 c_0^2)^{1/3} t}{Y_0^{1/3}} = \frac{c_0 K_0^{1/3} t}{Y_0^{1/3}} \quad (2.10)$$

where, $K_0 = \rho_0 c_0^2$, which is the bulk modulus of the ambient water.

Making use of this set of π 's Equation 2.7 can be written

$$\frac{p}{K_0} = G\left(\frac{K_0^{1/3} R}{Y_0^{1/3}}, \frac{c_0 K_0^{1/3} t}{Y_0^{1/3}}\right) \quad (2.11)$$

where G is some unknown function.

³Buckingham, E., 1914, "On Physically Similar Systems; Illustrations of the Use of Dimensional Equations," Physical Review, Vol. 4, p 345

*The reader is referred to References 3 and 4 for the method of determining convenient sets of π 's.

⁴Johnson, Walter C., 1944, "Mathematical and Physical Principles of Engineering Analysis," McGraw-Hill, (Chapter IX)

If we restrict our consideration to a single explosive, we can replace Y_0 in Equation 2.11 by W , the weight of explosive, and obtain

$$\frac{p(R,t)}{K_0} = H \left(\frac{K_0^{1/3} R}{W^{1/3}}, \frac{c_0 K_0^{1/3} t}{W^{1/3}} \right) \quad (2.12)$$

which is similar to Equation 2.5 except we have retained the desired dependence on c_0 and K_0 . Note, if we assume K_0 and c_0 are constants, then Equation 2.12 is equivalent to the familiar shock wave scaling expressed by Equation 2.5.

Generalized Similitude Equations. Note that the similitude equations, Equations 2.1 through 2.4, are simply power curve fits to experimental data using dimensionless variables. Thus, our generalized similitude equations are simply

$$\frac{P_{MAX}}{K_0} = k^* \left(\frac{K_0^{1/3} R}{W^{1/3}} \right)^{-\alpha} \quad (2.13)$$

$$\frac{c_0 K_0^{1/3} t}{W^{1/3}} = \ell^* \left(\frac{K_0^{1/3} R}{W^{1/3}} \right)^{\beta} \quad (2.14)$$

$$\frac{c_0 I}{K_0^{2/3} W^{1/3}} = m^* \left(\frac{K_0^{1/3} R}{W^{1/3}} \right)^{-\gamma} \quad (2.15)$$

$$\frac{E}{K_0^{2/3} W^{1/3}} = n^* \left(\frac{K_0^{1/3} R}{W^{1/3}} \right)^{-\delta} \quad (2.16)$$

The exponents-- α , β , γ , and δ --are the same as in Equations 2.1 through 2.4. The coefficients-- k^* , ℓ^* , m^* , and n^* --can be calculated from k , ℓ , m , and n , respectively, by transforming Equations 2.1 through 2.4 to the same form as 2.13 through 2.16, respectively. Comparison then shows that

$$k^* = \frac{k}{K_0^{1 - \frac{\alpha}{3}}} \quad (2.17)$$

$$i^* = i c_0 K_0^{(1-\beta)/3} \quad (2.18)$$

$$m^* = \frac{m c_0}{K_0^{(2-\gamma)/3}} \quad (2.19)$$

$$n^* = n K_0^{(\delta-2)/3} \quad (2.20)$$

Equations 2.17 through 2.20 can be used to compare data fits made using Equations 2.13 through 2.16 to those made using Equations 2.1 through 2.4.

By substitution into Equations 2.13 through 2.16, we determine the changes in P_{MAX}, θ , I, and E at constant range due to different ambient conditions. They are as follows:

$$\frac{P_{MAX_2}}{P_{MAX_1}} = \left(\frac{K_{O_2}}{K_{O_1}} \right)^{1 - \frac{\alpha}{3}} \quad (2.21)$$

$$\frac{\theta_2}{\theta_1} = \frac{c_{O_1}}{c_{O_2}} \left(\frac{K_{O_1}}{K_{O_2}} \right)^{\frac{1-\beta}{3}} \quad (2.22)$$

$$\frac{I_2}{I_1} = \frac{c_{O_1}}{c_{O_2}} \left(\frac{K_{O_2}}{K_{O_1}} \right)^{\frac{2-\gamma}{3}} \quad (2.23)$$

$$\frac{E_2}{E_1} = \left(\frac{K_{O_1}}{K_{O_2}} \right)^{\frac{\delta-2}{3}} \quad (2.24)$$

Changes in the similitude coefficients--k, ℓ , m, n--from one ambient state to another can be computed from Equations 2.17 through 2.20. They are

$$\frac{k_2}{k_1} = \left(\frac{K_{O_2}}{K_{O_1}} \right)^{1 - \frac{\alpha}{3}} \quad (2.25)$$

$$\frac{\ell_2}{\ell_1} = \frac{c_{O_1}}{c_{O_2}} \left(\frac{K_{O_1}}{K_{O_2}} \right)^{\frac{1-\beta}{3}} \quad (2.26)$$

$$\frac{m_2}{m_1} = \frac{c_{O_1}}{c_{O_2}} \left(\frac{K_{O_2}}{K_{O_1}} \right)^{\frac{2-\gamma}{3}} \quad (2.27)$$

$$\frac{n_2}{n_1} = \left(\frac{K_{O_1}}{K_{O_2}} \right)^{\frac{\delta-2}{3}} \quad (2.28)$$

3. RESULTS

The pairs of curves shown on the right-hand side of Figures 1.1 through 1.4 have been calculated from the corresponding curves shown on the left using Equations 2.13 through 2.20 and the values for ambient water density and sound speed measured on the respective shots. They have been scaled to the same ambient water condition, $\rho_0 = 1 \text{ gm/cc}$ and $c_0 = 5000 \text{ ft/sec}$. For these tests the generalized similitude equations, Equations 2.13 through 2.16, do a good job of accounting for the observed changes in all of the shock wave parameters, P_{MAX}, θ , I, and E. The calculated change in energy flux density from Dahlgren to Key West is a decrease of about 0.1% which is too small to detect experimentally or to observe on Figure 1.4.

4. DISCUSSION

Inserting current NSWC values⁵, $\alpha = 1.19$, $\beta = 0.26$, $\gamma = 0.90$, $\delta = 2.10$, for the similitude equation exponents for cast 50/50 pentolite into Equations 2.21 through 2.24, we get

$$\frac{P_{MAX_2}}{P_{MAX_1}} = \left(\frac{K_{O_2}}{K_{O_1}} \right)^{0.60} \quad (4.1)$$

$$\frac{\theta_2}{\theta_1} = \frac{c_{O_1}}{c_{O_2}} \left(\frac{K_{O_1}}{K_{O_2}} \right)^{0.25} \quad (4.2)$$

$$\frac{I_2}{I_1} = \frac{c_{O_1}}{c_{O_2}} \left(\frac{K_{O_2}}{K_{O_1}} \right)^{0.37} \quad (4.3)$$

$$\frac{E_2}{E_1} = \left(\frac{K_{O_1}}{K_{O_2}} \right)^{0.03} \quad (4.4)$$

The result for peak pressure is essentially the same as Lehto and Gaspin's result (Equation 1.1). The result for decay constant is apparently more complete than their result (Equation 1.2). The results for impulse and energy flux density are new and are in agreement with experimental measurements.

⁵Price, Robert S., NSWC limited distribution report

In the final analysis, the value of these generalized similitude equations will only be demonstrated by extensive use. This should include incorporation into the shock wave data analysis programs used by the Naval Surface Weapons Center. The equations needed to do this are derived in the Appendix.

APPENDIX A

POWER LAW FITS TO MEASURED DATA

Since self-consistent units of measurement are not used in underwater explosion research in this country, it is not recommended to make power law fits to experimental measurements using Equations 2.13 through 2.16. Instead, we can make use of the dimensionless variables implied in Equations 2.13 through 2.16 and scale our measured experimental quantities--R, P_{MAX}, θ, I, E--to some standard condition, e.g., fresh water at some standard temperature and pressure*. Thus, using Equations 2.13 through 2.16

$$R^* = \frac{K_0^{1/3} R}{W^{1/3}} = \frac{K_s^{1/3} R_s}{W^{1/3}} \quad (A.1)$$

$$P_{MAX}^* = \frac{P_{MAX}}{K_0} = \frac{P_{MAX}_s}{K_s} \quad (A.2)$$

$$\theta^* = \frac{c_0 K_0^{1/3} \theta}{W^{1/3}} = \frac{c_s K_s^{1/3} \theta_s}{W^{1/3}} \quad (A.3)$$

$$I^* = \frac{c_0 I}{K_0^{2/3} W^{1/3}} = \frac{c_s I_s}{K_s^{2/3} W^{1/3}} \quad (A.4)$$

$$E^* = \frac{E}{K_0^{2/3} W^{1/3}} = \frac{E_s}{K_s^{2/3} W^{1/3}} \quad (A.5)$$

*The author recommends that a standard condition be adopted for reporting measured values of similitude coefficients and suggests that fresh water at 15°C and 1 atmosphere pressure would be suitable. With this choice $\rho_s = 0.99913$ gm/cc and $c_s = 4809.3$ ft/sec.⁶

⁶Del Grosso, V. A., "New Equation for the Speed of Sound in Natural Waters (With Comparisons to Other Equations)," J. Acoust. Soc. Am., October 1974

where "*" denotes a dimensionless variable and subscript "s" denotes standard condition.

Solving Equations A.1 through A.5 for R_s , $PMAX_s$, θ_s , I_s , E_s , respectively, we get

$$R_s = \left(\frac{K_0}{K_s}\right)^{1/3} R \quad (A.6)$$

$$PMAX_s = \frac{K_s}{K_0} PMAX \quad (A.7)$$

$$\theta_s = \left(\frac{c_0}{c_s}\right) \left(\frac{K_0}{K_s}\right)^{1/3} \theta \quad (A.8)$$

$$I_s = \left(\frac{c_0}{c_s}\right) \left(\frac{K_s}{K_0}\right)^{2/3} I \quad (A.9)$$

$$E_s = \left(\frac{K_s}{K_0}\right)^{2/3} E \quad (A.10)$$

The derived quantities R_s , $PMAX_s$, θ_s , I_s and E_s can be used to make the power law fits indicated by the ordinary similitude equations (Equations 2.1 through 2.4); and thereby obtain coefficients-- k_s , ℓ_s , m_s , n_s --and exponents-- α_s , β_s , γ_s , δ_s --scaled to the desired standard condition. This can be verified by substituting Equations A.6 through A.10 into Equations 2.13 through 2.16 to get

$$PMAX_s = k^* K_s^{1-\frac{\alpha}{3}} \left(\frac{R_s}{W^{1/3}}\right)^{-\alpha} \quad (A.11)$$

$$\frac{\theta_s}{W^{1/3}} = \frac{\ell^*}{c_s K_s} \frac{(1-\beta)/3}{(1-\beta)/3} \left(\frac{R_s}{W^{1/3}}\right)^{\beta} \quad (A.12)$$

$$\frac{I_s}{W^{1/3}} = \frac{m^* K_s^{(2-\gamma)/3}}{c_s} \left(\frac{R_s}{W^{1/3}} \right)^{-\gamma} \quad (\text{A.13})$$

$$\frac{E_s}{W^{1/3}} = \frac{n^*}{K_s^{(\delta-2)/3}} \left(\frac{R_s}{W^{1/3}} \right)^{-\delta} \quad (\text{A.14})$$

Substituting Equations 2.17 through 2.20 into Equations A.11 through A.14, respectively, we get

$$P_{MAX_s} = k_s \left(\frac{W^{1/3}}{R_s} \right)^\alpha \quad (\text{A.15})$$

$$\frac{\theta_s}{W^{1/3}} = \ell_s \left(\frac{R_s}{W^{1/3}} \right)^\beta \quad (\text{A.16})$$

$$\frac{I_s}{W^{1/3}} = m_s \left(\frac{W^{1/3}}{R_s} \right)^\gamma \quad (\text{A.17})$$

$$\frac{E_s}{W^{1/3}} = n_s \left(\frac{W^{1/3}}{R_s} \right)^\delta \quad (\text{A.18})$$

which is our desired result.

DISTRIBUTION

	Copies
Director Defense Advanced Research Project Agency Attn: Technical Library Washington, D. C. 20301	1
Chief of Naval Operations Department of the Navy Attn: OP-981F OP-981F1 OP-324 OP-324T Washington, D. C. 20350	1 1 1 1
Commander Naval Air Systems Command Department of the Navy Attn: AIR-350D Washington, D. C. 20361	1
Commander Naval Sea Systems Command Attn: SEA-322 (J. Sullivan) SEA-322 (D. M. Hurt) SEA-322 (R. E. Fuss) SEA-62R32 (G. D. Edwards) SEA-62R (W. W. Blaine) SEA-09G32 SEA-03B Washington, D. C. 20362	1 1 1 1 1 2 1
Commander David Taylor Naval Research & Development Center Attn: Code 17 Code 1740 Code 1740.1 Code 1750 Code 1720 Code 1720.3 Code 042 Bethesda, Maryland 20084	1 1 1 1 1 1 1
Chief of Naval Material Department of the Navy Attn: MAT-0323 Washington, D. C. 20360	1

DISTRIBUTION (Cont.)

	Copies
Underwater Explosions Research Division David Taylor Naval Ship Research & Development Center Attn: Technical Reference Center R. Oliver Portsmouth, Virginia 23709	1 1
Director Naval Research Laboratory Attn: Code 2027 Code 8400 Code 8406 Washington, D. C. 20375	1 1 1
Commander Naval Weapons Center Attn: Code 533 (Technical Library) Code 385 (A. B. Amster) China Lake, California 93555	1 1
Commander Naval Ocean Systems Center Attn: Technical Library San Diego, California 92152	1
Commanding Officer Naval Underwater Systems Center Attn: Technical Library Newport, Rhode Island 02840	1
Defense Technical Information Center Cameron Station Alexandria, Virginia 22314	12
Defense Nuclear Agency Attn: SPSS Washington, D. C. 20305	2
Office of Naval Research 800 N. Quincy Street Attn: Code 474 Code 480 Arlington, Virginia 22217	1 2
Commanding Officer Naval Weapons Station Attn: Dr. Lewis R. Rothstein (NEDED) Dr. William McBride (NEDED) Yorktown, Virginia 23491	1 1

DISTRIBUTION (Cont.)

	Copies
Commander Naval Coastal Systems Center Attn: Library Panama City, Florida 32407	1
Chief of Naval Material Office of Naval Technology Attn: MAT-07 (J. W. Enig) Washington, D. C. 20360	1
Dr. Hans G. Snay 17613 Tree Lawn Drive Ashton, Maryland 20702	1
Department of Mechanical Engineering Catholic University Attn: Robert J. Urick Washington, D. C.	1
Director Waterways Experiment Station Attn: Technical Library	1
J. N. Strange	1
Kim Davis	1
WESNE	1
P. O. Box 631 Vicksburg, Mississippi 39180	
Lovelace Biomedical & Environmental Research Institute, Inc. Attn: E. Royce Fletcher P. O. Box 5890 Albuquerque, New Mexico 87115	1
Tetra Tech, Inc. Attn: Li-San Hwang 630 N. Rosemead Blvd. Pasadena, California 91107	1

TO AID IN UPDATING THE DISTRIBUTION LIST
FOR NAVAL SURFACE WEAPONS CENTER, WHITE
OAK TECHNICAL REPORTS PLEASE COMPLETE THE
FORM BELOW:

TO ALL HOLDERS OF NSWC/TR 80-491
by John F. Goertner, Code RI4

DO NOT RETURN THIS FORM IF ALL INFORMATION IS CURRENT

A. FACILITY NAME AND ADDRESS (OLD) (Show Zip Code)

NEW ADDRESS (Show Zip Code)

B. ATTENTION LINE ADDRESSES:

C.

REMOVE THIS FACILITY FROM THE DISTRIBUTION LIST FOR TECHNICAL REPORTS ON THIS SUBJECT.

D.

NUMBER OF COPIES DESIRED _____

**DEPARTMENT OF THE NAVY
NAVAL SURFACE WEAPONS CENTER
WHITE OAK, SILVER SPRING, MD. 20910**

**OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE, \$300**

**POSTAGE AND FEES PAID
DEPARTMENT OF THE NAVY
DOD 316**



**COMMANDER
NAVAL SURFACE WEAPONS CENTER
WHITE OAK, SILVER SPRING, MARYLAND 20910**

ATTENTION: CODE R14

END

DATE
FILMED

9 - 8 1

DTIC