

AD-A105551

AD A-105551

MEMORANDUM REPORT ARBRL-MR-03136

TRAJECTORY PREDICTIONS FOR A 75 MM SOLID
FUEL RAMJET TUBULAR PROJECTILE

Carl W. Nelson

September 1981



US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND
BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND

Approved for public release; distribution unlimited.

Destroy this report when it is no longer needed.
Do not return it to the originator.

Secondary distribution of this report by originating
or sponsoring activity is prohibited.

Additional copies of this report may be obtained
from the National Technical Information Service,
U.S. Department of Commerce, Springfield, Virginia
22151.

The findings in this report are not to be construed as
an official Department of the Army position, unless
so designated by other authorized documents.

*The use of trade names or manufacturers' names in this report
does not constitute indorsement of any commercial product.*

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER MEMORANDUM REPORT ARBRL-MR-03136	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) TRAJECTORY PREDICTIONS FOR A 75 MM SOLID FUEL RAMJET TUBULAR PROJECTILE		5. TYPE OF REPORT & PERIOD COVERED BRL Memorandum Report
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) CARL W. NELSON		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS US Army Armament Research & Development Command US Army Ballistic Research Laboratory ATTN: DRDAR-BLI Aberdeen Proving Ground, MD 21005		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 11161101A91A
11. CONTROLLING OFFICE NAME AND ADDRESS US Army Armament Research & Development Command US Army Ballistic Research Laboratory ATTN: DRDAR-BL Aberdeen Proving Ground, MD 21005		12. REPORT DATE SEPTEMBER 1981
		13. NUMBER OF PAGES 28
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Solid Fuel Ramjet Tubular Projectile Air Breathing Combustion Trajectory Guns		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) jmk The AFAPL ramjet design analysis code was modified to predict a point mass trajectory for a 75 mm solid fuel ramjet tubular projectile. Projectile velocity was found sensitive to the combustion efficiency relation assumed.		

TABLE OF CONTENTS

	Page
LIST OF ILLUSTRATIONS.	5
I. INTRODUCTION	7
II. ASSUMPTIONS.	7
III. FUEL DATA.	8
IV. COMBUSTION	8
V. RESULTS.	13
REFERENCES	15
LIST OF SYMBOLS.	17
APPENDIX A	19
DISTRIBUTION LIST.	23

LIST OF ILLUSTRATIONS

Figure	Page
1. Fuel-in-Cowl Schematic.	10
2. Comparison of Correlated and Measured Combustion Efficiency . .	12
3. Non-Linear Fitting Function for Combustion Efficiency	12
4. Velocity vs Range for 75 mm SFRJ-TP	13
5. Combustion Chamber Performance of 75 mm SFRJ-TP	14
6. Effect of Combustion Efficiency Correlation on Predicted Efficiency.	14

I. INTRODUCTION

Army interest in Solid Fuel Ramjets (SFRJ) spawned a technology demonstration program for a gun launched tubular projectile with an SFRJ combustion chamber. Chemical Systems Division of United Technologies Corp designed a 75 mm demonstration round after wind tunnel and direct connect tests*. New flight regimes were encountered in the high velocity (Mach 4 plus) at sea level. Almost all ramjet experience has been with either low velocity or high altitude; performance correlations have not been developed for the tubular projectile flight regime. Data remain scarce on regression rate and combustion efficiency dependence on air flow conditions.

Predicting the performance of these SFRJ projectiles requires coupling the solid fuel combustion chamber to the supersonic diffuser inlet. An AFAPL (Air Force Aero Propulsion Laboratory) computer code¹ for ramjet design analysis was modified to compute combustion in the solid fuel chamber. Expected performance of the 75 mm SFRJ tubular projectiles is hereby reported.

II. ASSUMPTIONS

1. Enthalpy versus temperature and pressure for incoming air taken from Keenan and Kaye** properties of air at low pressure. The values were supplied with the AFAPL code. At the nominal launch velocity (Mach 4.29) on a standard day at sea level, the air stagnation temperature and pressure are 1260K and 24.9 MPa.
2. US Standard Atmosphere. For these sea level, standard day trajectories no altitude variations need be considered.
3. Constant drag coefficient (.0645). A value suggested by Chemical Systems Division after its preliminary design studies and some wind tunnel tests. That the coefficient will be velocity dependent has been conveniently ignored.
4. Constant nozzle efficiency (0.98). A reasonable value for conical nozzles. Variations due to chamber conditions and nozzle design have been ignored.
5. Normal shock inlet operation. Pressure loss ratios in the inlet calculated from standard normal shock tables for an ideal gas of 1.4 specific heat ratio. Exact inlet calculations are not made; only area ratios are considered.
6. Adiabatic processes. No heat loss to projectile body.
7. Combustion fully established as initial condition. Ignition transient not considered.

**A direct connect test is a combustion chamber without inlet. Air enters the chamber at flow conditions expected at the inlet dump plane.*

¹*K. A. Watson, "Air breathing Missile Design Program-FJ", AFAPL-FJT-TM-77-29, AF Aero Propulsion Laboratory, (November 77).*

***Provided without reference citation.*

III. FUEL DATA

Fuel thermodynamic data, supplied by Chemical Systems Division, are shown in Table 1. The values represent complete combustion at the air temperature and equivalence ratio. In the calculations final temperature is corrected for combustion efficiency in the standard method

$$T_f = T_a + \eta_c (T_{t_f} - T_a) ,$$

where η_c = combustion efficiency,

T_f = final temperature,

T_a = incoming air temperature,

T_{t_f} = theoretical final temperature.

Specific heat ratio and molecular weight were assumed unaffected by combustion efficiency. The data are given only for one pressure (3.0 MPa). No corrections were attempted for pressure. (Nominal chamber pressure is near that level.)

IV. COMBUSTION

Flow of fuel from the solid surface into the combustion chamber is governed by the simple

$$\dot{w}_f = \rho_f \dot{r} S.$$

Calculations of regression rate (\dot{r}) and surface area (s) provide the only challenge. Regression rate is available for a few fuels from CSD monthly contract reports in the form

$$\dot{r} = a G^n ,$$

where G is the air mass velocity and constants a and n can vary with air stagnation temperature and pressure. CSD's data for the fuel intended for the 75 mm demonstration rounds produces a regression rate correlation of

$$\dot{r} = 0.116 G^{0.64} . \tag{1}$$

TABLE 1. FUEL THERMODYNAMIC DATA

$P_4 = 440$ psia

ϕ	0.306	0.394	0.499	0.604	0.700	0.796	0.901	1.00
AIR TEMPERATURE (R)	FINAL TEMPERATURE (K)							
1300	1465	1645	1860	2060	2225	2380	2528	2605
1900	1765	1920	2120	2298	2448	2585	2692	2760
2500	2060	2220	2380	2550	2675	2775	2755	2902
3000	2280	2425	2585	2720	2825	2908	2975	3012
	SPECIFIC HEAT RATIO							
1300	1.297	1.2875	1.2745	1.2595	1.2435	1.227	1.203	1.176
1900	1.284	1.272	1.2575	1.2425	1.226	1.2045	1.177	1.161
2500	1.266	1.254	1.240	1.220	1.199	1.178	1.1585	1.149
3000	1.248	1.236	1.222	1.1985	1.1785	1.162	1.149	1.142
	MOLECULAR WEIGHT							
1300	29.10	29.15	29.20	29.25	29.30	29.30	29.30	29.05
1900	29.10	29.15	29.15	29.25	29.25	29.20	29.12	28.95
2500	29.10	29.10	29.15	29.22	29.17	29.07	28.95	28.75
3000	29.05	29.05	29.15	29.15	29.05	28.92	28.75	28.50

Exposed fuel surface is a straightforward geometry problem. All planned configurations for the gun a launched projectiles are internally perforated cylinders. (The high spin rate precludes the common form spoke gain of guided missile applications). Only one complication is presented - the grain length. The fuel-in-cowl design packs in more fuel but regression shortens the exposed length. Exact surface calculation depends on the specific internal cowl design but the goemetry adjustment is straightforward. Figure 1 shows a typical fuel-in-cowl design.



Figure 1. Fuel in Cowl Schematic

Combustion efficiency correlations are also available from CSD monthly contract reports for a few fuels. It is in the form

$$\eta = b \phi^c T_a^d \frac{A_3}{A_i} \quad (2)$$

The equivalence ratio ϕ comes from the fuel and air flow calculations and the step area ratio $\frac{A_3}{A_i}$ from the chamber geometry.

CSD's reported correlation² for the 75 mm fuel is

$$\eta = 0.22 \phi^{-.45} \frac{T_a}{1000}^{1.16} \frac{A_3}{A_i}^{0.38} \quad (3)$$

Both regression rate and combustion efficiency change with time because air conditions change with projectile velocity and because the fuel regresses to increase the step area ratio A_3/A_i .

²Monthly Progress Report No. 22, Chemical Systems Divisions, (August 80).

The combustion efficiency correlation was derived from tests where the efficiency never exceeded 0.90. Extrapolation to the combustion chamber conditions for the 75 mm projectile would predict efficiencies greater than 1.0. Maximum of 1.0 was assigned despite arguments³ for greater measured efficiencies.

Some recent CSD performance calculations for a 35 mm SFRJ-TP used an efficiency expression

$$\eta = \frac{0.18}{\phi^{-.45}} \frac{A_3}{A_i}^{0.3} \frac{T_a}{1000}^{1.1}, \quad (4)$$

although no source was cited.

An independent analysis of the reported CSD test data for fuel 21862 obtained a least squares fit⁴ of

$$\eta = \frac{.232}{\phi^{-.347}} \frac{A_3}{A_i}^{.491} \frac{T_a}{1000}^{.944}. \quad (5)$$

Figure 2 compares experimental with correlated values of efficiency for Eq. (5). Appendix A gives the data used in the analysis.

The transition from the linear correlation,

$$\eta = a X,$$

where X is the power function of all the influencing variables to a limit of $\eta \rightarrow 1.0$ requires some imagination. The test data do not extend to those conditions. An arbitrary selection of a functional dependence must suffice. It should satisfy a few conditions: (1) for mid range ($0.4 < aX < 0.8$) it should be $\eta = aX$; (2) for $aX < 0.4$ it is irrelevant in present applications, (3) it must approach $\eta = 1$ for $aX < 0.8$ smoothly. Final forms are limited only by the imagination; physics provides few clues. After some acrobatics the following form makes a reasonable estimate

³R. Dunlap, G. E. Jensen, "Combustion Efficiency in a SFRJ at the Fuel Grain Exit Plan", 16th JANNAF Combustion Meeting, Monterey, CA (September 1979).

⁴R. H. Moore, R. K. Zeigler, "The Solution of the General Least Squares Problem with Special Reference to High Speed Computers" Los Alamos Scientific Laboratory Report LA2367 (March 1960).

$$\eta = 1 - [4 - \frac{1}{2} (X-3)^2] \sqrt{X} e^{-1.1X} \quad (6)$$

For $a = 0.23$ comparison of η with aX is shown in Figure 3.




Figure 2. Comparison of Correlated and Measured Combustion Efficiency




Figure 3. Non-linear fitting function for Combustion Efficiency

Regression rate was also obtained from a least square fit for fuel 21862. With air temperature dependence, the best fit is

$$\dot{r} = .0634 G^{.833} \frac{T_a}{1000}^{.614} \quad (7)$$

The regression rates obtained with this fit are close to those obtained with the CSD reported dependence (Eq. (1)).

V. RESULTS

Trajectories were calculated for the 75 mm SFRJ-TP designed for gun firing demonstration. Figure 4 shows the velocity versus range on non-dimensional scales of velocity divided by initial velocity and range divided by range at burnout. Security classification precludes reporting actual velocities and ranges.




Figure 4. Velocity vs range for 75 mm SFRJ-TP

The three trajectories in Figure 4 come from different assumptions on combustion efficiency. The central curve represents the amended least squares fit of Eq. (6); the upper curve represents the CSD offered efficiency of Eq. (3); the lower curve represents the CSD suggested Eq. (4).

The spread among the calculated trajectories demonstrates the sensitivity to the assumption of combustion efficiency. Since each represents an extrapolation from the test data from which the correlations were derived, they may all be wrong. Both the need for extrapolation and the sensitivity demonstrate the necessity for data in the expected conditions.

Some details of the combustion chamber performance are shown in Figure 5 which displays time history of regression rate and air mass velocity.




Figure 5. Chamber performance of 75 mm SFRJ-TP

Figure 6 shows the predicted combustion efficiency for various assumptions about its dependence on chamber conditions. Curve 30 uses the CSD Eq. (3); Curve 44 uses the amended fit Eq. (6); Curve 40 uses the re-analyzed CSD data correlation, Eq. (5); Curve 29 uses the CSD correlation of Eq. (4). All the calculations limited the efficiency to 1.0 arbitrarily.




Figure 6. Effect of Combustion Efficiency Correlation on Predicted Efficiency

REFERENCES

1. K. A. Watson, "Air breathing Missile Design Program-FJ", AFAPL-FJT-TM-77-29, AF Aero Propulsion Laboratory, (November 77).
2. Monthly Progress Report No. 22, Chemical Systems Divisions, (August 80).
3. R. Dunlap, G. E. Jensen, "Combustion Efficiency in a SFRJ at the Fuel Grain Exit Plan", 16th JANNAF Combustion Meeting, Monterey, CA (September 79).
4. R. H. Moore, R. K. Zeigler, "The Solution of the General Least Squares Problem with Special Reference to High Speed Computers" Los Alamos Scientific Laboratory Report LA2367 (March 1960).

LIST OF SYMBOLS

G	air mass velocity
r	fuel regression rate
S	Fuel surface area
T_a	Air Temperature (Stagnation)
T_f	Final Combustion Temperature
T_{tf}	Theoretical Final Combustion Temperature
\dot{W}	Mass flow rate
n_c	Combustion efficiency
ϕ	Equivalence ratio
ρ_f	Fuel density

APPENDIX A
CSD TEST DATA

APPENDIX A
CSD TEST DATA

<u>Test</u>	<u>T_a</u>	$\frac{A_3}{A_1}$	<u>P</u>	<u>G</u>	<u>φ</u>	<u>regr rate</u>	<u>η</u>
7068	1285	2.017	116	.566	.543	.049	.576
7070	1845	2.334	204	.729	.580	.074	.753
7071	1860	2.354	271	.965	.539	.091	.786
7072	1860	2.334	250	.927	.876	.106	.627
7073	1850	1.572	191	.826	.850	.087	.520
7074	1850	1.490	127	.573	.882	.061	.522
7075	2200	1.572	200	.807	.613	.081	.831
7076	2200	2.198	207	.768	.696	.090	.882
7078	2200	1.541	203	.814	.844	.084	.677
7079	2200	1.715	155	.753	.717	.091	.822
6939	1850	1.399	319	1.120	.522	.090	.555
6940	1850	1.394	222	.780	.590	.071	.525
6941	1850	1.391	115	.390	.777	.048	.443
6942	1850	1.405	62	.200	1.069	.033	.447
6943	1860	1.353	269	1.000	.534	.080	.549
6944	1850	1.391	264	.980	.415	.083	.581
6945	1855	1.374	329	.990	.393	.079	.610
6946	1860	1.373	346	1.00	.524	.080	.574
6947	1855	1.432	223	.970	.598	.091	.587
6948	1850	1.449	207	.930	.489	.095	.586
6928	1840	1.419	234	.970	.409	.082	.649
6929	1885	1.410	239	1.00	.408	.084	.625
6930	1885	1.429	236	.980	.433	.088	.580
6931	1885	1.438	238	.980	.432	.088	.581
6933	1910	1.464	244	.970	.574	.088	.489
6934	1880	1.478	247	.960	.599	.091	.510
6935	1850	1.401	323	1.14	.392	.092	.743
6936	1850	1.389	214	.780	.442	.070	.587
6937	1850	1.389	111	.400	.589	.048	.475
6938	1850	1.392	58	.200	.786	.032	.382
6916	1850	1.359	236	1.0	.439	.088	.688
6917	1850	1.391	241	.99	.448	.090	.681
6918	1850	1.401	260	1.02	.586	.092	.624
6919	1850	1.463	267	1.00	.579	.091	.654
6921	1600	1.521	214	.86	.383	.070	.711
6922	2020	1.415	250	.98	.468	.094	.696
6923	2020	1.391	259	1.01	.576	.089	.612
6924	1850	1.409	289	.97	.401	.080	.683
6925	1850	1.392	302	.99	.532	.081	.632
6927	1840	1.030	234	.96	.427	.085	.630
6871	1870	1.589	254	1.40	.498	.113	.689
6872	2050	1.660	271	1.35	.576	.130	.702
6873	2050	1.543	194	1.03	.643	.106	.650
6874	2060	1.313	323	1.54	.564	.148	.733
6875	1850	1.224	180	1.02	.609	.098	.646
6876	1840	1.307	304	1.53	.543	.140	.707

APPENDIX A

CSD TEST DATA

<u>Test</u>	<u>T_a</u>	$\frac{A_3}{A_i}$	<u>P</u>	<u>G</u>	<u>ϕ</u>	<u>regr rate</u>	<u>η</u>
6877	1840	1.688	315	1.61	.508	.138	.736
6878	1845	1.307	326	1.64	.513	.143	.728
6879	2050	1.589	259	1.28	.807	.126	.625
6880	1840	1.319	360	1.80	.496	.153	.743
6881	1770	1.656	362	1.92	.511	.164	.707
6892	1850	1.523	307	1.40	.541	.121	.722
6855	2080	1.719	409	1.62	.542	.149	.705
6856	2080	1.268	237	0.98	.670	.108	.619
6857	1750	1.237	212	.98	.670	.105	.564
6858	1750	1.672	362	1.58	.513	.136	.655
6860	1775	1.488	173	1.01	.664	.105	.556
6861	1770	1.222	326	1.41	.551	.121	.517
6863	2050	1.619	298	1.31	.609	.132	.514
6864	1750	1.223	288	1.42	.762	.128	.440
6865	1750	1.257	314	1.72	.659	.138	.585
6866	2025	1.672	302	1.67	.657	.138	.652
6867	2025	1.254	260	1.34	.739	.120	.655
6868	1850	1.569	258	1.40	.710	.120	.555

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
12	Commander Defense Technical Info Center ATTN: DDC-DDA Cameron Station Alexandria, VA 22314	1	Commander US Army Armament Materiel Readiness Command ATTN: DRSAR-LEP-L, Tech Lib Rock Island, IL 61299
1	Director Defense Advanced Research Projects Agency ATTN: LTC. C. Buck 1400 Wilson Boulevard Arlington, VA 22209	1	Commander US Army Watervliet Arsenal ATTN: Code SARWV-RD, R. Thierry Watervliet, NY 12189
2	Director Institute for Defense Analyses ATTN: H. Wolfhard R.T. Oliver 400 Army-Navy Drive Arlington, VA 22202	1	Director US Army ARRADCOM Benet Weapons Laboratory ATTN: DRDAR-LCB-TL Watervliet, NY 12189
1	Commander US Army Materiel Development and Readiness Command ATTN: DRCMDM-ST 5001 Eisenhower Avenue Alexandria, VA 22333	1	Commander US Army Aviation Research and Development Command ATTN: DRDAV-E 4300 Goodfellow Blvd. St. Louis, MO 63120
6	Commander US Army Armament Research and Development Command ATTN: DRDAR-LCA, J. Lannon DRDAR-LCA, D. Downs DRDAR-LCA, L. Harris DRDAR-LC, J.P. Picard DRDAR-LCE, R.F. Walker DRDAR-SCA, L. Stiefel Dover, NJ 07801	1	Director US Army Air Mobility Research and Development Laboratory Ames Research Center Moffett Field, CA 94035
2	Commander US Army Armament Research & Development Command ATTN: DRDAR-TSS Dover, NJ 07801	1	Commander US Army Communications Rsch and Development Command ATTN: DRDCO-PPA-SA Ft. Monmouth, NJ 07703
		1	Commander US Army Electronics Research & Development Command Technical Support Activity ATTN: DELSD-L Fort Monmouth, NJ 07703

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Commander US Army Missile Command ATTN: DRSMI-R Redstone Arsenal, AL 35809	1	Office of Naval Research ATTN: Code 473 800 N. Quincy Street Arlington, VA 22217
1	Commander US Army Missile Command ATTN: DRSMI-YDL Redstone Arsenal, AL 35809	1	Commander Naval Sea Systems Command ATTN: J.W. Murrin (NAVSEA-62R2) National Center Building 2, Room 6E08 Washington, DC 20360
1	Commander US Army Natick Research and Development Command ATTN: DRXRE, D. Sieling Natick, MA 01762	2	Commander Naval Surface Weapons Center ATTN: S.J. Jacobs/Code 240 Code 730 Silver Springs, MD 20910
1	Commander US Army Tank Automotive Rsch and Development Command ATTN: DRDTA-UL Warren, MI 48090	1	Commander Naval Surface Weapons Center ATTN: Library Br, DX-21 Dahlgren, VA 22448
1	Commander US Army White Sands Missile Range ATTN: STEWS-DP-AL WSMR, NM 88002	1	Commander Naval Underwater Systems Center Energy Conversion Department ATTN: R.S. Lasar/Code 5B331 Newport, RI 02840
1	Commander US Army Materiel & Mechanics Research Center ATTN: DRXMR-ATL Watertown, MA 02172	2	Commander Naval Weapons Center ATTN: R. Derr C. Thelen F. Zarlingo China Lake, CA 93555
1	Commander US Army Research Office ATTN: Tech Lib Research Triangle Park, NC 27706	1	Commander Naval Research Laboratory ATTN: Code 6180 Washington, DC 20375
1	Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SL, Tech Lib White Sands Missile Range, NM 88002	2	Superintendent Naval Post Graduate School ATTN: Tech Lib D. Netzer Monterey, CA 93940

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
2	Commander Naval Ordnance Station ATTN: S. Livanis Tech Lib Indian Head, MD 20640	1	Calspan Corporation ATTN: E.B. Fisher P.O. Box 400 Buffalo, NY 14211
3	AFOSR ATTN: L. Caveny B.T. Wolfson Bolling AFB, DC 20332	1	Chemical Systems Division ATTN: D. Altman A. Holtzman P.O. Box 358 Sunnyvale, CA 94088
2	AFRPL (DYSC) ATTN: D. George J.N. Levine Edwards AFB, CA 93523	1	Foster Miller Associates, Inc. ATTN: A.J. Erickson 135 Second Avenue Waltham, MA 02154
1	Wright Propulsion Laboratories ATTN: F.D. Stull/RJT Wright Patterson, AFB, OH 45433	1	General Electric Company Armament Department ATTN: M.J. Bulman Lakeside Avenue Burlington, VT 05402
1	National Bureau of Standards ATTN: T. Kashiwagi Washington, DC 20234	1	General Electric Company Flight Propulsion Division ATTN: Tech Lib Cincinnati, OH 45215
1	Lockheed Palo Alto Rsch Labs ATTN: Tech Info Ctr 3521 Hanover Street Palo Alto, CA 94304	2	Hercules Incorporated Alleghany Ballistic Lab ATTN: R. Miller Tech Lib Cumberland, MD 21501
1	Aerojet Solid Propulsion Co. ATTN: P. Micheli Sacramento, CA 95813	1	IITRI ATTN: M.J. Klein 10 West 35th Street Chicago, IL 60615
1	Atlantic Research Corporation ATTN: M.K. King 5390 Cherokee Avenue Alexandria, VA 22314		
1	AVCO Corporation AVCO Everett Research Lab Div ATTN: D. Stickler 2385 Revere Beach Parkway Everett, MA 02149		

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	Olin Corporation Badger Army Ammunition Plant ATTN: J. Ramnarace Baraboo, WI 53913	1	Brigham Young University Dept of Chemical Engineering ATTN: M. W. Beckstead Provo, UT 84601 Provo, UT 84601
2	Olin Corporation New Haven Plant ATTN: R.L. Cook D.W. Riefler 275 Winchester Avenue New Haven, CT 06504	1	California Institute of Tech 204 Karmar Lab ATTN: F.E.C. Culick 1201 E. California Street Pasadena, CA 91125
1	Paul Gough Associates, Inc. ATTN: P.S. Gough P.O. Box 1014 Portsmouth, NH 03801	1	Case Western Reserve Univ. Division of Aerospace Sciences ATTN: J. Tien Cleveland, OH 44135
1	Physics International Company 2700 Merced Street San Leandro, CA 94577	5	Georgia Institute of Technology School of Aerospace Engineering ATTN: B.T. Zinn E. Price W.C. Strahle Atlanta, GA 30332
1	Pulsepower Systems, Inc. ATTN: L.C. Elmore 815 American Street San Carlos, CA 94070	1	Institute of Gas Technology ATTN: D. Gidaspow 3424 S. State Street Chicago, IL 60616
1	Science Applications Inc. 21133 Victory Boulevard Suite 210 ATTN: R. Edelman Canoga Park, CA 91303	1	Johns Hopkins University/APL Chemical Propulsion Information Agency ATTN: T. Christian Johns Hopkins Road Laurel, MD 20810
2	United Technologies ATTN: R. Brown Tech Lib P.O. Box 358 Sunnyvale, CA 94088	1	Massachusetts Institute of Technology Dept of Mechanical Engineering ATTN: T. Toong Cambridge, MD 02139
1	Universal Propulsion Co. ATTN: H.J. McSpadden 1800 W. Deer Valley Rd. Phoenix, AZ 85027		
1	Battelle Memorial Institute ATTN: Tech Lib 505 King Avenue Columbus, OH 43201		

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
1	Pennsylvania State University Applied Research Lab ATTN: G.M. Faeth P.O. Box 30 State College, PA 16801	4	SRI International ATTN: Tech Lib J. Barker D. Crosley D. Golden 333 Ravenswood Avenue Menlo Park, CA 94025
1	Pennsylvania State University Dept of Mechanical Engineering ATTN: K. Kuo University Park, PA 16801	1	Stevens Institute of Technology Davidson Laboratory ATTN: R. McAlevy, III Hoboken, NJ 07030
1	Pennsylvania State University Dept of Material Sciences ATTN: H. Palmer University Park, PA 16810	1	University of Illinois Dept of Mechanical Engineering ATTN: H. Krier 144 MEB, 1206 W. Green Street Urbana, IL 61801
1	Princeton University Forrestal Campus ATTN: Tech Lib P.O. Box 710 Princeton, NJ 08540	1	University of Minnesota Dept of Mechanical Engineering ATTN: E. Fletcher Minneapolis, MN 55455
1	Purdue University School of Mechanical Engineering ATTN: J. Osborn TSPC Chaffee Hall West Lafayette, IN 47906	1	University of Southern California Dept of Chemistry ATTN: S. Benson Los Angeles, CA 90007
		2	University of Texas Dept of Chemistry ATTN: W. Gardiner H. Schaefer Austin, TX 78712
		2	University of Utah Dept of Chemical Engineering ATTN: A. Baer G. Flandro Salt Lake City, UT 84112

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>
	<u>Aberdeen Proving Ground</u>
	Dir, USAMSAA ATTN: DRXSY-D DRXSY-MP, H. Cohen
	Cdr, USATECOM ATTN: DRSTE-TO-F
	Dir, USACSL, Bldg. E3516, EA ATTN: DRDAR-CLB-PA M. Miller

USER EVALUATION OF REPORT

Please take a few minutes to answer the questions below; tear out this sheet, fold as indicated, staple or tape closed, and place in the mail. Your comments will provide us with information for improving future reports.

1. BRL Report Number _____

2. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which report will be used.)

3. How, specifically, is the report being used? (Information source, design data or procedure, management procedure, source of ideas, etc.) _____

4. Has the information in this report led to any quantitative savings as far as man-hours/contract dollars saved, operating costs avoided, efficiencies achieved, etc.? If so, please elaborate.

5. General Comments (Indicate what you think should be changed to make this report and future reports of this type more responsive to your needs, more usable, improve readability, etc.) _____

6. If you would like to be contacted by the personnel who prepared this report to raise specific questions or discuss the topic, please fill in the following information.

Name: _____

Telephone Number: _____

Organization Address: _____

