

AD-A217 775

DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

It is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including this burden estimate, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Avenue, Washington, DC 20540, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE July 1989		3. REPORT TYPE AND DATES COVERED Final Report, 1 Aug 87 -30 Jun 89	
4. TITLE AND SUBTITLE THEORY SYSTEM RELIABILITY DEMONSTRATION AND BURN-IN DESIGN (Unclassified)				5. FUNDING NUMBERS AFOSR-87-0306 61102F 2304/A5	
6. AUTHOR(S) Dr. Saul Blumenthal					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Ohio State University Research Foundation 1314 Kinnear Road Columbia, OH 43212-1194				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Office of Scientific Research Mathematical and Information Sciences Building 410 Bolling AFB, DC 20332-6448				10. SPONSORING/MONITORING AGENCY REPORT NUMBER AFOSR-DR-80-0118	
11. SUPPLEMENTARY NOTES					
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public-release; distribution unlimited.				12b. DISTRIBUTION STATEMENT CODE S DTIC ELECTE FEB 07 1990 D E	
13. ABSTRACT (Maximum 200 words) Research accomplishments were registered in three areas. The first is lifetime estimation with truncated data. Maximum likelihood estimators and their asymptotic properties were studied. A Monte Carlo comparison of several estimators was performed when only interval data on lifetimes is available. The second area is under what conditions a "burn-in" was developed and tested using sequential estimation. Thirdly, distributions other than Poisson were tried, and it was found that in some cases a binomial approximation provides a more robust testing scheme for series systems with aging components. (SD)					
14. SUBJECT TERMS				15. NUMBER OF PAGES 4	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED		18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED		19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	
				20. LIMITATION OF ABSTRACT UL	



Theory System Reliability Demonstration and Burn-In Design

Saul Blumenthal
Department of Statistics

United States Air Force
Air Force Office of Scientific Research
Bolling Air Force Base, D. C. 20332

Grant No. 87-0306
Final Report
RF Project 766252/719817



July 1989

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced Justification	<input type="checkbox"/>
By _____	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

90 02 06 290

AFOSR RESEARCH GRANT 87-0306 - FINAL REPORT - JULY 1989

Subject: Final Report on the Project No. AFOSR 87-0306, July 1989
To: Air Force Office of Scientific Research, AFOSR/NM
Bldg. 410, Bolling AFB, DC
Program element no. 6.1102F, Project No. 2304, Task no. K3
From: Saul Blumenthal, Ohio State University, OSU Research Foundation Project
No. 716366

RESEARCH OF SAUL BLUMENTHAL ON AFOSR GRANT 87-0306

I. ESTIMATION WITH TRUNCATED DATA

1. Estimation of Sample Size with Grouped Data, submitted to J. Statist. Planning & Inference (with R. C. Dahiya).
2. Estimating N with Percentile Grouped, and Truncated Data from a Scale Parameter Distribution, Communications in Statist. Theor. Meth. 17, 1988, pp.3607-3628.
3. Estimating the Size of the Sample, to appear, Proc. Indo-U.S. Workshop on Bayesian Inference in Statist. and Econometrics, 1989, Springer Verlag.

We are given N random variables X_1, \dots, X_N with common density $f(x; \theta)$ where both N and θ are unknown. The values of the X 's can be observed only if they lie in the interval $(0, T)$. The problem addressed is estimation of N and θ . Maximum likelihood estimators and variants of these, namely Bayes modal estimators are derived and asymptotic properties are studied.

In [1], an additional restriction is imposed, namely that the interval $(0, T)$ is subdivided and only the number of X 's falling in each subinterval is reported, with all other details about actual values being lost. General techniques to analyze data in this form are developed, and restrictions on the estimation procedures are derived to assure the stochastic consistency of the estimator of N . A widely used iterative computing scheme is shown to fail the consistency conditions and several alternative schemes which are consistent are examined. An analysis of a software reliability data set is carried out, and Monte Carlo comparison of several estimators is performed, leading to one of them being recommended for use.

In [2], instead of grouping at fixed time points and observability on an interval of length T , it is assumed that only a fixed subset of the quantiles of the X 's can be

SAUL BLUMENTHAL - FINAL REPORT ON AFOSR GRANT 87-0306, JULY 1989

observed, the largest one being the (n/N) th, with $n < N$. Problems of the type considered in [1] are examined for this alternative model.

The paper [3] is a review of recent work on all aspects of estimation with truncated data, but concentrates on applications of this work to estimating the number of undetected errors remain in computer software after an initial testing period. Both the papers in the software reliability literature which lead to truncated data models, and the papers discussing the statistical analysis of these models are reviewed.

II. BURN-IN.

1. Burn-in with Mixed Populations. Ohio State University, Statistics Department Technical Report No. 372, August 1987 (with U.Q. Pan).
2. Burn-in using a sequential screening procedure. Technical Report 1987.14, Dept of Mathematics and Statistics, Wright State Univ., December 1987 (with U.Q. Pan).
3. A Reliability Model for Burn-in. Technical Report 1987.12, Dept of Mathematics and Statistics, Wright State Univ., November 1987 (with U.Q. Pan).

Closely related to the problem described in Part I is the burn-in problem. In its simplest form, a batch of M items contains N (unknown) defectives with known failure distribution. A sequential stopping rule is desired for removing enough of the defectives to assure that with a specified high probability the reliability of the remaining items in the lot after burn-in exceeds some given lower bound. Various stopping rules have been studied for both exact and approximate (large lot size) properties. The technical report [1] is based on the dissertation of Dr. Pan. In [2], a procedure for burn-in based on a sequential estimation scheme published previously by the proposer is extracted from [1], additional computations of its small lot size properties are made and some additional analytic properties are developed. This report is currently being readied for submission for possible publication. In [3], the characterization of the fixed burn-in time procedure which achieves the after burn-in reliability goal is extracted from [1]. This fixed time depends on knowing more than is generally available, but serves as a benchmark to which to compare the sequential schemes to see how much extra time they take because the extra information is not available. This too, will soon be ready for submission to a journal.

III. RELIABILITY DEMONSTRATION.

1. Reliability Demonstration for New Series Systems, in preparation.
2. A New Approximation for the Reliability of New Series Systems, in preparation.
3. A Two-Stage Procedure for Reliability Demonstration of New Series Systems, in preparation.

Series systems exhibit wear out if the components tend to wear out as they age. Acceptance sampling criteria are usually stated in terms of Mean Time Between Failures (MTBF) for an aged (or equilibrium) system. However, the acceptance test is often administered to a newly produced system. If the test does not take into account the fact that the new system has a much larger MTBF than it will have after aging, too high a proportion of poor quality systems will be accepted. In [1], we have developed tests which take this aging phenomenon into account. They are based on a Poisson approximation for the distribution of the number of failures a new system will have in a fixed time period, and on the assumption that the component failure distribution is known except for the value of a scale parameter. We have also looked into the robustness of the O.C. curves of these procedures in case the failure distribution is a gamma or Weibull with unknown shape parameter.

In [2], we have studied alternatives to the Poisson approximation and found that for moderate size systems, a binomial approximation fits the true distribution more closely than the Poisson or any of several other possible approximations. We are now looking at test design using the binomial.

In [3], we are studying a two stage testing procedure for gamma failure densities which develops an estimate of the shape parameter based on the first stage data, and then uses that estimate to develop an appropriate test time and acceptance criterion for the second stage so that a desired O.C. can be achieved.