

AD-A220 295

MEMORANDUM REPORT BRL-MR-3817

**BRL**

FILE COPY

PURIFICATION AND PROCESSING OF  
ELECTROCHEMICALLY PRODUCED  
HYDROXYLAMMONIUM NITRATE

**S** DTIC  
ELECTE  
APR 10 1990  
*Co* **B** **D**

NATHAN KLEIN  
JOSEPHINE Q. WOJCIECHOWSKI  
CHARLES S. LEVERITT

MARCH 1990

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

U.S. ARMY LABORATORY COMMAND

BALLISTIC RESEARCH LABORATORY  
ABERDEEN PROVING GROUND, MARYLAND

## NOTICES

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

# UNCLASSIFIED

<b>REPORT DOCUMENTATION PAGE</b>			Form Approved OAS No. 0704-0100
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Service, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0100), Washington, DC 20503.			
<b>1. AGENCY USE ONLY (Leave blank)</b>	<b>2. REPORT DATE</b> March 1990	<b>3. REPORT TYPE AND DATES COVERED</b> Memorandum	
<b>4. TITLE AND SUBTITLE</b> Purification and Processing of Electrochemically Produced Hydroxylammonium Nitrate		<b>5. FUNDING NUMBERS</b>  PR: F03A909AJGH3  WU: DA306905	
<b>6. AUTHOR(S)</b> Klein, Nathan; Wojciechowski, Josephine Q.; and Leveritt, Charles S.		<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b>	
<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b>		<b>9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b> US Army Ballistic Research Laboratory ATTN: SLCBR-DD-T Aberdeen Proving Ground, MD 21005-5066	
<b>10. SPONSORING / MONITORING AGENCY REPORT NUMBER</b>  BRL-MR-3817		<b>11. SUPPLEMENTARY NOTES</b> We acknowledge the assistance of Ms. Sharon Taylor who carried out the titrimetric analyses. We would also like to acknowledge Ronald A. Sassé and Dr. Eli Freedman for graciously reviewing and commenting on this work.	
<b>12a. DISTRIBUTION / AVAILABILITY STATEMENT</b> Approved for public release; distribution unlimited		<b>12b. DISTRIBUTION CODE</b>	
<b>13. ABSTRACT (Maximum 200 words)</b> Hydroxylammonium nitrate (HAN) is the major component of the aqueous monopropellants used in the liquid propellant gun. It is produced by the electrolytic reduction of nitric acid, a process that results in a dilute HAN-water mixture containing excess nitric acid. This excess acid must be removed before the HAN is concentrated for use in propellant production. A strongly acidic, cation exchange resin, INIAC CUP-110, has been evaluated for this purpose and works quite well. The resin is used to replace the hydrogen ion in the HAN-acid mixture with hydroxylammonium, thus removing the undesirable acid and producing additional HAN. The possibilities of using basic, anion exchange resins are also discussed.			
<b>14. SUBJECT TERMS</b> Liquid Propellants; Hydroxylammonium Nitrate; HAN; LGP 1845; LGP 1846; Ion-exchange		<b>15. NUMBER OF PAGES</b> 22	
<b>16. PRICE CODE</b>		<b>17. SECURITY CLASSIFICATION OF REPORT</b> UNCLASSIFIED	
<b>18. SECURITY CLASSIFICATION OF THIS PAGE</b> UNCLASSIFIED		<b>19. SECURITY CLASSIFICATION OF ABSTRACT</b> UNCLASSIFIED	
<b>20. LIMITATION OF ABSTRACT</b> SAR		<b>21. LIMITATION OF ABSTRACT</b>	

## GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to stay within the lines to meet optical scanning requirements.

### Block 1. Agency Use Only (Leave blank).

**Block 2. Report Date.** Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

**Block 3. Type of Report and Dates Covered.** State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

**Block 4. Title and Subtitle.** A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

**Block 5. Funding Numbers.** To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract	PR - Project
G - Grant	TA - Task
PE - Program Element	WU - Work Unit Accession No.

**Block 6. Author(s).** Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

**Block 7. Performing Organization Name(s) and Address(es).** Self-explanatory.

**Block 8. Performing Organization Report Number.** Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

**Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es).** Self-explanatory.

**Block 10. Sponsoring/Monitoring Agency Report Number.** (If known)

**Block 11. Supplementary Notes.** Enter information not included elsewhere such as: Prepared in cooperation with...; Trans. of...; To be published in.... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

**Block 12a. Distribution/Availability Statement.** Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."

DOE - See authorities.

NASA - See Handbook NHB 2200 2.

NTIS - Leave blank.

### Block 12b. Distribution Code.

DOD - Leave blank.

DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.

NASA - Leave blank.

NTIS - Leave blank.

**Block 13. Abstract.** Include a brief (Maximum 200 words) factual summary of the most significant information contained in the report.

**Block 14. Subject Terms.** Keywords or phrases identifying major subjects in the report.

**Block 15. Number of Pages.** Enter the total number of pages.

**Block 16. Price Code.** Enter appropriate price code (NTIS only).

**Blocks 17. - 19. Security Classifications.** Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

**Block 20. Limitation of Abstract.** This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.

TABLE OF CONTENTS

I. INTRODUCTION . . . . . 1

II. BACKGROUND . . . . . 2

III. EXPERIMENTAL METHODS . . . . . 6

IV. RESULTS AND DISCUSSION . . . . . 7

V. CONCLUSIONS . . . . . 10

<b>Accession For</b>	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification _____	
By _____	
Distribution/	
<b>Availability Codes</b>	
Dist	Avail and/or Special
A-1	



INTENTIONALLY LEFT BLANK.

#### ACKNOWLEDGMENT

We acknowledge the assistance of Ms. Sharon Taylor who carried out the titrimetric analyses. We would also like to acknowledge Ronald A. Sasse' and Dr. Eli Freedman for graciously reviewing and commenting on this work.

INTENTIONALLY LEFT BLANK.

## I INTRODUCTION

The US Army is currently investigating the use of liquid propellants in large and medium caliber guns. Propellants that are aqueous and homogeneous and contain hydroxylammonium nitrate (HAN) as an oxidizer have been determined to be the most promising candidates. Propellants LGP 1845 and LGP 1846 have undergone extensive characterization and testing and consist of HAN as the oxidizer, triethanolammonium nitrate (TEAN) as the fuel, and water as a diluent and solvent. Propellant compositions are shown in Table 1.

TABLE 1

### Propellant Compositions in Weight Percent

	HAN	TEAN	H <sub>2</sub> O
LGP 1845	63.2	20.0	16.8
LGP 1846	60.8	19.2	20.0

As shown in Table 1, HAN is the major ingredient in both of these propellants. There is currently only one commercial source of HAN in the United States, Southwest Analytical Chemicals, Austin, TX. The compound is sold in dilute solution (20-25 %) and must be concentrated (>80 %) for use in propellant production. Since this source produces HAN using a proprietary process not available to the US Army, the Army was compelled to develop a process for production of HAN.

## II BACKGROUND


The Olin Chemicals division of the Olin Corporation was awarded a six-month contract in 1985 that was to demonstrate a feasible method for the production of high purity HAN by electrolytic reduction of nitric acid. The first task in that contract was to review the existing HAN literature in such areas as production, physical properties, toxicology, stability, environmental impact and safety. Results of this review showed that HAN had been prepared 1) in an electrodialysis cell from hydroxylammonium chloride and nitric acid; 2) from reaction of hydroxylammonium sulfate (HAS) and barium nitrate; 3) from a three-step cation exchange process employing HAS and nitric acid; 4) from the reduction of nitric acid by molecular hydrogen in the presence of a palladium catalyst; and 5) electrolytically from the reduction of nitric oxide.<sup>1</sup>

During this feasibility study, Olin also successfully demonstrated production of HAN by the electrolytic reduction of nitric acid. The electrochemical cell was fabricated from acrylic plastic, had a mercury pool cathode, and several different anode materials. Catholyte and anolyte chambers were separated by a membrane. Temperature of the cathode chamber was controlled by a cooling chamber directly beneath the cathode. Feasibility was demonstrated and a small quantity of HAN at a concentration of about 15 weight percent was produced.



Based on the electrochemistry demonstrated during the feasibility study, Olin was awarded a contract to develop a continuous electrochemical reactor. This second, fourteen-month effort evaluated such operating parameters as anolyte and catholyte nitric acid concentrations, cathode recycle rates and catholyte temperature in order to determine their effects on cell operation

and thus optimize efficiency. A cell ten times larger than that used in the previous study was fabricated from chlorinated polyvinylchloride. As before, a horizontal mercury pool was used for the cathode and several anode materials were evaluated. The anode and cathode chambers were separated by a membrane and the cathode was cooled by a chamber beneath the cathode bedplate.


The reactions that take place in the reactor are shown below. Water in the anode chamber is oxidized to produce hydrogen ions and oxygen:



while the nitric acid in the cathode chamber is reduced to the weak base hydroxylamine. Since excess nitric acid is present, the hydroxylamine reacts to form HAN:



The overall reaction observed is thus:



Nitric acid concentrations in the two electrode chambers are critical to proper operation of the reactor. At low nitric acid concentrations hydroxylamine is reduced at the cathode to ammonia. At high nitric acid concentrations, the HAN produced is oxidized to various  $\text{NO}_x$  compounds. A balance between the nitric acid concentrations in the two electrode chambers is required in order to enhance water transport across the membrane and maximize

the efficiency of the cell. Based on these considerations, it was evident that the product leaving the cathode chamber would have to contain some excess nitric acid. The highest current efficiency was obtained in the larger scale cell when the product that exited the reactor contained approximately 25 % HAN and 2.8 % nitric acid.<sup>2</sup>

As stated earlier, the HAN concentration needed for propellant manufacture is approximately 80 % so that concentration of reactor product is required. Concentration of the 25 % HAN without removal of the excess nitric acid can result in loss of the HAN and is potentially dangerous. As water is removed from this mixture, the HAN and nitric acid react to produce  $\text{NO}_x$ . Since this reaction is exothermic, reaction rate increases as the reaction proceeds and a violent runaway reaction can readily occur. Based on these constraints, Olin set about to develop a method for removal of the excess acid. The first method attempted involved the production of free hydroxylamine from a readily available hydroxylammonium salt. Hydroxylamine vapor was to be bubbled into the reactor product. Attempts to implement this procedure in a laboratory scale apparatus were unsuccessful because of the low vapor pressure of hydroxylamine.

Sassé suggested to Olin that they try a weakly basic anion exchange resin in order to exchange hydroxide for nitrate, thus removing the excess acid.<sup>3</sup> Olin personnel evaluated several resins and were able to generate a product with acceptable levels of nitric acid concentration. A more detailed consideration of this procedure results in cause for concern. The HAN-nitric acid mixture dissociates into hydroxylamine, hydronium, and nitrate ions. The weak base amine resin protonates and the nitrate is then absorbed on the resin leaving the free amine. HAN is obtained in the column eluant only when the ion-exchange resin is

sufficiently depleted to permit nitric acid to bleed through the resin bed and neutralize the hydroxylamine either in the collected eluant or on the column. Although the end result of this procedure is a HAN solution free of excess nitric acid, neutralization of free hydroxylamine in the resin column could pose a safety problem. The neutralization reaction is exothermic and the amine is thermally unstable. The amine decomposes to produce  $\text{NO}_x$  compounds which, in turn, can react with the resin or with other materials present on the column. If enough heat and gas is liberated in the column an explosion could result.

In considering this procedure, it would seem that the use of a strongly acidic cation exchange resin would be a more efficient approach. The use of a cation column would entail a two-stage exchange. First, the resin in its acid form would be charged, using a readily available hydroxylammonium salt such as HAS. The electrochemical reactor product would then be passed through the column, exchanging hydroxylammonium for hydronium ions. This would avoid having the neutralization reaction previously mentioned occurring in the resin bed. Sulfuric acid is the by-product of this reaction sequence.

The production of HAN through use of HAS and nitric acid in a cation exchange system is described by Wheelwright.<sup>4-6</sup> The process described involves the production of HAN for use in plutonium recovery, an application in which excess nitric acid is acceptable. Although the procedure is quite similar to that needed for our specific application, it differs in that we are only using the process to purify electrolytically produced HAN rather than for manufacture of a material.

### III EXPERIMENTAL METHODS

A search was undertaken for a suitable strong cation ion-exchange resin. The foremost requirement was that the resin be chemically stable to mixtures of HAN and nitric acid. Since this was to be only a feasibility study, considerations such as resin capacity, cost, and optimal operating conditions were of secondary concern. The resin IONAC CFP-110\* was chosen. This material is a macroporous, sulfonated styrene-divinylbenzene copolymer and is reported by the manufacturer to be stable in moderately concentrated nitric acid. Particle size range of the resin beads is 0.35-1.2 mm.

A quantity of resin was placed in a glass chromatography column that was 4.5 cm OD and 111.8 cm high. The resin beads were fractionated by backflushing for two hours with tap water using the full column length. After settling, a bed volume of 780 mL was obtained. There was no indication of channeling in the bed. The column was prepared for use by washing with 1.5 L of 5 % nitric acid to remove any cations captured from the tap water and to insure that the resin was in its acidic form. The bed was then charged with 3 L of 5 % HAS in distilled water at a flow rate of 50 mL/min. The charged resin bed was rinsed with 2 L of distilled water at 50 mL/min and 6 L of distilled water at 200 mL/min. The column was operated at 50 mL/min with a solution of HAN and nitric acid that was 22.8 % HAN and 2.8 % acid, a mixture that closely resembles the electrochemical reactor effluent. Incremental 25 mL samples were taken and analyzed titrimetrically.<sup>7</sup>

\* Sybron Chemicals Inc., Subsidiary of Sybron Corp.,  
Birmingham, NJ.

#### IV RESULTS AND DISCUSSION

Neither heat evolution nor significant volume changes are observed during any operations with the resin column. When permitted to soak in 5 % nitric acid for periods of 24 hours or longer, a yellow-tan color develops in the liquid that is in contact with the beads. Although no chemical changes of the resin bed seem to be associated with this liquid color change, it would be prudent to prohibit prolonged contact of the resin with nitric acid.

The results of analysis of aliquots of the 25 mL samples taken are shown in Figure 1. The Figure presents HAN, acid, and the HAN:acid ratio, the values of the stock solution used appearing as the 0 volume values. One observes that the first 250 mL obtained are essentially pure water, this being the hold-up volume of the column. HAN then appears in the eluant, the concentration increasing to approximately 23 %. This is expected and shows that the nitric acid introduced in the stock solution is being converted to HAN on the column. After two hold-up volumes of stock solution have passed through column, some nitric acid begins to appear in the eluant indicating depletion of the resin. The resin is not fully depleted, however, until two more hold-up volumes have been eluted.

The chemical stability of the resin in contact with HAN and nitric acid was investigated by recharging the column using concentrations and flow rates described above. Since the column had been exposed to HAN and nitric acid but not to the metal ions that are present in tap water, the acid rinse that preceded charging with HAS was not included. Results obtained with the recharged column duplicate the data of Figure 1 quite precisely indicating that little or no deterioration of the resin occurred.




Figure 1. Performance of the CFP-110 Resin

The work described was carried out solely for the purpose of demonstrating the feasibility of an ion-exchange procedure for excess acid removal from electrolytically-produced HAN. A great deal of additional work is needed prior to its incorporation into a production facility. It would appear from the data obtained that ion-exchange columns will have to operate serially since two hold-up volumes of HAN-acid mixture are obtained before the column is totally depleted and requires recharging. Routing such partially purified eluant to a fully charged second column should increase the efficiency and reduce the overall cost of the acid removal process. In like manner, the pure water that is the first hold-up volume obtained with a freshly charged column should not be combined with the HAN solution obtained subsequently in order to avoid the expense of additional distillation. Other problems will probably surface and require attention before a practical production system for excess acid removal is completed.

Although not investigated experimentally, the use of an anion exchange resin for safe removal of excess nitric acid is also potentially feasible. The resin would be charged using aqueous ammonia. HAS would then be passed through the column producing an aqueous solution of hydroxylamine which would be used to titrate the excess nitric acid in the electrolytically produced HAN. Since the exothermic neutralization reaction does not take place on the column, the potential hazards cited earlier are avoided. Reaction by-product in this case is ammonium sulfate. The selection of cation exchange or anion exchange resins, or of a process that utilizes both cannot be recommended at this time since final selection would have to be strongly based on economic rather than technical feasibility.

## V CONCLUSIONS

An ion-exchange method using a strongly acidic, cation resin for this purpose has been demonstrated. Although the resin IONAC CFP-110 was used successfully, no resin selection is implied since similar resins from other suppliers were not evaluated.

## REFERENCES

1. Dotson, R.L., "High Purity Hydroxylammonium Nitrate Study", Final Report on Contract No. DAAAK15-85-C-0001, Olin Chemicals, New Haven, CT, August 1985
2. Barnatt, J.H., Dotson, R.L. and Leistra, J.A., "Development of a Production Process for Hydroxylammonium Nitrate by Electrolytic Reduction of Nitric Acid", Final Report on Contract No. DAAA15-87-C-0007, Olin Corporation, Northeast Process Technology, New Haven, CT, March 1988
3. Private communication with Ronald A. Sassé, US Army Ballistic Research Laboratory, September 1987
4. E.J. Wheelwright, "Cation Exchange Conversion of Hydroxylamine Sulfate to Hydroxylamine Nitrate," US Patent 3695834, 3 October 1972
5. E.J. Wheelwright, "Cation-Exchange Conversion of Hydroxylamine Sulfate to Hydroxylamine Nitrate", BNWL-CC-2180, May 1969, Pacific Northwest Laboratory, Battelle Memorial Institute, Richland, WA
6. L.E. Bruns and S.W. Swafford, "Hydroxylamine Nitrate from Hydroxylamine Nitrate", ARH-1309, July 1969, Atlantic Richfield Hanford Company, Richland, WA
7. M.M. Decker, E. Freedman, N. Klein, C.S. Leveritt, and J.Q. Wojciechowski, "Titrimetric Analysis of HAN-Based Liquid Propellants", BRL-TR-2907, March 1988, US Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD

INTENTIONALLY LEFT BLANK.

No of Copies	Organization
1	Office of the Secretary of Defense OUSD(A) Director, Live Fire Testing ATTN: James F. O'Bryon Washington, DC 20301-3110
Unclass., unlimited) 12	Administrator
Unclass., limited) 2	Defense Technical Info Center
Classified) 2	ATTN: DTIC-DDA Cameron Station Alexandria, VA 22304-6145
1	HQDA (SARD-TR) WASH DC 20310-0001
1	Commander US Army Materiel Command ATTN: AMCDRA-ST 5001 Eisenhower Avenue Alexandria, VA 22333-0001
1	Commander US Army Laboratory Command ATTN: AMSLC-DL Adelphi, MD 20783-1145
2	Commander Armament RD&E Center US Army AMCCOM ATTN: SMCAR-MSI Picatinny Arsenal, NJ 07806-5000
2	Commander Armament RD&E Center US Army AMCCOM ATTN: SMCAR-TDC Picatinny Arsenal, NJ 07806-5000
1	Director Benet Weapons Laboratory Armament RD&E Center US Army AMCCOM ATTN: SMCAR-CCB-TL Watervliet, NY 12189-4050
1	Commander US Army Armament, Munitions and Chemical Command ATTN: SMCAR-ESP-L Rock Island, IL 61299-5000
1	Commander US Army Aviation Systems Command ATTN: AMSAV-DACL 4300 Goodfellow Blvd. St. Louis, MO 63120-1798

No of Copies	Organization
1	Director US Army Aviation Research and Technology Activity Ames Research Center Moffett Field, CA 94035-1099
1	Commander US Army Missile Command ATTN: AMSMI-RD-CS-R (DOC) Redstone Arsenal, AL 35898-5010
1	Commander US Army Tank-Automotive Command ATTN: AMSTA-TSL (Technical Library) Warren, MI 48397-5000
1	Director US Army TRADOC Analysis Command ATTN: ATAA-SL White Sands Missile Range, NM 88002-5502
(Class. only) 1	Commandant US Army Infantry School ATTN: ATSH-CD (Security Mgr.) Fort Benning, GA 31905-5660
(Unclass. only) 1	Commandant US Army Infantry School ATTN: ATSH-CD-CSO-OR Fort Benning, GA 31905-5660
1	Air Force Armament Laboratory ATTN: AFATL/DLODL Eglin AFB, FL 32542-5000  <u>Aberdeen Proving Ground</u>
2	Dir, USAMSAA ATTN: AMXSY-D AMXSY-MP, H. Cohen
1	Cdr, USATECOM ATTN: AMSTE-TO-F
3	Cdr, CRDEC, AMCCOM ATTN: SMCCR-RSP-A SMCCR-MU SMCCR-MSI
1	Dir, VLAMO ATTN: AMSLC-VL-D

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
5	Commander US Army Armament, Research, Development and Engineering Center ATTN: SMCAR-TSS SMCAR-TDC (2 copies) SMCAR-MSI (2 copies) Picatinny Arsenal, NJ 07806-5000	2	Director CPIA The Johns Hopkins University ATTN: T. Christian Tech Library Johns Hopkins Road Laurel, MD 20707
1	Commander US Army Armament, Research, Development and Engineering Center ATTN: SMCAR-FSS-DA, Bldg 94 N. Kendl Picatinny Arsenal, NJ 07806-5000		
2	Commander US Army Harry Diamond Laboratories ATTN: SLCHD-TA-L 2800 Powder Mill Road Adelphi, MD 20783-1197		
1	Director US Army Laboratory Command Army Research Office ATTN: Tech Library P.O. Box 12211 Research Triangle Park, NC 27709-2211		
1	Commander Naval Ordnance Station ATTN: P. Skahan, Cxle 2810G Indian Head, MD 20640		
2	Director Jet Propulsion Lab ATTN: Tech Library 4800 Oak Grove Drive Pasadena, CA 91109		
4	Olin Corporation ATTN: Ken Woodard Dave Crawford Sanders Moore Ronald L. Dotson P.O. Box 248 Charleston, TN 37310		
2	Morton-Thiokol, Inc. ATTN: R. Biddle R. Brasfield P.O. Box 241 Elkton, MD 21921-0241		
1	Freedman Associates ATTN: Dr. Eli Freedman, Pres. 2411 Diana Road Baltimore, MD 21209		

## USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. BRL Report Number BRL-MR-3817 Date of Report MAR 90

2. Date Report Received \_\_\_\_\_

3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

CURRENT  
ADDRESS

\_\_\_\_\_  
Name

\_\_\_\_\_  
Organization

\_\_\_\_\_  
Address

\_\_\_\_\_  
City, State, Zip Code

7. If indicating a Change of Address or Address Correction, please provide the New or Correct Address in Block 6 above and the Old or Incorrect address below.

OLD  
ADDRESS

\_\_\_\_\_  
Name

\_\_\_\_\_  
Organization

\_\_\_\_\_  
Address

\_\_\_\_\_  
City, State, Zip Code

(Remove this sheet, fold as indicated, staple or tape closed, and mail.)

-----FOLD HERE-----

**DEPARTMENT OF THE ARMY**

Director  
U.S. Army Ballistic Research Laboratory  
ATTN: SLCBR-DD-T  
Aberdeen Proving Ground, MD 21005-5066  
**OFFICIAL BUSINESS**




**NO POSTAGE  
NECESSARY  
IF MAILED  
IN THE  
UNITED STATES**

**BUSINESS REPLY MAIL**  
FIRST CLASS PERMIT No 0001, APG, MD

POSTAGE WILL BE PAID BY ADDRESSEE

Director  
U.S. Army Ballistic Research Laboratory  
ATTN: SLCBR-DD-T  
Aberdeen Proving Ground, MD 21005-9989



-----FOLD HERE-----