MEMORANDUM REPORT BRL-MR-3875

# BRL

# AN ALTERNATIVE FORM OF THE
# MODIFIED POINT-MASS EQUATION OF MOTION

JAMES W. BRADLEY

NOVEMBER 1990

U.S. ARMY LABORATORY COMMAND

## BALLISTIC RESEARCH LABORATORY
## ABERDEEN PROVING GROUND, MARYLAND

90 11 21 084

## NOTICES

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22151.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

# REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

| 1. AGENCY USE ONLY (Leave blank) | 2. REPORT DATE | 3. REPORT TYPE AND DATES COVERED |
|---|---|---|
| | November 1990 | Final   Jun-Aug 90 |

| 4. TITLE AND SUBTITLE | 5. FUNDING NUMBERS |
|---|---|
| An Alternative Form of the Modified Point-Mass Equation of Motion | 1L162618AH80 |

**6. AUTHOR(S)**

James W. Bradley

| 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) | 8. PERFORMING ORGANIZATION REPORT NUMBER |
|---|---|
| | |

| 9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) | 10. SPONSORING / MONITORING AGENCY REPORT NUMBER |
|---|---|
| Ballistic Research Laboratory<br>ATTN:  SLCBR-DD-T<br>Aberdeen Proving Ground, MD   21005-5066 | BRL-MR-3875 |

**11. SUPPLEMENTARY NOTES**

| 12a. DISTRIBUTION / AVAILABILITY STATEMENT | 12b. DISTRIBUTION CODE |
|---|---|
| Approved for public release; distribution is unlimited. | |

**13. ABSTRACT (Maximum 200 words)**

The point-mass equation of motion is usually given in the form of an explicit expression for the acceleration $\dot{\vec{U}}$. The modified point-mass equation is obtained by adding yaw-of-repose terms to the right-hand side. These new terms are functions of $\dot{\vec{U}}$, so that $\dot{\vec{U}}$ now occurs on both sides of the equation. In this report, the modified point-mass equation is rewritten in the form of an explicit expression for the acceleration.

| 14. SUBJECT TERMS | | 15. NUMBER OF PAGES |
|---|---|---|
| Point Mass Equation          Equations of Motion<br>Modified Point Mass Equation<br>Yaw of Repose | | 13 |
| | | **16. PRICE CODE** |

| 17. SECURITY CLASSIFICATION OF REPORT | 18. SECURITY CLASSIFICATION OF THIS PAGE | 19. SECURITY CLASSIFICATION OF ABSTRACT | 20. LIMITATION OF ABSTRACT |
|---|---|---|---|
| UNCLASSIFIED | UNCLASSIFIED | UNCLASSIFIED | SAR |

INTENTIONALLY LEFT BLANK.

# Table of Contents

Accession For

NTIS  GRA&I

DTIC TAB

Unannounced

Justification

By

Distribution/

Availability Codes

Dist | Avail and/or
Special

A-1

INTENTIONALLY LEFT BLANK.

# I.  Introduction

Early in our attempt to create a program for fitting the modified point-mass (MPM) equation to radar data, we noted a peculiar feature of this equation in its present form: it is not given as an explicit expression for the highest order derivative (in this case, the acceleration vector $\dot{\vec{U}}$). Instead, it has the form

$$\dot{\vec{U}} = f(t, P, \vec{U}, \dot{\vec{U}}) \tag{1}$$

where $P$ is a parameter set.

This feature of $\dot{\vec{U}}$ co-existing on both sides of (1) is not an intolerable burden when the aim is merely to solve the equation numerically, using a specified set of parameter values.  Indeed, for a given set $P$, our Firing Tables Branch routinely solves (1) by a predictor-corrector technique ideally suited to handling that ubiquitous $\dot{\vec{U}}$ (although additional calculations are required at the start of the integration).

In our fitting problem, however, the trajectory is known and we want to determine the parameter values that yield the best fit (say, in some least-squares sense) to that observed trajectory. In order to use one of the packaged routines for accomplishing this curve fitting, we decided that it was–if not absolutely essential–then at least extremely desirable to work with an explicit expression for the acceleration.

In the hope that such a re-formulation may be of interest to a wider audience than the one enthralled by our ongoing trajectory fitting problem (the latter group being a very small one indeed), we decided to release the transformation as an independent result.

# II.  Modifying a Modified Equation

The point-mass equation of motion can be written in the form

$$\dot{\vec{U}} = -A\vec{V} + \vec{G} \tag{2}$$

where

$\vec{U}$ = projectile velocity with respect to the earth

$\vec{V} = \vec{U} - \vec{W}$ = projectile velocity with respect to the air

$\vec{W}$ = wind velocity with respect to the earth

$\vec{G}$ = the sum of the gravity and Coriolis accelerations

and where

$$A = \left(\frac{\rho S \ell}{2m} C_D\right)\left(\frac{V}{\ell}\right).$$

(All symbols are defined in the List of Symbols.)

The MPM equation - the modified version of Eq.(2) - is derived in Reference 1.[1] This MPM equation differs from the point-mass equation in that the modified version contains additional terms involving the yaw of repose, $\vec{\alpha}_e$. (The yaw of repose is the steady-state angle of attack resulting from the gravity-induced curvature of the trajectory.) In the expression given in Ref. 1 for $\vec{\alpha}_e$, we will ignore the Magnus moment coefficient; that is, we set

$$C_{M_{pa}} = 0. \tag{3}$$

Under this minor restriction, the expression for $\vec{\alpha}_e$ [Eq.(3.3) of Ref. 1] reduces to

$$\vec{\alpha}_e = B\,\dot{\vec{U}} \times \vec{V} \tag{4}$$

where

$$B = \left( \frac{k_a^2}{\frac{\rho S \ell}{2m} C_{M_\alpha}} \right) \left( \frac{\dot{\phi}\ell}{V} \right) \left( \frac{\ell}{V^3} \right)$$

and where $\dot{\phi}$ is the axial spin rate.

Then the MPM equation [Eq.(3.1) of Ref. 1] can be written in the form

$$\dot{\vec{U}} = -A\vec{V} + \vec{G} + \frac{h_L \vec{\beta}}{V} - \frac{h_M \vec{\beta} \times \vec{V}}{V^2} \tag{5}$$

where

$$\vec{\beta} = \vec{\alpha}_e/B = \dot{\vec{U}} \times \vec{V}$$

and where $h_L$ and $h_M$ are dimensionless coefficients related to the lift and Magnus forces, respectively:

$$h_L = k_a^2 \left( \frac{C_{L_\alpha}}{C_{M_\alpha}} \right) \left( \frac{\dot{\phi}\ell}{V} \right)$$

$$h_M = k_a^2 \left( \frac{C_{N_{pa}}}{C_{M_\alpha}} \right) \left( \frac{\dot{\phi}\ell}{V} \right)^2 .$$

For spin-stabilized artillery rounds, MPM trajectories based on Eq.(5) – compared with point-mass trajectories – are in much closer agreement with complete 6DOF rigid-body computer runs.

Eq.(5) differs from the point-mass equation (2) not only in the addition of the $h_L$ and $h_M$ terms, but also in the fact that the drag coefficient $C_D$ contained in coefficient $A$ is now allowed to vary linearly with $|\vec{\alpha}_e|^2$:

$$C_D = C_{Do} + C_{D2}|\vec{\alpha}_e|^2. \tag{6}$$

---

[1] "Equations of Motion for a Modified Point Mass Trajectory," Robert F. Lieske and Mary L. Reiter, US Army Ballistic Research Laboratory, Aberdeen Proving Ground, Maryland, Report R1314, March 1966, AD 485869.

Thus we see that in the MPM equation (5), $\dot{\vec{U}}$ appears not only on the left-hand side but *in every term except* $\vec{G}$ *on the right-hand side*. The purpose of this report is to present the following explicit expression for $\dot{\vec{U}}$:

$$\boxed{\dot{\vec{U}} = (C - A)\vec{V} + \vec{G}_A}$$  (7)

where

$$C = \frac{h_a(\vec{G} \bullet \vec{V})}{(1 + h_a)V^2}$$

$$\vec{G}_A = \frac{1}{1 + h_a}\left[\vec{G} + \frac{h_L(\vec{G} \times \vec{V})}{(1 - h_M)V}\right]$$

$$h_a = \frac{h_L^2}{1 - h_M} - h_M.$$

The derivation of this form of the MPM equation is given in the Appendix.

The attentive reader may be uneasy about that coefficient $A$ in Eq.(7). It does, after all, contain $C_D$, which in turn contains $|\vec{\alpha}_e|$, which would seem to involve $\dot{\vec{U}}$. However, a $\dot{\vec{U}}$-free expression for $\vec{\alpha}_e$ can now be obtained by substituting for $\dot{\vec{U}}$ from Eq.(7) in the definition of $\vec{\alpha}_c$, Eq.(4). We obtain

$$\boxed{\vec{\alpha}_e = B\vec{G}_A \times \vec{V}}$$  (8)

– an expression devoid of $\dot{\vec{U}}$.

## III.   Concluding Remarks

Note that the appearance of $\dot{\vec{U}}$ on the right-hand side of the original MPM equation (5) is, in a sense, illusory. If we use the re-defined yaw of repose from Eq.(8), then (5), like (7), represents an explicit expression for $\dot{\vec{U}}$.

The fact that the drag term vanishes in the cross-product $\dot{\vec{U}} \times V$ is what allows us to declare $C_D$ a function of $\vec{\alpha}_e$ and still obtain an explicit expression for $\dot{\vec{U}}$. If an unkind ballistician insisted that one or both of the aerodynamic parameters $h_L$ and $h_M$ must depend on the yaw of repose then no such explicit expression could be obtained.

# Appendix : Derivation of Eq.(7)

To obtain Eq.(7) of the text, we need a series of preliminary relationships. First, we note that Eq.(4) implies that $\vec{a}_e$ -- and hence $\vec{\beta}$ -- are perpendicular to $\vec{V}$. Therefore

$$\vec{\beta} \bullet \vec{V} = 0. \tag{A1}$$

Next we note that by Eq.(5),

$$\dot{\vec{U}} \bullet \vec{V} = \left( -A\vec{V} + \vec{G} + \frac{h_L \vec{\beta}}{V} - \frac{h_M \vec{\beta} \times \vec{V}}{V^2} \right) \bullet \vec{V}.$$

But the $h_L$ term above is zero by Eq.(A1) and the $h_M$ term is zero by the triple scalar product rule. Hence

$$\dot{\vec{U}} \bullet \vec{V} = -AV^2 + \vec{G} \bullet \vec{V} \equiv h_b \tag{A2}$$

where the symbol $h_b$ is introduced as a temporary convenience. Then

$$\begin{aligned} \vec{\beta} \times \vec{V} &= (\dot{\vec{U}} \times \vec{V}) \times \vec{V} \\ &= h_b \vec{V} - V^2 \dot{\vec{U}} \end{aligned} \tag{A3}$$

by the triple vector product rule. This same rule gives us

$$\begin{aligned} (\vec{\beta} \times \vec{V}) \times \vec{V} &= (\vec{\beta} \bullet \vec{V})\vec{V} - V^2 \vec{\beta} \\ &= -V^2 \vec{\beta}. \end{aligned} \tag{A4}$$

We can now obtain a convenient expression for $\vec{\beta}$:

$$\begin{aligned} \vec{\beta} &= \dot{\vec{U}} \times \vec{V} \\ &= \left( -A\vec{V} + \vec{G} + \frac{h_L \vec{\beta}}{V} - \frac{h_M \vec{\beta} \times \vec{V}}{V^2} \right) \times \vec{V} \\ &= \vec{G} \times \vec{V} + \frac{h_L (\vec{\beta} \times \vec{V})}{V} - \frac{h_M (\vec{\beta} \times \vec{V}) \times \vec{V}}{V^2} \end{aligned}$$

so that by Eqs.(A3) and (A4),

$$\vec{\beta} = \vec{G} \times \vec{V} + \frac{h_L (h_b \vec{V} - V^2 \dot{\vec{U}})}{V} + h_M \vec{\beta}.$$

Combining the $\vec{\beta}$ terms, we obtain

$$\vec{\beta} = \frac{\vec{G} \times \vec{V} + (h_L h_b / V)\vec{V} - (h_L V)\dot{\vec{U}}}{1 - h_M}. \tag{A5}$$

Substituting (A3) and (A5) in Eq.(5) of the text, we obtain

$$\dot{\vec{U}} = -A\vec{V} + \vec{G} + \frac{h_L}{(1 - h_M)V} \left[ \vec{G} \times \vec{V} + \left( \frac{h_L h_b}{V} \right) \vec{V} - (h_L V)\dot{\vec{U}} \right] - \frac{h_M}{V^2} \left[ h_b \vec{V} - V^2 \dot{\vec{U}} \right].$$

Combining similar terms, we have

$$\left(1 + \frac{h_L^2}{1 - h_M} - h_M\right)\dot{\vec{U}} = \left[-A + \frac{h_b}{V^2}\left(\frac{h_L^2}{1 - h_M} - h_M\right)\right]\vec{V} + \vec{G} + \frac{h_L\vec{G} \times \vec{V}}{(1 - h_M)V}$$

or

$$(1 + h_a)\dot{\vec{U}} = \left(-A + \frac{h_a h_b}{V^2}\right)\vec{V} + \vec{G} + \frac{h_L\vec{G} \times \vec{V}}{(1 - h_M)V}. \tag{A6}$$

But from Eq.(A2),

$$
\begin{aligned}
-A + \frac{h_a h_b}{V^2} &= -A + h_a\left(-A + \frac{\vec{G} \bullet \vec{V}}{V^2}\right) \\
&= -(1 + h_a)A + \frac{h_a\vec{G} \bullet \vec{V}}{V^2}. \tag{A7}
\end{aligned}
$$

Substituting (A7) in (A6), we have

$$(1 + h_a)\dot{\vec{U}} = -(1 + h_a)A\vec{V} + \left(\frac{h_a\vec{G} \bullet \vec{V}}{V^2}\right)\vec{V} + \vec{G} + \frac{h_L\vec{G} \times \vec{V}}{(1 - h_M)V}.$$

from which Eq.(7) of the text follows at once.

# List of Symbols

$A$ $\qquad$ $\left(\frac{\rho S \ell}{2m} C_D\right)\left(\frac{V}{\ell}\right)$

$B$ $\qquad$ $\left(\frac{k_a^2}{\frac{\rho S \ell}{2m} C_{M_\alpha}}\right)\left(\frac{\dot{\phi}\ell}{V}\right)\left(\frac{\ell}{V'^3}\right)$

$C$ $\qquad$ $\frac{h_a(\vec{G}\bullet\vec{V})}{(1+h_a)V'^2}$

$C_D$ $\qquad$ drag coefficient, $|drag\ force|/(\rho V^2 S/2)$

$C_{Do},\ C_{D2}$ $\qquad$ zero-yaw and yaw-drag coefficients:
$$C_D = C_{Do} + C_{D2}|\vec{\alpha}_e|^2$$

$C_{\ell_p}$ $\qquad$ roll damping moment coefficient:
$$|roll\ damping\ moment| = \pm(\rho V^2 S\ell/2)(\dot{\phi}\ell/V)C_{\ell_p}$$

$C_{L_\alpha}$ $\qquad$ lift force coefficient:
$$|lift\ force| = \pm(\rho V^2 S/2)|\vec{\alpha}_e|C_{L_\alpha}$$

$C_{M_{p\alpha}}$ $\qquad$ Magnus moment coefficient:
$$|Magnus\ moment| = \pm(\rho V^2 S\ell/2)(\dot{\phi}\ell/V)|\vec{\alpha}_e|C_{M_{p\alpha}}$$

$C_{M_\alpha}$ $\qquad$ static moment coefficient:
$$|static\ moment| = \pm(\rho V^2 S\ell/2)|\vec{\alpha}_e|C_{M_\alpha}$$

$C_{N_{p\alpha}}$ $\qquad$ Magnus force coefficient:
$$|Magnus\ force| = \pm(\rho V^2 S/2)(\dot{\phi}\ell/V)|\vec{\alpha}_e|C_{N_{p\alpha}}$$

$\vec{G}$ $\qquad$ the sum of gravity and Coriolis accelerations

$\vec{G}_A$ $\qquad$ $\frac{1}{1+h_a}\left[\vec{G} + \frac{h_L(\vec{G}\times\vec{V})}{(1-h_M)V}\right]$

$h_a$ $\qquad$ $\frac{h_l^2}{1-h_M} - h_M$

$h_b$ $\qquad$ $\dot{\vec{U}}\bullet\vec{V} = -AV^2 + \vec{G}\bullet\vec{V}$

$h_l$ $\qquad$ $k_a^2\left(\frac{C_{L\alpha}}{C_{M_\alpha}}\right)\left(\frac{\dot{\phi}\ell}{V}\right)$

$h_M$ $\qquad$ $k_a^2\left(\frac{C_{N_{p\alpha}}}{C_{M_{..}}}\right)\left(\frac{\dot{\phi}\ell}{V}\right)^2$

$I_x$ $\qquad$ axial moment of inertia

| | |
|---|---|
| $k_a^2$ | $I_x/m\ell^2$ |
| $\ell$ | reference length |
| $m$ | projectile mass |
| MPM | Modified Point Mass |
| $R$ | effective radius of the earth (6 356 766 m) |
| $S$ | reference area, $\pi\ell^2/4$ |
| $t$ | time |
| $\vec{U}$ | projectile velocity with respect to the earth |
| $V$ | $|\vec{V}|$ |
| $\vec{V}$ | $\vec{U} - \vec{W}$, projectile velocity with respect to the air |
| $\vec{W}$ | wind velocity with respect to the earth |
| $\vec{\alpha}_e$ | the yaw of repose, $B\,\dot{\vec{U}} \times \vec{V} = B\,\vec{G}_A \times \vec{V}$ |
| $\vec{\beta}$ | $\vec{\alpha}_e/B$ |
| $\rho$ | air density |
| $\dot{\phi}$ | axial spin rate |
| $\dot{(\ )}$ | $d(\ )/dt$ |

| No. of<br>Copies | Organization | No. of<br>Copies | Organization |
|---|---|---|---|
| 2 | Commander<br>US Army, ARDEC<br>ATTN: SMCAR-AET-A,<br>Stan Kahn<br>Roy Kline<br>Picatinny Arsenal, NJ 07806-5000 | | <u>Aberdeen Proving Ground</u> |
| | | 1 | Cdr, CRDEC, AMCCOM<br>ATTN: SMCCR-RSP-A, Miles C. Miller |
| 1 | US Air Force Armament Laboratory<br>ATTN: AFATL/FXA, G.L. Winchenbach<br>Eglin AFB, FL 32542-5000 | 3 | Dir, USAHEL<br>ATTN: W. Dousa<br>J. Wall<br>G. Horley |
| 1 | US Army Harry Diamond Laboratories<br>ATTN: John Miller<br>2800 Powder Mill Road<br>Adelphi, MD 20783-1197 | | |
| 1 | ANCOMP Corporation<br>ATTN: Dr. Anil K. Aggarwal<br>2720 Portobello Drive<br>Torrance, CA 90505 | | |
| 2 | Arrow Tech Associates, Inc.<br>ATTN: Robert Whyte<br>Wayne Hathaway<br>P.O. Box 4218<br>South Burlington, VT 05401-0042 | | |

No. of
Copies  Organization

1    Ecole Royale Militaire
     ATTN:  Prof. E. Celens
     Avenue de La Renaissance 30
     1040 Bruxelies
     BELGIUM

INTENTIONALLY LEFT BLANK.

# USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. BRL Report Number _____BRL-MR-3875_____ Date of Report ___NOVEMBER 1990___

2. Date Report Received _____

3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

_____

_____

4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

_____

_____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. _____

_____

_____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

_____

_____

_____

CURRENT
ADDRESS

| Name |
| --- |
| Organization |
| Address |
| City, State, Zip Code |

7. If indicating a Change of Address or Address Correction, please provide the New or Correct Address in Block 6 above and the Old or Incorrect address below.

OLD
ADDRESS

| Name |
| --- |
| Organization |
| Address |
| City, State, Zip Code |

(Remove this sheet, fold as indicated, staple or tape closed, and mail.)