



# Projected Effectiveness of Airbag Supplemental Restraint Systems in U. S. Army Helicopter Cockpits

By

Dennis F. Shanahan  
Samuel G. Shannon  
James E. Bruckart

OTM  
ELE  
NOV 30 1993  
S B D

Impact, Tolerance, and Protection Division

September 1993

Approved for public release; distribution unlimited.

93-29068  
404  
578

93 11 26 108

United States Army Aeromedical Research Laboratory  
Fort Rucker, Alabama 36362-5292

Notice

Qualified requesters

Qualified requesters may obtain copies from the Defense Technical Information Center (DTIC), Cameron Station, Alexandria, Virginia 22314. Orders will be expedited if placed through the librarian or other person designated to request documents from DTIC.

Change of address

Organizations receiving reports from the U.S. Army Aeromedical Research Laboratory on automatic mailing lists should confirm correct address when corresponding about laboratory reports.

Disposition

Destroy this document when it is no longer needed. Do not return it to the originator.

Disclaimer

The views, opinions, and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other official documentation. Citation of trade names in this report does not constitute an official Department of the Army endorsement or approval of the use of such commercial items.

Reviewed:

  
JOHN V. BARSON  
LTC, MC, SFS  
Director, Impact, Tolerance,  
and Protection Division

  
ROGER W. WILLEY, O.D., Ph.D.  
Chairman, Scientific  
Review Committee

Released for publication:

  
DAVID H. KARNEY  
Colonel, MC, SFS  
Commanding

Unclassified

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
1a. REPORT SECURITY CLASSIFICATION Unclassified		1b. RESTRICTIVE MARKINGS			
2a. SECURITY CLASSIFICATION AUTHORITY		3. DISTRIBUTION / AVAILABILITY OF REPORT Approved for public release, distribution unlimited			
2b. DECLASSIFICATION / DOWNGRADING SCHEDULE		4. PERFORMING ORGANIZATION REPORT NUMBER(S) USAARL Report No. 91-31			
6a. NAME OF PERFORMING ORGANIZATION U.S. Army Aeromedical Research Laboratory		6b. OFFICE SYMBOL (If applicable) SGRD-UAD-IE	7a. NAME OF MONITORING ORGANIZATION U.S. Army Medical Research and Development Command		
6c. ADDRESS (City, State, and ZIP Code) P.O. Box 620577 Fort Rucker, AL 36362-0577		7b. ADDRESS (City, State, and ZIP Code) Fort Detrick Frederick, MD 21702-5012			
8a. NAME OF FUNDING / SPONSORING ORGANIZATION		8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER		
8c. ADDRESS (City, State, and ZIP Code)		10. SOURCE OF FUNDING NUMBERS			
		PROGRAM ELEMENT NO. 0602787A	PROJECT NO. BM162787A87	TASK NO. AG	WORK UNIT ACCESSION NO. 138
11. TITLE (Include Security Classification) Projected effectiveness of airbag supplemental restraint systems in U.S. Army helicopter cockpits					
12. PERSONAL AUTHOR(S) Dennis F. Shanahan, Samuel G. Shannon, James E. Bruckart					
13a. TYPE OF REPORT Final		13b. TIME COVERED FROM _____ TO _____		14. DATE OF REPORT (Year, Month, Day) 1993 September	15. PAGE COUNT 17
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP	Airbag, restraint system, helicopter, cockpits, rotary-wing aircraft, airframes		
13	12				
01	03				
19. ABSTRACT (Continue on reverse if necessary and identify by block number)					
<p>Despite significant advances in accident prevention, crashworthiness, and individual protective equipment, head and torso injuries continue to cause death and disabling injuries in survivable Army helicopter accidents. Most of these injuries are caused by the occupant striking internal structures. The purpose of this study was to review Army helicopter accident records to determine the number of fatal and disabling injuries in pilots and copilots that could be prevented with the introduction of an airbag supplemental restraint system into U.S. Army helicopter cockpits.</p> <p>Computerized records from the U.S. Army Safety Center of all class A and B mishaps of the six most commonly used helicopters from October 1983 through September 1992 were reviewed. A computer model was developed to identify cockpit crewmembers who would have reduced severity of injury if the mishap helicopter were equipped with a proposed three-bag</p>					
20. DISTRIBUTION / AVAILABILITY OF ABSTRACT <input checked="" type="checkbox"/> UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION Unclassified		
22a. NAME OF RESPONSIBLE INDIVIDUAL Chief, Scientific Information Center			22b. TELEPHONE (Include Area Code) 205-255-6907	22c. OFFICE SYMBOL SGRD-UAX-SI	

19. Abstract (Continued):

airbag supplemental restraint system. The model considered severity and mechanism of injury as well as the type helicopter and dynamics of the crash. Over the 9-year study period, we identified 30 fatalities and 11 crewmembers with disabling injuries that could have been prevented with an airbag system. Including the hospital costs of lesser injured individuals, the estimated annual injury cost savings associated with an effective cockpit airbag system was approximately \$4.3 million.

Table of contents

List of tables . . . . . 2  
List of figures . . . . . 2  
Introduction . . . . . 3  
Materials and methods . . . . . 4  
Results . . . . . 7  
Discussion . . . . . 11  
References . . . . . 17

DTIC QUALITY INSPECTED 5

<b>Accession For</b>	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution/	
<b>Availability Codes</b>	
Dist	Avail and/or Special
A-1	

List of figures

Figure	Page
1. Proposed three-bag airbag system for U.S. Army attack helicopters . . . . .	5
2. Estimated annual injury cost based on 1992 helicopter utilization without and with airbags . . . . .	12
3. Cost of injury per 100,000 flight hours without and with airbags . . . . .	13

List of tables

Table	Page
1. U.S. Army rotary-wing mishaps, FY 84-92 . . . . .	8
2. Degree of injury for cockpit crewmembers involved in U.S. Army rotary-wing class A and B crashes, FY 84-92 . . . . .	9
3. Cost of injury to cockpit crewmembers involved in U.S. Army rotary-wing class A and B mishaps, FY 84-92 (\$million) . . . . .	9
4. Estimated injury reductions associated with an airbag system in U.S. Army rotary-wing aircraft, FY 84-92 . . . . .	10
5. Projected amortization period to recoup the costs of retrofitting airbags into existing helicopter airframes . . . . .	14

## Introduction

In 1908, while flying with Orville Wright, an unhelmeted Army pilot named Thomas Selfridge became the first powered aircraft fatality when he suffered lethal head injuries in the crash of a Wright Flyer (Combs, 1979). Despite all efforts to the contrary, aircraft have continued to crash with alarming regularity resulting in the deaths and injury of people throughout the world. Recognizing that aircraft will continue to crash in spite of advances in aviation safety and aircraft reliability, regulators, manufacturers, and operators have placed increasing emphasis on aircraft crashworthiness and individual protective equipment. These improvements have reduced significantly the potential for injury in crashes of aircraft designed to modern crashworthiness standards (Shanahan and Shanahan, 1989). The U.S. Army has been a world leader in instituting improvements in crash protection and was the first service to develop and implement crashworthiness design standards (Department of Defense, 1988 and Department of the Army, 1989). In spite of these advances, injury, and particularly head injury, continues to be a major problem in crashes of U.S. Army helicopters (Bezreh, 1961; McMeekin, 1985; and Shanahan and Shanahan, 1989).

Addressed in MIL-STD-1290A (1988) are five basic areas of aircraft design that should be considered in order to provide protection for the occupants in the event of a crash:

- a. Structural crashworthiness. Ensuring the aircraft structure maintains livable space for occupants throughout a crash.
- b. Occupant load limitations. Ensuring the loads on the occupants do not exceed the range of human tolerance through the use of crushable structure, load limiting landing gear and load limiting seats.
- c. High mass item retention. Ensuring high mass items such as rotor blades, transmissions, and engines do not penetrate occupied areas during a crash.
- d. Noninjurious interior. Providing optimum occupant restraint and adequate padding, frangibility, or placement of potentially injurious interior items to prevent injury from occupant flailing during a crash.
- e. Postcrash protection. Providing protection from fire in the postcrash environment through containment of flammable fluids and reduction of ignition sources. Also, providing adequate avenues of egress for all occupants.

To provide crash protection for occupants of Army helicopters, current helicopters include crash resistant fuel systems, lap and upper body restraints, and, in some helicopters, energy-absorbing landing gear and seat systems. Personal protective equipment worn by the aviator includes a flight helmet, survival vest, and fire resistant flight clothing. These enhancements significantly reduce the risk of injury and death for Army personnel involved in aircraft accidents. For example, the introduction of crash resistant fuel systems into most Army helicopters in the 1970s reduced the incidence of thermal deaths in survivable crashes to a negligible level (Shanahan and Shanahan, 1989). Also, Crowley (1991) reported less than one-sixth the number of fatal head injuries in Army helicopter crashes for occupants who wore protective helmets versus those who did not.

Although advances in crashworthiness of Army helicopters and in personal protective equipment have greatly reduced the potential for serious injury in a crash, a recent study of injury in Army helicopter crashes showed that five out of six injuries were due to occupants striking aircraft structure. This occurred even though occupants wore seat belts and upper torso harnesses and, in most cases, protective helmets (Shanahan and Shanahan, 1989). A feasibility study of incorporating airbags into attack helicopters further showed that a simple airbag system reduced most head injury severity indices by as much as 70 percent in simulations of severe crashes (Alem et al., 1992). The purpose of this study was to review Army helicopter crashes to determine if an airbag system incorporated into Army cockpits would reduce the number of fatal and serious nonfatal injuries for cockpit crewmembers in crashes.

### Materials and methods

Information on all U.S. Army class A and B helicopter mishaps over the 9-year period from 1 October 1983 through 30 September 1992 was obtained through the Army Safety Management Information System (ASMIS) of the U.S. Army Safety Center (USASC). Class A mishaps are defined by regulation as crashes for which the resulting total cost of property damage, occupational illness, or injury is \$1 million or greater, or in which an injury results in a fatality or permanent total disability (Department of the Army, 1993). Class B mishaps are defined as crashes for which the total cost is greater than \$500,000 but less than \$1 million. The starting date of this study was selected to correspond with the initiation of ASMIS data recording of severity and mechanism of occupant injuries.

The current ASMIS database does not contain specific information for predicting the potential of an airbag to prevent injury

of cockpit crewmembers in a given crash. Therefore, a computer algorithm was developed to use available injury data, estimated kinematic parameters, and other aircraft specific information to estimate the potential effectiveness of an airbag system. The modeled airbag system was a three-bag system with forward and lateral placement of the airbags (Figure 1, Department of the Army, 1991).

The analysis was limited to front seat occupants involved in crashes of UH-1, OH-58, CH-47, and UH-60 series helicopters and both occupants of AH-1 and AH-64 attack helicopters. A crash was defined as a Class A or B mishap where the vertical velocity at primary ground impact exceeded zero. This vertical velocity limitation eliminated mishaps occurring during ground operations, mishaps involving obstacle collisions where the helicopter was subsequently able to land safely, and mishaps where personnel or material fell from the helicopter during flight.




Figure 1. Proposed three-bag airbag system for U.S. Army attack helicopters.

## Computer modeling

The algorithm first determined the most severe injury for each individual. Then a Poisson regression model was used to determine the threshold of fatal injury for each major impact parameter including vertical velocity, longitudinal velocity, and helicopter attitude (pitch, roll, and yaw). The threshold value of each parameter was selected to be the point where fatal injury became significant at the 0.05 level after controlling for the other variables. Aircraft type was dichotomized into precrash-worthy (designed before the introduction of MIL-STD-1290 standards) and crashworthy (UH-60 and AH-64). Each helicopter was coded into one of four functional groups: attack, observation, utility, or cargo.

It was essential to exclude from consideration those crashes which occur at such extreme velocities or attitudes that resulting accelerations or structural deformations would create an environment where survival would be impossible even with an effective airbag system. To accomplish this, the threshold values of crash kinematic parameters for fatal injury determined by the Poisson regression model were used to exclude from consideration all crashes which exceeded potentially survivable limits. The threshold value for longitudinal velocity for fatal injury (the point at which longitudinal velocity became significant in the model) was 100 ft/s, the threshold value for pitch angle was -5 degrees (pitch down) and +10 degrees (pitch up) with a second, smaller threshold at -10 and +30 degrees. The threshold for roll was 35 degrees, and the threshold for vertical velocity was 60 ft/s for precrashworthy helicopters and 85 ft/s for crashworthy helicopters. While we expected a difference in threshold values among helicopter types (attack, observation, utility, cargo), the data did not support this hypothesis. This may be due to the overwhelming effect of crashworthy versus precrashworthy design and the relatively small number of crashes of certain helicopters (AH-64 and CH-47) available for study.

After excluding crashes with excessive kinematic parameters, the algorithm examined each remaining crash and determined which injuries would have been prevented by an airbag system. A preventable injury was defined as an injury to the head, neck, chest, abdomen, or upper arm that was coded as major, critical, or fatal, with a mechanism of injury identified as "struck by," "struck against," or "caught in/under/between." Minor injuries such as abrasions, small lacerations, and contusions were excluded from consideration. If the injury mechanism was "exposed to" or "experienced," the injury was considered preventable except when the injury was coded as caused by excessive g-forces or multiple injury-causing mechanisms. In the case of injuries caused by thermal or chemical burn, the injury was considered preventable if other injuries would not have precluded the

crewmember from exiting the aircraft immediately after impact. This decision was made because postcrash fires in potentially survivable crashes of helicopters equipped with crash resistant fuel systems usually occur after the crew has had adequate time to escape the aircraft. We also set as not preventable any injury that occurred before impact, since the airbag would deploy only on impact. Internal injuries defined as lacerations (liver, spleen, great vessels, etc.) were not considered preventable because they are caused frequently by excessive acceleration and not by striking an internal object.

Finally, the algorithm estimated the expected degree of injury of each individual if the helicopter had been equipped with a functioning airbag system. This was accomplished by reviewing every injury reported for each injured crewmember and eliminating the injuries considered preventable with an airbag system. The remaining injuries were used to determine the degree of injury expected for the same crash with an airbag-equipped helicopter. Thus, a fatality was considered preventable if all fatal injuries sustained by the individual were preventable with an airbag. Depending on the remaining injuries, this individual would be classified with some lesser degree of injury or no injury.

It should be emphasized that the airbag system was considered to be 100 percent effective in preventing contact injuries of the upper torso if the crash was determined to be potentially survivable. We recognize this is an overly optimistic assumption due to the potential for "bottoming out" of the bags in severe but survivable impacts or failure to remain inflated throughout an extended crash sequence. However, since inflation parameters for an airbag system are not yet determined and since such events will occur rarely, we believe the assumption is appropriate for the purposes of this study.

The cost of airbag preventable injuries was calculated using the injury costs specified in AR 385-40 (1993). This regulation specifies the cost for a flying officer fatality at \$1.1 million, permanent total disability (critical injury) at \$1.3 million, and permanent partial disability (major injury) at \$210,000. We used the degree of injury code in the ASMIS database to determine the severity and cost for preventable injuries.

## Results

From 1 October 1983 through 30 September 1992 there were 282 Army Class A and B mishaps of the six helicopter types considered in this study (Table 1). These crashes resulted in 128 fatalities, 26 aviators with disabling injuries, and 176 with injuries sufficient to require hospitalization or days away from work.

Table 1.

U.S. Army rotary-wing mishaps, FY 84-92.

Helicopter type	Classification of mishap		
	A	B	Total
AH-1	27	13	40
AH-64	18	2	20
CH-47	10	3	13
OH-58	70	7	77
UH-1	80	12	92
UH-60	32	8	40
Total	237	45	282

Table 2 summarizes these injuries for each helicopter type using the Department of Defense classification for degree of injury as reported in the ASMIS database (Department of the Army, 1983).

Table 3 summarizes the estimated monetary cost of the injuries sustained by cockpit crewmembers over the 9-year period of the study. For purposes of comparison, these costs have been delineated by helicopter type. There is not a complete correlation between Table 3 and Table 2 for the injury categories workdays away and workdays restricted as evidenced by zero costs being shown in cells of Table 3 where Table 2 shows a positive value. This is because, in order to estimate costs in these injury categories, it is necessary to know the total number of days the individual was away from work or on restricted activity. Since this information was not available in many reports, the decision was made to err on the conservative side by showing zero cost rather than speculating on the number of days the individual was away or restricted. This results in a small underestimation of total injury cost since the costs associated with days away or days of restricted activity are relatively insignificant compared to higher degrees of injury (Table 2).

Note that the magnitude of injury cost for any particular helicopter series is dependent upon the mishap rate and the number of hours flown over the period as well as the severity of the crashes. Therefore, high injury costs associated with a particular helicopter type may be more dependent upon the number of airframes in the fleet and the hours flown (total exposure) than upon any deficiency in design or operation.

Table 2.

Degree of injury for cockpit crewmembers involved in U.S. Army class A and B rotary-wing crashes, FY 84-92.

Degree of injury	Helicopter type						Total
	AH-1	AH-64	CH-47	OH-58	UH-1	UH-60	
Fatal	24	7	7	31	35	24	128
Permanent total disability	0	0	0	1	1	1	3
Permanent partial disability	1	2	0	10	5	5	23
Workdays away	13	16	2	41	49	23	144
Workdays restricted	2	4	4	11	10	1	32
No lost workdays	2	0	0	3	2	4	11
First aid only	10	4	3	21	26	8	72
No injury reported	28	7	10	33	55	14	147
<b>Total</b>	<b>80</b>	<b>40</b>	<b>26</b>	<b>151</b>	<b>183</b>	<b>80</b>	<b>560</b>

Table 3.

Cost of injury to cockpit crewmembers involved in U.S. Army rotary-wing class A and B mishaps, FY 84-92 (\$Million).

Degree of injury	Helicopter type						Total
	AH-1	AH-64	CH-47	OH-58	UH-1	UH-60	
Fatal	26.00	7.70	7.70	34.10	38.50	26.40	140.40
Permanent total	0	0	0	1.30	1.30	1.30	3.90
Permanent partial	0.25	0.50	0	2.50	1.25	1.25	5.75
Workdays away	0.02	0	0	0.02	0.36	0	0.40
Workdays restricted	0	0.06	0.01	0.02	0.04	0	0.13
<b>Total</b>	<b>26.27</b>	<b>8.26</b>	<b>7.71</b>	<b>37.94</b>	<b>41.45</b>	<b>28.95</b>	<b>150.58</b>

When the algorithm developed for this study was applied to each crash and each cockpit crewmember, the model predicted significant reductions in major injury assuming an airbag system was available at the time of each crash. Table 4 shows the number of crewmembers predicted to be "saved" from injury by an airbag for each injury category. Actual number of aircrew members "saved" as well as percent are shown. Note that zero indicates the model did not predict any reductions in injury with an airbag system for that particular cell. A period represents a missing value, indicating there was no injury reported in that cell prior to applying the model (Table 2). It is interesting that, in general, airbags are more effective in preventing nonfatal injuries. Also notice that the overall values in Table 4 can be used to estimate the potential effectiveness of retrofitting airbags to any particular helicopter type, assuming flight hours and severity of crashes remain relatively constant over time. This analysis indicates the highest rates of reduction for the AH-64 and AH-1, followed by the UH-1.

Table 4.

Estimated injury reductions associated with an airbag system in U.S. Army rotary-wing aircraft, FY 84-92

Degree of injury	Helicopter type						Total
	AH-1	AH-64	CH-47	OH-58	UH-1	UH-60	
Fatal	8 33.3%	1 14.3%	1 14.3%	9 29.0%	7 20.0%	4 16.7%	30 23.4%
Permanent total	.	.	.	1 100%	1 100%	1 100%	3 100%
Permanent partial	0	1 50.0%	.	2 20.0%	3 60.0%	2 40.0%	8 34.8%
Workdays away	10 76.9%	10 62.5%	2 100%	16 39.0%	25 51.0%	11 47.8%	74 51.4%
Workdays restricted	1 50.0%	3 75.0%	1 25.0%	2 18.2%	6 60.0%	1 100%	14 43.8%
Total	19 47.5%	15 51.7%	4 30.8%	30 31.9%	42 42.0%	19 35.2%	129 39.1%

In order to compensate for fluctuations in number of airframes and annual flight hours for each type of helicopter, injury costs with and without an airbag system were calculated based on 1992 utilization data (Figure 2). All Class A and B mishaps over the 9-year period of the study were used as the basis for the injury cost estimates. This analysis projects an annual injury cost savings ranging from approximately \$750,000 to over \$1 million for all helicopters except the CH-47. The highest annual payoff was for the OH-58 followed by the AH-1 and UH-60.

Figure 3 shows a similar analysis, but normalized to 100,000 hours of flight time. This figure shows that, assuming equivalent exposure (identical flight hours), airbags will yield the greatest reductions in injury costs for the AH-1, UH-60, and OH-58 series helicopters.

Table 5 provides an estimate of the number of years required to amortize the cost of retrofitting airbags to the helicopters included in this study. This analysis assumes fiscal year 1992 utilization levels and constant number of airframes. The cost of retrofitting an airbag system was estimated at \$10,000 per airframe based on the projected cost of the current prototype three-bag system. The amortization period varied from a low of 9.7 years for the AH-1 to over 33 years for the UH-1.

### Discussion

The purpose of this study was to provide a basis for estimating the potential savings in injury and injury costs associated with incorporation of an airbag system into Army helicopter cockpits. Ideally, this study would have involved a comprehensive review of the narrative and photographic evidence of each mishap by a team of injury and crash investigation experts. Since such a study was beyond the time and resource constraints available, we elected to use the data in the Army Safety Management Information System database and construct a computer model to predict airbag effectiveness. The major technical advantages of this method other than economy are that it ensures repeatability and eliminates subjective judgments in determining individual injury outcomes. The major disadvantage is the method requires rigorous selection criteria based on data available in the ASMIS, and does not allow for adjustments based on photographic or narrative information. Nevertheless, considering the relatively long period covered by the study and the large total number of crashes, we believe this analytical method provides a reasonable and conservative estimate on which to base programmatic decisions. It should be stressed also that the available data covered only mishaps occurring during a period of relative peace. No combat losses are included in the ASMIS data




Figure 2. Estimated annual injury cost based on 1992 helicopter utilization without and with airbags.




Figure 3. Cost of injury per 100,000 flight hours without and with airbags.

Table 5.

Projected amortization period to recoup the costs of retrofitting airbags into existing helicopter airframes.

	Helicopter type							Overall
	AH-1	AH-64	CH-47	OH-58	UH-1	UH-60		
1992 Flight hours	106,065	94,032	62,928	254,043	507,548	169,660		1,194,276
No. of airframes	780	658	422	1,876	2,884	1,150		7,770
Hours/airframe	135.98	142.91	149.12	135.42	175.99	147.53		153.70
Injury cost reduction/100K hours	\$759K	\$330K	\$219K	\$464K	\$170K	\$475K		\$344K
Injury cost reduction/airframe	\$1,032	\$471	\$327	\$628	\$300	\$701		\$528
Years to recoup	9.7	21.2	30.6	15.9	33.4	14.3		18.9

and few of the cases occurred in combat zones. The effectiveness of an airbag system would be more apparent during wartime when the number of crashes due to mishaps and enemy action would be greatly increased.

The effectiveness of an airbag system measured in terms of lives saved or injuries prevented for a particular airframe depends on the number of crashes occurring over a period of time, the severity of these crashes, and the types of injuries typically associated with the crashes. The types or mechanisms of injury occurring in crashes is highly related to airframe design parameters and configuration of seating positions. Consequently, for a given crash pulse, certain airframes may be more prone to involve injury amenable to prevention by an airbag than others. An example of a configuration particularly suited to an airbag is Army attack helicopters which have nonfrangible gunsights located within the strike envelope of the copilot/gunner. Airbags located on the gunsight have been shown to be very effective in reducing the probability of severe injury in these cockpits (Alem et al., 1992). In any case, the decision to retrofit an airbag system to any airframe should consider all potential factors to ensure achieving the expected results.

The model used in this study to predict airbag effectiveness was based on parameters derived from previous crashes of Army helicopters. Accident rates, crash severity and injury mechanisms were best estimated by considering the entire study period. However, since the UH-60 and AH-64 were being phased in over the period of study, projected annual flight hours would be severely underestimated if they were calculated as an average of the period. Conversely, over the same period, other airframes were being reduced in number which would result in an over-estimation of flight hours. For this reason, we chose to base our estimates of projected airbag effectiveness on the 1992 flight hours of each helicopter series (Figure 2 and Table 5).

Table 5 provides the best basis for comparisons between helicopter types because the estimates contained in it are based on a defined number of airframes and flight hours. Either parameter can be reset based on other projections of future utilization. These estimates show an airbag system would be most effective in preventing injury in the AH-1, followed by the UH-60 and the OH-58. The AH-64 would benefit somewhat less from airbags. To many, this result will appear surprising due to the apparent similarities in configuration and mission profile between the AH-1 and the AH-64. In spite of these apparent

similarities, these helicopters actually perform quite differently in a crash. The AH-64 fuselage tends to fracture between the copilot and pilot seats in severe crashes which exposes the copilot to an extreme probability of severe or fatal injury which would not be reduced by the presence of an airbag. Conversely, the pilot position provides excellent protection against structural collapse. This factor, along with the presence of energy-absorbing landing gear and seats, provides an already low injury rate for the AH-64 pilot position in crashes which would not be greatly enhanced with an airbag. These two factors result in a relatively small projected benefit for an airbag system in the Apache.

Airbag supplemental restraint systems have proven themselves highly effective in preventing injury in automobile crashes. Although the crash environment of the helicopter is somewhat more complex, this analysis of helicopter injury data strongly suggests that a three-bag airbag supplemental restraint system would be extremely effective in Army helicopters. We estimate a 39.1 percent reduction in all injuries which would result in an injury cost savings of over \$4.3 million per year if airbags were installed in the six most common helicopters in current use by the U.S. Army. Without considering the added benefit in reduced personal suffering and increased confidence and morale, the complete cost of such a retrofit program could be amortized in less than 19 years.

## References

- Alem, N. M., Shanahan, D. F., Barson, J. V., and Muzzy, W. H. 1992. The effectiveness of airbags in reducing the severity of head injury from gunsight strikes in attack helicopters. Neuilly-sur-Seine, France: AGARD Conference Proceedings 532.
- Bezreh, A. A. 1961. Army experience with crash injuries and protective equipment. Fort Rucker, AL: U.S. Army Board for Aviation Accident Research.
- Combs, H. 1979. Kill Devil Hill. Englewood, CO: Ternstyle Press Ltd., 304.
- Crowley, J. S. 1991. Should helicopter frequent flyers wear head protection? Journal of occupational medicine. 33: 766-769.
- Department of the Army. 1993. Accident reporting and records. Washington, DC: AR 385-40 (Draft). May.
- Department of the Army. 1989. Aircraft crash survival design guide. Fort Eustis, VA: Aviation Applied Technology Directorate, U.S. Army Aviation Research and Technology Activity. USAAVSCOM TR 89-D-22. December.
- Department of the Army. 1991. Dynamic cockpit restraint for the LH. Training and Doctrine Command, Systems Manager, Light Helicopter. Unpublished, January.
- Department of Defense. 1988. Light fixed- and rotary-wing aircraft crash resistance. Washington, DC: MIL-STD-1290A(AV). September.
- McMeekin, R. R. 1985. Aircraft accident investigation. In: Fundamentals of aerospace medicine. DeHart, R. L. (ed). Philadelphia: Lea and Febiger, 762-814.
- Shanahan, D. F., and Shanahan, M. O. 1989. Injury in U.S. Army helicopter crashes, October 1979-September 1985. Journal of trauma, 415-422.

Initial distribution

Commander, U.S. Army Natick Research,  
Development and Engineering Center  
ATTN: SATNC-MIL (Documents  
Librarian)  
Natick, MA 01760-5040

U.S. Army Communications-Electronics  
Command  
ATTN: AMSEL-RD-ESA-D  
Fort Monmouth, NJ 07703

Commander  
10th Medical Laboratory  
ATTN: Audiologist  
APO New York 09180

Naval Air Development Center  
Technical Information Division  
Technical Support Detachment  
Warminster, PA 18974

Commanding Officer, Naval Medical  
Research and Development Command  
National Naval Medical Center  
Bethesda, MD 20814-5044

Deputy Director, Defense Research  
and Engineering  
ATTN: Military Assistant  
for Medical and Life Sciences  
Washington, DC 20301-3080

Commander, U.S. Army Research  
Institute of Environmental Medicine  
Natick, MA 01760

Library  
Naval Submarine Medical Research Lab  
Box 900, Naval Sub Base  
Groton, CT 06349-5900

Director, U.S. Army Human  
Engineering Laboratory  
ATTN: Technical Library  
Aberdeen Proving Ground, MD 21005

Commander  
Man-Machine Integration System  
Code 602  
Naval Air Development Center  
Warminster, PA 18974

Commander  
Naval Air Development Center  
ATTN: Code 602-B (Mr. Brindle)  
Warminster, PA 18974

Commanding Officer  
Armstrong Laboratory  
Wright-Patterson  
Air Force Base, OH 45433-6573

Director  
Army Audiology and Speech Center  
Walter Reed Army Medical Center  
Washington, DC 20307-5001

Commander/Director  
U.S. Army Combat Surveillance  
and Target Acquisition Lab  
ATTN: DELCS-D  
Fort Monmouth, NJ 07703-5304

Commander, U.S. Army Institute  
of Dental Research  
ATTN: Jean A. Setterstrom, Ph. D.  
Walter Reed Army Medical Center  
Washington, DC 20307-5300

Commander, U.S. Army Test  
and Evaluation Command  
ATTN: AMSTE-AD-H  
Aberdeen Proving Ground, MD 21005

Naval Air Systems Command  
Technical Air Library 950D  
Room 278, Jefferson Plaza II  
Department of the Navy  
Washington, DC 20361

Director  
U.S. Army Ballistic  
Research Laboratory  
ATTN: DRXBR-OD-ST Tech Reports  
Aberdeen Proving Ground, MD 21005

Commander  
U.S. Army Medical Research  
Institute of Chemical Defense  
ATTN: SGRD-UV-AO  
Aberdeen Proving Ground,  
MD 21010-5425

Commander, U.S. Army Medical  
Research and Development Command  
ATTN: SGRD-RMS (Ms. Madigan)  
Fort Detrick, Frederick, MD 21702-5012

Director  
Walter Reed Army Institute of Research  
Washington, DC 20307-5100

HQ DA (DASG-PSP-O)  
5109 Leesburg Pike  
Falls Church, VA 22041-3258

Harry Diamond Laboratories  
ATTN: Technical Information Branch  
2800 Powder Mill Road  
Adelphi, MD 20783-1197

U.S. Army Materiel Systems  
Analysis Agency  
ATTN: AMXSU-PA (Reports Processing)  
Aberdeen Proving Ground  
MD 21005-5071

U.S. Army Ordnance Center  
and School Library  
Simpson Hall, Building 3071  
Aberdeen Proving Ground, MD 21005

U.S. Army Environmental  
Hygiene Agency  
Building E2100  
Aberdeen Proving Ground, MD 21010

Technical Library Chemical Research  
and Development Center  
Aberdeen Proving Ground, MD  
21010-5423

Commander  
U.S. Army Medical Research  
Institute of Infectious Disease  
SGRD-UIZ-C  
Fort Detrick, Frederick, MD 21702

Director, Biological  
Sciences Division  
Office of Naval Research  
600 North Quincy Street  
Arlington, VA 22217

Commander  
U.S. Army Materiel Command  
ATTN: AMCDE-XS  
5001 Eisenhower Avenue  
Alexandria, VA 22333

Commandant  
U.S. Army Aviation  
Logistics School ATTN: ATSQ-TDN  
Fort Eustis, VA 23604

Headquarters (ATMD)  
U.S. Army Training  
and Doctrine Command  
ATTN: ATBO-M  
Fort Monroe, VA 23651

IAF Liaison Officer for Safety  
USAF Safety Agency/SEFF  
9750 Avenue G, SE  
Kirtland Air Force Base  
NM 87117-5671

Naval Aerospace Medical  
Institute Library  
Building 1953, Code 03L  
Pensacola, FL 32508-5600

Command Surgeon  
HQ USCENTCOM (CCSG)  
U.S. Central Command  
MacDill Air Force Base, FL 33608

Air University Library  
(AUL/LSE)  
Maxwell Air Force Base, AL 36112

U.S. Air Force Institute  
of Technology (AFIT/LDEE)  
Building 640, Area B  
Wright-Patterson  
Air Force Base, OH 45433

Henry L. Taylor  
Director, Institute of Aviation  
University of Illinois-Willard Airport  
Savoy, IL 61874

Chief, National Guard Bureau  
ATTN: NGB-ARS (COL Urbauer)  
Room 410, Park Center 4  
4501 Ford Avenue  
Alexandria, VA 22302-1451

Commander  
U.S. Army Aviation Systems Command  
ATTN: SGRD-UAX-AL  
4300 Goodfellow Blvd., Building 105  
St. Louis, MO 63120

U.S. Army Aviation Systems Command  
Library and Information Center Branch  
ATTN: AMSAV-DIL  
4300 Goodfellow Boulevard  
St. Louis, MO 63120

Federal Aviation Administration  
Civil Aeromedical Institute  
Library AAM-400A  
P.O. Box 25082  
Oklahoma City, OK 73125

Commander  
U.S. Army Academy  
of Health Sciences  
ATTN: Library  
Fort Sam Houston, TX 78234

Commander  
U.S. Army Institute of Surgical Research  
ATTN: SGRD-USM (Jan Duke)  
Fort Sam Houston, TX 78234-6200

AAMRL/HEX  
Wright-Patterson  
Air Force Base, OH 45433

John A. Dellinger,  
Southwest Research Institute  
P. O. Box 28510  
San Antonio, TX 78284

Product Manager  
Aviation Life Support Equipment  
ATTN: AMCPM-ALSE  
4300 Goodfellow Boulevard  
St. Louis, MO 63120-1798

Commander and Director  
USAE Waterways Experiment Station  
ATTN: CEWES-IM-MI-R  
Alfrieda S. Clark, CD Department  
3909 Halls Ferry Road  
Vicksburg, MS 39180-6199

Commanding Officer  
Naval Biodynamics Laboratory  
P.O. Box 24907  
New Orleans, LA 70189-0407

Assistant Commandant  
U.S. Army Field Artillery School  
ATTN: Morris Swott Technical Library  
Fort Sill, OK 73503-0312

Mr. Peter Seib  
Human Engineering Crew Station  
Box 266  
Westland Helicopters Limited  
Yeovil, Somerset BA20 2YB UK

U.S. Army Dugway Proving Ground  
Technical Library, Building 5330  
Dugway, UT 84022

U.S. Army Yuma Proving Ground  
Technical Library  
Yuma, AZ 85364

AFFTC Technical Library  
6510 TW/TSTL  
Edwards Air Force Base,  
CA 93523-5000

Commander  
Code 3431  
Naval Weapons Center  
China Lake, CA 93555

Aeromechanics Laboratory  
U.S. Army Research and Technical Labs  
Ames Research Center, M/S 215-1  
Moffett Field, CA 94035

Sixth U.S. Army  
ATTN: SMA  
Presidio of San Francisco, CA 94129

Commander  
U.S. Army Aeromedical Center  
Fort Rucker, AL 36362

Strughold Aeromedical Library  
Document Service Section  
2511 Kennedy Circle  
Brooks Air Force Base, TX 78235-5122

Dr. Diane Damos  
Department of Human Factors  
ISSM, USC  
Los Angeles, CA 90089-0021

U.S. Army White Sands  
Missile Range  
ATTN: STEWS-IM-ST  
White Sands Missile Range, NM 88002

U.S. Army Aviation Engineering  
Flight Activity  
ATTN: SAVTE-M (Tech Lib) Stop 217  
Edwards Air Force Base, CA 93523-5000

Ms. Sandra G. Hart  
Ames Research Center  
MS 262-3  
Moffett Field, CA 94035

Commander, Letterman Army Institute  
of Research  
ATTN: Medical Research Library  
Presidio of San Francisco, CA 94129

Commander  
U.S. Army Medical Materiel  
Development Activity  
Fort Detrick, Frederick, MD 21702-5009

Commander  
U.S. Army Health Services Command  
ATTN: HSOP-SO  
Fort Sam Houston, TX 78234-6000

U. S. Army Research Institute  
Aviation R&D Activity  
ATTN: PERI-IR  
Fort Rucker, AL 36362

Commander  
U.S. Army Safety Center  
Fort Rucker, AL 36362

U.S. Army Aircraft Development  
Test Activity  
ATTN: STEBG-MP-P  
Cairns Army Air Field  
Fort Rucker, AL 36362

Commander, U.S. Army Medical Research  
and Development Command  
ATTN: SGRD-PLC (COL Schnakenberg)  
Fort Detrick, Frederick, MD 21702

TRADOC Aviation LO  
Unit 21551, Box A-209-A  
APO AE 09777

Netherlands Army Liaison Office  
Building 602  
Fort Rucker, AL 36362

British Army Liaison Office  
Building 602  
Fort Rucker, AL 36362

Italian Army Liaison Office  
Building 602  
Fort Rucker, AL 36362

Directorate of Training Development  
Building 502  
Fort Rucker, AL 36362

Chief  
USAHEL/USAAVNC Field Office  
P. O. Box 716  
Fort Rucker, AL 36362-5349

Commander, U.S. Army Aviation Center  
and Fort Rucker  
ATTN: ATZQ-CG  
Fort Rucker, AL 36362

Chief  
Test & Evaluation Coordinating Board  
Cairns Army Air Field  
Fort Rucker, AL 36362

MAJ Terry Newman  
Canadian Army Liaison Office  
Building 602  
Fort Rucker, AL 36362

German Army Liaison Office  
Building 602  
Fort Rucker, AL 36362

French Army Liaison Office  
USAAVNC (Building 602)  
Fort Rucker, AL 36362-5021

Australian Army Liaison Office  
Building 602  
Fort Rucker, AL 36362

Dr. Garrison Rapmund  
6 Burning Tree Court  
Bethesda, MD 20817

Commandant, Royal Air Force  
Institute of Aviation Medicine  
Farnborough, Hampshire GU14 6SZ UK

Commander  
U.S. Army Biomedical Research  
and Development Laboratory  
ATTN: SGRD-UBZ-I  
Fort Detrick, Frederick, MD 21702

Defense Technical Information  
Cameron Station, Building 5  
Alexandra, VA 22304-6145

Commander, U.S. Army Foreign Science  
and Technology Center  
AIFRTA (Davis)  
220 7th Street, NE  
Charlottesville, VA 22901-5396

Director,  
Applied Technology Laboratory  
USARTL-AVSCOM  
ATTN: Library, Building 401  
Fort Eustis, VA 23604

Commander, U.S. Air Force  
Development Test Center  
101 West D Avenue, Suite 117  
Eglin Air Force Base, FL 32542-5495

Aviation Medicine Clinic  
TMC #22, SAAF  
Fort Bragg, NC 28305

Dr. H. Dix Christensen  
Bio-Medical Science Building, Room 753  
Post Office Box 26901  
Oklahoma City, OK 73190

Commander, U.S. Army Missile  
Command  
Redstone Scientific Information Center  
ATTN: AMSMI-RD-CS-R  
/ILL Documents  
Redstone Arsenal, AL 35898

Director  
Army Personnel Research Establishment  
Farnborough, Hants GU14 6SZ UK

U.S. Army Research and Technology  
Laboratories (AVSCOM)  
Propulsion Laboratory MS 302-2  
NASA Lewis Research Center  
Cleveland, OH 44135

COL John F. Glenn  
U.S. Army Medical Research  
& Development Command  
SGRD-ZC  
Fort Detrick, Frederick, MD 21702-5012

Dr. Eugene S. Channing  
7985 Schooner Court  
Frederick, MD 21701-3273

USAMRDC Liaison at Academy  
of Health Sciences  
ATTN: HSHA-ZAC-F  
Fort Sam Houston, TX 78234

Dr. A. Kornfield, President  
Biosearch Company  
3016 Revere Road  
Drexel Hill, PA 29026

NVEOD  
AMSEL-RD-ASID  
(Attn: Trang Bui)  
Fort Belvoir, VA 22060

CA Av Med  
HQ DAAC  
Middle Wallop  
Stockbridge, Hants S020 8DY UK

Dr. Christine Schlichting  
Behavioral Sciences Department  
Box 900, NAVUBASE NLON  
Groton, CT 06349-5900

COL C. Fred Tyner  
U.S. Army Medical Research  
& Development Command  
SGRD-ZB  
Fort Detrick, Frederick, MD 21702-5012

Director  
Directorate of Combat Developments  
ATZQ-CD  
Building 515  
Fort Rucker, AL 36362