



**AFRL-HE-WP-TP-2006-0085**

**The Characterization of Spinal Compression  
in Various-Sized Human and Manikin  
Subjects During +Gz Impact**

**Erin Caldwell  
John Plaga**

**Biosciences and Protection Division  
Human Effectiveness Directorate**

**July 2006**

**Interim Report for September 2004 to September 2005**

**Approved for public release;  
distribution is unlimited.**

**Air Force Research Laboratory  
Human Effectiveness Directorate  
Biosciences and Protection Division  
Biomechanics Branch  
Wright-Patterson AFB OH 45503-7947**

## NOTICE AND SIGNATURE PAGE

Using Government drawings, specifications, or other data included in this document for any purpose other than Government procurement does not in any way obligate the U.S. Government. The fact that the Government formulated or supplied the drawings, specifications, or other data does not license the holder or any other person or corporation; or convey any rights or permission to manufacture, use, or sell any patented invention that may relate to them.

This report was cleared for public release by the Air Force Research Laboratory Wright Site Public Affairs Office and is available to the general public, including foreign nationals. Copies may be obtained from the Defense Technical Information Center (DTIC) (<http://www.dtic.mil>).

THIS TECHNICAL REPORT (AFRL-HE-WP-TP-2006-0085) HAS BEEN REVIEWED AND IS APPROVED FOR PUBLICATION IN ACCORDANCE WITH ASSIGNED DISTRIBUTION STATEMENT.

FOR THE DIRECTOR

//SIGNED//

---

Mark M. Hoffman  
Deputy Chief, Biosciences and Protection Division  
Air Force Research Laboratory

This report is published in the interest of scientific and technical information exchange, and its publication does not constitute the Government's approval or disapproval of its ideas or findings.

# REPORT DOCUMENTATION PAGE

*Form Approved*  
**OMB No. 0704-0188**

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Washington Headquarters Service, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188) Washington, DC 20503.

**PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.**

<b>1. REPORT DATE (DD-MM-YYYY)</b> July 2006			<b>2. REPORT TYPE</b> Interim		<b>3. DATES COVERED (From - To)</b> September 2004 – September 2005	
<b>4. TITLE AND SUBTITLE</b> The Characterization of Spinal Compression in Various-Sized Human and Manikin Subjects During +Gz Impact					<b>5a. CONTRACT NUMBER</b>	
					<b>5b. GRANT NUMBER</b>	
					<b>5c. PROGRAM ELEMENT NUMBER</b> 62202F	
<b>6. AUTHOR(S)</b> Erin Caldwell John Plaga					<b>5d. PROJECT NUMBER</b> 7184	
					<b>5e. TASK NUMBER</b> 02	
					<b>5f. WORK UNIT NUMBER</b> 16	
<b>7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)</b> Air Force Materiel Command Air Force Research Laboratory Human Effectiveness Directorate Warfighter Interface Division Battlespace Visualization Branch Wright Patterson AFB OH 45433-7947					<b>8. PERFORMING ORGANIZATION REPORT NUMBER</b>	
<b>9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)</b>					<b>10. SPONSOR/MONITOR'S ACRONYM(S)</b> AFRL/HEPA	
					<b>11. SPONSORING/MONITORING AGENCY REPORT NUMBER</b> AFRL-HE-WP-TP-2006-0085	
<b>12. DISTRIBUTION AVAILABILITY STATEMENT</b> Approved for public release; Distribution is unlimited.						
<b>13. SUPPLEMENTARY NOTES</b> Published in the SAFE Association 43 <sup>rd</sup> Annual Symposium Proceedings, Oct 2005, pgs 5-11. Cleared as AFRL/WS-05—2259, 28 Sep 05.						
<b>14. ABSTRACT</b> The objective of this research was to characterize spinal compression resulting from +Gz impacts and determine how well test manikins replicate responses of similar-sized humans. Various-sized humans were tested with identical conditions on a cervical deceleration tower. Seat and chest accelerations were used to calculate the damping ratio, natural frequency and spring constant of each subject. Data analysis was performed to determine what correlations may exist between spinal compression and sitting height, torso mass, gender or vibration parameters. Results show that spinal compression had no significant correlation to sitting height, torso mass, gender, damping ratio, undamped natural frequency or spring constant. The Large JPATS, Large ADAM, and LOIS manikins were found to align closely with human spinal compression.						
<b>15. SUBJECT TERMS</b> Ejection, catapult, slump, manikin, spinal compression, damping						
<b>16. SECURITY CLASSIFICATION OF:</b>			<b>17. LIMITATION OF ABSTRACT</b>	<b>18. NUMBER OF PAGES</b>	<b>19a. NAME OF RESPONSIBLE PERSON</b> John Plaga	
<b>a. REPORT</b> U	<b>b. ABSTRACT</b> U	<b>c. THIS PAGE</b> U			<b>19b. TELEPHONE NUMBER (Include area code)</b>	

# The Characterization of Spinal Compression in Various-Sized Human and Manikin Subjects during +Gz Impact

Erin Caldwell

John Plaga

AFRL/HEPA

Wright-Patterson AFB, OH

## ABSTRACT

*Background:* During +Gz impacts such as those encountered during ejection, the human torso and spine compress or slump due to the inertial forces acting on the body. Spinal compression can be characterized by a second-order differential equation involving coefficients such as damping ratio, natural frequency and spring constant. *Objective:* To characterize spinal compression resulting from +Gz impacts and determine how well test manikins replicate responses of similar size humans. *Methods:* Various-sized humans were tested with identical conditions on a vertical deceleration tower. Seat and chest accelerations were used to calculate the damping ratio, natural frequency and spring constant of each subject. Data analysis was performed to determine what correlations may exist between spinal compression and sitting height, torso mass, gender or vibration parameters. *Results:* Results show that spinal compression had no significant correlation to sitting height, torso mass, gender, damping ratio, undamped natural frequency or spring constant. Estimated 5<sup>th</sup>, 50<sup>th</sup>, and 95<sup>th</sup> percentiles of spinal compression were 1.1", 1.7", and 2.5" for the Vertical Impact Protection seat and 2.4", 2.8", and 3.6" for the ACES II seat. The Large JPATS, Large ADAM and LOIS manikins were found to align closely with human spinal compression.

## INTRODUCTION

During an in-flight emergency, the crew is often faced with very little time to decide to eject from an ailing aircraft. In many aircraft, once the crewmember pulls the ejection handle, the aircraft canopy needs to be jettisoned prior to the ejection. At high sink rates or adverse attitudes, the few tenths of a second required for the

canopy to clear the aircraft could be the difference between life and death. For this reason, many combat aircraft including the F-35 Joint Strike Fighter are utilizing a through-the-canopy approach. As the crewmember initiates the ejection by pulling the handle, a sequencing system sends a signal to a Transparency Removal System (TRS) or a canopy fragilization system that either cuts or weakens the transparency material and allows the seat with supplemental transparency penetrators to pass through the canopy. This results in reducing the ejection time by up to 300 milliseconds. Many combat aircraft also have a backup mode which allows the seat to penetrate the transparency even if the canopy fails to jettison or if the TRS or fragilization systems happen to fail. One of the disadvantages of going through the transparency is that a tall crewmember's head may hit the transparency prior to the seat transparency penetrators, thereby possibly causing head/neck injuries to the crewmember. Ejection seat tests are conducted with test manikins to determine if the escape systems are safe. However, ejection seats are tested with only a few size manikins, and human responses are often different than manikin responses. The objective of this study was to determine the degree of human slump, or vertical compression, during an ejection, and to determine a correlation between subject anthropometry (e.g. sitting height, upper body mass, etc.) and how much they slump. This study also examined the differences between human and manikin slump and the differences in slump for tests conducted using a generic research seat and an actual ejection seat.

## METHODS

Data analysis was performed from an approved IRB 1999 study<sup>1</sup> involving tests that were

## Report Documentation Page

*Form Approved  
OMB No. 0704-0188*

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

1. REPORT DATE <b>28 SEP 2005</b>	2. REPORT TYPE <b>N/A</b>	3. DATES COVERED <b>-</b>	
4. TITLE AND SUBTITLE <b>The Characterization of Spinal Compression in Various-Sized Human and Manikin Subjects During + Gz Impact</b>		5a. CONTRACT NUMBER	
		5b. GRANT NUMBER	
		5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)		5d. PROJECT NUMBER	
		5e. TASK NUMBER	
		5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) <b>AFRL/HEPA Wright-Patterson AFB, OH 45433</b>		8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)		10. SPONSOR/MONITOR'S ACRONYM(S)	
		11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT <b>Approved for public release, distribution unlimited</b>			
13. SUPPLEMENTARY NOTES <b>Published in the Proceedings of the Forty Third Annual SAFE Association Symposium, Held in the Salt Lake City, Utah, October 24-26, 2005. SAFE Association, Post Office Box 130, Creswell, OR 97426-0130. <a href="http://www.safeassociation.org">http://www.safeassociation.org</a></b>			
14. ABSTRACT			
15. SUBJECT TERMS <b>Safe</b>			
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT <b>SAR</b>
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>	
			18. NUMBER OF PAGES <b>7</b>
			19a. NAME OF RESPONSIBLE PERSON

conducted on the Air Force Research Laboratory's Vertical Deceleration Tower (VDT; Figure 1) using a generic Vertical Impact Protection (VIP) seat that was mounted to the carriage. The carriage and seat were released and a +Gz acceleration pulse was generated when the plunger, mounted on the back of the carriage, entered the hydraulic decelerator.




Figure 1. Vertical Deceleration Tower (VDT)

This study had 40 human subjects (23 male; 17 female) of various weight and height that were tested three times under identical conditions at seat accelerations of +10 Gz.<sup>2</sup> The positions of the headrest and seat back were directly aligned with the seat acceleration, and the seat pan was aligned perpendicular to the seat back. The subjects wore a standard HGU-55/P helmet and were confined to the seat by a MB-6 double shoulder harness and lap belt (Figure 2).<sup>2</sup> During vertical deceleration, various body displacements, such as the chest and head, were measured by the SELSPOT Motion Analysis System which consists of two on-board cameras that capture 500 samples per second.<sup>2</sup>



Figure 2. 1999 Study with Vertical Impact Protection (VIP) Seat

Vertical displacements of the chest for each test were then compiled in the Air Force Research Laboratory's Biodynamics Data Bank, as well as the subject's sitting height, total body mass and gender. Sitting height was measured as the vertical distance from the sitting surface to the top of the head. Variables such as torso mass and vibration parameters were determined from 23 subjects (12 male; 11 female) out of a total of 40 subjects from the 1999 study. The selection process of these 23 subjects was based on a representative sample for a total body mass distribution. Torso mass was then estimated by the Generator of Body Data (GEBOD) computer model, which incorporates 32 anthropometric measurements to determine the mass.<sup>3</sup> Next, the subject's vibration parameters were determined by modeling the compression of the human spine as a second-order differential equation shown in Equation 1.<sup>4,5,6</sup>

$$-\frac{d^2z}{dt^2} = \frac{d^2\delta}{dt^2} + 2\zeta\omega_n \frac{d\delta}{dt} + \omega_n^2 \delta \quad (1)$$

where:

$$\frac{d^2z}{dt^2} \quad \text{seat acceleration as a function of time}$$

$\delta$	deflection of the body mass with respect to the seat (in)
$\omega_n$	undamped natural frequency (rad/s)
$\zeta$	damping ratio
$\frac{d^2 \delta}{dt^2}$	chest acceleration as a function of time relative acceleration of the mass with respect to the seat

Equation 1 was used to determine different combinations of  $\omega_n$  and  $\zeta$  with the aid of an in-house computer integration program that

required input parameters of  $\frac{d^2 z}{dt^2}$  and  $\frac{d^2 \delta}{dt^2}$ .

Figure 3 illustrates the program's output of the actual mass acceleration response

$\left( \frac{d^2 z}{dt^2} + \frac{d^2 \delta}{dt^2} \right)$  and the computed mass

acceleration response for a given  $\omega_n$  and  $\zeta$ . Final values of  $\omega_n$  and  $\zeta$  were determined from the best fit computation using the method of least squares.




Figure 3. Model and Empirical Acceleration Response

The last vibration parameter calculated was the spring constant, as shown from Equation 2.<sup>7</sup>

$$k = \omega_n^2 \times m \quad (2)$$

where:

$k$  spring constant of the body (lb<sub>f</sub>/ft)  
 $m$  mass of torso (lb<sub>f</sub>\*s<sup>2</sup>/ft)

Statistical analysis was performed by Simple Linear Regression to determine whether maximum z displacement correlated with gender, height, mass, natural frequency, damping ratio, or spring constant. The Weibull Cumulative Distribution was used to fit the sample cumulative proportions to determine estimated 5<sup>th</sup>, 50<sup>th</sup>, and 95<sup>th</sup> percentile chest displacements for human subjects during a +Gz acceleration impact.

Since manikins were not tested during the 1999 study, a separate analysis was used to compare the impact responses between humans and manikins. Data were gathered from the Biodynamics Data Bank on an approved IRB 2004 study.<sup>1</sup> Thirteen human subjects (9 male and 4 female) and three manikins (Large JPATS, ADAM and LOIS) were identically tested in a VDT at +10 Gz. The test conditions consisted of an ACES II F-16 ejection seat, PCU-15P or PCU-16/P harness, HBU lab belt, and HGU-55/P flight helmet. The seat back and headrest were aligned with the vertical acceleration, and the seat pan was positioned perpendicular to the seat back, as shown in Figure 4. Chest displacement data were collected from a Weinberger Motion Analysis System that consists of 2 cameras capturing 11 positioned targets at 500 samples per second.



Figure 4. 2004 Study with ACES II Seat

From these data, the Weibull Cumulative Distribution was utilized to fit the sample

cumulative proportions to determine estimated 5<sup>th</sup>, 50<sup>th</sup>, and 95<sup>th</sup> percentile for chest displacement of the human population. This distribution then served as a comparison for the Large JPATS, ADAM and LOIS manikin chest displacement.

## RESULTS

The Simple Linear Regression method<sup>8</sup> was used to determine which individual variables may have influence on spinal compression (maximum z-chest displacement). Out of the 40 subjects exposed to +Gz impact in the VIP seat, variables from 23 subjects (12 male and 11 female) were collected or calculated. These variables included torso mass, damping ratio, damping frequency, spring constant and the average maximum chest displacement. Figure 5 was plotted with chest displacement versus the subjects' sitting height, and showed no correlation, with  $p=0.67$  and  $p=0.50$ , for male and female respectively. Likewise, Figure 6 shows no correlation for chest displacement versus the subjects' torso mass with  $p=0.32$  for male and  $p=0.61$  for female.




Figure 5. Maximum Chest Displacement versus a Subject's Sitting Height




Figure 6. Maximum Chest Displacement versus a Subject's Torso Mass

Figure 7 contains a bubble plot for the maximum z chest displacement in the VIP seat illustrated by bubbles with the sitting height in the y-axis and the torso mass in the x-axis. The size of the bubble indicates absolute chest displacement, with the largest circle having the greatest z displacement and the smallest circle having the least z displacement.




Figure 7. Plot of Sitting Height and Torso Mass versus Maximum Chest Displacement

There was no correlation found for the damping ratio ( $p=0.50$  male;  $p=0.41$  female; Figure 8), spring constant ( $p=0.81$  male;  $p=0.76$ ; Figure 9), or the damping frequency ( $p=0.47$  male;  $p=0.56$  female; Figure 10) with chest displacement as the independent variable.




Figure 8 Plot of Damping Ratio versus Maximum Chest Displacement




Figure 9 Plot of Spring Constant versus Maximum Chest Displacement




Figure 10. Maximum Chest Displacement versus a Subject's Damping Frequency

A two-tailed two-sample t-test<sup>8</sup> did not find a significant difference in the maximum z displacement of males vs. females for the VIP seat (means: male = -1.9 in, female = -1.6 in,  $p = 0.14$ ). Although chest displacement did not correlate with either mass or height, a second test was performed to evaluate genders of the same size. An Analysis of Covariance<sup>8</sup> was used to compare genders at the average sitting height and torso mass across all subjects. Similarly, no significant difference was found in gender (means: male = -1.8 in, female = -1.9 in,  $p = 0.94$ ).

The Weibull Cumulative Distribution was used to fit the sample cumulative proportions of maximum spinal compression for the VIP seat (Figure 11; Table 1) and ACES II seat (Figure 12; Table 1) with minimum and maximum values from the sample data. Two displacement values for the VIP seat (-3.5 and -3.2 in) and ACES II seat (-3.9 and -1.6 in) were discarded because these points did not fit the general populated trend.<sup>8</sup>




Figure 11. Weibull Fit of Sample Cumulative Proportions of Maximum Chest Displacement Using the VIP Seat. (N=40)




Figure 12. Weibull Fit of Sample Cumulative Proportions of Maximum Chest Displacement Using the ACESII Seat (N=13)

Table 1. The Chest Displacement Range for VIP and ACES II Seats

	<b>VIP Chest Displacement (in)</b>	<b>ACES II Chest Displacement (in)</b>
Min	-0.8	-1.6
5%	-1.1	-2.4
50%	-1.7	-2.8
95%	-2.5	-3.6
Max	-3.4	-3.9

Last, the ADAM, Large JPATS, and LOIS manikins respectively exhibited maximum chest displacements of -3.8in., -2.7in., and -1.5

inches, respectively, when exposed to +Gz acceleration impact tests in the ACES II seat (Table 2).

Table 2. The Average Maximum Chest Displacement of Manikins During +10Gz Impact

Manikin	Chest Displacement (in)
Large JPATS	-2.7
ADAM	-3.8
LOIS	-1.5

## DISCUSSION

Statistical results concluded that spinal compression did not correlate with the subject's height, torso mass, or gender. Likewise, no significant relationship was found between the vibration parameters ( $\omega_n$ ,  $k$  and  $\zeta$ ) and compression of the spine.

When comparing VIP and ACES II seat chest displacement, there was a significant difference that resulted in a p-value of 0.0001. One obvious reason for there to be a significant difference was the difference in the seat structures. While the VIP seat was a flat wooden seat mounted on an aluminum fixture with no seat cushion, the ACES II seat was an aluminum structure with a fiberglass seat pan and a seat cushion that was comprised of layered poly foam, temper foam and space fabric. As a result, greater vertical displacement was expected to occur during impact with the ACES II seat due to the flexion of the fiberglass seat pan and cushion.

Humans tested in the VIP seat showed a displacement of -2.5, -1.7 and -1.1 inches for the 5<sup>th</sup>, 50<sup>th</sup> and 95<sup>th</sup> cumulative percentages respectively. Human tested in the ACES II seat had greater chest displacement values of -3.6, -2.8 and -2.4 inches for the 5<sup>th</sup>, 50<sup>th</sup> and 95<sup>th</sup> cumulative percentages respectively. To ensure manikins were representative of humans, manikins were also tested in the ACES II seat during +10Gz impact tests. The manikin with the smallest displacement was the LOIS manikin which had a chest compression of -1.5 inches in the vertical direction. The JPATS manikin had

an average displacement of -2.7 inches. The ADAM manikin had the largest displacement (-3.8 inches) relative to the other manikins and humans.

## CONCLUSIONS

In conclusion, absolute vertical displacement of the spine was found to be dependent on the selected seat structure. However, vertical displacement due to spinal compression was found to be unpredictable among subjects. It is recommended that further analysis be conducted to characterize compression of the spine utilizing other parameters such as back strength or posture. In the end, LOIS, Large JPATS and Large ADAM manikins were found to display a human range of spinal compression.

## REFERENCES

1. Biodynamics Databank, United States Air Force.
2. Buhrman J. and Wilson D. Effects of Crewmember Gender and Size of Factors Leading to Increased Risk of Spinal Injury During Aircraft Ejection. Proceedings of the 40<sup>th</sup> Annual SAFE Symposium, 2002.
3. Gross M.E. The GEBODIII program user's guide and description. Air Force Research Laboratory Technical Report AL-TR-1991-0102, March 1991.
4. Brinkley J.W. and Shaffer J.T. Dynamic Simulation Techniques for the Design of Escape Systems: Current Application and Future Air Force Requirements. Aerospace Medical Research Laboratory, Wright Patterson Air Force Base, Ohio.
5. Buhrman J. and Mosher S. A Comparison of Male and Female Acceleration Responses During Laboratory +Gz Impact Tests. Proceedings of the 37<sup>th</sup> Annual SAFE Symposium, 1999.
6. Stech E. C. and Payne P.R., Dynamic Models of the Human Body, AMRL-TR-66-157, Aerospace Medical Research Laboratory, Wright Patterson Air Force Base, Ohio, AD 701 383, November 1969.

7. Humar J.L., *Dynamics of Structures*, Prentice Hall, Englewood Cliffs, New Jersey, 1990, pp 168-188.
8. Evans M., Hastings N., and Peacock B. (2000), *Statistical Distributions*, 3<sup>rd</sup> Edition, New York: John Wiley & Sons Inc., pp 192-195.

women in combat aircraft, and effects of downwash on pararescuemen.

## **DISCLAIMER**

The findings and conclusions in this report/presentation have not been formally disseminated by the Air Force and should not be construed to represent any agency determination or policy.

## **ACKNOWLEDGEMENTS**

The authors wish to express their thanks to Chuck Goodyear and Steve Mosher from General Dynamics for their support and expertise.

## **BIOGRAPHIES**

**Erin Caldwell** is a biomedical engineer who is supported by an appointment of the Research Participation Program at the Biomechanics Branch, Human Effectiveness Directorate, Air Force Research Laboratory, Wright Patterson AFB, administered by the Oak Ridge Institute for Science and Education through an interagency agreement between the U.S. Department of Energy and AFRL/HEP.

**John Plaga** is research aerospace engineer who has been with the Biomechanics Branch of the Human Effectiveness Directorate, Air Force Research Laboratory, for 16 years. He has been involved in escape system research since his graduation from The Ohio State University in 1989. His research projects have included flow stagnation concepts, windblast deflection studies, biomechanics of helmet-mounted displays, development of ejection seat instrumentation systems, studies of ejection seat dynamics, investigation of the Russian K-36 ejection seat, investigation of the implications of