

73rd MORSS CD Cover Page

UNCLASSIFIED DISCLOSURE FORM CD Presentation

712CD

For office use only 41205

21-23 June 2005, at US Military Academy, West Point, NY

Please complete this form 712CD as your cover page to your electronic briefing submission to the MORSS CD. Do not fax to the MORS office.

Author Request (To be completed by applicant) - The following author(s) request authority to disclose the following presentation in the MORSS Final Report, for inclusion on the MORSS CD and/or posting on the MORS web site.

Name of Principal Author and all other author(s): Jeffrey R. Cares

Principal Author's Organization and address:

Alidade Incorporated
31 Bridge Street
Newport, RI 02840

Phone: _401-367-0040_____

Fax: ___401-633-6420_____

Email: __jeff.cares@alidade.net_____

Original title on 712 A/B: A Technical Analysis of Speed for Expeditionary Naval Forces

Revised title:

Presented in (input and Bold one): (**WG18**, CG___, Special Session ____, Poster, Demo, or Tutorial):

This presentation is believed to be:
UNCLASSIFIED AND APPROVED FOR PUBLIC RELEASE

Report Documentation Page

Form Approved
OMB No. 0704-0188

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

1. REPORT DATE 22 JUN 2005	2. REPORT TYPE N/A	3. DATES COVERED -	
4. TITLE AND SUBTITLE A Technical Analysis of Speed for Expeditionary Naval Forces		5a. CONTRACT NUMBER	
		5b. GRANT NUMBER	
		5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)		5d. PROJECT NUMBER	
		5e. TASK NUMBER	
		5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Alidade Incorporated 31 Bridge Street Newport, RI 02840		8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)		10. SPONSOR/MONITOR'S ACRONYM(S)	
		11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited			
13. SUPPLEMENTARY NOTES See also ADM201946, Military Operations Research Society Symposium (73rd) Held in West Point, NY on 21-23 June 2005 . , The original document contains color images.			
14. ABSTRACT			
15. SUBJECT TERMS			
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	UU
			18. NUMBER OF PAGES 52
			19a. NAME OF RESPONSIBLE PERSON



ALIDADE
INCORPORATED

**A Technical Analysis of Speed for
Expeditionary Naval Forces**

Jeffrey R. Cares
73rd MORSS



Tasking

- Role of platform speed in determining requirements for Littoral Combat
 - Numbers of ships
 - Operating concepts
 - Speed advantage over CSG/ESG to provide requisite SA/BSP for AA
 - DMER5
 - Mission profile impacts



DMER5

- Deployment
- Management
- Exploitation
- Refueling
- Repositioning
- Recovery
- Replacement
- Redeployment

OF
Sensors
Off Board Systems

Platforms, Numbers, Speed

(Notional Relationships)

Speed for
Expeditionary
Naval Forces

	Air	Surface	Submarine	Information	Space
#s	10s- 100s	1s-10s	1s	1000s	1s
Speed	100s	10s	10s	100000s	1000s
Detection mode	EM/R F/EO	EM/RF /EO	Acoustic	Electronic	EM/RF/EO
Decision time	Sec	Min	Min-hours	sec-days	Hours-days

Analysis Parameters

- Vessel Speed:
 - 10-300 kt.
- Operating Area:
 - 160,000 nm. sq. (400 x 400 nm.); SSG/CNAN-based
 - Also have spreadsheets for other area sizes
- Sensor detection range
 - 5 nm (surface v. surface) → Our major focus is here
 - 50 nm (air v. surface)
 - 1 nm (surf v. sub)
- Sensor endurance
 - 8hr-180days



Analysis Bounds

- Speed
 - Deployment (ships)
 - Search
 - Ships only and Off-board Searchers
 - Perfect search and Random search
 - DMR5 (not 'E')
- Single/Multiple ship(s) and a sensor field
 - UVs and stationary sensors
 - vs. surf and sub targets



Relationships

- Littoral Area Search Problem
 - Sensors
 - detection range and speed determines area coverage rate
 - area coverage determines number sensors emplaced
 - Sensor endurance
 - Generates revisit/replenishment rates for sensors
 - Non-random and Random
 - Best and worst cases to bound the problem (time-distance problem)
 - Probability of Detection: $P_{\text{det}}=90\%$
 - Speed vs. searcher numbers requirement

Problem Timeline

- Surge from CONUS and Intra/Inter-Theater
 - Variation: Crisis response in Theater
- LCS sprint and search:
 - Lays sensor field (mobile or fixed) or conducts search
 - Issue: how much time to lay field and gain requisite Pd prior to CSG/ESG arrival?
- LCS maintains sensor field (DMR5)
 - No comments about “E”
 - Issue: Speed v. Numbers required to complete
- Objective:
 - Understand “Power Projection Lead Time” (PPLT)
 - Understand “Power Projection Lead Speed” (PPLS)



PPLT-PPLS

- Power Projection Lead Time: The time it takes the Assured Access Force to surge ahead of the Main Body (CSG/ESG), establish a sensor field and search the AOI to a predetermined level of situational awareness*
- Power Projection Lead Speed: Speed required for the Assured Access Force to surge ahead and still have enough time to search AOI to specified level of confidence so that CSG/ESG can project power upon arrival in AOI.

*in this analysis, the proxy for 'predetermined level of situational awareness is P_{det}

Problem

- 400 x 400 NM box
- 1 surface threat
 - The ‘easiest’ of a set of hard problems
 - Only one vice many things to sort through
- Assumed radar search by generic “searchers”
 - Best case search (perfect ‘lawn mower’ sweep)
 - Worst case search (completely random search)
- Standard for “clearance”: $P_{\text{det}} = 0.9$
 - Until better quantitative measures for situational awareness are invented, P_{det} will be our proxy*

*Information Theoretic measures for ‘SA’ exist, little work has been done to convert theory to practical measurements and techniques that have operational meaning.

Baseline Case w/Scenario

Speed for
Expeditionary
Naval Forces

- Current LCS concept of operations
 - 50kt top speed
 - Single digit off board sensors
 - 2-3 LCS per CSG
- Scenario
 - CSG/ESG w/LCS squadron surges to crisis
- Question (s)
 - What is PPLT and how does it vary with speed, theater, and numbers?
 - Follow on issues/sensitivity analysis from this answer

Specific Issues

- “Getting there” for IPB before CSG/ESG in a surge from CONUS Scenario
 - How much ahead of the battle group does LCS need to be in order to seed the sensor field for assured access
 - LCS and CSG/ESG leave at same time
 - LCS surges forward first
- How do these figures change vs. speed?
- How do these figures change vs. payload?
- How do these figures change vs. P_{det} ?



Theaters of Interest and Distances (NM)

Speed for Expeditionary Naval Forces

US East Coast to Med Sea	4300
US East Coast to PG	8400
US West Coast to Korea	5300
US West Coast to PG	11000
Hawaii to Korea	3200
Hawaii to PG	8900
Intratheater-1	1000
Intratheater-2	2000

Distances are representative, not policy approved distances typically used for force structure/deployment policy calculations

LCS Advance Arrival (Days)

Speed for
Expeditionary
Naval Forces

	50 kt	100 kt	Time delta (50 v. 100)
US East Coast to Med Sea	5.4	7.2	1.8
US East Coast to PG	10.5	14	3.5
US West Coast to Korea	6.6	8.8	2.2
US West Coast to PG	13.8	18.3	4.5
Hawaii to Korea	4	5.3	1.3
Hawaii to PG	11.1	14.8	3.7
Intratheater-1	1.3	1.7	.4
Intratheater-2	2.5	3.3	.8

- Assumes CSG/ESG SOA of 20 kt.
- Doubling speed gains are marginal except for long transits

LCS “Surge Ahead” Times

Speed for Expeditionary Naval Forces

Deployment Distances	NM	LCS Advance Time (@ 50kt)
US East Coast to Med	4300	5.4
US East Coast to PG	8400	10.5
US West Coast to Korea	5300	6.6
US West Coast to PG	11000	13.8
Hawaii to Korea	3200	4
Hawaii to PG	8900	11.1
Intra-Theater Crisis A	1000	1.3
Intra-Theater Crisis B	2000	2.5

- Time required for LCSs to find a single surface threat (the ‘simplest’ problem)
 - $P_{det}=0.9$
 - 50kt
 - 3 LCS
- Time of random search (‘hardest’)
 - 10.4 days
- Time of ‘perfect’ search (‘easiest’)
 - 4.4 days



Analysis

- For random (hardest) search,
 - All except longest transits do not allow enough time to sweep the area.
- Implies LCS must
 - Have ‘warning’: surge before CSG/ESG
 - Or be forward deployed in theater of interest
- For a ‘perfect’ search,
 - All except the shortest transits allow enough time
 - Argues for dispersed LCS operations in theater

Strategic issue: forward deployment and stationing
Operational issue: Day-to-day operating posture with
CSG/ESG

LCS only sensitivity analysis

Speed for Expeditionary Naval Forces

- 3 LCS are the only searchers
- What if required $P_{det} = 0.8$?
 - Requires 175 hr (7.3 days)
 - Save 3 days for worst case search time
 - Still requires long transits to avoid need for strategic warning or forward presence
- What if required $P_{det} = 0.95$?
 - Requires 315 hr (13 days)
 - 3 extra days required
 - Barely time for search even for longest transit distance
- Perfect search: no change in analysis
 - No uncertainty $P_{det} = 1.0$, no wasted search time.

Deployment Distances	NM	LCS Advance Time (@ 50kt)
US East Coast to Med	4300	5.4
US East Coast to PG	8400	10.5
US West Coast to Korea	5300	6.6
US West Coast to PG	11000	13.8
Hawaii to Korea	3200	4
Hawaii to PG	8900	11.1
Intra-Theater Crisis A	1000	1.3
Intra-Theater Crisis B	2000	2.5



LCS only sensitivity analysis

- What if LCS surged and searched at 80 kt?

LCS-Only Sensitivity Analysis

Speed for
Expeditionary
Naval Forces

Deployment Distances	NM	LCS Advance Time (@ 50kt)	LCS Advance Time (@ 80kt)
US East Coast to Med	4300	5.4	6.7
US East Coast to PG	8400	10.5	13.1
US West Coast to Korea	5300	6.6	8.3
US West Coast to PG	11000	13.8	17.2
Hawaii to Korea	3200	4	5
Hawaii to PG	8900	11.1	13.9
Intra-Theater Crisis A	1000	1.3	1.6
Intra-Theater Crisis B	2000	2.5	3.1

- LCS surge-search at 80 kt
- Time required to find a single surface threat
 - $P_{det}=0.9$
 - 80kt
 - 3 LCS
- Time for random search
 - 6.5 days
- Time for ‘perfect’ search
 - 2.8 days

Analysis

- For random (hardest) search
 - Most deployment transits generate enough lead time to sweep the area.
- 30 kts extra speed for LCS
 - Generates shorter ‘warning’ requirement for surge or
 - Gives flexibility of choice in forward deployed theaters
- For a ‘perfect’ search,
 - All except the shortest transit allows enough time
 - Shorter ‘tether’ LCS operations in theater possible

Strategic issue: forward deployment and stationing
Operational issue: Day-to-day operating posture with
CSG/ESG

LCS Sensitivity Analysis

Speed for
Expeditionary
Naval Forces

- Each LCS carries 10 off board searcher vehicles that can search at 50 kt
- Surge speed/times for LCS remain the same (50kt transit)
- LCSs deploy search vehicles upon arrival in AOI
- 30 Searchers, $P_{det}=0.9$, 400x400nm box:
 - Perfect search: 10.6 hr
 - Random search: 24 hr
- ***Analysis: Off board vehicles can relieve the high speed transit requirement dramatically***
 - ***Decreased search time by factor of 4-10!***
- Next issue: Maintaining this level of ‘awareness’

LCS to maintain awareness

- Search Problem:
 - 400 x 400 nm area,
 - $P_{\text{det}} = 0.9$
 - UV endurance: 24 hours
 - Remember, UVs search at max speed (50kt)
- 30 UVs in random search can achieve this requirement
- Queuing analysis determines minimum number LCS to maintain 30 vehicle search ‘grid’/field/force
 - Assumes UVs uniformly distributed
 - 30 minutes to service each (arbitrary assumption)
 - LCSs go to UVs vice meet half way
- **Result: 3 LCS sufficient to execute this task (but they operate at 50kt the whole time)**

Maintain Awareness

Sensitivity analysis

- What if UV endurance was only 12 hours?
 - 5 LCSs required
 - Halving sensor endurance *increases* LCS requirement by a factor of 1.7
- If UV endurance was 48 hours?
 - 1 LCS Required
 - Doubling sensor endurance *reduces* LCS requirement by factor of 3



Maintain Awareness

Sensitivity analysis

- What if nodes were immobile/drifted sensors and more numerous?
 - 80 nodes,
 - 24 hour endurance,
 - 50kt LCS
- 5 LCS required
 - Double endurance, drop to 3 LCS
 - Double nodes, increase to 8 LCS



ALIDADE INCORPORATED

Complex Systems Research

Process Innovation & Analysis

Strategic Investment Advice

Future Concept Generation

Corporate/Government War Games & Events

QUESTIONS?



ALIDADE
INCORPORATED


Speed for
Expeditionary
Naval Forces

Chart Appendix

73rd MORSS


LCS vs. CSG/ESG

Speed for Expeditionary Naval Forces






LCS Required for Perfect Search 400x400 nm box






LCS Required for Pd=0.9 vs. Surface Ship(s)






LCS Required for Pd=0.9 vs. subsurface target






LCS Required for Pd=0.8






Single Platform Random Search 400x400NM






3-Platform Random Search 400 x 400 NM box





10-Platform Random Search 400 x 400 NM box





ALIDADE
INCORPORATED

Speed for
Expeditionary
Naval Forces


30 platform random search

73rd MORSS



Time to Seed a Fixed Size Sensor Field


Speed for
Expeditionary
Naval Forces



Minimum # LCS to maintain an 80 Node grid

Speed for Expeditionary Naval Forces

Min LCS (400x400nm area) for 80 node grid variable endurance





ALIDADE
INCORPORATED

**Speed for
Expeditionary
Naval Forces**

BACK UPS

73rd MORSS

LCSs to service UV/Sensor Fields

Speed for
Expeditionary
Naval Forces

- 3 LCS: 50 and 225 node fields, 24 hr endurance, 400 x 400 nm box
 - 60 kt. (50)
 - Cannot accomplish for 225 nodes unless endurance increases:
 - 48 hr: 130kt.
 - 72 hr: 50 kt.
- 50kt LCS:
 - 4 LCS (50)
 - 10 LCS (225)
- 80kt LCS:
 - 3 LCS (50)
 - 8 LCS (225)

Architecting a Problem

Speed for
Expeditionary
Naval Forces

- Littoral Search Area Problem
- Area:
 - 1240NM (2000KM) x 1240NM (2000)KM (~1.5M nm. sq.)
 - NWDC AA briefing
 - 1.5M nm. sq. generates ridiculous numbers
 - More useful areas for analysis:
 - 100NM x 100NM (10,000 nm. sq.)
 - 200NM x 200NM (40,000 nm. sq.)
 - 400NM x 400NM (160,000 nm. sq.)
- Missions/tasks: DMR5 a sensor or unmanned vehicle field
 - Sensor area coverage and detection range drives number of sensors emplaced
 - Sensor endurance and failure rate determine R5 (service) demand
- Highlighted issues:
 - Revisit/replenishment rates for sensors: # LCS to maintain field
 - Single ship speed requirement
 - Speed vs. ship numbers requirement
- Tradespace information:
 - Speed, numbers, geography



Time to Seed a Fixed Size Sensor Field

Speed for
Expeditionary
Naval Forces

	Speed	20	30	40	50	60	70	80	90	100
Field Size	Distance									
100x100	1009.3	2.1	1.4	1.1	0.8	0.7	0.6	0.5	0.5	0.4
200x200	2018.5	4.2	2.8	2.1	1.7	1.4	1.2	1.1	0.9	0.8
400x400	4037.0	8.4	5.6	4.2	3.4	2.8	2.4	2.1	1.9	1.7
1240x1240	12514.7	26.1	17.4	13.0	10.4	8.7	7.4	6.5	5.8	5.2



Speed for
Expeditionary
Naval Forces

area L	800	800
area W	100	100
nmsq	80000	80000
grid spacing	20	20
nodes (#)	240	240
total track to lay grid	4030	4030
deploy speed	10	20
deploy time-hr	403	201.5
deploy time-days	16.8	8.4
speed delta		10
time delta-hr		-201.5
percent time delta		50%



LCS to Service Sensor/UV Fields

- Geographic area (A)
 - 100x100NM
 - 200x200NM
 - 1240x1240NM (PESG OV-1=2000x2000KM)
- Number of Nodes (N)
 - 80 nodes (variable density)
 - Constant density (based on 80 nodes in 200x200NM area)
- LCS speed (s)
 - 30-300kt
 - Covers a 3x-10x increase in speed capability
- Node endurance (e)
 - 8, 16, 24, 48, 72 hours
 - Determines the ‘demand for service signal’



Analysis

- The fundamental comparison here is to find the time that an LCS or squadron of LCS can arrive in theater before the CSG/ESG so that the field can be placed and ‘situational awareness’ established for follow-on forces.
 - Note: the time that it takes to build an adequate ‘picture’ of the battle space is beyond the scope of this project as it requires a separate information theoretic analysis.
- For a 100x100 nm field of 80 sensors
 - 2 days at 20 kt, decreasing linearly in direct proportion to speed
 - A 5 kt speed advantage gets the LCS in theater in greater than 2 days in all cases.
- 200X200:
 - 4 days, same
- 400X400
 - 8 days, same
- 1024x1024
 - 26 days

Operational Level Example

- Speed at the Operational Level of War:
- Repositioning of forces for:
 - TBMD—Operational utility of TBM umbrellas
 - Forcible Entry—Operational utility of ‘feints’
 - Blockade of Port—Operational Utility of limited cognitive span/information capability




Thoughts on Analysis problem

- Numbers of off board vehicles vs. speed
- 100nm coastline
 - Missile tubes engagement envelope vs. speed tending requirements, etc.
- Oblique questions
 - Why do I need a 30 kt mmcruiser to protect the DAL?
 - Need a 2 kt arsenal boat protected by 60kt lcs using MUSICAL
- Operational applications
 - DMER5 across peace, combat, transit/logistics/sustainment
- Looking for a reference document and more studies


Results-Constant Node Density

Speed for Expeditionary Naval Forces

#LCS to maintain constant density sensor field
1240x1240NM




LCS to maintain 100x100 NM field, constant sensor density






#LCS for 1240x1240nm grid of 80 nodes



Speed for Expeditionary Naval Forces

LCS for 80 node grid (100x100nm area) variable endurance





Speed for
Expeditionary
Naval Forces

Minimum # LCS to maintain 80 node 200x200NM grid

