



# VEA

VEHICLE ELECTRONICS AND ARCHITECTURE

**TARDEC'S VICTORY SIL is a Key Tool for Advancing Standardized Ground Vehicle Electronic Architecture**

## Report Documentation Page

*Form Approved*  
*OMB No. 0704-0188*

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

1. REPORT DATE <b>02 AUG 2012</b>		2. REPORT TYPE <b>Briefing</b>		3. DATES COVERED <b>01-07-2012 to 01-08-2012</b>	
4. TITLE AND SUBTITLE <b>TARDEC's VICTORY SIL is a Key Tool for Advancing Standardized Gound Vehicle Electronic Architecture</b>				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) <b>Nikia Williams</b>				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) <b>U.S. Army TARDEC, 6501 East Eleven Mile Rd, Warren, Mi, 48397-5000</b>				8. PERFORMING ORGANIZATION REPORT NUMBER <b>#23227</b>	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) <b>U.S. Army TARDEC, 6501 East Eleven Mile Rd, Warren, Mi, 48397-5000</b>				10. SPONSOR/MONITOR'S ACRONYM(S) <b>TARDEC</b>	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S) <b>#23227</b>	
12. DISTRIBUTION/AVAILABILITY STATEMENT <b>Approved for public release; distribution unlimited</b>					
13. SUPPLEMENTARY NOTES <b>Submitted to 2012 NDIA Ground Vehicle Systems Engineering and Technology Symposium August 14-16 Troy, Michigan</b>					
14. ABSTRACT <b>VICTORY SIL is a Tool for Advancing Standardized Ground Vehicle Electronic Architecture -Build In-house Environment and Knowledge Base to Support Future R&amp;D Capability Regarding Vehicle Electronics and Architecture -Capability to Test and Verify Vendor Components and Subsystems -Advance SWaP-C with Porting and Testing VICTORY Implementations to Small, Open and Powerful Process Modules</b>					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT <b>Public Release</b>	18. NUMBER OF PAGES <b>14</b>	19a. NAME OF RESPONSIBLE PERSON
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>			




# Agenda

- VICTORY SIL Background
- Timing Plan
- Development Process
- Testing Scheme and Process
- Test Results
- Interoperability
- Small SWaP
- Summary

## VICTORY SIL is a Tool for Advancing Standardized Ground Vehicle Electronic Architecture

- Build In-house Environment and Knowledge Base to Support Future R&D Capability Regarding Vehicle Electronics and Architecture
- Capability to Test and Verify Vendor Components and Subsystems
- Advance SWaP-C with Porting and Testing VICTORY Implementations to Small, Open and Powerful Process Modules


# VICTORY Architecture Concept



- Provide an independent implementation of the VICTORY 1.0 Proposed Standards
- Provide Validation and Verification of the VICTORY 1.0 Proposed Standards
- Advance VICTORY Standards from “Proposed” to “Draft”
- Identify and clarify issues with the VICTORY 1.0 Proposed Standards
- The SIL will continue to evolve and change over time as new VICTORY Standards are released (1.1, 1.2, 1.3, 1.4, 2.0, ...)
- Utilize a representative vehicle cabin to demonstrate the VICTORY 1.0 Standards in a system level vehicle environment

**Provide Independent Verification of vendors components to VICTORY Standard via Test Service Agreements**

# Detailed Milestone Schedule



## Phased Development Based on VICTORY 1.0 Standard Specification


- Phase 1: Core Services (Time Synchronization, Position, Direction of Travel, Orientation), Threat Detection and Reporting, Remote Weapons Station
- Phase 2: VICTORY Data Bus (VDB) Data Transport Interfaces, Management Interfaces, Component Interfaces, C4ISR System Interfaces, VICTORY Configuration Language, and Automotive Services
- Phase 3: Security and Information Awareness Build Up and Validation

# VICTORY 1.0 SIL: End State Architecture

# VEA

VEHICLE ELECTRONICS AND ARCHITECTURE

UNCLASSIFIED



- **Shared Services**
  - ✓ Time
  - ✓ Orientation
  - ✓ Direction of Travel
  - ✓ Position
  - ✓ Threat
  - ✓ RWS
- **Networking**
  - ✓ IPv4 and IPv6
  - ✓ Multicast
  - ✓ SOAP
  - ✓ Auto-Discovery
  - ✓ SNMP
- **Information Assurance**
  - ✓ Access Control CDS
  - Inline Network Encryptors
  - Firewalls
  - Intrusion Detection Systems
- **Voice and Video**
  - ✓ Voice Communication Interfaces
  - ✓ Radio Management
  - ✓ Video Enhanced Situational Awareness (VESA)
  - ✓ Streaming Video
  - ✓ Camera Management
- **Automotive Services**

## Elements of testing at the SIL

- Specification 1.0 Verification - Message content & Format
- Functional Testing - VICTORY Service Functional Performance
- Management Interface Testing
- VICTORY Service(s) Resource Usage Testing



## Test Plan Development

- Review of the documentation provided for the VICTORY standard specifications.
- Develop experimental procedures for validating the documented specifications. The procedures target each specification being evaluated.
- Create a logical and physical design for executing the experiment. Design the hardware and software configurations necessary to perform the experiment.

# Test Results in VICTORY SIL

## Elements of testing at the SIL


- SIL network built for testing
- Tools Developed to execute the test plan
- Management Interface Testing showed predictable results
- VICTORY Service(s) Resource Usage Testing was well within the limits of network capability.



Static parameters	Values received by client	Values stored in the 'Static Configuration Settings' file
Interface ID	N/A	N/A
Source ID list	N/A	N/A
Interface type	Position	Position
Interface standard version	1.0	1.0
Configuration Version	TARDEC_VEA_VIDS_1.0	TARDEC_VEA_VIDS_1.0
Geodetic datum	N/A	N/A
Timestamp uncertainty	0	0
Minimum update period	0	0
Nominal data available	0, 0, 0	0, 0, 0

Update Period Setting	Average value update for VDM message from Wireshark
1 sec	1.000837923 sec



Specification Version	Number of Proposed Specifications Tested and Verified	Number of Proposed Specifications
1.0	45	96
<b>TOTAL</b>	<b>45</b>	<b>96</b>



# Interoperability with Independent VICTORY Implementations

## Interoperability Testing


- TARDEC's Implementation of VICTORY services and clients executed interoperated successfully with the SwRI's implementation.
- Future testing will include testing of this service with the network fully implemented and with many end user application implemented on the network.



# VICTORY Services Implemented on Small-SWAP Board

## Small-SWAP Testing

- The Small-SWAP Board inserted into the network that included sensors that provided raw data for Position, Orientation, Timing, Threat and Remote Weapons Station.
- The results were very encouraging with very low power consumption (3.15 Watts), less than 1% system memory and CPU utilization and very low heat dissipation.
- Overall, developing and executing services on a Small-SWAP Board type computer on a vehicle platform with tight SWAP requirements is achievable with hardening the system to MIL standards.



**Laptop-like performance**


- TI OMAP3530
- 600 MHz superscaler ARM® Cortex™-A8
- More than 1200 Dhrystone MIPS
- Up to 10 Million polygons per sec graphics
- HD video capable C64x+™ DSP core
- Memory**
- 128MB LPDDR RAM
- 256MB NAND flash

3"

**Flexible expansion**

- IFC, IFS, SPI, MMC/SD
- DVI-D
- JTAG
- S-Video
- SD/MMC+
- Stereo Out
- Stereo In
- USB 2.0 HS OTG
- Alternate Power
- RS-232 Serial

# Verification of Vendor Components



- Built Capability for Open and Standardized Vehicle/EW Architecture.
- VICTORY 1.0 implementation is FMC by September, 2012
- Capability to test and verify vendor provided VICTORY capable components & subsystems
- Advancing SWAP-C with porting and testing 1.0 implementation to small, open and powerful process modules