ARMY RESEARCH LABORATORY

Impact Dynamics of the M557 Fuze

by G. A. Gazonas

ARL-TR-1713 July 1998

19980715 068

Approved for public release; distribution is unlimited.

DTIC QUALITY INSPECTED 1

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

Army Research Laboratory
Aberdeen Proving Ground, MD 21005-5066

ARL-TR-1713 **July 1998**

Impact Dynamics of the M557 Fuze

G. A. Gazonas
Weapons and Materials Research Directorate, ARL

Approved for public release; distribution is unlimited.

Abstract

This report outlines the results of a combined experimental and computational study that investigates the transient structural response of the M557 point detonating fuze subjected to low-speed (200 m/s) oblique impact by a hardened-steel projectile. The problem is of interest to the explosive ordnance disposal (EOD) community as it is a method that is currently used to "render-safe" ordnance and other explosive devices found in the field. An inert M557 fuze is instrumented with a low-mass (1.5 gram) 60-kilo-g uniaxial accelerometer and subjected to oblique impact by launching a 300-gram projectile from a 4-in airgun. The transient structural response of the fuze is compared to the predicted response using the Lagrangian finite element code DYNA3D. Peak accelerations measured in two tests average 35 kilo-g, whereas DYNA3D predicts a 40- to 50-kilo-g peak acceleration depending upon the amount of prescribed damping. Both measured and computed acceleration histories are Fourier-transformed, and the estimated spectral response at the base of the fuze is shown to be dependent upon the failure strength of the flash tube.

Acknowledgments

This work was funded by the Naval Explosive Ordnance Disposal Technology Division, Indian Head, MD. The author thanks Ara Abrahamian, William McIntosh, and Edward Szymanski for conducting the airgun tests.

INTENTIONALLY LEFT BLANK.

Table of Contents

		Page
	Acknowledgments	iii
	List of Figures	vii
1.	**Introduction**	1
2.	**DYNA3D Computations**	3
3.	**Airgun Experiments**	6
4.	**Comparison of Airgun Test Results With DYNA3D Predictions**	8
4.1	Additional Airgun Tests	11
4.2	Additional DYNA3D Simulations	12
4.3	Global Damping	13
5.	**Discussion and Conclusions**	15
6.	**References**	19
	Distribution List	21
	Report Documentation Page	35

INTENTIONALLY LEFT BLANK.

List of Figures

Figure		Page
1.	Cutaway View of a Typical Fuze Illustrating Internal Components	2
2.	Cutaway View of the Finite Element Model Illustrating the Geometry and Grid of Elements of the Fuze and Projectile	2
3.	DYNA3D Simulation Results Showing Deformed Fuze and Ogive Fragmentation at 200 and 500 μs	5
4.	Velocity History of the Projectile cg	5
5.	View of 4-in Airgun From Breech End	7
6.	View of 4-in Airgun From Muzzle Showing M557 Fuze	7
7.	Accelerometer Response for Shot No. 1	8
8.	Periodogram for Shot No. 1	9
9.	Simulated Accelerometer Response	10
10.	Periodogram for Simulated Response	10
11.	Accelerometer Response for Fuze Simulant	11
12.	Periodogram for Fuze Simulant	11
13.	Simulated Accelerometer Response to 200 μs for Weak, Nominal, and Strong Flash-Tube Failure Strengths	13
14.	Periodograms for Weak, Nominal and Strong Flash-Tube Simulations (Note Log Scale on Vertical Axis)	13
15.	Acceleration Histories for Damping Coefficients $\beta = 10^{-8}$, and $\beta = 10^{-6}$ in the UBA	14

Figure | Page

16. Periodograms Showing UBA Spectral Response With Damping Coefficients $\beta = 10^{-8}$ and $\beta = 10^{-6}$ 15

17. Periodograms Showing a Decrease in Power Spectrum in the Accelerometer by Halving the Accelerometer Mesh Density 15

1. Introduction

The explosive ordnance disposal (EOD) community utilizes a variety of devices to disarm or "render-safe" ordnance and other explosive devices found in the field [1]. One class of render-safe methods can be termed "mechanical" in that it relies on a measured use of mechanical force to sever or disrupt the explosive initiation train within the fuze. In this study, the Navy EOD customer was interested in assessing the predictive capabilities of a Lagrangian-based hydrocode in modeling the oblique impact and penetration of the M557 fuze by a hardened-steel projectile.

The work focused on investigating the "structural" damage (i.e., the mechanical response) imparted to an inert fuze as a result of an oblique impact, rather than establishing the impact conditions necessary to render-safe an actual fuze device. A typical fuze geometry consists of a right-circular cone that threads into the ordnance at its base (Figure 1). The cutaway view also illustrates some of the important internal fuze components such as the firing pin, detonator and booster. Although these components are critical for proper operation of the fuze under normal impact conditions, replacing the "fine" internal structure of the fuze with a homogeneous core material simplified modeling the oblique impact problem.

The fuze selected for analysis was the M557 point detonating fuze comprised of a thin-walled mild-steel (1006) ogive that houses a threaded mild-steel base and flash tube. The firing pin, safety spring, detonator, and other intricate nose-cone components were modeled with a homogeneous 6061-T6 aluminum nose cone. The solid, 300-gram cylindrical projectile consisted of hardened Rc-57 steel, 1 in in diameter and 3 in in length. The projectile is designed to strike the fuze normal to its axis of symmetry during render-safe procedures (Figure 2).

The explicit Lagrangian hydrocode DYNA3D (the 1994 version) [2, 3] was used to simulate the transient impact event since this code has been successfully employed to model other highly transient, physical phenomena [4]. In order to quantitatively assess the predictive capabilities of



Figure 1. Cutaway View of a Typical Fuze Illustrating Internal Components.



Figure 2. Cutaway View of the Finite Element Model Illustrating the Geometry and Grid of Elements of the Fuze and Projectile.

the hydrocode, the fuze was instrumented with a lightweight 60 kilo-g uniaxial accelerometer and subjected to oblique impact by launching a 300-gram projectile at constant velocity (200 m/s) from a 4-in airgun. Acceleration histories recorded by the accelerometer mounted on the base of the fuze were compared to the accelerations predicted by DYNA3D. The accelerometer was modeled as a small, rectangular, lightweight mass attached to the base of the fuze.

The results of two oblique fuze impact tests revealed that peak accelerations at the base of the fuze averaged 35 kilo-g, while the predicted peak accelerations ranged from 40 to 50 kilo-g depending upon the amount of prescribed damping. The measured acceleration histories were highly variable in the time domain, so the signals were Fourier-transformed to determine how well the frequency content of the impact event compared with the frequencies of the predicted response using DYNA3D. The measured accelerations contained a dominant energy peak near 30 kHz, whereas the computational results revealed the presence of an energy peak at 30 kHz and another at 120 kHz. The predicted temporal and spectral responses recorded at the base of the fuze strongly depended upon the failure strength of the flash tube.

2. DYNA3D Computations

Computations were performed using the explicit Lagrangian hydrocode, DYNA3D, developed by the Lawrence Livermore National Laboratory (LLNL) in 1977. The code is in use by the aircraft industry (Boeing) and the automobile industry (Volvo, Saab, General Motors, and Japanese manufacturers) for crash and safety modeling and has seen continuous development and use since its initial introduction. The finite element computational grid consists of 76,970 nodes and 53,516 hexahedral finite elements (Figure 2). The ogive consists of three hexahedral elements through the thickness. Computations proceeded through three phases: pre-processor, main cycle, and post-processor, corresponding to PATRAN, DYNA3D, and TAURUS routines, respectively. The rate and temperature-dependent Johnson-Cook model simulated the constitutive behavior of the 1006 mild steel and 6061-T6 materials. The accelerometer behavior was linear elastic. Fixing the outer surface coordinates of the fuze base simulated the experimental test condition, whereby the fuze base was threaded into a massive steel plate to

prevent motion during impact. Nonreflecting boundary conditions were also assigned to the nodes on this surface. The flash tube is threaded into the upper base assembly (UBA) (Figure 2), which contains internal structure not included in the finite element model. To simulate stress wave attenuation in the UBA, the global-damping feature available in DYNA3D (Rayleigh damping extended to nonlinear analysis) was used with damping coefficients set at $\alpha = 0$, and $\beta = 10^{-8}$ [2]. The projectile strikes the fuze at an initial velocity of 200 m/s. The impact position was identical to that in the airgun tests described in section 3. Ten sliding interface definitions prevented interpenetration of the various colliding solids during impact. The simulation of penetration and fragmentation of the ogive employed the "slidesurfaces with adaptive new definitions" (SAND) algorithm. Ogive failure commenced when the equivalent plastic strain of a particular element in the ogive attains a value of $\bar{\varepsilon}^p = 0.30$. Flash-tube fracture was simulated using the "node spotwelded to surface" slideline feature in DYNA3D. The slideline releases nodes along a "failure" surface when a predefined level of the normal and shear failure strength of the flash tube is exceeded [2].

Computations were conducted on a 64-bit Cray C90 vector computer and terminated at 500 μs with a sampling rate of 2 μs/pt (500 kHz), corresponding to a Nyquist rate of 250 kHz. The computations cost an average of 0.1 central-processing-unit (CPU) hr/μs. The computed accelerations of various fuze components, such as the center of gravity (cg) of the accelerometer, were directly compared with measured accelerations. Some salient features of render-safe impact dynamics that depict the fuze deformation history appear in Figure 3. The gross features of ogive fragmentation and flash-tube failure were successfully simulated. However, some minor slideline interpenetration occurred between the base of the fuze and the ogive at 500 μs due to the complexity of the multiple slideline definitions. The projectile velocity vs. time plot (Figure 4) shows that projectile deceleration corresponds to impact into the ogive and nose cone/flash tube. Constant velocity portions of the curve represent periods of time when the projectile is essentially in "free flight." The projectile pierces through the thin-walled ogive at 45 μs and impacts the nose cone at 68 μs. At 104 μs, the projectile is in full contact with the flash tube. At 140 μs, the projectile severs the flash tube at its base and begins to severely



Figure 3. DYNA3D Simulation Results Showing Deformed Fuze and Ogive Fragmentation at 200 and 500 μs.



Figure 4. Velocity History of the Projectile cg.

deform the interior surface of the ogive. The projectile pierces completely through the ogive at 200 μs, and, at 500 μs, the nose cone and flash tube rotate up and out of the flight path of the projectile.

3. Airgun Experiments

Oblique fuze impact tests were conducted at an indoor airgun test range at Adelphi, MD. The test range includes a variety of airgun devices designed to gradually accelerate projectiles to ballistic velocities for high-g impact experiments. The airgun consists of eight 12-ft-long sections, connected in tandem to form a single gun tube 96 ft long, with a 4-in inner diameter. The projectile is loaded into the breech (right-hand side of Figure 5), after which the entire gun tube ahead of the projectile is evacuated to ~1 torr. The projectile is released and gradually accelerated toward the muzzle of the gun by atmospheric pressure acting on its base. The exit velocity of the projectile is determined with either a streak camera or a light-emitting diode system mounted near the barrel exit (Figure 6). Since the projectile diameter in these experiments is much less than the bore diameter of the airgun, a cylindrical bakelite carrier, 4 in in diameter, transports the projectile during flight down the gun tube. Several trial test shots establish the precise weight (projectile + carrier) necessary to achieve an exit velocity of 200 m/s. The projectile flies through a 2-in hole in a steel plate at muzzle exit, which strips off the bakelite carrier (Figure 6). During impact, the projectile pierces through the ogive and severs the flash tube near its base. New bakelite carriers were used for each test, as they shattered on impact with the steel plate.

A 1.5-gram 60-kilo-g uniaxial ENDEVCO Model 7270A-60K piezoresistive accelerometer was mounted on the base of the fuze just below the flash tube and within the cavity which normally contains explosive booster material (Figure 1). The vertical component of the acceleration vector at the base of the fuze was recorded. The 7270A accelerometer is a rugged undamped unit designed specifically for shock measurements. The mounted resonance frequency is 700 kHz, and a near-zero damping allows the accelerometer to respond accurately to fast rise-time, short- duration shock events. The accelerometer signal was conditioned using a Pacific Instruments signal conditioner (Model 8655). Using a signal generator to input a 10-kHz signal with a voltage range comparable to a shock amplitude ranging from 10 to 80 kilo-g, the maximum output voltage had a peak-to-peak amplitude error on the order of 5%. In addition, by maintaining constant voltage and stepping the input frequency in 10-kHz steps to 200 kHz, the



Figure 5. View of 4-in Airgun From Breech End.



Figure 6. View of 4-in Airgun From Muzzle Showing M557 Fuze.

output voltage decreased by 0.82 dB at 100 kHz and 3 dB at 165 kHz. Data were sampled at a rate of 0.5 μs/pt (2 MHz), corresponding to a Nyquist rate of 1 MHz, and stored on a Nicolet 2090 oscilloscope for subsequent analysis.

4. Comparison of Airgun Test Results With DYNA3D Predictions

The acceleration history for shot no. 1 of two separate airgun tests is shown in Figure 7. The measured peak vertical accelerations were on the order of 35 kilo-g and decay rapidly with time. The variability in the observed acceleration histories highlights one difficulty associated with data acquisition in structures subjected to shock and impact. Consequently, the requirement for model validation in the time domain was relaxed by comparing the spectral characteristics (frequency domain) of the measured and predicted signals. To this end, the power spectral density of the acceleration history was estimated by computing the so-called periodogram [5], which is based upon computation of the fast Fourier transform (FFT) [6]. The computational economy of the FFT makes this approach one of the most popular methods for spectral estimation. Conventional FFT spectral estimation is based upon a Fourier series model of the data; that is, the process is assumed to be composed of a set of harmonically related sinusoids.



Figure 7. Accelerometer Response for Shot No. 1.

For this problem, this is not a bad assumption given the fundamental nature of wave propagation in media. FFTs of the measured accelerations were computed using the Mathcad 7.0 software package [7], and, from these transformations, periodograms were computed (Figure 8). The FFT of the vector v_k in Mathcad 7.0 is computed using,

$$c_j = \frac{1}{\sqrt{N}} \sum_{k=o}^{N-1} v_k e^{2\pi i (j/N)k}, \tag{1}$$

with corresponding frequencies,

$$f_k = \frac{k}{N} f_s, \tag{2}$$

which depend upon the sampling frequency f_s and the number of samples N. The periodogram plots were formed by squaring the magnitude of the vector in equation 1 (see e.g., Oppenheim and Schafer [8]) and revealed the presence of a dominant energy peak at 30 kHz that is undoubtedly related to some physical phenomenon associated with the impact event. The longitudinal wave speed, 146,316 in/s, in the accelerometer was estimated from its modulus and bulk density. Hence, the fundamental frequency of an acoustic wave traveling vertically through the 0.11-in-thick accelerometer was computed to be about 665 kHz. Thus, the relatively low frequency peak at 30 kHz is produced by some other mechanical disturbance, possibly due to the fracture failure of the flash tube. The discussion in a subsequent section examines this



Figure 8. Periodogram for Shot No. 1.

Hypothesis. The same spectral estimation methodology was applied to the vertical accelerations computed for the cg of the modeled accelerometer in the DYNA3D analysis. The acceleration history for the DYNA3D analysis is shown in Figure 9. Comparison of the actual and simulated periodograms in Figures 8 and 10 reveals that the measured accelerations contain a dominant energy peak at 30 kHz, whereas the computational results predict an energy peak at 30 kHz and an additional energy peak at 120 kHz. Additional airgun tests and simulations were performed to gain a better understanding of the physical phenomenon causing the observed energy peak at 30 kHz and why DYNA3D predicts an energy peak at 120 kHz.



Figure 9. Simulated Accelerometer Response.



Figure 10. Periodogram for Simulated Response.

4.1 Additional Airgun Tests. Two additional airgun experiments were performed whereby the M557 fuze was replaced with a fuze "simulant" constructed from hot rolled steel. In addition, the simulant was further simplified by removing the ogive and nose cone, so that only the flash tube and base were subjected to impact. The impact and boundary conditions were identical to those in the previous airgun impact tests. The acceleration histories and periodograms for one test appear in Figures 11 and 12. Interestingly, the periodograms for the fuze simulant tests also reveal dominant energy peaks at 30 kHz and indicate that the ogive and nose-cone structural components do not appreciably contribute to the spectral response of the M557 fuze. Although



Figure 11. Accelerometer Response for Fuze Simulant.



Figure 12. Periodogram for Fuze Simulant.

the projectile pierces through the ogive and impacts the nose cone during render-safe operations, these collisions do not measurably influence the spectral response of the M557 fuze.

4.2 Additional DYNA3D Simulations. Another parameter that can influence the measured spectral response is the failure strength of the flash tube. As described in section 2, flash-tube failure was modeled using the "node spotwelded to surface" slideline feature in DYNA3D. With this feature, nodes along a "failure" surface are released when a predefined level of the normal and shear failure strength of the flash tube is exceeded. The flash-tube failure strength was artificially modified by conducting two additional simulations whereby its strength is first decreased and then increased by an order of magnitude, from its nominal value in prior simulations. The acceleration histories and periodograms for the "weak," "nominal," and "strong" flash-tube simulations appear in Figure 13. The waveforms for the weak and nominal strength simulations were very similar as compared to the strong flash-tube simulation which exhibited a high-amplitude acceleration response that did not decay appreciably with time. Furthermore, the flash tube did not fail in the strong simulation as progressive distortion of the finite elements in the impact region rapidly decreased the stable time step governed by the Courant condition. Thus, the simulation was terminated at 180 μs. Periodograms are computed for the three cases investigated and are plotted in semi-log form in Figure 14. The simulations involving the weak and nominal flash-tube strengths were nearly identical in the estimate of the power spectral density of the shock signal. However, the energy associated with the impact into the strong flash tube was several orders of magnitude greater and was more uniform in strength across the frequency spectrum; thus, increasing the flash-tube failure strength has the effect of transmitting higher energy modes to the accelerometer. The results indicate that changing the failure strength of the flash tube can substantially modify the temporal and frequency response of the fuze that is subjected to oblique impact.



Figure 13. Simulated Accelerometer Response to 200 μs for Weak, Nominal and Strong Flash-Tube Failure Strengths.



Figure 14. Periodograms for Weak, Nominal and Strong Flash-Tube Simulations (Note Log Scale on Vertical Axis).

4.3 Global Damping. In order to simulate the effect of the UBA's intricate internal structure, the damping coefficient was $\beta = 10^{-8}$ for the computations reported thus far. As the precise effect of this internal structure on the resulting waveform was unknown, the damping

coefficient in the UBA was increased to $\beta = 10^{-6}$ in an effort to further attenuate the 120-kHz energy peak. A comparison of the acceleration histories for the cg of the UBA for the cases $\beta = 10^{-8}$ and $\beta = 10^{-6}$ reveals that increasing the damping coefficient attenuates the resulting waveform (Figure 15). In addition, increasing the damping coefficient to $\beta = 10^{-6}$ attenuates the peak acceleration in the accelerometer to 41 kilo-g. Interestingly, the cg of the UBA contains an energy peak at 30 kHz, but the 120-kHz energy peak is highly attenuated (Figure 16), relative to that predicted in the accelerometer (Figure 10). This observation is independent of the value of β used in the analysis.

Another possible source of the anomalous energy at 120 kHz could be related to spurious frequencies induced by the finite element mesh in the accelerometer. The 0.11-in-thick accelerometer was initially modeled with six hexahedral elements through its thickness resulting in the power spectral density illustrated in Figure 10. Halving the finite element mesh density resulted in attenuation of the energy associated with the spurious frequency at 120 kHz, but the energy at 30 kHz was attenuated as well (Figure 17).



Figure 15. Acceleration Histories for Damping Coefficients $\beta = 10^{-8}$ and $\beta = 10^{-6}$ in the UBA.



Figure 16. Periodograms Showing UBA Spectral Response With Damping Coefficients $\beta = 10^{-8}$ and $\beta = 10^{-6}$. Note the Relatively Weak Signal Power in the 120-kHz Range.



Figure 17. Periodograms Showing Decrease in Power Spectrum in the Accelerometer by Halving the Accelerometer Mesh Density.

5. Discussion and Conclusions

This report outlined the results of a combined experimental and computational study that investigated the transient structural response of the M557 point detonating fuze subjected to low-speed (200 m/s) oblique impact by a hardened-steel projectile. Peak accelerations measured in

the airgun tests averaged 35 kilo-g, whereas peak accelerations predicted by DYNA3D ranged from 40 to 50 kilo-g depending upon the value used for critical damping in the UBA.

A comparison of the estimated spectral response of the simulations and experiments revealed that both contain spectral energy at 30 kHz. Additional tests on fuze simulants whereby the ogive and nose cone were removed from the fuze also contained spectral energy at 30 kHz. This observation indicates that the ogive and nose-cone structural components do not significantly contribute to the frequency content of the observed waveforms. Furthermore, the estimated spectral response at the base of the fuze was shown to be largely dependent upon the failure strength of the flash tube; impact energy is transmitted to the accelerometer as long as the flash tube remains in contact with the UBA. The DYNA3D hydrocode also predicted the presence of a strong spectral peak in the accelerometer at 120 kHz, which was not observed in the impact tests. This spurious spectral peak appears to be an artifact of the finite element analysis as this spectral component is highly attenuated in the cg response of the UBA. How then is energy at this frequency being excited in the model accelerometer?

A final investigation examined the spectral response of a vertical line of nodes along the central axis of the UBA. These axial nodes are a subset of the total number of nodes that comprise the cg response of the UBA. When the nodes that comprise the "spotwelded" failure surface are suddenly released during failure, a high-g stress wave is introduced into the mesh, which attenuates as it travels downward through the UBA. This stress wave excites the axial nodes in the UBA, which contain a dominant spectral energy peak that is phase-shifted in a band around 120 kHz. If the acceleration histories of this subset of nodes are summed and spectrally analyzed, the 120-kHz energy peak attenuates and broadens. The summing procedure is known as signal stacking in the geophysics literature [9] and has the effect of improving the signal-to-noise ratio. As an increasing number of UBA nodes are included in the analysis, the cg response is approached (Figure 16). Why the spectral peaks of axial nodes shift phase in a band around 120 kHz is not known but is currently an area of active study. In real media, however, phase shifts are caused by wave reflections, caustics, and geometrical or material dispersion effects. It is interesting to conjecture that the 120-kHz frequency is related to the fundamental axial mode of vibration of the UBA. Since the height of the UBA is about 0.55 in and the longitudinal wave

speed is 129,816 in/s, this results in a fundamental frequency of about 118 kHz. The 120-kHz energy can be further attenuated with more suitably chosen Rayleigh damping coefficients, or post-processing the finite element transients, which inherently contain spurious frequencies related to multiple wave reflection phenomena and element size effects as discussed in Holmes and Belytschko [10].

INTENTIONALLY LEFT BLANK.

6. References

1. Gazonas, G. A., S. B. Segletes, V. M. Boyle, and S. R. Stegall. "Oblique Impact Modeling of Fuzes." *International Journal of Impact Engineering*, vol. 18, no. 4, pp. 435-457, 1996.

2. Hallquist, J. O., and R. G. Whirley. *DYNA3D Users Manual (Nonlinear Dynamic Analysis of Structures in Three Dimensions),* UCID-19592, Rev. 5, Lawrence Livermore National Laboratory, Livermore, CA, May 1989.

3. Hallquist, J. O. *Theoretical Manual for DYNA3D*, UCID-19401, Lawrence Livermore National Laboratory, Livermore, CA, March, 1983.

4. Gazonas, G. A. "Lagrangian Simulation of Linear Shaped Demolition Charge Formation." *Proceedings of the 4th International Conference on Structures Under Shock and Impact IV*, N. Jones, C. A. Brebbia, and A. J. Watson (editors), Computational Mechanics Publications, Southampton and Boston, pp. 361-372, 1996.

5. Schuster, A. "On the Investigation of Hidden Periodicities with Application to a Supposed 26 Day Period of Meteorological Phenomena." *Terrestrial Magnetism*, vol. 3, pp. 13-42, 1898.

6. Brillinger, D. R. "Fourier Analysis of Stationary Processes." *Proceedings IEEE*, vol. 62, pp. 1628-1634, 1974.

7. Mathsoft, Inc. Mathcad 7.0 Software Program. 101 Main Street, Cambridge, MA, 1997.

8. Oppenheim, A. V, and R. W. Schafer. *Digital Signal Processing*. p. 585, Prentice Hall, Inc., Englewood Cliffs, NJ, 1975.

9. Telford, W. M., L. P. Geldart, R. E. Sheriff, and D. A. Keys. *Applied Geophysics*. p. 860, Cambridge University Press, Cambridge, 1976.

10. Holmes, N., and T. Belytschko. "Postprocessing of Finite Element Transient Response Calculations by Digital Filters." *Computers and Structures*, vol. 6, pp. 211-216, 1976.

INTENTIONALLY LEFT BLANK.

NO. OF COPIES	ORGANIZATION
2	DEFENSE TECHNICAL INFORMATION CENTER DTIC DDA 8725 JOHN J KINGMAN RD STE 0944 FT BELVOIR VA 22060-6218
1	HQDA DAMO FDQ DENNIS SCHMIDT 400 ARMY PENTAGON WASHINGTON DC 20310-0460
1	DPTY ASSIST SCY FOR R&T SARD TT F MILTON RM 3EA79 THE PENTAGON WASHINGTON DC 20310-0103
1	OSD OUSD(A&T)/ODDDR&E(R) J LUPO THE PENTAGON WASHINGTON DC 20301-7100
1	CECOM SP & TRRSTRL COMMCTN DIV AMSEL RD ST MC M H SOICHER FT MONMOUTH NJ 07703-5203
1	PRIN DPTY FOR TCHNLGY HQ US ARMY MATCOM AMCDCG T M FISETTE 5001 EISENHOWER AVE ALEXANDRIA VA 22333-0001
1	DPTY CG FOR RDE HQ US ARMY MATCOM AMCRD BG BEAUCHAMP 5001 EISENHOWER AVE ALEXANDRIA VA 22333-0001
1	INST FOR ADVNCD TCHNLGY THE UNIV OF TEXAS AT AUSTIN PO BOX 202797 AUSTIN TX 78720-2797

NO. OF COPIES	ORGANIZATION
1	GPS JOINT PROG OFC DIR COL J CLAY 2435 VELA WAY STE 1613 LOS ANGELES AFB CA 90245-5500
3	DARPA L STOTTS J PENNELLA B KASPAR 3701 N FAIRFAX DR ARLINGTON VA 22203-1714
1	US MILITARY ACADEMY MATH SCI CTR OF EXCELLENCE DEPT OF MATHEMATICAL SCI MDN A MAJ DON ENGEN THAYER HALL WEST POINT NY 10996-1786
1	DIRECTOR US ARMY RESEARCH LAB AMSRL CS AL TP 2800 POWDER MILL RD ADELPHI MD 20783-1145
1	DIRECTOR US ARMY RESEARCH LAB AMSRL CS AL TA 2800 POWDER MILL RD ADELPHI MD 20783-1145
3	DIRECTOR US ARMY RESEARCH LAB AMSRL CI LL 2800 POWDER MILL RD ADELPHI MD 20783-1145
	ABERDEEN PROVING GROUND
4	DIR USARL AMSRL CI LP (305)

NO. OF COPIES	ORGANIZATION
2	PEO FAS SFAE FAS PM H GOLDMAN T MCWILLIAMS PICATINNY ARSENAL NJ 07806-5000
2	PM CRUSADER G DELCOCO J SHIELDS PICATINNY ARSENAL NJ 07806-5000
5	PM SADARM SFAE GCSS-SD B ELLIS M DEVINE W DEMASSI J PRITCHARD S HROWNAK PICATINNY ARSENAL NJ 07806-5000
5	PM TMAS SFAE GSSC TMA COL PAWLICKI K KIMKER E KOPACZ R ROESER B DORCY PICATINNY ARSENAL NJ 07806-5000
1	PM TMAS SFAE GSSC TMA SMD R KOWALSKI PICATINNY ARSENAL NJ 07806-5000
1	CDR ARDEC F MCLAUGHLIN PICATINNY ARSENAL NJ 07806-5000
3	CDR ARDEC AMSTA AR (2 CPS) E FENNELL PICATINNY ARSENAL NJ 07806-5000

NO. OF COPIES	ORGANIZATION
6	CDR ARDEC AMSTA AR CCH S MUSALLI P CHRISTIAN R CARR M LUCIANO T LOUCEIRO PICATINNY ARSENAL NJ 07806-5000
7	CDR ARDEC AMSTA AR CCH B B KONRAD E RIVERA G EUSTICE S PATEL G WAGNECZ R SAYER F CHANG BLDG 65 PICATINNY ARSENAL NJ 07806-5000
1	CDR ARDEC AMSTA AR CCH P J LUTZ PICATINNY ARSENAL NJ 07806-5000
3	CDR ARDEC AMSTA AR FSA A WARNASH B MACHAK C CHIEFA PICATINNY ARSENAL NJ 07806-5000
1	CDR ARDEC AMSTA AR FSE T GORA PICATINNY ARSENAL NJ 07806-5000
1	CDR ARDEC AMSTA AR FSF T C LIVECCHIA PICATINNY ARSENAL NJ 07806-5000
2	CDR ARDEC AMSTA-AR-FSP-G M SCHIKSNIS D CARLUCCI PICATINNY ARSENAL NJ 07806-5000

NO. OF COPIES	ORGANIZATION
2	CDR ARDEC AMSTA AR M D DEMELLA F DIORIO PICATINNY ARSENAL NJ 07806-5000
1	CDR ARDEC AMSTA AR QAC M829E3 IPT T D RIGOGLIOSO B354 PICATINNY ARSENAL NJ 07806-5000
1	CDR ARDEC AMSTA AR QAC T/C C PATEL PICATINNY ARSENAL NJ 07806-5000
1	CDR ARDEC AMSTA AR SRE D YEE PICATINNY ARSENAL NJ 07806-5000
3	CDR ARDEC AMSTA AR TD R PRICE V LINDNER C SPINELLI PICATINNY ARSENAL NJ 07806-5000
1	CDR ARDEC INDSTRL ECLGY CTR T SACHAR B172 PICATINNY ARSENAL NJ 07806-5000
8	DIR ARL AMSRL CP CA D SNIDER AMSRL WM MB T LI A ABRAHAMIAN M BERMAN A FRYDMAN W MCINTOSH E SZYMANSKI AMSRL WT L D WOODBURY 2800 POWDER MILL RD ADELPHI MD 20783-1197

NO. OF COPIES	ORGANIZATION
5	DIR ARO G ANDERSON J CHANDRA A CROWSON K IYER R SINGLETON PO BOX 12211 RESEARCH TRIANGLE PARK NC 27709-2211
1	CDR ATCOM AVN APPLIED TECH DIR J SCHUCK FORT EUSTIS VA
8	DIR BENET LABS AMSTA AR CCB J KEANE J BATTAGLIA J VASILAKIS G FFIAR V MONTVORI J WRZOCHALSKI R HASENBEIN SMCAR CCB R S SOPOK WATERVLIET NY 12189
1	CDR USA BRDEC STRBE JBC FORT BELVOIR VA 22060-5606
1	DIR USA CRREL P DUTTA 72 LYME RD HANOVER NH 03755
3	CDR MICOM AMSMI RD W MCCORKLE AMSMI RD ST P DOYLE AMSMI RD ST CN T VANDIVER REDSTONE ARSENAL AL 35898-5247
1	DIR PBMA AMSMC PBM K PICATINNY ARSENAL NJ 07806-5000

NO. OF COPIES	ORGANIZATION
5	CDR TACOM AMSTA JSK S GOODMAN J FLORENCE AMSTA TR D B RAJU L HINOJOSA D OSTBERG WARREN MI 48397-5000
3	CDR WATERVLIET ARSENAL SMCWV QAE Q B VANINA B44 SMCWV QA QS K INSCO SMCWV SPM T MCCLOSKEY B253 WATERVLIET NY 12189-4050
1	DIR DAVID TAYLOR RSCH CTR SHIP STRCTRS & PRTN DEPT CODE 1702 J CORRADO BETHESDA MD 20084
2	DIR DAVID TAYLOR RSCH CTR R ROCKWELL W PHYILLAIER BETHESDA MD 20054-5000
1	EXPDTNRY WF DIV N85 F SHOUP 2000 NAVY PENTAGON WASHINGTON DC 20350-2000
15	NAVAL EOD TECH CTR CODE 50B M H SHERLOCK (5 CP) CODE 6012A A PATEL (5 CP) R GOLD (5 CP) INDIAN HEAD, MD 20640-5070
1	DIR NAVAL RSCH LAB CODE 6383 I WOLOCK WASHINGTON DC 20375-5000
1	CDR NSSC D LIESE 2531 JEFF DAVIS HWY ARLINGTON VA 22242-5160
2	CDR NSWC CARDEROCK CODE 2802 R CRANE CODE 6553 C WILLIAMS 3A LEGGETT CIR ANNAPOLIS MD 21402

NO. OF COPIES	ORGANIZATION
11	CDR NSWC DAHLGREN CODE B02 M E LACY CODE G06 CODE G30 J H FRANCIS CODE G32 D WILSON R D COOPER CODE G33 J FRAYSSE E ROWE T DURAN L DE SIMONE G33-C R HUBBARD CODE 323 TECH LBRY 17320 DAHLGREN RD DAHLGREN VA 22448-5000
1	CDR NSWC CRANE DIVISION CODE 20H4 M JOHNSON LOUISVILLE KY 40214-5245
2	OFC OF NAVAL RSCH MECH DIV CODE 1132SM Y RAJAPAKSE D SIEGEL 351 800 N QUINCY ST ARLINGTON VA 22217-5660
1	OFC OF NAVAL RSCH J KELLY 800 N QUINCEY ST ARLINGTON VA 22217-5000
1	NAVSEA OJRI G CAMPONESCHI 2351 JEFF DAVIS HWY ARLINGTON VA 22242-5160
1	USMC SYSTEMS CMD PM GROUND WPNS R OWEN 2083 BARNETT AVE STE 315 QUANTICO VA 22134-5000

NO. OF COPIES	ORGANIZATION
6	CDR USAF WL WRIGHT PATTERSON AFB FIV A MAYER MLBM S DONALDSON T BENSON-TOLLE C BROWNING J MCCOY F ABRAHAMS 2941 P STREET STE 1 DAYTON OH 45433
1	USAF WL MLS-OL A HAKIM 5225 BAILEY LOOP 243E MCCLELLAN AFB CA 55552
1	USAF WL/MLBC E SHINN 2941 PST STE 1 WRIGHT PATTERSON AFB OH 45433-7750
2	DIR DARPA J KELLY B WILCOX 3701 N FAIRFAX DR ARLINGTON VA 22203-1714
1	DIR DFNS NUCLEAR AGNCY INNOVATIVE CONCEPTS DIV R ROHR 6801 TELEGRAPH RD ALEXANDRIA VA 22310-3398
2	FAA TECH CENTER AAR-431 D OPLINGER P SHYPRYKEVICH ATLANTIC CITY INTERNATIONAL AP NJ 08405
1	NASA LANGLEY RSCH CTR MS 188E CC POE NEWPORT NEWS VA 23608
2	NASA LANGLEY RSCH CTR AMSRL VS MS 266 W ELBER F BARTLETT JR HAMPTON VA 23681-0001

NO. OF COPIES	ORGANIZATION
1	NASA LANGLEY RSCH CTR MS 389 J MASTERS HAMPTON VA 23662-5225
2	DIR LANL MS B216 F ADDESSIO MS F668 J REPPA PO BOX 1633 LOS ALAMOS NM 87545
5	DIR LLNL R CHRISTENSEN S DETERESA F MAGNESS M FINGER L282 M MURPHY PO BOX 808 LIVERMORE CA 94550
2	DIR ORNL A WERESZCZAK MS 6069 B4515 PO BOX 2008 OAKRIDGE TN 37831-6064
1	DIR ORNL R M DAVIS PO BOX 2008 OAK RIDGE TN 37831-6195
1	PACIFIC NW LAB M SMITH PO BOX 999 RICHLAND WA 99352
4	DIR SNL APLD MECH DEPT DIV 8241 W KAWAHARA K PERANO D DAWSON P NIELAN PO BOX 969 LIVERMORE CA 94550-0096
1	DIR SNL MS 9405 D BAMMANN LIVERMORE CA 94551-0969

NO. OF COPIES	ORGANIZATION
2	DIR SNL MS0439 E BUTCHER J DOHNER PO BOX 5800 ALBUQUERQUE NM 87185-0439
7	CVL ENGR RSCH FNDTN H BERNSTEIN PRES C MAGNELL K ALMOND R BELLE M WILLETT E DELO B MATTES 1015 15TH ST NW STE 600 WASHINGTON DC 20005
1	DREXEL UNIV A WANG 32ND & CHESTNUT ST PHILADELPHIA PA 19104
9	IAT UNIV OF TX AUSTIN T KIEHNE H FAIR P SULLIVAN W REINECKE I MCNAB S BLESS S SATAPATHY K T HSIEH B K KIM 4030 2 W BRAKER LN AUSTIN TX 78759
2	IIT RESEARCH CTR D ROSE 201 MILL ST ROME NY 13440-6916
1	MI STATE UNIV R AVERILL 3515 EB, MSM DEPT EAST LANSING MI 48824-1226
1	MIT P LAGACE 77 MASS AVE CAMBRIDGE MA 01887

NO. OF COPIES	ORGANIZATION
1	NC STATE UNIV CVL ENGRG DEPT W RASDORF PO BOX 7908 RALEIGH NC 27696-7908
5	NIST STRCTR & MECH GRP POLYMER DIV RM A209 G MCKENNA R PARNAS J DUNKERS M VANLANDINGHAM D HUNSTON GAITHERSBURG MD 20899
1	NW UNIV DEPT OF THEORETICAL AND APPLIED MECHANICS T BELYTSCHKO EVANSTON IL 60208
2	PA STATE UNIV C BAKIS R MCNITT 227 N HAMMOND UNIVERSITY PARK PA 16802
1	PA STATE UNIV R ENGEL 245 HAMMOND BLDG UNIVERSITY PARK PA 16801
1	PURDUE UNIV SCHL OF AERO & ASTRO C T SUN W LAFAYETTE IN 47907-1282
1	RENNSAELER POLYTECH INST R B PIPES PRESIDENT OFC PITTSBURGH BLDG TROY NY 12180-3590
1	STANFORD UNIV DEPT OF AERONAUTICS & AEROBALLISTICS S TSAI DURANT BLDG STANFORD CA 94305

NO. OF COPIES	ORGANIZATION
2	SW RSCH INST C ANDERSON ENGRNG & MATL SCNCS J RIEGEL 6220 CULEBRA RD PO DRAWER 28510 SAN ANTONIO TX 78228-0510
3	TUSKEGEE UNIV MATLS RSCH LAB SCHOOL OF ENGR & ARCH S JEELANI H MAHFUZ U VAIDYA TUSKEGEE, AL 36088
1	UCLA MANE DEPT ENGR IV H HAHN LOS ANGELES CA 90024-1597
3	UDLP MS170 P JANKE MS236 T GIOVANETTI MS389 B VAN WYK 4800 E RIVER RD MINNEAPOLIS MN 55421-1498
1	UNIV OF CINCINNATI DEPT OF AEROSPACE ENGNG & ENGNG MECH A TABIEI CINCINNATI OH 45221-0070
3	UNIV OF DAYTON RSCH INST R KIM A ROY J WHITNEY 300 COLLEGE PARK AVE DAYTON OH 45469-0168
2	UNIV OF DE CTR FOR CMPST MATLS J GILLESPIE M SANTARE 201 SPENCER LAB NEWARK DE 19716

NO. OF COPIES	ORGANIZATION
1	UNIV OF IL AT URBANA CHAMPAIGN NCCMR J ECONOMY 216 TALBOT LAB 104 S WRIGHT ST URBANA IL 61801
1	UNIV OF IL AT URBANA CHAMPAIGN NCSA 4121 BECKMAN INST FOR ADVNCD S&T F AHMAD URBANA ILL 61801
1	UNIV OF KY L PENN 763 ANDERSON HALL LEXINGTON KY 40506-0046
1	UNIV OF MD DEPT OF AEROSPC ENGNG A VIZZINI COLLEGE PARK MD 20742
3	UNIV OF TX AT AUSTIN CTR FOR ELCTRMCHNCS J PRICE A WALLS J KITZMILLER 10100 BURNET RD AUSTIN TX 78758-4497
1	UNIV OF UTAH DEPT OF MECH & INDSTRL ENGR S SWANSON SALT LAKE CITY UT 84112
1	UNIV OF WYOMING D ADAMS PO BOX 3295 LARAMIE WY 82071
3	VA POLYTECH INST & STATE UNIV DEPT OF ESM M W HYER K REIFSNIDER R JONES BLACKSBURG VA 24061-0219

NO. OF COPIES	ORGANIZATION
1	AAI CORP T STASTNY PO BOX 126 HUNT VALLEY MD 21030-0126
2	ADVNCD CMPST MATLS CORP P HOOD J RHODES 1525 S BUNCOMBE RD GREER SC 29651-9208
3	ALLIANT TECHSYS INC J BODE C CANDLAND K WARD 5901 LINCOLN DR MINNEAPOLIS MN 55346-1674
8	ALLIANT TECHSYS INC G JOHNSON T HOLMQUIST C CANDLAND R BECKER L LEE R LONG D KAMDAR G KASSUELKE 600 2ND ST NE HOPKINS MN 55343-8367
1	AMOCO PERF PRDCTS INC M MICHNO JR 4500 MCGINNIS FERRY RD ALPHARETTA GA 30202-3944
1	AMOCO POLYMERS J BANISAUKAS 4500 MCGINNIS FERRY RD ALPHARETTA GA 30005
1	APPLIED COMPOSITES W GRISCH 333 NORTH SIXTH ST ST CHARLES IL 60174
1	ARMTEC DFNS PRDCTS S DYER 85 901 AVE 53 PO BOX 848 COACHELLA CA 92236

NO. OF COPIES	ORGANIZATION
1	ARROW TECH ASSO 1233 SHELBURNE RD STE D 8 SOUTH BURLINGTON VT 05403-7700
1	ASRDD CORP D ELDER PO BOX 49472 COLORADO SPRINGS CO 80949-9472
1	BALLISTIC IMPCT DYNMCS R RECHT 3650 S CHEROKEE 2 ENGLEWOOD CO 80110
1	BATTELLE C R HARGREAVES 505 KING AVE COLUMBUS OH 43201-2681
1	BOEING MC 5021322 R BOHLMANN PO BOX 516 ST LOUIS MO 63166-0516
4	BOEING MS 449-53 D CARLSON MS 67-MW B DOPKER MS 2T-20 R LUNDQUIST MS 49-53 J SELL PO BOX 3707 SEATTLE WA 98124-2207
1	BOEING DOUGLAS PRDCTS DIV L J HART-SMITH D800-0019 3855 LAKEWOOD BLVD LONG BEACH CA 90846-0001
2	BOEING ROTORCRAFT P MINGURT P HANDEL 800 B PUTNAM BLVD WALLINGFORD PA 19086
1	BRIGS CO J BACKOFEN 2668 PETERBOROUGH ST HERDON VA 22071-2443

NO. OF COPIES	ORGANIZATION
1	BRUNSWICK DFNS T HARRIS 1745 JEF DAVIS HWY STE 410 ARLINGTON VA 22202
1	CA RSCH & TECH D ORPHAL 5117 JOHNSON DR PLEASANTOWN CA 94566
1	CMPTNL MECH ASSOC J ZUKAS PO BOX 11314 BALTIMORE, MD 21239-0314
1	CUSTOM ANAL ENGR SYS INC A ALEXANDER 13000 TENSOR LANE NE FLINTSTONE MD 21530
1	CYTEC M LIN 1440 N KRAEMER BLVD ANAHEIM CA 92806
1	DOW-UT S TIDRICK 15 STERLING DR WALLINGFORD CT 06492
1	DUPONT CO CMPSTS ARAMID FIBERS S BORLESKE DEV MGR CHESNUT RN PL PO BOX 80702 WILMINGTON DE 19880-0702
1	DYNA EAST CORP P CHOU 3201 ARCH ST PHILADELPHIA PA 19104-2711
5	GEN CORP AEROJET D PILLASCH T COULTER C FLYNN D RUBAREZUL M GREINER 1100 WEST HOLLYVALE ST AZUSA CA 91702-0296

NO. OF COPIES	ORGANIZATION
1	GDLS DIV D BARTLE PO BOX 1901 WARREN MI 48090
3	HERCULES INC R BOE F POLICELLI J POESCH PO BOX 98 MAGNA UT 84044
3	HERCULES INC G KUEBELER J VERMEYCHUK B MANDERVILLE JR HERCULES PLZ WILMINGTON DE 19894
1	HEXCEL M SHELENDICH 11555 DUBLIN BLVD PO BOX 2312 DUBLIN CA 94568-0705
1	HEXCEL T BITZER 11711 DUBLIN BLVD DUBLIN CA 94568
1	IAP RESEARCH INC A CHALLITA 2763 CULVER AVE DAYTON OH 45429
1	INTGRTD CMPST TECH H PERKINSON JR PO BOX 397 YORK NEW SALEM PA 17371-0397
1	INTERFEROMETRICS INC R LARRIVA VP 8150 LEESBURG PIKE VIENNA VA 22100
1	KBS2 INC J KENNEDY 455 S FRONTAGE RD STE 112 BURR RIDGE IL 60521-7104

NO. OF COPIES	ORGANIZATION
1	D R KENNEDY & ASSOC INC D KENNEDY PO B0X 4003 MOUNTAIN VIEW CA 94040
1	LIVERMORE SFTWR TECH CORP J HALLQUIST 2876 WAVERLY WAY LIVERMORE CA 94040
1	LOCKHEED MARTIN R FIELDS 1195 IRWIN CT WINTER SPRINGS FL 32708
1	LOCKHEED MARTIN D/73-62 MZ 0648 S REEVE 8650 COBB DR MARIETTA GA 30063-0648
1	LORAL VOUGHT SYS PM ADVANCED CONCEPTS MS WT 21 J TAYLOR PO BOX 650003 DALLAS TX 76265-0003
2	LORAL VOUGHT SYS G JACKSON K COOK 1701 W MARSHALL DR GRAND PRAIRIE TX 75051
2	MARTIN MARIETTA CORP P DEWAR L SPONAR 230 E GODDARD BLVD KING OF PRUSSIA PA 19406
1	MATLS SCIENCES CORP B W ROSEN 500 OFC CTR DR STE 250 FORT WASHINGTON PA 19034
1	NOESIS INC A BOUTZ 1110 N GLEBE RD STE 250 ARLINGTON VA 22201-4795

NO. OF COPIES	ORGANIZATION
2	NORTHROP GRUMMAN ENVIRONMENTAL PRGRMS R OSTERMAN 8900 E WASHINGTON BLVD PICO RIVERA CA 90660
1	PRATT & WHITNEY D HAMBRICK 400 MAIN ST MS 114-37 EAST HARTFORD CT 06108
2	PRIMEX TECH INC FLINCHBAUGH DIV E STEINER B STEWART PO BOX 127 RED LION PA 17356
1	PRIMEX TECH INC L WHITMORE 10101 9TH ST NO ST PETERSBURG FL 33702
1	SAIC DAN DAKIN 2200 POWELL ST STE 1090 EMERYVILLE CA 94608
1	SAIC M PALMER 2109 AIR PARK RD S E ALBUQUERQUE NM 87106
1	SAIC R ACEBAL 1225 JHNSN FRY RD STE 100 MARIETTA GA 30068
1	SAIC G CHRYSSOMALLIS 3800 W 80th ST STE 1090 BLOOMINGTON MN 55431

NO. OF COPIES	ORGANIZATION
5	SIKORSKY H BUTTS T CARSTENSAN B KAY S GARBO J ADELMANN 6900 MAIN ST PO BOX 9729 STRATFORD CT 06601-1381
1	SPARTA INC J GLATZ 9455 TOWNE CTR DR SAN DIEGO CA 92121-1964
2	UNITED DEFENSE LP P PARA G THOMAS 1107 COLEMAN AVE BOX 367 SAN JOSE CA 95103
1	ZERNOW TECHNICAL SVCS L ZERNOW 425 W BONITA AVE STE 208 SAN DIMAS CA 91773
1	R EICHELBERGER CONSULTANT 409 W CATHERINE ST BEL AIR MD 21014-3613
1	J HEBERT PO BOX 1072 HUNT VALLEY MD 21030-0126

NO. OF COPIES	ORGANIZATION
	ABERDEEN PROVING GROUND
83	DIR ARL AMSRL CI, C MERMAGEN AMSRL CI C, W STUREK AMSRL CI CB, R KASTE AMSRL CI S, A MARK AMSRL SL B AMSRL SL BA AMSRL SL BE, D BELY AMSRL SL EI AMSRL WM B, A HORST E SCHMIDT AMSRL WM BA, F BRANDON W D AMICO AMSRL WM BB, J BORNSTEIN AMSRL WM BC, P PLOSTINS D LYON J NEWILL S WILKERSON T ERLINE AMSRL WM BD, R FIFER B FORCH R PIESCE-RODRIGUEZ B RICE AMSRL WM BE, G KELLER C LEVERITT D KOOKER AMSRL WM BF, J LACETERA AMSRL WM M, D VIECHNICKI G HAGNAUER J MCCAULEY AMSRL WM MA, R SHUFORD S MCKNIGHT

NO. OF COPIES	ORGANIZATION
	AMSRL WM MB,
	C HOPPEL
	D HENRY
	R KASTE
	R KLINGER
	M LEADORE
	R LIEB
	E RIGAS
	D SPAGNUOLO
	W SPURGEON
	J TZENG
	B BURNS
	W DRYSDALE
	J BENDER
	T BLANAS
	T BOGETTI
	R BOSSOLI
	L BURTON
	J CONNORS
	S CORNELISON
	P DEHMER
	R DOOLEY
	B FINK
	G GAZONAS (5 CPS)
	S GHIORSE
	D GRANVILLE
	D HOPKINS
	AMRSL WM MC,
	R ADLER
	T HYNES
	AMSRL WM MD, W ROY
	AMSRL WM T, W MORRISON
	AMSRL WM TA,
	W GILLICH
	W BRUCHEY
	T HAVEL
	AMSRL WM TC,
	K KIMSEY
	D SCHEFFLER
	T BJERKE
	R COATES
	W DE ROSSET

NO. OF COPIES	ORGANIZATION
	AMSRL WM TD,
	T CHOU
	D DIETRICH
	A D GUPTA
	M RAFTENBERG
	S SEGLETES
	S SCHOENFELD
	A RAJENDRAN
	D GROVE
	AMSRL WM TE,
	A ZIELINSKI
	J POWELL

NO. OF COPIES	ORGANIZATION
1	AEROSPATIALE S ANDRE A/BTE/CC/RTE MD132 316 ROUTE DE BAYONNE TOULOUSE 31060 FRANCE
1	ARISTOTLE UNIV OF THESSALONIKI DEPT OF MECH & MATLS E AIFANTIS THESSALONIKI 54006 GREECE
1	CIVIL AVIATION ADMINSTRATION T GOTTESMAN PO BOX 8 BEN GURION INTERNATL AP LOD 70150 ISRAEL
1	DAIMLER-BENZ AEROSPACE J BAUER D-81663 MUNCHEN MUNICH GERMANY
1	DEUTSCHE AEROSPACE AG DYNAMICS SYSTEMS M HELD PO BOX 1340 D 86523 SCHROBENHAUSEN GERMANY
2	DFNS TECH & PROC AGCY GRD G LAUBE H HAUS 3602 THUN SWITZERLAND
3	DRA FORT HALSTEAD P N JONES D SCOTT M HINTON SEVENOAKS KENT TN 147BP UNITED KINGDOM

NO. OF COPIES	ORGANIZATION
2	DREV A DUPUIS F LESAGE PO BOX 8800 2459 BOULEVARD PIE XI NORTH COURCELETTE GOA IRO QUEBEC CANADA
1	DSTO MTL NAVAL PLATFORM VLNRBLTY SCHIP STRUCTURES & MATLS DIV N BURMAN PO BOX 50 ASCOT VALE VICTORIA 3032 AUSTRALIA
1	DYNAMEC RESEARCH AB A PERSSON PARADISGRND 7 S 151 36 SODERTALJE SWEDEN
1	ECOLE POLYTECH J MANSON DMX-LTC CH-1015 LAUSANNE SWITZERLAND
1	ECOLE ROYAL MILITAIRE AVE DE LA RENAISSANCE 30 E CELENS 1040 BRUXELLE BELGIUM
1	DIR ERNST MACH INST EMI HAUPTSTRASSE 18 79576 WEIL AM RHEIN GERMANY
1	ERNST MACH INST EMI A STILP ECKERSTRASSE 4 7800 FREIBURG GERMANY

NO. OF COPIES	ORGANIZATION
2	FOA NATL DFNS RSCH ESTAB DIR DEPT OF WPNS & PRTCTN B JANZON R HOLMLIN S 172 90 STOCKHOLM SWEDEN
1	INSTITUT FRANCO ALLEMAND DE RECHERCHES DE SANIT LOUIS D M GIRAUD 5 RUE DU GENERAL CASSAGNOU BOITE POSTALE 34 F 68301 SAINT LOUIS CEDEX FRANCE
1	INST FUR MATERIALFORSCHUNG II C TSAKMAKIS POSTFACH 3640 FORSCHUNGSZENTRUM KARLSRUHE D-76021 KARLSRUHE GERMANY
1	ISRAEL INST OF TECHNOLOGY FACULTY OF MECHANICAL ENGINEERING S BODNER HAIFA 3200 ISRAEL
1	MERL LTD R MARTIN TAMWORTH RD HERTFORD SG13 7DG UNITED KINGDOM
1	MINISTRY OF DEFENCE RAFAEL ARMAMENT DEV AUTH M MAYSELESS PO BOX 2250 HAIFA 31021 ISRAEL
1	NATL TECH UNIV OF ATHENS DEPT OF ENGNRNG SCIENCE I VARDOULAKIS ATHENS 15773 GREECE

NO. OF COPIES	ORGANIZATION
2	ROYAL MILITARY COLLEGE OF SCIENCE SHRIVENHAM D BULMAN B LAWTON SWINDON WILTS SN6 8LA UNITED KINGDOM
1	SMC SCOTLAND P W LAY DERA ROSYTH ROSYTH ROYAL DOCKYARD DUNFERMLINE FIFE KY 11 2XR UNITED KINGDOM
1	SWISS FED ARMMNTS WORKS W LANZ ALLMENDSTRASSE 86 3602 THUN SWITZERLAND
1	TNO DEFENSE RESEARCH I H PASMAN POSTBUS 6006 2600 JA DELFT THE NETHERLANDS
1	TNO PRINS MAURITS LAB LANGE KLEIWEG 137 PO BOX 45 R IJSSELSTEIN 2280 AA RIJSWIJK THE NETHERLANDS
1	UNIV OF PATRAS DEPT OF CIVIL ENGINEERING D BESKOS PATRAS 26500 GREECE

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project(0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY *(Leave blank)*	2. REPORT DATE	3. REPORT TYPE AND DATES COVERED
	July 1998	Final, Sep 96 - Mar 97

4. TITLE AND SUBTITLE

Render-Safe Impact Dynamics of the M557 Fuze

5. FUNDING NUMBERS

622618AH80

6. AUTHOR(S)

G. A. Gazonas

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

U.S. Army Research Laboratory
ATTN: AMSRL-WM-MB
Aberdeen Proving Ground, MD 21005-5069

8. PERFORMING ORGANIZATION REPORT NUMBER

ARL-TR-1713

9. SPONSORING/MONITORING AGENCY NAMES(S) AND ADDRESS(ES)

10. SPONSORING/MONITORING AGENCY REPORT NUMBER

11. SUPPLEMENTARY NOTES

12a. DISTRIBUTION/AVAILABILITY STATEMENT

Approved for public release; distribution is unlimited.

12b. DISTRIBUTION CODE

13. ABSTRACT *(Maximum 200 words)*

This report outlines the results of a combined experimental and computational study that investigates the transient structural response of the M557 point detonating fuze subjected to low-speed (200 m/s) oblique impact by a hardened-steel projectile. The problem is of interest to the explosive ordnance disposal (EOD) community as it is a method that is currently used to "render-safe" ordnance and other explosive devices found in the field. An inert M557 fuze is instrumented with a low-mass (1.5 gram) 60-kilo-g uniaxial accelerometer and subjected to oblique impact by launching a 300-gram projectile from a 4-in airgun. The transient structural response of the fuze is compared to the predicted response using the Lagrangian finite element code DYNA3D. Peak accelerations measured in two tests average 35 kilo-g, whereas DYNA3D predicts a 40- to 50-kilo-g peak acceleration depending upon the amount of prescribed damping. Both measured and computed acceleration histories are Fourier-transformed, and the estimated spectral response at the base of the fuze is shown to be dependent upon the failure strength of the flash tube.

14. SUBJECT TERMS

impact dynamics, render-safe, DYNA3D, FFT spectral analysis, finite elements

15. NUMBER OF PAGES

39

16. PRICE CODE

17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT
UNCLASSIFIED	UNCLASSIFIED	UNCLASSIFIED	UL

NSN 7540-01-280-5500

Standard Form 298 (Rev. 2-89)
Prescribed by ANSI Std. 239-18 298-102

INTENTIONALLY LEFT BLANK.

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. ARL Report Number/Author ARL-TR-1713 (Gazonas) Date of Report July 1998

2. Date Report Received _____

3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. _____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

CURRENT ADDRESS

Organization

Name E-mail Name

Street or P.O. Box No.

City, State, Zip Code

7. If indicating a Change of Address or Address Correction, please provide the Current or Correct address above and the Old or Incorrect address below.

OLD ADDRESS

Organization

Name

Street or P.O. Box No.

City, State, Zip Code

(Remove this sheet, fold as indicated, tape closed, and mail.)

(DO NOT STAPLE)