D		
`_		

AD-E403 058

Contractor Report ARAET-CR-05006

ALKALINE HYDROLYSIS OF CL-20

P. Karakaya
M. Sidhourn
C. Christodoulatos
Center for Environmental Technology
Stevens Institute of Technology
Castle Point and the Hudson
Hoboken, NJ 07030

Wendy Balas
Steven Nicolich
Project Engineers
ARDEC

August 2005



ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER

Armaments Engineering and Technology Center

Picatinny, New Jersey

Approved for public release; distribution is unlimited.

20050816 094

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government, nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinion of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Destroy this report when no longer needed by any method that will prevent disclosure of its contents or reconstruction of the document. Do not return to the originator.

			OMB No. 0/04-01-0188				
The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden to Department of Defense, Washington Headquarters Services Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.							
1. REPORT DATE (DD-MM-YYYY)	2. REPORT TYPE		3. DATES COVERED (From – To)				
August 2005							
4. TITLE AND SUBTITLE		5a. CC	NTRACT NUMBER				
ALKALINE HYDROLYSIS OF CL-20			5b. GRANT NUMBER				
	•	5c. PROGRAM ELEMENT NUMBER					
		OO. I ROOF OUT ELEMENT NOWIDER					
6 ALITHODS	· · · · · · · · · · · · · · · · · · ·	5d. PROJECT NUMBER					
6. AUTHORS P. Karakaya, M. Sidhoum, C. Christodoulatos, Stevens Institute of							
Technology		5e. TASK NUMBER					
W. Balas and S. Nicolich, Project En	gineers, ARDEC	5f. WORK UNIT NUMBER					
7. PERFORMING ORGANIZATION NAME(S	S) AND ADDRESS(ES)	8	B. PERFORMING ORGANIZATION				
Center for Environmental Technology USA	A ARDEC, AETC		REPORT NUMBER				
	rgetics, Warheads & Environmental						
	nnology (AMSRD-AAR-AEE-W)						
Hoboken, NJ 07030 Pica	atinny, NJ 07806-5000						
9. SPONSORING/MONITORING AGENCY ARDEC, EM	NAME(S) AND ADDRESS(ES).	1	10. SPONSOR/MONITOR'S ACRONYM(S)				
Technical Research Center (AMSRD-AAR-EMK) Picatinny, NJ 07806-5000			11. SPONSOR/MONITOR'S REPORT NUMBER(S)				
		(Contractor Report ARAET-CR-05006				
12. DISTRIBUTION/AVAILABILITY STATEM	MENT	•					
·							
Approved for public release; distribution is unlimited.							
13. SUPPLEMENTARY NOTES		······					
•							
14. ABSTRACT							
The Energetics and Warheads Divis	ion of the U.S. Army Armament	Resea	arch Development and Engineering				
Center has been involved in the dev	element of CL 20. An alkaling	hydro	ducic study was porformed to better				
understand the fate and transport of	CL-20 through environmental s	vstem	s.				
		,					
•							
•							
45 OUD ITOT TEDMO							
15. SUBJECT TERMS							

17. LIMITATION OF

SAR

ABSTRACT

18. NUMBER

OF PAGES

13

REPORT DOCUMENTATION PAGE

Alkaline hydrolysis

a. REPORT

16. SECURITY CLASSIFICATION OF:

b. ABSTRACT

CL-30

c. THIS PAGE

19a. NAME OF RESPONSIBE PERSON

19b. TELEPHONE NUMBER (Include area

W. Balas/S. Nicolich

code) (973) 724-4919

Form Approved

CONTENTS

					· · · ug·
Summary					1
Introduction				 ÷	. 1
Aqueous Hydrolysis Setup			. "		2
Homogeneous Alkaline Hydroly Heterogeneous Alkaline Hydro		٠.			2 2
Results and Discussion					2
Conclusions					6
References					7
Bibliography		•	•		7
Distribution List			* .		9

SUMMARY

CL-20, also known as HNIW (2,4,6,8,10,12-hexanitro-2,4,6,8,10,12-hexaaziaisowurtzitane), is a high energy, high density material. Concerns regarding the environmental fate and transport of CL-20 are arising due to its potential introduction into soil and water matrices. The aqueous hydrolysis of CL-20 was investigated as a possible remediation technique. Alkaline hydrolysis experiments were conducted at temperatures of 15, 20, 30, and 40°C, with hydroxide concentrations ranging from 0.25 to 300 mM. Like RDX and HMX, alkaline hydrolysis of CL-20 follows second-order kinetics. CL-20 alkaline hydrolysis was found to proceed at a significantly faster rate than RDX. The temperature dependency of the second-order rate constants was evaluated using the Arrehnius model. The activation energy for CL-20 was found to be within close range of the activation energies reported for RDX and HMX.

INTRODUCTION

The rate of reaction of energetic materials under alkaline conditions depends on the concentrations of the base and the energetic compound. Heilmann et al. (ref. 1) and Hoffsommer et al. (ref. 2) suggested that the alkaline hydrolysis of the nitramines HMX and RDX proceeds via the E-2-elimination mechanism, which is a common elimination mechanism in organic chemistry and follows a second-order rate law. Accordingly, the kinetics of alkaline hydrolysis of CL-20 using a strong base (NaOH) is represented as follows

$$\frac{dC_{CL-20}}{dt} = -k_2 C_{CL-20} C_{NaOH} \tag{1}$$

where $C_{\text{CL-20}}$ is the CL-20 concentration, C_{NaOH} is the base concentration, and k_2 is the second-order rate constant. Because the consumption of NaOH cannot be accurately or conveniently measured during the time course of reaction, it is difficult to determine the second-order rate constant (k_2) directly. However, by adjusting the experimental conditions, a pseudo-first order rate constant (k_1) can be obtained. This situation can be realized, by either maintaining the NaOH concentration constant throughout the reaction or at least sufficiently in excess such that any change in the concentration of the base is negligible compared to the change in concentration of CL-20. Under such experimental conditions, equation 1 is reduced to the following pseudo-first order rate equation

$$\frac{dC_{CL-20}}{dt} = -k_1 C_{CL-20}$$
 (2)

where k_1 is given by

$$k_1 = k_2 C_{NaOH} ag{3}$$

By monitoring the CL-20 concentration during the time course of the reaction at a given NaOH concentration and temperature, one can obtain k_1 using the integrated form of equation 2

$$1nC_{CL-20} = 1nC_{CL-20}^0 - k_1 t (4)$$

where C_{CL-20}^0 is the initial concentration of CL-20. According to equation 4, the slopes of the semi-logarithmic plots of the concentration-time data yield the rate constant k_1 . Next, by varying the NaOH concentration at a given temperature, the second-order rate constants can be computed using equation 3.

AQUEOUS HYDROLYSIS SETUP

Batch hydrolysis experiments were carried out at four temperatures (15, 20, 30, and 40°C) below solubility limits (homogeneous alkaline hydrolysis) and above solubility limits (heterogeneous alkaline hydrolysis) using NaOH concentrations ranging from 0.25 to 300 mM. The temperature of the reaction medium was regulated using a water bath (Fisher Scientific, Model Isotemp-210).

Homogeneous Alkaline Hydrolysis Experiments

De-ionized water (495 mL) containing dissolved reactant was placed in a 1-L beaker. A three-blade propeller rotated by an overhead Cole Parmer Stirpak 4554-10 lab stirrer set at 150 rpm was centered and lowered into the beaker and raised to a height of 1 cm above the beaker bottom. Next, 5 mL of concentration NaOH solution of appropriate molarity were added to the solution.

Heterogeneous Alkaline Hydrolysis Experiments

De-ionized water (from 291 to 297 mL) containing reactant powder was placed in a 600-mL beaker. The propeller was centered and lowered into the beaker and the stirrer was adjusted to 1000 rpm. The high mixing speed was required to minimize CL-20 particles flotation. Next, 3 to 9 mL of concentrated NaOH solution of appropriate molarity was introduced into the solution to yield a 300 mL reaction volume.

Samples (2 mL) withdrawn periodically from the reaction were added to test tubes containing appropriate amounts of H₂SO₄, to neutralize the sample. The purposes of neutralization are first to quench the base hydrolysis reaction and secondly to protect the HPLC column from alkaline conditions. The neutralized samples were further diluted with acetonitrile (1:1 by volume) prior to analysis. All samples were analyzed immediately at the end of each run.

RESULTS AND DISCUSSION

A series of kinetic runs for the homogeneous CL-20 alkaline hydrolysis were carried out with initial CL-20 concentrations of about 3 mg/L (~6.849 x 10⁻⁶ M) and NaOH concentrations ranging from 0.25 to 10 mM. The experiments were performed at 15, 20, 30, and 40°C. Data for the CL-20 homogeneous alkaline hydrolysis are presented in figure 1. In these studies, the molar ratio of NaOH to CL-20 ranged from 36.5:1 to 1460:1. To validate the assumption that base concentration in the solution was measured at the end of the experiments (when CL-20 is depleted). At the lowest NaOH concentration used (0.25 mM at 40°C), the NaOH consumption was found to be negligible (about 2%); which supports the pseudo-first order kinetics assumption under the present experimental conditions.




Figure 1
Concentration-time profiles of CL-20 homogeneous alkaline hydrolysis at (a) 15°C, (b) 20°C, (c) 30°C, and (d) 40°C at various alkalinities

Another set of experiments was conducted to examine the kinetics of heterogeneous CL-20 alkaline hydrolysis, with initial CL-20 concentrations at about 500 mg/L (-1.142 x 10⁻³ M) at 15, 20, 30, and 40°. The obtained data are shown in figure 2. In these experiments, the NaOH concentration was varied from 25 to 300 mM, with molar ratios of NaOH to CL-20 ranging from 21.9:1 to 262.8:1. At the lowest NaOH concentration studied (25 mM at 40°C) the decrease in NaOH concentration during heterogeneous alkaline hydrolysis was about 9% and was considered to be within acceptable limits for the application of the pseudo-first order kinetics assumption.




Figure 2
Concentration-time profiles of CL-20 heterogeneous alkaline hydrolysis at (a) 15°C, (b) 20°C, (c) 30°C, and (d) 40°C at various alkalinities

From the concentration-time profiles (figs. 1 and 2) it is clear that the rate of alkaline hydrolysis of CL-20 depends on alkali strength. For example, at 20°C and 3 mg/L of initial CL-20, 85% of the compound, reacts with 10 mM NaOH within 5 min; however, with 1 mM NaOH, it requires about 65 min to achieve the same degree of transformation. The temperature effect on the rate of alkaline hydrolysis of CL-20 is also illustrated in figure 1. For instance at 1 mM NaOH and 3 mg/L of initial CL-20, when the temperature is increased form 20°C to 30°C, the time required for the same extent of removal (85%) drops from 65 to 12 min.


The CL-20 concentration-time profiles were used to obtain the relevant kinetic parameters for homogeneous and heterogeneous alkaline hydrolysis, by applying non-linear regression analysis. The computed pseudo-first order rate constants (k_1) and corresponding standard errors are presented in table 1. The experimental data correlate closely with the assumed pseudo-first order kinetic model with excellent correlation coefficients.

Table 1
Pseudo first-order rate constants k₁ (min⁻¹) and corresponding correlation coefficients (R²) for alkaline hydrolysis of CL-20 for different NaOH concentrations and temperatures

C _{NaOH} (mM)	15°C	20°C	30°C	40°C
Homogeneous alkaline	e hydrolysis			,
10	$0.1639 (0.0025)^a$ $R^2 = 0.9987$	$0.4086 (0.0103)$ $R^2 = 0.9982$		
5	0.0776 (0.0007) $R^2 = 0.9994$	$0.1869 (0.0025)$ $R^2 = 0.9993$	$0.8089 (0.0160)$ $R^2 = 0.9991$	
1	$0.0129 (0.0003)$ $R^2 = 0.9961$	0.0320 (0.0009) $R^2 = 0.9962$	0.1531 (0.0030) $R^2 = 0.9986$	0.5696 (0.0155) $R^2 = 0.9979$
0.5			$0.0763 (0.0022)$ $R^2 = 0.9963$	0.2902 (0.0064) $R^2 = 0.9982$
0.25	•			0.1273 (0.0032) $R^2 = 0.9975$
leterogeneous alkalir	ne hydrolysis			
300	$0.0427 (0.0020)$ $R^2 = 0.9898$	$0.1051 (0.0115)$ $R^2 = 0.9750$		
200	$0.0319 (0.0012)$ $R^2 = 0.9945$	$0.0686 (0.0021)$ $R^2 = 0.9952$	$0.2501 (0.0155)$ $R^2 = 0.9853$	
100	$0.0156 (0.0006)$ $R^2 = 0.9928$	$0.0437 (0.0005)$ $R^2 = 0.9991$	$0.1531 (0.0070)$ $R^2 = 0.9860$	0.4281 (0.0643) $R^2 = 0.9027$
50			0.0709 (0.0017) $R^2 = 0.9972$	0.1731 (0.0068) $R^2 = 0.9915$
25				$0.1151 (0.0019)$ $R^2 = 0.9988$

^aNumbers in parentheses are standard errors.

The k_2 values were obtained as the slopes of the plots k_1 versus NaOH concentration (fig. 3). The second-order rate constants obtained at homogeneous conditions (k_2^{hom}) and at heterogeneous conditions (k_2^{het}), by linear regression for the temperatures studied and the corresponding correlation coefficients are presented in table 2. The values of k_2^{hom} are significantly higher than those obtained for k_2^{het} , with ratios of 109, 112, 122, and 137 at temperatures of 15, 20, 30, and 40°C, respectively. The lower k_2^{het} values may be attributed to mass transfer limitations that commonly occur in heterogeneous reactions, which indicate that the heterogeneous hydrolysis of CL-20 may not be under kinetic control.



The second-order rate constants (k₂) are calculated from the slopes of the curves.

Figure 3
Linear regression analysis using equation 3 for (a) homogeneous and (b) heterogeneous alkaline hydrolysis of CL-20

Table 2 Second-order rate constants (k₂) and corresponding correlation coefficients (R²)

Temperature (°C)	K ₂ ^{hom} (M ⁻¹ min ⁻¹)	K₂ ^{het} (M⁻¹min⁻¹)
15	16.1897	0.1481
	$R^2 = 0.9977$	$R^2 = 0.9769$
20	10.0992	0.3544
	$R^2 = 0.9957$	$R^2 = 0.9607$
30	161.3619	1.3119
	$R^2 = 0.9997$	$R^2 = 0.9591$
40	568.7810	4.1404
	$R^2 = 0.9974$	$R^2 = 0.9733$

The temperature dependency of k₂ can be represented by the Arrhenius law

$$k_2 = Ae^{\frac{E}{RT}} \tag{5}$$

where A is the frequency factor or Arrhenius constant, E the activation energy (kJ/mol) of the reaction, R the gas constant (8.314 J.mol^{-1.0}K⁻¹) and T (°K) the absolute temperature. This expression fits the experimental data well over wide temperature ranges and is strongly suggested from various standpoints as being a very good approximation to the true temperature dependency (ref. 3). The parameters, A and E, are determined from a linear least square fit of the logarithm of the obtained average second-order rate constants (table 2) against the reciprocal of the absolute temperature as shown in figure 4. The value of the activation energy, E was calculated as 105.64 KJ/mol for homogeneous alkaline hydrolysis (R²=0.9979). The apparent activation energy for the heterogeneous reaction was calculated as 98.81 KJ/mol (R²=0.9970). Although small, this difference in activation energy values could be attributed to external mass-transfer limitations that might not have been fully addressed by the mixing speed used in the heterogeneous experiments. The activation energy values obtained for the CL-20 base hydrolysis are within close range of those reported by Heilmann et al. (refs. 1 and 4) for RDX (99.9 kJ/mol) and HMX (111.9 kJ/mol) and the heterogeneous activation energy reported by Christodoulatos et al. (ref. 5) for nitrocellulose (100.9 kJ/mol). The Arrhenius pre-exponential constants for the homogeneous and heterogeneous reactions are 2.52 x 10²⁰ and 1.34 x 10¹⁷, respectively.

CONCLUSIONS

Alkaline hydrolysis is a simple and effective treatment technology for energetic materials including CL-20. The alkaline hydrolysis of CL-20 above and below solubility limits follows second order kinetics. Homogeneous alkaline hydrolysis rates of CL-20 are higher than heterogeneous rates, and in both cases the reaction is faster in comparison to the alkaline hydrolysis of RDX. The activation energy for CL-20 undergoing alkaline hydrolysis is within close range of the reported activation energies for other nitrated energetic compounds. Further studies are necessary to evaluate mass transfer effects on the alkaline hydrolysis rates of CL-20 and to identify the intermediate and end products of the alkaline reactions.

REFERENCES

- 1. Heilmann, H.M.; Wiesmann, U.; and Stenstrom, M.K., "Kinetics of the Alkaline Hydrolysis of High Explosives RDX and HMX in Aqueous Solution and Adsorbed to Activated Carbon," Environmental Science Technology.30, 1475-1492, 1996.
- 2. Hoffsommer, J.C.; Kubose, D. A.; and Glover, D. J., "Kinetic Isotope Effects and Intermediate Formulation for the Acqueous Alkaline Homogeneous Hydrolysis of 1,3,5-triaza-1,3,5-trinitrocyclohexane (RDX),", Journal of Physical Chemistry, 81(5), 380-385, 1977.
- 3. Levenspiel, O., <u>Chemical Reaction Engineering</u>, Second Edition, John Wiley & sons, New York, 1972.
- 4. Heilmann, H. M.; Stenstron, M. K.; Hesselmann, R. P. X.; and Wiesmann, U., "Kinetics of Aqueous Alkaline Homogeneous Hydrolysis of High Explosive 1,3,5,7-tetraaza-1,3,5,7-tetranitrocyclootane (HMX)," Water Science and Technology 30(5), 1484-1492, 1994.
- 5. Christodoulatos, C.; Su, T-L; and Koutsospyros, A., "Kinetics of the Alkaline Hydrolysis of Nitrocellulose," Water Environment Research 73(2), 185-191, 2001.

BIBLIOGRAPHY

- Balakrishnan, V. K.; Halazs, A.; and Hawari, J., "Alkaline Hydrolysis of the Cyclic Nitramine Explosives RDX, HMX, and SL-20: New Insights into Degradation Pathways Obtained by the Observation of Novel Intermediates, Environmental Science and Technology 37(9), 1838-1843, 2003.
- 2. Bishop, R. L.; Flesner, R. L.; Dell'Oreo, P. C.; Spontarelli, T.; and Larson, S. A., "Application of Gas-Liquid Film Theory to Base Hydrolysis of HMX Powder and HMX-Based Plastic-Bonded Explosives Using Sodium Carbonate," Industrial Engineering and Chemistry Research 37(12), 551-4559, 1998.
- 3. Bishop, R. L.; Flesner, R. L.; Dell'Oreo, P. C.; Spontarelli, T.; Larson, S. A.; and Bell, D. A., "Base Hydrolysis of HMX and HMX-Based Plastic-Bonded Explosives with Sodium Hydroxide Between 100 and 155°C," Industrial Engineering and Chemistry Research 38(6), 2254-2259, 1999.
- Dohanyosova, P.; Dohnal, V.; and Fenclova, D., "Temperature Dependence of Acquious Solubility of Antracenes: Accurate Determination by a New Generator Column Apparatus," Fluid Phase Equilibria 214, 151-167, 2003.
- Felt, D. R.; Larson, S. L.; and Hansen, L. D., "Kinetics of Base-Catalyzed 2,4,6,Trinitrotoluene Transformation," ERDC/EL TR-01-17, U.S. Army Engineer Research and Development enter, Vicksburg, MS, 2001.
- 6. Kim, J-H.; Park, Y-C; Yim, Y-J.; and Han J-S., "Crystallization Behaviour of Hexanitrohexaazaisowurtzitane at 298K and Quantitive Analysis of Mixtures of its Polymorphs by FTIR," J. Chem. Eng., Japan 31, 478-481, 1998.

BIBLIOGRAPHY

(continued)

- 7. Larson, S. L.; Felt, D. R.; Escalon, L.; Davis, J. D.; and Hansen, L. D., "Analysis of CL-20 in Environmental Matrices: Water and Soil," ERDC/EL TR-01-21, U.S. Army Engineering Research and Development Center, Vicksburg, MS, 2001.
- 8. Larson, S. L.; Felt, D. R.; Escalon, L.; Davis, "Analysis of CL-20 in Environmental Matrices: Water and Soil," Journal of Chromatographic Science 40(4), 201-206, 2002.
- 9. National Research Council, "Advances Energetic Materials," The National Academies Press, Washington, http://books.nap.educatalog/10918.html, DC, 2004.
- 10. Nielsen, A. T., "Caged Polynitramine Compound," U.S. Patent 5,693,794, 1997.
- 11. Nielson, A. T.; Chafin, A. P.; Christian, S. L.; Moore, D. W.; Nadler, M. P.; Nissan, R. A.; and Vanderah, D. J., "Synthesis of Polyazapolycyclic Caged Polynitramines," Tetrahedron 54, 11793-11812, 1998.
- 12. Qasim, M.; Flemming, B.; and Hansen, L., "An Approximation Methods Study and Comparison of the Chemical and Physical Properties of CL-20 and RDX for Prediction of Reactivities," Proceedings of Curr. Trends Comp. Chem., 184-187, 2000.
- 13. Reid, R. C.; Prausnitz, J. M.; and Poling, B. E., <u>The Properties of Gases and Liquids</u>, 4th Ed., McGraw-Hill, New York, NY, 1987.
- Spontarelli, T.; Buntain, G. A.; Flesner, R. L.; Sanchez, J. A.; and Unkefer, P. J., "An Engineered System Using Base Hydrolysis for Complete Destruction of Energetic Materials," International Symposium on Energetic Materials Technology, Orlando, FL, American Defense Preparedness Association (ADPA), 1994.
- 15. Wu, Y-C., "Alkaline Hydrolysis of TNT Modeling Mass Transport Effect," Ph.D Dissertation, University of California at Los Angeles, 2001.

DISTRIBUTION LIST

USA ARDEC

ATTN: AMSRD-AAR-EMK

AMSRD-AAR-GC

AMSRD-AAR-AEE, C. Anderson AMSRD-AAR-AAE-W, W. Balas (5) S. Nicolich

Picatinny, NJ 07806-5000

Defense Technical Information Center (DTIC)

ATTN: Accessions Division

8725 John J. Kingman Road, Ste 0944

Fort Belvoir, VA 22060-6218

Commander

Soldier and Biological/Chemical Command

ATTN: AMSSB-CII, Library

Aberdeen Proving Ground, MD 21010-5423

Director

U.S. Army Research Laboratory

ATTN: AMSRL-CI-LP, Technical Library

Bldg. 4600

Aberdeen Proving Ground, MD 21005-5066

Chief

Benet Weapons Laboratory, AETC

U.S. Army Research, Development and Engineering Command

Armament Research, Development and Engineering Center

ATTN: AMSRD-AAR-AEW Watervliet, NY 12189-5000

Director

U.S. Army TRADOC Analysis Center-WSMR

ATTN: ATRC-WSS-R

White Sands Missile Range, NM 88002

Chemical Propulsion Information Agency

ATTN: Accessions

10630 Little Patuxent Parkway, Suite 202

Columbia, MD 21044-3204

GIDEP Operations Center

P.O. Box 8000

Corona, CA 91718-8000

Commander Naval Surface Warfare Center Indian Head Division (2) 101 Strauss Avenue Indian Head, MD 20640

Commander
Air Force Research Laboratory
Munitions Directorate
ATTN: Energetic Materials Branch (2)
Eglin AFB, FL 32542